An Audited, Budget-Disclosed Benchmark of Classical Teachers and Learned Students on a Simulated Arm

Author Name (placeholder)
Affiliation (placeholder)
Email (placeholder)

***Abstract*—Learning-based controllers are often reported to beat classical ones, yet comparisons rarely give the classical side extended tooling, a disclosed budget, and rules fixed before testing. We propose an audited protocol for classical-versus-learned arm control in simulation: extended classical tooling, three-axis budgets, rules pre-specified in time-stamped hypothesis cards, a sanity gate for learners, and an access log. Across 8 tracking, juggling and whip settings, no learned method beat the strongest classical baseline by the pre-specified +10 pp bar, but only the whip has headroom; in 3 settings the residual-RL learner did not learn, and with a single-seed-gated exploration scale (gate passed) it nevertheless degraded the base by 17.6–23.8 pp where tested. On realistic whip, locked sets (n=500) show true parameters add +17.6 pp [12.6, 22.6], yet most of that gap is recovered without better parameters: scoring candidate swings across several plausible plants, a rule built first for the learned side and then given to the classical side, recovers 0.59 [0.36, 0.82] of it with a classical Laplace ensemble and 0.90 [0.68, 1.16] with estimators trained on simulator labels. Under this rule the learned side is ahead by +5.6 pp [0.6, 10.6]; 10 pp cannot be excluded. One simulator, mostly one task.**

***Index Terms*—robot manipulation, classical versus learned control, imitation learning, residual reinforcement learning, evaluation protocol, whip**

I. Introduction

A learned controller that beats a classical one is a common headline, and the comparison behind it is often weaker than it looks. Our own first experiment shows how. A residual PPO policy beat the untuned computed-torque teacher on a 2-DoF tracking task by 16.7% in RMSE without disturbances. After a two-parameter gain retune of the teacher, the advantage disappeared: the learned side was 7.1% worse, with a 95% CI of $[-13.8, +0.3]\%$ (Table III, S1). The gap was a tuning gap, not a learning gap.

This paper asks a narrower question than "does learning win": *what extra ingredient does a learned student need to beat its classical teacher?* Candidate ingredients are more information (privileged state), better optimisation (reinforcement learning on top of the teacher), a richer model class (generative students), and more data. To answer under one set of rules, we built a benchmark with an explicit protocol and report every deviation from it. All claims are scoped to this protocol and to one simulator.

We make four contributions, each tied to a named evidence set: the access log for K1, locked sets for K2 and K3, and fresh but unlocked seeds for K4.

- **K1 An audited protocol** (Section III): classical tooling extended on the same footing as the learner's, three-axis budgets with disclosed over-runs, rules pre-specified in time-stamped hypothesis cards, a sanity gate that a learner must pass before its null is interpreted, and an access log for test evaluations. The gate passed only marginally (+10.2 pp against a +10 pp threshold), and its first lesson was that a default exploration scale left PPO unable to learn a learnable correction.
- **K2 A cross-setting result with one whip qualification** (Section V-A): in 8 tracking, juggling and whip settings no learned method beat the strongest classical baseline by the +10 pp bar. On whip, a learned estimator is ahead of the upgraded classical one by +5.6 pp [0.6, 10.6] under the same robust plan-selection rule, and an advantage of 10 pp or more cannot be excluded.
- **K3 A headroom decomposition on realistic whip** (Section V-B): true parameters add +17.6 pp [12.6, 22.6] over fitted ones, and scoring candidate swings across several plausible plants recovers 0.59 [0.36, 0.82] of that gap with a classical Laplace ensemble and 0.90 [0.68, 1.16] with learned estimators.
- **K4 A multimodal-teacher result** (Section V-C): replacing a multimodal teacher by a canonicalised one raised every student's success by 17.5–33.5 pp, while the best generative student added only +5.0 pp $[-0.3, 10.2]$ over an MLP.

Two sources of fragility run through these results, and we state them here rather than in the limitations. First, in 3 of the 8 settings the RL learner did not learn, so those settings cannot show that classical is better. Second, the classical comparator on whip, a Laplace ensemble, was added after the learned method had already beaten the original classical baseline; the final contrast is pre-specified, but the comparator was built with the learned result in view.

To our knowledge no prior work combines an independent-physics manipulator, an auditable fairness protocol, extended classical tooling and a headroom ladder (the literature search ended in October 2026; Section II). Every number in the text is traced to a result file, a README line or a code constant (`numbers_check.md` in the accompanying repository); the appendices give the deviations, budgets and the remaining

experiments.

II. Related Work

Classical versus learned comparisons. OSCAR [1] compares a learned-dynamics operational-space controller with operational-space, inverse-kinematics and joint-space baselines on a Franka Panda, but every policy is trained with PPO, so the classical controller is an action space rather than an independent opponent. The Real Robot Challenge [2] found classical methods ahead in its 2020 phase and RL ahead in 2021. Aljalbout et al. [3] study 13 control spaces with over 250 RL agents, RL only. The closest work in spirit is Kunapuli et al. [4]: for quadrotor tracking, the gap between an RL tracker and a geometric controller is much smaller than previously published once objective, tuning data and feedforward are equalised; they use no imitation learner. Samuel and Verma [5] compare PID, LQR, MPC, SAC and a BC+DAgger student distilled from MPC on a hybrid rigid-pneumatic arm, in a simulator that is the controllers' own model and with an RL baseline that stalls; the student does not beat the teacher (92.4 versus 95.0% at $N{=}2$ on identical goals) and is no more robust to a mass and inertia mismatch. We differ in using an independent-physics manipulator, pre-specified rules with a deviation table, and a headroom decomposition.

Distilling MPC into networks. Nubert et al. [6] approximate a robust MPC law with a network on a robot manipulator; Tagliabue and How [7] learn robust multirotor policies from MPC with tube-guided augmentation; Marquez Julbe et al. [8] use diffusion to imitate multi-modal MPC actions on a 7-DoF arm in a kinematic simulation, where the student has a higher success rate but a larger end-of-run error than the MPC and no model-error test is run. Our S3 and S8 settings put generative students against an exact or privileged teacher with the same budget accounting as the other methods.

Residual learning and generative policies. Residual policy learning [9], [10] adds a learned correction to a hand-designed controller; ResiP [11] refines a frozen Diffusion Policy with RL, and its appendix reports that an MLP base loses success under exploration noise, converges to similar performance on the easier task and collapses on the harder one. Our exploration-scale lesson (Section III) is consistent with that sensitivity. Pan et al. [12] argue that generative control policies owe their advantage to iterative computation with supervised intermediate steps rather than to multi-modality, and that a two-step regression policy (MIP) essentially matches flow policies; one-step flow variants [13], [14] report large speed-ups (author-reported). Our K4 result is consistent with this direction but underpowered (Section V-C).

III. An Audited Protocol (K1)

The protocol has six parts. Each exists because a specific comparison in our own history would otherwise have been misread. Appendix A lists where we deviated from it. Fig. 1 shows how the parts fit together.

Extended classical tooling. The classical side is not frozen at the textbook controller. It has a ladder of tuned variants (retuned gains, integral action, robust CMA-ES tuning, online system identification, and for whip an extended model class with 13 parameters; Section IV). We call this tooling *extended on the same footing* as the learner's, not equal on every axis: the classical side receives the generative parameter distribution as bounds and priors, and the learner receives it as simulated training data with labels.

Three-axis budgets. Every method reports episodes, wall-clock and label source, and the declared cap is $2\times$ the classical episode budget. The learned side exceeded the cap in 4 of the 8 spikes of Appendix B: it used $2.3\times$ in the juggling PPO run, about $7\times$ in the whip PPO sweep, 9–$17\times$ in the estimator duel and $3.2\times$ in the idealised-whip re-run; in the other direction the classical tuning used about $7.7\times$ the simulation steps of one RL policy in the first tracking study (Appendix B). We report these ratios instead of equalising them.

Pre-specified rules. Hypotheses, metrics and decision rules are written in time-stamped, version-controlled cards (no external registry). A *win* requires a paired bootstrap CI that excludes 0 and a gain of at least 10% (tracking) or +10 pp (success rate); the +10 pp bar is our own choice and is not derived from a noise floor. Multiple tests inside one hypothesis family use Holm correction. Git order (rule committed before result) was verified for six early spikes (and for the headline rules of three more) and for the two locked-set runs of Section V-B; for ten spikes (01, 02, 03a, 04, 11a, 13b, 15b–15d, 16a) it cannot be shown because rule and result share a commit or the rule lived in a task prompt (Table IV). No case was found in which git shows a rule committed after its result (Appendix A). We therefore tag each result as pre-specified in git (**PRE-git**), pre-specified in a spike README only (**PRE-README**), or post hoc (**POST**). Because "no win at +10 pp" is not "matched", we add post hoc two one-sided tests (TOST) from the 90% CI at ± 10 and ± 5 pp; only rows whose whole 90% CI lies inside the margin are called equivalent. CIs and p-values are not corrected across spikes.

Disjoint seed sets with roles. Table I lists the sets. Tuning and selection use CAL; HOLD selected the best classical baseline in two spikes and was then reused, so it is optimistic for the classical side; the locked sets TEST-B, TEST-C and TEST-D were each evaluated once.

Sanity gate and learning check. Before a learner's null is interpreted, the learner must learn a known-learnable correction: a constant torque bias injected after a probe, with a pass of +10 pp over its initialisation with a CI above 0. A learner counts as having *learned* only if its CAL-selected checkpoint beats initialisation by at least 5 pp. The first gate passed marginally: with the exploration log-std -1.5 and 3M steps, PPO gained +10.2 pp [4.8, 15.6] on HOLD ($n{=}500$), best of 8 gate runs, 0.2 pp above the threshold, judged on $n{=}500$ instead of the pre-specified $n{=}200$; the zero-residual rule ($\leq$40%) was not met and SAC did not pass. The gate taught a lesson: the default exploration scale (log-std -3.5, 0.36 Nm) gave -3.0 pp [-8.5, +2.5] and learned nothing, while -2.0 gave +7.8 pp [3.0, 12.8]. Later gates are single-seed shots (Appendix B), so every RL null below reads "not learned under this recipe", never "cannot




Fig. 1. Protocol overview: seed-set roles (top) and the three rules that govern every comparison (bottom). The access log records arena evaluations on TEST seeds only.

TABLE I
SEED SETS. "LOCKED" SETS WERE USED ONCE FOR THE EVALUATION NAMED IN THE LAST COLUMN.

Set	Seeds	n	Role
CAL	1000–1049; +2000–2149 in spikes 13a–15c	50 (200)	tuning, selection
HOLD	1100–1599	500	classical selection; reused
TEST	0–49	50	older spikes; reused for juggling
TEST-B	20000–20499	500	locked, realistic whip (Sec. V-A)
TEST-C	30000–30499	500	locked, ladder (card v8)
TEST-D	40000–40499	500	locked, plan selection (card v9)
NEW	700000+	200	fresh confirmation

learn".

Audit log. Every arena evaluation on TEST seeds appends a line to a log, which has 111 lines. The log covers arena evaluations only: the TEST evaluations of the first five spikes ran outside it, so the line count is not the number of locked-set accesses and must not be quoted alone. The three locked sets of Table I were each accessed once.

IV. EXPERIMENTAL SETUP

Arm and simulator. All experiments run in MuJoCo with planar serial arms. The default arm has two links (0.5 and 0.4 m, 1.0 and 0.8 kg); the whip uses a three-link arm (0.40, 0.35 and 0.25 m; 1.0, 0.8 and 0.5 kg; 0.2 kg tip payload). A task, a robot, a controller and a list of perturbations plug into one environment interface. Controllers see only the nominal model; perturbations change the true plant. Control runs at 5 ms.

Seven tasks and where each is used. The task set is figure tracking (a tool-tip glyph), pole balancing, Push-T, ball juggling, ball catching, ball tossing into a basket, and whip. Learned-versus-classical comparisons with a full protocol cover tracking, juggling and whip (settings S1–S8, Table III). Pole balancing was run only on the classical ladder; catching, tossing and Push-T have classical pilots (5–20 demo seeds) and, in Appendix E, residual-PPO mini-comparisons that add breadth but not evidence for K2.

Whip. The arm flings a chain of ten capsules (0.10 m, 0.015 kg each, hinged at the tip) so that the *chain tip* passes within 0.08 m of a target 1.15–1.70 m from the shoulder, outside the arm's 1.0 m reach, within 2.5 s. The chain state is not observed. "Realistic conditions" add encoder noise (1e-3 rad, 1e-2 rad/s), actuator noise $U(0.01, 0.02)$ Nm, Coulomb friction 2e-3 Nm $\times$ $U(0.5, 1.5)$ and per-link mass factors $\exp U(-0.3, 0.3)$. These magnitudes are our choice, set before the results, and are not derived from hardware. Success is the primary metric.

Classical ladder. For tracking the ladder runs PID, computed torque with LQR (CTC+LQR), iLQR, iLQR-MPC and MPPI. For tuning, C0 is the untuned teacher, C1 retunes Kp/Kd or Q/R with CMA-ES on CAL, and C2 adds an integral term. For juggling and whip we use T-nom (nominal), T-robust (CMA-ES over the perturbation distribution), T-adapt (online system identification from a short probe) and, for realistic whip, T-adapt3 with an extended model class (length scale, ten per-link masses, damping, Coulomb friction; 13 parameters, called R0 below). On whip the plan comes from CMA-ES keyframes tracked by computed torque.

Learned methods. Imitation students are an MLP trained by behaviour cloning (BC, with DART noise or DAgger where stated), MIP (two-step regression), flow matching with 1 or 10 steps, and a DDIM-10 diffusion policy. Residual RL is PPO (SAC in sensitivity runs) on top of the strongest classical controller, with a residual capped at 12 Nm in juggling and whip. Learned estimators map a short probe to the plant parameters: L-est is an MLP on the probe's tracking residuals (12,000 probe-only training episodes, simulator labels), and L-dec4 is a GRU on the raw probe time series with a decision-weighted loss and four times the data, with three training seeds. Ensembles average the estimated parameters of the three frozen L-dec4 networks. All training seeds are at least 500,000.

Residual PPO recipe. The residual policy has two tanh layers of 256 units and a zero-initialised output, so the learner

TABLE II
THE EIGHT SETTINGS. "STRONGEST CLASSICAL" IS THE COMPARATOR OF TABLE III; ON S7 IT CHANGED FROM R0 TO C-ENS DURING THE STUDY (SECTION V-B).

	Task and condition	Strongest classical	Learned methods	Evidence sets
S1	tracking, weaknesses W0/W3 (2-link)	C1: gains retuned by CMA-ES	residual PPO (5 seeds)	TEST
S2	tracking + sensor noise + 30 ms delay	C1-new (retuned for noise and delay)	residual PPO	TEST
S3	tracking, clean nominal plant	CTC+LQR teacher (exact)	BC, MIP, flow-1, flow-10, DDIM-10 students	HOLD, fresh seeds
S4	juggling, one known error (pilot)	one-parameter retuned mirror-law teacher	residual PPO	TEST
S5	juggling, wide unknown error	T-robust (CMA-ES over the error distribution)	residual PPO, SAC, PPO with oracle observation	TEST, HOLD, fresh
S6	whip, idealised (noise-free, in model class)	T-adapt (online identification)	L-est, residual PPO, PPO with oracle observation	TEST, HOLD, fresh
S7	whip, realistic conditions	R0 (T-adapt3-full), later C-ens	L-est, L-dec4, ensembles (B), residual PPO, SAC	TEST-B/C/D, HOLD, NEW
S8	whip, privileged-teacher distillation	T-adapt3-full	students on multimodal and canonical teacher data	NEW

starts exactly at its base controller; its input includes lagged arm positions and velocities, and it is trained for 2.5M to 3M steps (12M in one probe) with learning rate 10^{-4}. Seven equally spaced checkpoints are evaluated on CAL and the best is chosen, with initialisation excluded; the learned verdict then uses disjoint seeds. The exploration log-std was the one parameter we found to matter most (Section III).

Reproducibility. Each result table is regenerated by a script from stored per-episode data, with the exception of runs that depend on untracked intermediate files; locked-set runs (TEST-B, TEST-C, TEST-D) were once-only and must not be repeated. All training seeds are at least 500,000 so that no training episode overlaps an evaluation set.

Headroom ladder. On whip we measure what each source of error costs with a fixed-order ladder on the same pipeline. R0 is the fitted-parameter pipeline; R1 gives it the true plant parameters; R2 adds the true chain state; R4 is an oracle planner with no probe time; R5 uses the canonical oracle. Paired differences between rungs give the size of each block. We also run the reverse order (true chain state first). R3 was not run.

Perturbations. Tracking uses payload error, torque cap, delay, Coulomb friction, sensor noise and torque pulses; ball tasks use drag, mass, release delay and observation noise or delay; whip uses chain mass, damping and length. S5 (juggling) draws restitution, ball mass and sensing delay per episode from a wide distribution that the controller does not know.

Statistics. Paired percentile bootstrap, 95% CI, per comparison, with 10^4 to 2×10^4 resamples depending on the script. "Recovered fraction" is $(\mathrm{X}-\mathrm{R0})/(\mathrm{R1}-\mathrm{R0})$ with the same resample in numerator and denominator. Holm correction applies within a hypothesis family: three hypotheses for the TEST-C card and four for the TEST-D card, both on one-sided bootstrap p-values at family $\alpha = 0.05$.

V. RESULTS

A. No learned method cleared the +10 pp bar against its strongest classical baseline

Table III and Fig. 2 summarise the learned-minus-classical contrast in each setting. Out of 8 enumerated settings, none has a learned method with a CI above 0 and a gain of at least +10 pp (or 10% RMSE) over the strongest classical baseline. The positive exceptions compare against weaker baselines: residual PPO against the untuned tracking teacher (+16.7% RMSE), against the untuned juggling teacher (+292% median hits; a one-parameter retune also reaches 100 hits), and against the weaker T-adapt of the juggling study (+9.3 pp [2.7, 17.3]).

Three patterns explain the rows. In **tracking** (S1–S3) there is little headroom by construction. With a retuned CTC controller there is no decisive difference from residual PPO on four clean and disturbed cells (S1: none of the four 90% CIs decides at $\pm10\%$); with noise and a 30 ms delay the retuned classical controller is better by 21.7% clean and 2.6% disturbed (S2); and all five imitation students match the teacher on a fresh-reference holdout, 0.5% to 6.2% worse in RMSE with CIs inside $\pm10\%$ (S3; the teacher is exact on the clean nominal plant). In **juggling and idealised whip** (S5, S6), residual PPO with the gate-chosen exploration scale degrades its base by 23.8 pp [20.7, 26.9] and 17.6 pp [14.9, 20.3] on HOLD, and by 23.0 pp and 18.7 pp on fresh seeds. The idealised whip base is at 96.8%, so a +5 pp learner effect is impossible there, and for S5 the gate is easy, so it tests plumbing rather than sensitivity. In **realistic whip** (S7), neither learned estimators (+0.9 pp [−3.5, 5.4] on TEST-B) nor PPO (−2.1 pp [−5.2, +1.1]) beat the best classical at that time; 11 PPO and 2 SAC configurations and a 12M-step run all stayed within −3 to +2 pp of initialisation. Privileged-teacher distillation (S8) leaves all students 12–45 pp below T-adapt3-full.

Three of the 8 settings (S5, S6, S7 PPO) had a learner that did not learn, so they cannot show that classical is better. The

TABLE III

LEARNED MINUS STRONGEST CLASSICAL, BY SETTING. SUCCESS SETTINGS IN PERCENTAGE POINTS, TRACKING IN RELATIVE RMSE CHANGE (POSITIVE = LEARNED BETTER). †COMPARED WITH R0, WHICH IS NO LONGER THE STRONGEST CLASSICAL ON WHIP. S5, S6 PPO ROWS USE THE EXPLORATION SCALE CHOSEN BY THE GATE (SINGLE SEED); THE OLDER ROWS WITH THE DEFAULT SCALE ARE IN THE SOURCE TABLES. TEST (n=50) WAS REUSED FOR JUGGLING BY THREE SPIKES; HOLD WAS REUSED (SECTION III). BUDGET RATIOS PER SETTING ARE IN APPENDIX B. THE PILOT S4 HAS NO ROW HERE (SEE THE EQUIVALENCE SUMMARY IN APPENDIX A). THIS TABLE IS GENERATED FROM RESULT FILES BY `FIGURES/MAKE_FIGS.PY`.

Set.	Learned vs. classical	n	Seeds	Δ [95% CI]	Learner
S5	PPO vs T-robust	500	HOLD	−23.8 [−26.9, −20.7]	degrades
S6	PPO vs T-adapt	500	HOLD	−17.6 [−20.3, −14.9]	degrades
S6	L-est vs T-adapt	50	TEST	−15.3 [−22.0, −8.7]	estimator
S7	PPO vs R0	500	HOLD	−2.1 [−5.2, +1.1]	not learned
S7	L-est-full vs R0	500	TEST-B	+0.9 [−3.5, +5.4]	estimator
S7	L-dec4 vs R0 (H14)	500	TEST-C	+6.1 [+1.5, +10.7]	estimator
S7	B vs C-ens (H16a)	500	TEST-D	+5.6 [+0.6, +10.6]	estimator + selection
S7	B vs R0 (weaker baseline)†	500	TEST-D	+16.2 [+11.0, +21.4]	estimator + selection
S8	MIP D-canon vs T-adapt3-full	200	NEW	−12.0 [−19.8, −4.0]	BC student
Tracking, relative RMSE change in % (positive = learned better)					
S1	PPO vs C1 (W0 clean)	50	TEST	−7.1 [−13.8, +0.3]	RL, 5 seeds
S2	PPO vs C1-new (noise+delay, clean)	50	TEST	−21.7 [−25.7, −17.9]	RL, 5 seeds
S2	PPO vs C1-new (noise+delay, disturbed)	50	TEST	−2.6 [−4.5, −0.7]	RL, 5 seeds
S3	BC student vs teacher	500	HOLD	−0.8 [−1.0, −0.6]	imitation
S3	flow-1 student vs teacher	500	HOLD	−0.5 [−0.7, −0.4]	imitation
S3	DDIM-10 student vs teacher	500	HOLD	−6.2 [−6.7, −5.7]	imitation




Fig. 2. Learned minus classical across settings. Left: success-rate settings, grey band ±10 pp, dashed line at the +10 pp bar; the hollow point compares with a weaker baseline (R0). Right: tracking settings in relative RMSE. Bars are 95% bootstrap CIs. Evidence sets differ across rows (Table III).

post hoc TOST rows show equivalence at ±10 pp only for some rows (for example S3, S7 estimators and S7 PPO) and clearly worse learners for others; S1 is undecidable and no row has the learner clearly better by more than 10 pp (Appendix A). Where we write "no detectable difference at the +10 pp bar" we do not claim equivalence.

The realistic whip is the setting where headroom is largest, so it is worth stating its history in one place. On the locked TEST-B set (n=500, one evaluation) the best classical, T-adapt3-full, scored 65.6% [61.4, 69.8], the oracle 89.2%, and the total headroom was +23.6 pp [18.8, 28.4]. The learned estimator with per-link labels (L-est-full) differed from the best classical by +0.9 pp [−3.5, 5.4], and a version without per-link mass labels by −1.2 pp [−5.8, 3.5]; the pre-specified hypothesis that a learned estimator beats the best classical by 10 pp was not supported. Residual PPO on that set was 0.0 pp [−4.0, 4.0], but it used the default exploration scale shown by the gate to be unlearnable, so we use the later 3-seed run (−2.1 pp) instead. These sets motivated the ladder of Section V-B.

Whip needs the qualification that carries K2. Against R0 alone, the learned ensemble B clears the bar on the locked TEST-D set: B−R0 is +16.2 pp [11.0, 21.4]. But a classical Laplace ensemble, C-ens, also beats R0 by +10.6 pp [5.8, 15.4], and against C-ens the learned side is ahead by only +5.6 pp [0.6,




Fig. 3. Headroom ladder on realistic whip, locked TEST-C. Dotted lines mark R0 and R1. Learned estimators sit between R0 and R1; the classical MAP with multi-start sits below R0.




Fig. 4. Robust plan selection on locked TEST-D. Bars: success with 95% CI; numbers above the bars: recovered fraction of the R1−R0 gap. L-ens uses the same frozen estimators as B but no robust selection. The y axis starts at 50%.

10.6] (Section V-B). C-ens exists because an earlier, unlocked study had shown B ahead of R0; the v9 card was written after C-ens was frozen and before TEST-D. A learned advantage of 10 pp or more therefore cannot be excluded, and we do not write "no learned method wins by 10 pp" without this qualification.

B. On realistic whip, parameters are the largest rung and robust plan selection recovers most of that gap

Ladder on a locked set. Fig. 3 shows the ladder on TEST-C (n=500, card v8 committed before the run). The fitted-parameter pipeline R0 reaches 65.6% [61.4, 69.6]; true parameters (R1) reach 83.2% [79.8, 86.4]; adding the true chain state (R2) gives 88.6%; the oracle R4 reaches 93.0% [90.6, 95.2]. The parameter step R1−R0 is +17.6 pp [12.6, 22.6] (H13 supported, Holm $p = 0.00015$). The probe cost R4−R2 is +4.4 pp [0.8, 7.8]: small but not zero, and the pre-specified bound (upper end below +5 pp) failed (H13b not supported). The chain-state step is R2−R1 +5.4 pp [1.6, 9.4], and the total headroom R4−R0 is +27.4 pp [22.6, 32.2]. In the reverse order the chain state first adds +4.8 pp [−0.8, 10.6] and the parameters then add +18.2 pp [13.4, 23.0], so the parameter step is about +18 pp in both orders. The same step appeared on the reused HOLD (+16.8 pp [12.0, 21.6]) and fresh NEW seeds (+13.0 pp [4.5, 21.5]; Appendix C). We call parameter estimation the *largest single rung* of this ladder, not *the* cause: rung sizes depend on order and are not additive.

Learned estimators versus the classical estimator. The pre-specified estimator duel on TEST-C (H14) compares L-dec4 with R0. L-dec4−R0 is +6.1 pp with a 90% CI of [2.2, 9.9], inside ±10 pp, but the Holm-adjusted p is 0.094, so equivalence is *not confirmed* after Holm (the unadjusted TOST passes by 0.1 pp). The estimator recovers 0.34 [0.10, 0.53] of the R0-to-R1 gap, L-est-full 0.10 [−0.18, 0.31], and a classical MAP with multi-start −0.14 [−0.56, 0.16] (descriptive). On the reused HOLD the same duel had given +1.1 pp [−3.3, 5.7], a 4–7% recovered fraction with a CI that crosses 0; the locked number supersedes it. Parameter error falls a lot (log-damping RMS 0.693 to 0.323) while success moves far less, so precision rather than direction of the error is the issue; success is also noisy in $\hat{\theta}$: re-running identical models with float-rounding changes moved HOLD success by up to 3.6 pp.

Robust plan selection (TEST-D). Both selection rules score 8 plus 3 candidate swings in four plausible plants and choose by a worst-case or hit-fraction aggregate. B uses three frozen learned estimators; C-ens uses a Laplace posterior around the classical fit, the same rule on the classical side. Fig. 4 shows TEST-D (n=500, card v9 committed before the run). R0 reaches 66.4% [62.2, 70.6], R1 84.4% [81.2, 87.6], C-ens 77.0% [73.2, 80.6] and B 82.6% [79.2, 85.8]. H15 holds: C-ens−R0 is +10.6 pp [5.8, 15.4]. H15b holds: B−R0 is +16.2 pp [11.0, 21.4]. The share of the R1−R0 gap recovered is 0.59 [0.36, 0.82] for C-ens and 0.90 [0.68, 1.16] for B. H16a holds under Holm: B−C-ens is +5.6 pp [0.6, 10.6] (Holm $p = 0.032$). **H16b is not supported**: the card's rule requires the 95% CI upper end below +10 pp, and it is 10.6. The card is internally inconsistent here: the rule uses the two-sided 95% CI, while the Holm step uses a one-sided p that corresponds to the 90% CI (upper end 9.8, $p = 0.043$). We apply the rule text, so a learned advantage of 10 pp or more is not excluded.

Controls. Before the TEST-D run, a reproduction check on holdout gave B 86.6% and C-ens 79.6% with 100% per-episode agreement with the earlier pipeline. On TEST-D the base candidate of the classical-ensemble run reproduced the independent R0 episode outcome in 100% of episodes, C-ens changed the R0 base pick in 80% of episodes, and the best of the executed candidates would have succeeded in 99.8% of episodes for both runs, so the gap lies in choosing among

candidates rather than in the candidate pool. The method choices were frozen from CAL picks among 22 variants (B) and 20 variants (C-ens); their CAL scores (91.5% and 81.0%) are optimistic against the holdout values (86.6% and 79.6%), a winner's-curse effect that the locked set is meant to remove.

What the learned side contributes alone. The learned estimator without robust selection gives only +4.4 pp [-1.4, 10.0] on TEST-D (L-ens, recovered 0.24); on TEST-C the same ensemble gave +8.0 pp [2.6, 13.6] (descriptive). The two locked sets differ by several points for the same frozen networks, which fits the noise floor above. Costs differ in the other direction: the classical ensemble needs about 63.3 s of CPU per episode against 20.4 s for B, and the learned side paid 13,120 training episode-equivalents with simulator labels. Post hoc and descriptive results, not in any verdict, are a 9-network learned ensemble (84.4% on TEST-D, recovered 1.00 [0.77, 1.29]), the reverse-order ladder, L-ens and C-MAP.

Reading. Most of the R1$-$R0 gap is recovered without better parameters (C-ens). We read this as plan selection mattering more than policy learning, but that is an interpretation of the 0.59 fraction, not a test: averaging the model score over four nearby plants may simply reduce variance in a success rate that is close to chaotic in $\hat{\theta}$, and we did not test this alternative.

C. A multimodal teacher: canonicalising it helps more than a richer student

When the whip teacher is the standard multimodal CMA-ES planner, re-planning the same situation varies by 0.96 rad RMS, as much as plans for different situations (0.92 rad); a continuation-warm-started canonical teacher varies by 0.27 rad within a scenario against 0.73 rad between scenarios. Replacing the multimodal teacher by the canonical one raised every student's success by 17.5–33.5 pp on NEW seeds (BC only, one data size, n=200; Fig. 5 in Appendix D). The best generative student exceeded the MLP by +5.0 pp [-0.3, 10.2] on the multimodal teacher's data: below the +10 pp bar, not an equivalence result, and the best student was identified post hoc. Neither result has locked-set confirmation, and the canonical teacher also changes plan smoothness, so the gain combines multimodality removal with plan regularity.

VI. Discussion

Answer to the main question. Under this protocol, in these settings, the data suggest three conditions, in this order. First, headroom the classical toolbox cannot reach: it exists only on realistic whip (an oracle gap of +27.4 pp on TEST-C), while tracking ties and no juggling cell gained 10 pp from classical re-tuning in a small diagnostic. Second, a learner that passes the sanity gate on that gap at the control level: PPO and SAC did not on whip or juggling, and with the gate-chosen exploration scale PPO degraded S5 and S6 by 23.8 and 17.6 pp. Third, a planning step that does not trust one estimate: scoring candidates across several plausible plants recovers 0.59 [0.36, 0.82] of the parameter gap with a classical Laplace ensemble and 0.90 [0.68, 1.16] with learned estimators, with the learned side ahead by +5.6 pp [0.6, 10.6]. The first and third conditions were met in our data; the second was not. Our reading, an inference rather than a test (Section V-B), is that the ingredient that helped was a *decision rule over an uncertainty set*, usable by either side, plus a small advantage for learned estimators trained with simulator labels. We did not find a control-level learner (PPO, SAC, imitation student) that beats the strongest classical controller, and we have not shown that control-level learning is unattainable.

Counter-evidence against "classical is at least as good". Under actuator noise four times larger, the classical T-adapt3-full lost 12.5 pp while the learned estimator did not: the paired difference is -16.5 pp [-28.5, -5.0] on HOLD (n=200, frozen methods, no re-tuning at the higher noise; Appendix C). This is weak evidence, but together with the locked-set advantage of H16a it argues against a blanket reading of K2.

Threats to the plan-selection reading. Three features could make the headline contrast look cleaner than it is. The classical ensemble uses the generative parameter distribution as a prior, so it is not neutral; the learned estimators see the same distribution as training data. Both selection rules were picked on CAL among 20 or 22 variants, and the multi-start classical family, an obvious alternative, was degenerate in our implementation (it found no distinct second solution in 439 of 500 holdout episodes). Finally, the success rate is close to chaotic in the estimated parameters, so differences of a few points between pipelines sit within the replicate noise we measured. The locked TEST-D set controls the selection effect but not the other two.

What the null does not say. It does not say that learning is worse. Three of eight settings had a learner that did not learn; the RL recipe was one family; 5 of the 8 settings have little or no headroom; and the +10 pp bar is ours. The comparison is also not equal on every axis: the learned estimators used 9–17$\times$ the classical episodes and simulator labels, whereas the classical ensemble costs about three times the CPU time per episode at test time.

Implications for benchmark design. Report the sanity gate and an oracle with every learned-versus-classical table, because a null from a learner that cannot learn a trivial correction is uninformative; tag each result as pre-specified or post hoc; log locked-set accesses; and state which classical baseline is meant when the baseline changes during the study. Our own change of the strongest classical baseline on whip (R0 to C-ens) moved the learned advantage from +16.2 pp to +5.6 pp.

VII. Limitations

1) **RL did not learn where it matters.** On realistic whip, 13 tuned PPO and SAC configurations and a 12M-step run stayed within -3 to +2 pp of initialisation; the first gate passed marginally and later gates are single-seed. Our null is "not learned under this recipe", not "cannot learn".
2) **Holdout reuse.** HOLD selected the best classical baseline and was then reused, so classical numbers are optimistic there (R0 69.2% on HOLD against 65.6–66.4% on the three locked sets).

3) **Our own realism.** Noise, friction and mass magnitudes were set by us, not derived from hardware.
4) **One simulator, one dominant task.** All results are MuJoCo and the mechanistic claims (K3, K4) rest on whip alone; there is no second engine or hardware.
5) **Budgets, multiplicity and the order of the classical upgrade.** Budget ratios were unequal (up to 9–17×); Holm applies within a hypothesis only; the classical ensemble was added after the learned result was seen, and the learned advantage +5.6 pp [0.6, 10.6] does not exclude 10 pp.
6) **Numerical warnings.** The TEST-D log contains 125,555 MuJoCo "simulation unstable" warnings; a re-run on 100 holdout episodes attributes 92–98% of them to planner model rollouts and none to the executed plant (0 of 100 executed episodes diverged), but the check is n=100 on holdout only.

Appendix A gives the full text of these items and the forking paths.

VIII. Conclusion

In a simulated arm benchmark with extended classical tooling, disclosed budgets and pre-specified rules, no control-level learned method beat the strongest classical baseline by +10 pp. On realistic whip, the largest rung of the headroom ladder is parameter estimation (+17.6 pp), and a decision rule that scores candidates across several plausible plants recovers most of it for either side, with the learned side ahead by +5.6 pp [0.6, 10.6] and a 10 pp advantage not excluded. The evidence is one simulator and mostly one task. The next experiments we consider most informative are a control-level learner that demonstrably closes part of the oracle gap, a second task with headroom in a second simulator, and equal-effort classical tuning for the estimator duel.

Acknowledgment

Use of AI tools. The research question, the choice of tasks, every direction change and every decision recorded in the hypothesis cards were made by the author. Most of the code, the execution of the experiments, the statistical analysis and the drafting of this text were carried out by AI agents (Anthropic's Claude models, used through Claude Code) working under the author's direction; internal reviews of the drafts were also simulated with AI agents. The author checked the results reported here and takes full responsibility for the content.

References

[1] J. Wong, V. Makoviychuk, A. Anandkumar, and Y. Zhu, "OSCAR: Data-driven operational space control for adaptive and robust robot manipulation," arXiv:2110.00704, 2021.
[2] S. Bauer, F. Widmaier, M. Wüthrich *et al.*, "Real robot challenge: A robotics competition in the cloud," arXiv:2109.10957, 2021.
[3] E. Aljalbout, F. Frank, M. Karl, and P. van der Smagt, "On the role of the action space in robot manipulation learning and sim-to-real transfer," arXiv:2312.03673, 2023.
[4] P. Kunapuli, J. Welde, D. Jayaraman, and V. Kumar, "Leveling the playing field: Carefully comparing classical and learned controllers for quadrotor trajectory tracking," arXiv:2506.17832, 2025, robotics: Science and Systems (RSS).
[5] A. R. G. Samuel and P. Verma, "Coupled state-space modelling, control, and policy distillation for hybrid rigid-pneumatic manipulators," arXiv:2609.29424, 2026.
[6] J. Nubert, J. Köhler, V. Berenz, F. Allgöwer, and S. Trimpe, "Safe and fast tracking on a robot manipulator: Robust MPC and neural network control," arXiv:1912.10360, 2019.
[7] A. Tagliabue and J. P. How, "Efficient deep learning of robust policies from MPC using imitation and tube-guided data augmentation," arXiv:2306.00286, 2023.
[8] P. Marquez Julbe, J. Nubert, H. Hose, S. Trimpe, and K. J. Kuchenbecker, "Diffusion-based approximate MPC: Fast and consistent imitation of multi-modal action distributions," arXiv:2504.04603, 2025.
[9] T. Silver, K. Allen, J. Tenenbaum, and L. Kaelbling, "Residual policy learning," arXiv:1812.06298, 2018.
[10] T. Johannink, S. Bahl, A. Nair, J. Luo, A. Kumar, M. Loskyll, J. Aparicio Ojea, E. Solowjow, and S. Levine, "Residual reinforcement learning for robot control," arXiv:1812.03201, 2018.
[11] L. Ankile, A. Simeonov, I. Shenfeld, M. Torne, and P. Agrawal, "From imitation to refinement – residual RL for precise assembly," arXiv:2407.16677, 2024.
[12] C. Pan, G. Anantharaman, N.-C. Huang, C. Jin, D. Pfrommer, C. Yuan, F. Permenter, G. Qu, N. Boffi, G. Shi, and M. Simchowitz, "Much ado about noising: Dispelling the myths of generative robotic control," arXiv:2512.01809, 2025, iCLR 2026.
[13] S. Li, L. Sun, and Y. Chen, "One-step flow policy: Self-distillation for fast visuomotor policies," arXiv:2603.12480, 2026.
[14] S. Wu *et al.*, "CoLA-Flow policy: Temporally coherent imitation learning via continuous latent action flow matching for robotic manipulation," arXiv:2601.23087, 2026.

APPENDIX A
DEVIATIONS AND AUDIT

A. Pre-specification audit

Table IV gives, for each spike, whether git shows the rule committed before the result. Timestamps are local commit times on one author clock; the repository has no external timestamping. "YES" means the rule text is in a commit strictly earlier than the first commit containing the result; "UNPROVABLE" means both arrive in one commit or the rule lived in a task prompt. No case was found in which git shows a rule committed after its result.

TABLE IV
GIT ORDER OF RULE AND RESULT.

Spike	Rule and note	Order
01, 02, 03a	Cards v1/v2, same snapshot commit as results; W1/W2 strengths set after a teacher-only look at TEST (spike02)	UNPROVABLE
03b, 05, 06, 07, 09b, 10b	Cards v2–v7.1 committed 1–4 h before results. Deviations: PPO recipe pre-lesson (03b); retroactive log entry (05); checkpoint selection added after round 1 (06); PPO not fixed before TEST (07); plant step changed after CAL tuning and dose curve run after locked TEST-B (10b)	YES
04	H7 written in the result commit and amended after seeing the delay break the old C1	UNPROVABLE, amended
11a, 13b	Rule in a task prompt or README of the result commit	UNPROVABLE
12a, 13a, 14a	Headline rule in the decision log earlier; details in the result commit. 13a: gate bias fell back to 6 Nm and the gate was judged on n=500 instead of 200	YES for headline
15a (TEST-C)	Cards v8 and v8.1 committed on their own about 2 h before the run; v8.1 re-trained L-dec4, predictions identical to the stored ones	YES
15b, 15c, 15d	Rules in README section 0 only; X1 (15b) and the 9-network extension (15c) added after results and labelled post hoc	UNPROVABLE
15e (TEST-D)	Card v9 committed on its own 1 h 22 min before the run; the code was uncommitted at run time, and the gated step was finished by the orchestrator with unchanged code	YES (card)
16a	Rule in README section 0, same commit as results; code uncommitted at run start	UNPROVABLE
learn_demo	Not pre-specified; hyper-parameters chosen after one TEST look; stale, superseded by S3 re-run	NO

B. The v9 card is internally inconsistent for H16b

The card's H16b rule is "B − C-ens, 95% CI upper end below +10 pp". Its Holm step uses a one-sided bootstrap p for H_0: difference ≥ 10, which corresponds to the 90% CI. On TEST-D the 95% upper end is 10.6 (rule fails), the 90% CI is [1.4, 9.8], and the one-sided p is 0.0432, which would pass at $\alpha = 0.05$ alone. We treat the rule text as binding, so H16b is not supported, and never write that the advantage is below 10 pp. The card's pre-written sentence for this outcome, applied on Holm-surviving verdicts, reads that the learned advantage may be ≥ 10 pp and that the paper rewrites K2 accordingly; Section V-A does so.

C. Order of the classical upgrade (C-ens)

The classical ensemble C-ens was built *after* the learned ensemble B had beaten R0 on holdout (a first commit at 18:07 on the day of the study) and was frozen in a second commit at 20:31; its selection was written to a file before holdout and new-seed collection, and the v9 card was written at 20:32, after C-ens was frozen and before TEST-D. B−C-ens is therefore a pre-specified locked contrast, but the classical comparator was built with the learned result in view. The rule was developed first for the learned side and then given to the classical side. C-ens was chosen on CAL among 20 ensemble variants (B among 22) and uses the generative parameter distribution as a prior (a disclosed, non-neutral choice); no Laplace-width sensitivity run was made, and the multi-start classical family was degenerate (439 of 500 holdout episodes without a distinct second solution). On the pre-locked sets the contrast was B−C-ens +7.0 pp [2.6, 11.4] (holdout) and +4.0 pp [−3.0, 11.0] (new seeds), verdict UNCERTAIN by the README rule.

D. Audit log scope

The log has 111 lines: 47 from the demo-student script, 56 from one MJX evaluation, one each for juggling spikes 05, 06, 07 (05 and 06 retroactively), whip spike 09b, TEST-C and TEST-D, and two for spike 10b (TEST-B and TEST). The log is written only by the arena's `evaluate`. The TEST evaluations of spikes 01, 02, 03a, 03b and 04 ran outside it; spikes 15b–15d and 16a added no lines because guards block the locked sets. TEST (seeds 0–49) was reused across several spikes, on the same task for juggling (05, 06, 07).

E. Equivalence summary (post hoc TOST)

Equivalent within ±10 (whole 90% CI inside): S2 disturbed, S3 (all five students), S4 restitution (pilot), S5 oracle-PPO (legacy), S7 L-est-full, L-est-eff, PPO (13a) and OOD. Within ±5 as well: S2 disturbed, S3 BC, MIP and flow, S5 oracle-PPO, S7 L-est-full and PPO. Not decidable: S1 (all four cells), S6 oracle-PPO (legacy), S8 best D-canon student. Learned clearly worse (90% CI below −10): S2 clean, S4 mass and sensing (pilot), S5 PPO (−23.8) and SAC, S6 PPO (−17.6) and L-est, S8 D-multi students. Learned clearly better beyond ±10: none.

F. Full limitations

1) **RL did not learn in the settings that matter most.** On realistic whip, 11 PPO and 2 SAC configurations tuned on CAL, three seeds of 3M steps and a 12M-step run all stayed within -3 to +2 pp of initialisation; in idealised whip all six PPO runs were flagged not learned; in juggling the residual stayed at 0.15–0.18 Nm of a 12 Nm cap and 4 of 6 runs chose the first checkpoint. The gate passed marginally, only after raising the exploration scale, among 8 gate runs. The S5 and S6 re-runs degrade the base by 23.8 and 17.6 pp, but each gate is a single-seed shot, the S5 gate is easy, the S6 budget is 3.2× classical, the recipe was not swept on the real condition, and the asymmetric-critic gate failed. The null is "not learned under about 3–12M steps, one recipe per setting and about 13 tuned configurations on whip".
2) **Holdout reuse.** HOLD was used to choose best-classical in spikes 09b and 10b (on 300 of the 500 seeds) and then as the main evaluation set in spikes 13a, 13b and 14a. R0 is 69.2% on HOLD against 65.6, 65.6 and 66.4% on TEST-B, TEST-C and TEST-D. The multimodal-teacher result, the group split, the fragility sweep and the 9-network extension have no locked-set confirmation.
3) **Realistic conditions are our own choice.** The friction value is an estimate.
4) **One simulator.** No second engine, no hardware.
5) **Concentration on whip.** Five of the eight settings are tracking or juggling, where headroom is small or absent.
6) **Unequal tuning knobs.** The classical side tuned 5–13 parameters with 750–9,050 episodes and received the generative distribution as bounds and priors; the learned side used 10^4–10^5 episodes and simulator labels. In the estimator duel the classical side tried only three strengthened variants.
7) **Forking paths.** W1/W2 strengths set after seeing TEST (spike02); hyper-parameters chosen after one TEST look (learn_demo); RL recipe repaired after round 1 (spike06); PPO not fixed before TEST (spike07); plant step changed after CAL tuning and dose curve after the locked TEST-B (spike10b); post hoc analyses in spikes 13b and 14a. There is no correction across spikes, so positive exceptions are exploratory.
8) **Pipeline noise.** Re-running identical estimator models with float-rounding changes moved holdout success by up to 3.6 pp per model, comparable to several reported differences.
9) **Power and equivalence.** Most pre-specified tests had CI half-widths of 4–9 pp (TEST n=50 comparisons up to about 15 pp). "No side wins at the 10 pp bar" is not an equivalence test. Differences of +1 to +5 pp (for example the three-model ensemble, +4.8 pp [-0.8, 10.4]) cannot be excluded.
10) **Fairness of the plan-selection duel.** See the C-ens paragraph above; the learned side used 13,120 training episodes with simulator labels, and both sides are frozen by the v9 card.
11) **Pre-specified versus post hoc.** Besides the earlier spikes marked YES in Table IV, only cards v8, v8.1 and v9 were committed on their own before their runs; spike15b/15c/15d rules are README-only; the 9-network extension, B9, the reverse-order ladder, S6-X1 and L-ens/C-MAP are post hoc or descriptive.
12) **Numerical warnings.** The check of the 125,555 warnings (4,621 on holdout) was a re-run on 100 holdout episodes; the full holdout and TEST-D check was not repeated. No executed episode record contained a non-finite outcome.
13) **Order of the classical upgrade.** See above.

APPENDIX B
BUDGETS AND THE RL GATE

TABLE V
BUDGET BY SPIKE (EPISODES, STEPS, WALL-CLOCK WHERE REPORTED). COUNTING CONVENTIONS DIFFER BETWEEN STEPS, EPISODES AND PROBE-EQUIVALENTS; THE SPIKE09B CLASSICAL DESIGN COST (ABOUT 1,300 EPISODES) IS AN ESTIMATE.

Spike	Classical side / learned side	Ratio
03a (tracking)	classical tuning 6.4M–9.0M steps; RL 2M steps per policy	classical about 7.7× (C1+C2, one weakness)
06 (juggling)	classical 118.2M steps; RL 121.0M	1.02×
07 (juggling)	PPO and oracle about 144M steps (107.6M without out-of-memory reruns); SAC 27M	2.3× (1.7×)
10b (whip)	classical 11,300 episodes (2× cap 22,600); learned methods each inside the cap	within cap
13a (whip RL)	about 160k episodes vs 22.6k classical	about 7×
14a (estimator duel)	learned about 13,120 episode-equivalents vs classical about 1,500	9–17×
15b (S6 re-run)	33k episodes vs 10,350 classical	3.2×
16a (catch / toss / Push-T)	classical tuning 16,200 / 10,200 / 2,100 episodes; PPO 16,227 / 10,222 / 2,114	about 1×

APPENDIX C
REPLICATION ON REUSED AND FRESH SEEDS, AND SENSITIVITY

On TEST-B the total headroom (T-oracle minus the best classical) is +23.6 pp [18.8, 28.4]. The R2−R1 step is significant on NEW but not on HOLD, and the R4−R2 sign flips, so these blocks are not replicated as real; the earlier suggestion that the oracle gap was mostly probe time and chain state was a winner's-curse artefact and is superseded. A post hoc group split on HOLD (wrong damping 18.4 pp, per-link masses 16.2, length 7.4, friction 4.6 when only that group is wrong) is non-additive and not used for claims.

Under sensor noise the ordering is not distinguishable (T-adapt3-full -10.0 pp [-19.5, -1.0] at ×2, L-est-full +0.5 [-8.5, 9.5]). The paired difference of the two drops at actuator noise ×4 is -16.5 pp [-28.5, -5.0].

TABLE VI

ALL RL GATES AND CHECKPOINT DECISIONS (SINGLE SEED OR BEST-OF-N FLAGGED). DIFFERENCES ARE PAIRED LEARNED MINUS INITIALISATION (GATES) OR MINUS BASE (REAL CONDITIONS), IN PP.

Gate or run	What is single-seed or best-of	Result
13a gate, log-std -3.5 (default)	gate set n=200	-3.0 [-8.5, +2.5]
13a gate, log-std -2.0	HOLD n=500	+7.8 [3.0, 12.8]
13a gate, log-std -1.5, 3M steps	best of 8 runs, CAL-selected	+10.2 [4.8, 15.6]
13a gate, SAC	single seed	+1.8 [-3.4, 7.0]
13a real condition	11 PPO + 2 SAC configs, one seed each; confirmation 3 seeds	HOLD -2.1 [-5.2, 1.1]; NEW -1.3 [-6.5, 3.8]; 12M steps -0.6 [-4.6, 3.4]
15b S6 gate (bias 6 Nm)	one seed, one shot	+15.4 [10.2, 20.6]
15b S5 gate (bias 1 Nm)	one seed, one shot; easy gate	+63.2 [58.8, 67.4]
15b S6-X1 (weak base, post hoc)	CAL picks looked like +5.0, +11.5, +5.0 and vanished on disjoint seeds	holdout -5.0 [-8.7, -1.5]; fresh -3.3 [-8.7, +2.0]
15c asymmetric critic	two seeds, one extra attempt allowed; failed	+7.2 [2.0, 12.4]; +1.2 [-4.0, 6.4]

TABLE VII

HEADROOM LADDER ON HOLD (n=500) AND NEW (n=200): SUCCESS % [95% CI].

Rung	HOLD	NEW
R0 fitted	69.2 [65.2, 73.2]	69.0 [62.5, 75.5]
R1 true θ	86.0 [83.0, 89.0]	82.0 [76.5, 87.0]
R2 + chain state	89.0 [86.2, 91.6]	89.5 [85.0, 93.5]
R3 oracle at rest, waits 0.6 s	88.2 [85.4, 91.0]	85.5 [80.5, 90.5]
R4 oracle	90.8 [88.2, 93.2]	87.5 [82.5, 92.0]
R5 canonical oracle	92.0 [89.6, 94.2]	92.5 [88.5, 96.0]
L-est-full (3 nets)	64.7 [62.1, 67.3]	66.7 [62.5, 70.8]
R1$-$R0	+16.8 [12.0, 21.6]	+13.0 [4.5, 21.5]
R2$-$R1	+3.0 [-1.0, 7.0]	+7.5 [1.0, 14.0]
R4$-$R2	+1.8 [-1.6, 5.4]	-2.0 [-8.0, 4.0]

Dose curve and out-of-distribution. On HOLD (n=200 per level; run after the locked TEST-B), success of best classical / L-est-full / L-est-eff / T-oracle is 71.0 / 64.3 / 67.5 / 92.0 at $\times$0.5, 69.5 / 61.2 / 61.2 / 89.5 at $\times$1 and 53.0 / 60.3 / 56.8 / 91.0 at $\times$2. The paired L-est-full minus classical is -6.7 [-13.5, 0.2], -8.3 [-16.2, -0.3] and +7.3 [-0.0, 14.7]: a single point at the strongest condition. For estimators trained or tuned at $\times$0.5 and $\times$2 and evaluated at $\times$1, L-est-OOD minus T-adapt3-OOD is +5.9 pp [1.1, 10.8] on TEST-B, but the classical OOD variant was tuned with fewer episodes (350). Classical was not re-tuned at $\times$2.

Estimator duel on reused sets. L-dec4$-$R0 is +1.1 pp [-3.3, 5.7] on HOLD and +0.5 pp [-6.7, 7.8] on NEW (recovered 0.07 and 0.04). The post hoc three-model ensemble gives +4.8 pp [-0.8, 10.4] and +3.5 pp [-5.0, 12.0]. Adding independent Gaussian noise of the learned estimator's size to the true parameters gives 65.0% (noise $\times$1) and 74.0% ($\times$0.5) against 86.0% for the true parameters, a post hoc diagnostic that the planner needs errors well below the learned error. Classical strengthening (MAP prior, multi-start, K-step resets) did not improve the pipeline.

APPENDIX D
MULTIMODAL TEACHER (K4) AND PRIVILEGED DISTILLATION

Canonicalising the teacher raised each student by: MLP 25.7 pp [19.8, 31.5], MIP 33.5 pp [28.0, 38.8], DDIM-10 23.3 pp [17.7, 29.0], flow-10 23.3 pp [17.3, 29.2], flow-1 17.5 pp [11.7, 23.5]. On D-multi, the differences from the MLP are flow-1 +5.0 [-0.3, 10.2], flow-10 +3.8 [-1.0, 8.7], diffusion -3.2 [-7.7, 1.3] and MIP -4.2 [-8.8, 0.5]. The canonical oracle teacher reaches 96.0% [93.0, 98.5] and T-adapt3-full 67.0% [60.5, 73.5], so the best D-canon student (MIP, 55.0%) is -12.0 pp [-19.8, -4.0] below it (best student chosen on the same final episodes, which is optimistic for the learned side); all D-multi students are 36.3–45.5 pp below. In the earlier privileged-teacher study (NEW n=200), the canonical oracle reached 92.5%, T-adapt3-full 60.0% and the students 58.0–59.5%. Seed-to-seed spread was 5–15 pp. The data are NEW only, behaviour cloning only (no DAgger) and one data scale (400 scenarios).

TABLE VIII

ACTUATOR-NOISE SWEEP, HOLD SEEDS 1100–1299 (n=200), PAIRED DROP RELATIVE TO THE $\times$1 NOISE LEVEL (PP [95% CI]). METHODS FROZEN, NOT RE-TUNED PER LEVEL.

Method	$\times$2	$\times$4	$\times$8
T-adapt3-full	+0.5 [-7.5, 8.5]	-12.5 [-21.5, -3.5]	-14.5 [-24.0, -5.0]
L-est-full	+7.0 [-1.5, 15.5]	+4.0 [-5.0, 13.0]	-0.5 [-10.0, 9.0]
T-oracle	+0.5 [-3.0, 4.0]	-3.5 [-7.0, 0.0]	-1.0 [-4.0, 1.5]




Fig. 5. Five students trained on data from the standard multimodal teacher (D-multi) or the canonical teacher (D-canon), NEW seeds (n=200), mean over three training seeds, 95% CI. The dashed line is T-adapt3-full on the same seeds.

APPENDIX E
BREADTH: OTHER TASKS AND CLASSICAL PILOTS

Residual PPO on catch, toss and Push-T. Table IX gives the mini-comparisons (rules in a spike README, order not provable from git; breadth only). Catch and Push-T ties are at the ceiling, where a +10 pp win is arithmetically impossible, and toss is uninterpretable because its gate failed four times (best +1.3 pp). Local and remote runs of 30 episodes had identical outcomes, lengths and joint trajectories; the only difference was 7.8e-16 in a Push-T summary statistic.

TABLE IX
RESIDUAL PPO ON THE CAL-TUNED STRONGEST CLASSICAL, LEARNED MINUS CLASSICAL (PP [95% CI]).

Task	Gate (pp)	Classical HOLD / NEW	HOLD (n=500)	NEW (n=200)	Verdict
Catch	+54.0 [48.3, 59.7]	0.992 / 1.000	−0.5 [−1.1, 0.1]	−0.7 [−1.8, 0.0]	tie (ceiling)
Push-T	+61.3 (1 seed)	0.990 / 0.995	+0.4 [−0.4, 1.2]	−1.5 [−3.5, 0.0]	tie (ceiling)
Toss	failed 4 times	0.680 / 0.685	+0.6 [−1.2, 2.4]	−1.0 [−3.0, 1.0]	no verdict

Classical pilots (demo seeds, no learned comparison). On the tracking ladder (n=5) the RMSE is 0.0074 (PID), 0.0061 (CTC+LQR), 0.0056 (iLQR), 0.0056 (iLQR-MPC) and 0.0073 (MPPI) rad. Catching succeeds 19 of 20 without error but 6 of 20 with 10 ms ball-position delay; whip with a chain 10% shorter succeeds 12 of 20; Push-T succeeds 19 of 20 with 20 ms sensor delay and 0 of 20 with 30 ms. These pilots motivated choosing whip and are not paper claims. An MJX-trained PPO reproduced the CPU PPO within CI with 4.7e6 steps/s on 4096 environments; this engineering result is not used for K1–K4.