INDUSTRIAL POLLUTION AND ENVIRONMENTAL MANAGEMENT

A PROJECT REPORT

Submitted by

NIDHISH RAGAV A	**2303811714821026**
PRASANNA I	**2303811714821030**
THIRUMURUGAN V	**2303811714821052**
SIVASRI D	**2303811714822047**

in partial fulfillment of the requirements for the award degree of Bachelor of Engineering

GEA1401 - ENVIRONMENTAL SCIENCES

DEPARTMENT OF CSE (ARTIFICIAL INTELLIGENCE AND MACHINE LEARNING)

K.RAMAKRISHNAN COLLEGE OF TECHNOLOGY (AUTONOMOUS)

SAMAYAPURAM - 621112

NOVEMBER 2026

K.RAMAKRISHNAN COLLEGE OF TECHNOLOGY (AUTONOMOUS)

SAMAYAPURAM - 621112

BONAFIDE CERTIFICATE

The work embodied in the present project report entitled **"INDUSTRIAL POLLUTION AND ENVIRONMENTAL MANAGEMENT"** has been carried out by the students NIDHISH RAGAV A, PRASANNA I, THIRUMURUGAN V, SIVASRI D. The work reported herein is original and we declare that the project is their own work, except where specifically acknowledged, and has not been copied from other sources or been previously submitted for assessment.

Date of Viva Voce:…….

Dr. M. GOVINDARAJ., M.Sc., B.Ed., M.Phil., Ph.D.,
SUPERVISOR
Professor of Chemistry, Department of Science and Humanities,
K. Ramakrishnan College of Technology,
Samayapuram- 621112.

Dr. T. AVUDAIAPPAN M.E., PhD.,
HEAD OF THE DEPARTMENT
Professor
Department of CSE (Artificial Intelligence and Machine Learning),
K. Ramakrishnan College of Technology,
Samayapuram - 621112

INTERNAL EXAMINER **EXTERNAL EXAMINER**

ABSTRACT

Industrial activities can release particulate matter, gaseous emissions, untreated wastewater effluents, and solid waste, creating serious risks to surrounding communities and ecosystems. Monitoring this pollution is difficult when environmental records are scattered across separate files, lack clear safety context, and provide no direct guidance for corrective action. This project presents EcoWatch, a prototype software platform designed to organize industrial air and water pollution records, compare pollutant values against reference Central Pollution Control Board (CPCB) safety benchmarks, flag potential exceedances, and suggest practical pollution-management actions. The system follows a five-stage architecture comprising Real Data Sources (CPCB, OpenAQ, and Data.gov.in logs), Data Ingestion and Validation using Python and Pandas, a FastAPI Backend with a rule-based recommendation engine, a relational SQLite Database, and an interactive React Web Dashboard powered by Recharts. Using point-source facility records, EcoWatch evaluates stack PM2.5 emissions (2026.0 μg/m³ vs. 60 μg/m³ CPCB limit) and wastewater BOD discharge (5.8 mg/L vs. 30 mg/L limit), pairing transparent risk flags with practical abatement recommendations.

Keywords: Industrial Pollution, Environmental Management, EcoWatch, Air and Water Quality Monitoring, CPCB NAAQS Benchmarks, FastAPI, React Dashboard.

ACKNOWLEDGEMENT

We thank our **Dr. N.Vasudevan**, Principal, for his valuable suggestions and support during the course of project work.

We thank our **Dr.T.Avudaiappan M.E., Ph.D.,** Head of the Department, Professor, Department of CSE (Artificial Intelligence and Machine Learning), for his valuable suggestions and support during the course of the project work.

We wish to record my deep sense of gratitude and profound thanks to our Guide **Dr. M. GOVINDARAJ M.Sc., B.Ed., M.Phil., Ph.D.,** Supervisor**,** Professor of Chemistry, Department of Science and Humanities, for his keen interest, inspiring guidance, constant encouragement with our work during all stages, to bring this report into fruition.

We are extremely indebted to our project coordinator **Dr. M. GOVINDARAJ M.Sc., B.Ed., M.Phil., Ph.D.,** Professor of Chemistry, Department of Science and Humanities, for his valuable suggestions and support during the course of our project work.

We also thank the faculty and non-teaching staff members of the Department of CSE (Artificial Intelligence and Machine Learning), K. Ramakrishnan College of Technology, Tiruchirappalli for their valuable support throughout the course of our project work.

Finally, we thank our parents, friends and our well wishes for their kind support.

SIGNATURE

NIDHISH RAGAV A

PRASANNA I

SIVASRI D

THIRUMURUGAN V

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT	**iii**
	LIST OF TABLES	**ix**
	LIST OF FIGURES	**x**
	LIST OF SYMBOLS AND ABBREVIATIONS	**xi**
1	**INTRODUCTION**	**1**
	1.1 BACKGROUND	1
	1.2 PROBLEM STATEMENT	2
	1.3 EXISTING SYSTEMS	2
	1.4 OBJECTIVES OF THE PROJECT	3
	1.5 PROPOSED SYSTEM AND APPLICATIONS	4
2	**LITERATURE SURVEY**	**6**
	2.1 REVIEW OF OPEN AIR QUALITY DATA PLATFORMS FOR ENVIRONMENTAL HEALTH RESEARCH AND ACTION PAPER	6
	2.2 REVIEW OF TRANSFORMING AIR POLLUTION MANAGEMENT IN INDIA WITH AI AND NAAQS BENCHMARKS PAPER	6
	2.3 REVIEW OF AERQ: A WEB-BASED DECISION SUPPORT TOOL FOR AIR QUALITY ASSESSMENT PAPER	7

CHAPTER NO.	TITLE	PAGE NO.
	2.4 REVIEW OF EXCEEDANCES AND TRENDS OF PARTICULATE MATTER (PM2.5) IN INDIAN CITIES PAPER	7
	2.5 REVIEW OF OPTIMIZING PROCESSES FOR BOD, COD AND TSS REMOVAL FROM WASTEWATER PAPER	8
3	**SYSTEM ARCHITECTURE AND SOFTWARE REQUIREMENTS**	**11**
	3.1 ECOWATCH TECHNICAL ARCHITECTURE OVERVIEW	11
	3.2 FIVE-STAGE ARCHITECTURE DESCRIPTION	12
	3.2.1 Stage 1: Real Data Sources	12
	3.2.2 Stage 2: Data Ingestion and Validation	12
	3.2.3 Stage 3: FastAPI Backend	12
	3.2.4 Stage 4: SQLite Database	13
	3.2.5 Stage 5: React Web Dashboard	13
	3.3 SOFTWARE AND DATA REQUIREMENTS	14
4	**METHODOLOGY AND WORKING PRINCIPLE**	**18**
	4.1 WORKING PRINCIPLE OVERVIEW	18

CHAPTER NO.	TITLE	PAGE NO.
	4.2 DATA INGESTION, NORMALIZATION, AND PROVENANCE VALIDATION	19
	4.3 RULE-BASED RISK FLAGGING ENGINE AND BENCHMARK REASONING	20
	4.4 PRACTICAL POLLUTION-MANAGEMENT RECOMMENDATIONS	20
	4.5 ANALYTICAL GUARDRAILS AND SOURCE ATTRIBUTION DISCLAIMERS	21
5	**RESULTS AND DISCUSSION**	**23**
	5.1 ECOWATCH MULTI-MEDIUM POLLUTION DISTRIBUTION OUTPUT	23
	5.2 INDUSTRIAL MULTI-MEDIUM POLLUTION AUDIT: AIR EMISSIONS VS. CPCB SAFETY THRESHOLD	24
	5.3 DISCUSSION OF EXPLAINABLE RISK FLAGS AND MANAGEMENT ACTIONS	25
6	**CONCLUSIONS AND FUTURE SCOPE**	**28**
	6.1 CONCLUSIONS	28
	6.2 FUTURE SCOPE	28
7	**APPENDIX**	**30**
	7.1 PROGRAMMING	30

CHAPTER NO.	TITLE	PAGE NO.
	7.1.1 EcoWatch FastAPI Backend, Pandas Normalization, and SQLite Service (main.py)	30
	7.1.2 EcoWatch React + Recharts Dashboard Component Overview (Dashboard.jsx)	32
	7.2 ENVIRONMENTAL POLLUTION INDEX AND EXCEEDANCE CALCULATIONS	33
	7.2.1 Pollutant Exceedance Factor and Risk Ratio Calculations	33
	7.2.2 Required Particulate Abatement Efficiency Calculation	33
8	**REFERENCES**	**35**

LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
2.1	Summary of Literature Survey on Industrial Pollution Monitoring and Environmental Management	9
3.1	Software Requirements and Technical Specifications for the EcoWatch Prototype	15
3.2	Monitored Environmental Parameters and Configurable Regulatory Benchmarks (CPCB / NAAQS)	16
5.1	Summary of EcoWatch Multi-Medium Audit Results, Risk Flags, and Recommended Engineering Controls	26
7.1	Pollutant Exceedance Factors and Required Abatement Efficiency Calculations	34

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE NO.
3.1	EcoWatch Technical Architecture — Industrial Pollution Monitoring and Environmental Management	12
3.2	EcoWatch Relational Database Schema, FastAPI REST Endpoints, and Rule-Based Recommendation Engine	14
4.1	EcoWatch End-to-End Working Principle Flowchart	19
4.2	Industrial Stack Particulate Control Efficiency and ETP Wastewater BOD_5 Reduction Profile	21
5.1	EcoWatch Dashboard Output — KPI Cards and Multi-Medium Pollution Distribution Across Facilities	23
5.2	EcoWatch Dashboard Output — Industrial Multi-Medium Pollution Audit: Actual Emissions vs. CPCB Safety Threshold	25
5.3	EcoWatch Explainable Risk Flag Evaluation — Ratio of Measured Concentration to CPCB Statutory Limit	26

LIST OF SYMBOLS AND ABBREVIATIONS

CPCB	-	Central Pollution Control Board
MoEF&CC	-	Ministry of Environment, Forest and Climate Change
NAAQS	-	National Ambient Air Quality Standards
OGD	-	Open Government Data Platform India
AQI	-	Air Quality Index
PM2.5	-	Fine Particulate Matter (aerodynamic diameter <= 2.5 µm)
PM10	-	Respirable Particulate Matter (aerodynamic diameter <= 10 µm)
SO_2	-	Sulfur Dioxide
NO_2	-	Nitrogen Dioxide
VOCs	-	Volatile Organic Compounds
CO	-	Carbon Monoxide
BOD	-	Biochemical Oxygen Demand
COD	-	Chemical Oxygen Demand
TSS	-	Total Suspended Solids
ETP	-	Effluent Treatment Plant
TSDF	-	Treatment, Storage, and Disposal Facility
API	-	Application Programming Interface

CHAPTER 1

INTRODUCTION

1.1 BACKGROUND

Rapid industrialization has driven economic growth and manufacturing productivity, yet industrial processes simultaneously generate complex multi-medium pollution loads across air, water, and land. Thermal combustion boilers, metallurgical smelting furnaces, chemical synthesis plants, and manufacturing units release fine and coarse particulate matter (PM2.5 and PM10), gaseous oxides such as sulfur dioxide (SO_2), nitrogen dioxide (NO_2), carbon monoxide (CO), and volatile organic compounds (VOCs), alongside organic-rich industrial wastewater measured by Biochemical Oxygen Demand (BOD) and Chemical Oxygen Demand (COD), as well as hazardous solid chemical sludge.

Effective environmental management requires timely, transparent, and scientifically grounded monitoring of these pollutant streams against statutory benchmarks established by regulatory authorities such as the Central Pollution Control Board (CPCB) and the Ministry of Environment, Forest and Climate Change (MoEF&CC) under the National Ambient Air Quality Standards (NAAQS) and general effluent discharge standards. However, raw environmental measurements are frequently fragmented across heterogeneous government portals, monitoring stations, and laboratory spreadsheets. Developing a centralized, data-driven software platform that unifies verified environmental measurements, preserves data provenance, highlights threshold exceedances through explainable rule-based risk flags, and recommends practical engineering controls is essential for modern industrial environmental management.

1.2 PROBLEM STATEMENT

Industrial activities can release particulate matter, gaseous pollutants, wastewater, and hazardous waste that affect people and ecosystems. Environmental measurements are often distributed across monitoring stations, datasets, and reports, making comparisons and timely review difficult. A centralized, data-driven system can organize verified readings, show trends, and support pollution-control decisions without assuming that ambient readings prove a specific factory caused pollution.

Specifically, when ambient air-quality records, point-source stack logs, and effluent quality reports are stored in incompatible file formats with inconsistent pollutant naming conventions, non-standardized units (such as µg/m³, mg/m³, ppm, or mg/L), and varying timestamp structures, environmental analysts face delays in identifying abnormal concentration spikes. At the same time, responsible environmental science requires distinguishing between ambient background concentrations (which reflect meteorology, traffic, and multiple regional sources) and point-source facility emissions, ensuring that automated risk flags remain transparent, auditable, and grounded in documented averaging periods and regulatory thresholds.

1.3 EXISTING SYSTEMS

In existing environmental monitoring workflows, environmental monitoring data may be collected by separate agencies, monitoring stations, and laboratory programmes. Air-quality and water-quality records frequently use different measurement units, timestamp formats, station identifiers, and reporting conventions. Consequently, environmental management teams often need to consult separate web portals or disconnected spreadsheets to compare readings and prepare compliance summaries.

The primary limitations identified in the existing system include:

• **Inconsistent Data Formats and Missing Values:** Heterogeneous schemas, unstandardized pollutant labels, and missing sensor values make automated cross-station analysis difficult.

• **Fragmented Visibility Across Locations and Time Periods:** Separate agency portals and isolated spreadsheets reduce holistic visibility across monitoring stations, media (air, water, and land), and historical periods.

• **Delayed Identification of Unusual Readings:** Manual compilation and delayed review slow the identification of acute pollutant spikes or threshold exceedances.

• **Source Attribution Ambiguity in Ambient Monitoring:** Ambient air or surface-water monitoring alone does not establish the specific industrial source of a pollutant without dispersion modeling, wind-vector analysis, or direct stack/effluent sampling.

1.4 OBJECTIVES OF THE PROJECT

The main objective of this project is to develop EcoWatch, a full-stack environmental monitoring prototype that imports real publicly available air-quality data, stores measurements and source metadata, visualizes trends, flags readings against documented configurable benchmarks, and presents practical pollution-management recommendations, with water-quality analysis included when a suitable verified dataset is available. The specific objectives are:

• **Automated Ingestion and Normalization of Real Environmental Data:** To import real ambient air-quality records from India Open Government Data (OGD) or OpenAQ alongside verified CSV datasets, normalizing pollutant names, units, timestamps, and station metadata.

• **Persistent Relational Storage with Full Provenance:** To store validated measurements, station coordinates, and original data-source provenance in a relational SQLite database accessed through a Python FastAPI REST backend.

• **Interactive Multi-Medium Trend Visualization:** To build a responsive React and Recharts web dashboard that filters and visualizes pollution records by station, pollutant, medium (air, water, land), and date.

• **Explainable Rule-Based Risk Flagging and Engineering Recommendations:** To generate transparent risk flags showing the exact regulatory benchmark and reasoning for each flag, paired with practical pollution-control recommendations for filtration, scrubbers, wastewater treatment, and hazardous waste handling, plus CSV export.

1.5 PROPOSED SYSTEM AND APPLICATIONS

To address the limitations of fragmented environmental reporting, the proposed EcoWatch system provides a five-stage full-stack architecture connecting verified open environmental data sources with a Python FastAPI validation service, a SQLite database, and a React analytical dashboard. The core features of the proposed system are:

• **Real Data & CSV Import Pipeline:** Imports real ambient air-quality measurements from India Open Government Data (OGD) or OpenAQ when API access is available, and supports structured CSV import for verified air, water, and facility audit records.

• **Automated Schema & Unit Normalization:** Standardizes pollutant identifiers (PM2.5, PM10, SO_2, NO_2, VOCs, CO, BOD, COD, Sludge), measurement units (µg/m³, mg/m³, mg/L, MT/month), ISO-8601 timestamps, and station metadata.

• **FastAPI Backend & SQLite Persistence:** Stores validated measurements and source provenance in a SQLite database (with optional PostgreSQL scalability) and exposes RESTful JSON endpoints.

• **Explainable Rule-Based Risk Flags:** Evaluates every reading against documented configurable benchmarks (such as CPCB NAAQS and effluent

standards) and displays both the benchmark value and explicit reasoning on each risk flag.

• **Practical Pollution-Control Recommendations & CSV Export:** Presents actionable remediation guidance covering baghouse filtration, electrostatic precipitators, wet scrubbers, Effluent Treatment Plant (ETP) biological oxidation, and Treatment, Storage, and Disposal Facility (TSDF) hazardous sludge containment, while allowing users to export filtered measurements and summaries to CSV.

CHAPTER 2

LITERATURE SURVEY

2.1 REVIEW OF OPEN AIR QUALITY DATA PLATFORMS FOR ENVIRONMENTAL HEALTH RESEARCH AND ACTION PAPER

"Open Air Quality Data Platforms for Environmental Health Research and Action", by Colleen Marciel Rosales, Jennifer R. Bratburd, Sebastian Diez, and Sara Duncan in 'Current Environmental Health Reports', 2025.

In this study, the authors survey global open air-quality data platforms—including OpenAQ and national government portals—that aggregate harmonized air pollution measurements (PM2.5, PM10, SO_2, NO_2, O_3, and CO) from regulatory reference monitors and sensor networks. The paper highlights that harmonizing disparate station identifiers, reporting units, averaging periods, and source metadata is critical for enabling transparent environmental health research and evidence-based pollution management. These findings directly informed EcoWatch's data ingestion and provenance-retention layer.

2.2 REVIEW OF TRANSFORMING AIR POLLUTION MANAGEMENT IN INDIA WITH AI AND NAAQS BENCHMARKS PAPER

"Transforming Air Pollution Management in India with AI and Machine Learning Technologies", Published in 'Scientific Reports (Nature Portfolio)', vol. 14, Art. no. 20412, 2024.

This research examines the evolution of air pollution legislation, the National Ambient Air Quality Standards (NAAQS) enforced by the Central Pollution Control Board (CPCB) in India, and the Air Quality Index (AQI) framework alongside data-driven air quality management strategies. The

authors emphasize that fine particulate matter (PM2.5, 24-hour CPCB standard of 60 μg/m³) and respirable particulate matter (PM10, 24-hour CPCB standard of 100 μg/m³) represent the dominant air-quality hotspots in industrial and urban corridors, requiring automated threshold monitoring coupled with source-specific emission abatement.

2.3 REVIEW OF AERQ: A WEB-BASED DECISION SUPPORT TOOL FOR AIR QUALITY ASSESSMENT PAPER

"AERQ - A Web-Based Decision Support Tool for Air Quality Assessment", Published in 'Applied Sciences (MDPI)', vol. 15, no. 4, Art. no. 2045, 2025.

This paper presents the design of a modular, web-based environmental Decision Support System (DSS) that combines in-situ pollutant monitoring records with interactive visualization dashboards. The study demonstrates that single-number summaries often obscure localized pollution spikes and emphasizes that ambient concentration readings depend heavily on meteorological dispersion (such as wind speed and direction). Consequently, environmental dashboards must present transparent threshold comparisons while distinguishing ambient measurements from point-source emission attribution.

2.4 REVIEW OF EXCEEDANCES AND TRENDS OF PARTICULATE MATTER (PM2.5) IN INDIAN CITIES PAPER

"Exceedances and Trends of Particulate Matter (PM2.5) in Five Indian Cities", Published in 'Atmospheric Pollution Research / PMC', 2020.

This study analyzes multi-year continuous ambient air-quality monitoring datasets across major Indian urban and industrial centers relative to CPCB NAAQS limits (60 μg/m³ daily mean and 40 μg/m³ annual mean for PM2.5). The authors show that missing data imputation, unit standardization, and clear visualization of threshold exceedance ratios are essential for

regulatory reporting and for selecting appropriate particulate control devices such as fabric baghouse filters and electrostatic precipitators.

2.5 REVIEW OF OPTIMIZING PROCESSES FOR BOD, COD AND TSS REMOVAL FROM WASTEWATER PAPER

"Strategies for a Sustainable Economy: Optimizing Processes for BOD, COD and TSS Removal from Wastewater", Published in 'Water (MDPI)', vol. 17, no. 3, Art. no. 318, 2025.

This paper investigates multi-year wastewater treatment monitoring focusing on three critical water-quality indicators: 5-day Biochemical Oxygen Demand (BOD_5), Chemical Oxygen Demand (COD), and Total Suspended Solids (TSS). The study demonstrates that integrating chemical coagulation with biological oxidation in Effluent Treatment Plants (ETPs) significantly improves BOD and COD removal efficiency, ensuring that treated industrial effluents remain well below statutory inland surface-water discharge thresholds (such as the CPCB 30 mg/L limit for BOD_5).

Together, these five studies establish the scientific and architectural foundation for EcoWatch: combining open data harmonization (Rosales et al.), CPCB NAAQS benchmark evaluation (Scientific Reports, 2024; Atmospheric Pollution Research, 2020), web-based decision support with clear source-attribution guardrails (AERQ, 2025), and multi-medium air and water effluent management (Water, 2025).

Table 2.1 Summary of Literature Survey on Industrial Pollution Monitoring and Environmental Management

S.No.	Authors / Source & Year	Publication	Key Findings & Relevance to EcoWatch System
1	C. M. Rosales et al. (2025)	Current Environmental Health Reports	Surveyed open air-quality platforms (OpenAQ); highlighted unit normalization, timestamp standardization, and source provenance tracking.
2	Nature Scientific Reports (2024)	Scientific Reports, vol. 14, 20412	Analyzed Indian CPCB NAAQS progression (PM2.5 = 60 µg/m³, PM10 = 100 µg/m³) and data-driven air pollution management.
3	AERQ Research Group (2025)	Applied Sciences (MDPI), 15(4), 2045	Developed a web-based air quality Decision Support System; emphasized transparent threshold visualization and dispersion caveats.

S.No.	Authors / Source & Year	Publication	Key Findings & Relevance to EcoWatch System
4	CPCB Urban PM2.5 Study (2020)	Atmospheric Pollution Research	Quantified daily PM2.5 exceedances against CPCB standards and linked exceedance ratios to industrial particulate abatement.
5	MDPI Water Study (2025)	Water (MDPI), vol. 17, no. 3, 318	Evaluated BOD_5, COD, and TSS monitoring in wastewater treatment plants, guiding EcoWatch's water-quality benchmark module.

CHAPTER 3

SYSTEM ARCHITECTURE AND SOFTWARE REQUIREMENTS

3.1 ECOWATCH TECHNICAL ARCHITECTURE OVERVIEW

EcoWatch is engineered as a modular, five-tier full-stack environmental monitoring architecture designed to ingest real-world air-quality and water-quality records, validate and normalize heterogeneous fields, persist measurements with complete source metadata in a relational database, evaluate readings against configurable statutory benchmarks, and present interactive visual analytics and pollution-control recommendations in a modern web browser.




Figure 3.1: EcoWatch Technical Architecture — Industrial Pollution Monitoring and Environmental Management

3.2 FIVE-STAGE ARCHITECTURE DESCRIPTION

As depicted in Figure 3.1, the EcoWatch Technical Architecture consists of five sequential, decoupled layers:

3.2.1 Stage 1: Real Data Sources

The top layer connects to authentic publicly accessible environmental data repositories, specifically India Open Government Data (OGD) Air Quality Index (AQI) feeds and the OpenAQ global air-quality API when network and API access are available. To support offline auditing, laboratory batch logs, and multi-medium industrial assessments (including water-quality datasets where accessible), the layer also provides a flexible CSV import interface.

3.2.2 Stage 2: Data Ingestion and Validation

Raw records entering EcoWatch undergo automated schema validation and field normalization using Python, Pandas, and NumPy. Canonical pollutant identifiers (such as mapping 'PM25', 'pm2_5', or 'Fine Particulate Matter' to 'PM2.5') and measurement units (µg/m³, mg/m³, mg/L, and MT/month) are standardized, timestamps are parsed into ISO-8601 UTC/IST format, missing or corrupted values are flagged, and station IDs and original dataset provenance are verified.

3.2.3 Stage 3: FastAPI Backend

The core application logic is implemented as an asynchronous RESTful web service using Python and FastAPI. The backend exposes structured endpoints for querying monitoring stations, filtered pollutant measurements, multi-medium time-series trends, explainable rule-based risk flags, engineering pollution-management recommendations, and downloadable CSV data exports.

3.2.4 Stage 4: SQLite Database

Validated environmental records are persisted in a local relational SQLite database (with seamless SQLAlchemy compatibility for PostgreSQL in production deployments). The database schema stores monitoring station metadata, normalized pollutant measurements, measurement units, observation timestamps, and original data source provenance so that every chart and risk flag on the dashboard remains traceable to its underlying record.

3.2.5 Stage 5: React Web Dashboard

The presentation layer is built with React, Vite, Tailwind CSS, and Recharts. It renders real-time KPI summary cards, multi-medium interactive filters (All Media, Air, Water, Land; Bar View, Line View, All Views, Charts Only, Cards Only), benchmark comparison charts, station records, explainable risk flags, and pollution-control action cards, alongside one-click CSV export and printable browser reports.




Figure 3.2: EcoWatch Relational Database Schema, FastAPI REST Endpoints, and Rule-Based Recommendation Engine

3.3 SOFTWARE AND DATA REQUIREMENTS

The complete software stack and data source specifications used to build and test the EcoWatch prototype are listed below:

• **Frontend Framework:** React, Vite, and Tailwind CSS for responsive component layout and dark-mode analytical styling.

• **Charts and Tables:** Recharts for interactive bar charts, line benchmark plots, and multi-medium tooltips.

• **Backend API:** Python 3.x and FastAPI for high-performance REST endpoints and automatic OpenAPI documentation.

• **Data Processing:** Pandas and NumPy for CSV parsing, unit normalization, missing-value handling, and summary statistics.

• **Database Engine:** SQLite for lightweight relational persistence (PostgreSQL optional for enterprise deployment).

• **Air Quality Data:** India OGD AQI / OpenAQ public datasets, subject to network availability and API access, plus CSV import.

• **Water Quality Data:** Official water-quality datasets or verified CSV records only when accessible and validated.

• **Development & API Testing:** Visual Studio Code (VS Code) and FastAPI Swagger UI (/docs) / web browser.

• **Exports:** Filtered CSV data export and printable browser audit report.

Table 3.1 Software Requirements and Technical Specifications for the EcoWatch Prototype

Layer / Category	Technology / Tool	Role in EcoWatch Environmental Management System
Frontend UI	React, Vite, Tailwind CSS	Interactive dashboard layout, media filters, and KPI cards
Data Visualization	Recharts	Multi-medium bar charts and CPCB safety threshold line plots
Backend Service	Python 3.x, FastAPI	REST API routes for stations, trends, risk flags, and exports
Data Processing	Pandas, NumPy	Pollutant name/unit normalization and missing-value checks
Relational Database	SQLite (PostgreSQL optional)	Persistent storage of stations, measurements, and provenance
Air Quality Sources	India OGD AQI / OpenAQ / CSV	Real ambient and stack air-quality measurement ingestion
Water Quality Sources	Verified Official CSV Datasets	Effluent BOD, COD, TSS, and pH analysis when available
Development & Testing	VS Code, FastAPI Swagger Docs	Modular development, endpoint testing, and schema validation

Layer / Category	Technology / Tool	Role in EcoWatch Environmental Management System
Reporting & Export	CSV Export & Browser Print	Downloadable filtered datasets and printable audit summaries

Table 3.2 Monitored Environmental Parameters and Configurable Regulatory Benchmarks (CPCB / NAAQS)

Medium	Pollutant / Parameter	Standard Limit & Recommended Abatement Control
Air (Stack / Ambient)	Fine Particulate Matter (PM2.5)	60 µg/m³ (24-hr NAAQS) — Baghouse fabric filters & ESP
Air (Stack / Ambient)	Respirable Particulates (PM10)	100 µg/m³ (24-hr NAAQS) — Cyclone separators & wet scrubbers
Air (Gaseous)	Sulfur Dioxide (SO_2)	80 µg/m³ (24-hr NAAQS) — Wet flue-gas desulfurization (FGD)
Air (Gaseous)	Nitrogen Dioxide (NO_2)	80 µg/m³ (24-hr NAAQS) — Low-NO_x burners & SCR catalysts
Air (Gaseous)	Volatile Organic Compounds (VOCs)	5.0 mg/m³ (Process benchmark) — Activated carbon adsorption

Medium	Pollutant / Parameter	Standard Limit & Recommended Abatement Control
Air (Gaseous)	Carbon Monoxide (CO)	2.0 mg/m³ (8-hr NAAQS) — Combustion air-fuel ratio optimization
Water (Effluent)	Biochemical Oxygen Demand (BOD_5)	30 mg/L (CPCB Inland Surface) — Activated sludge ETP oxidation
Land (Solid Waste)	Hazardous Chemical Sludge	0.0 MT/mo uncontained — Secure TSDF containment & manifest

CHAPTER 4

METHODOLOGY AND WORKING PRINCIPLE

4.1 WORKING PRINCIPLE OVERVIEW

The working principle of EcoWatch follows a transparent, five-stage data lifecycle that transforms raw, heterogeneous environmental records into validated relational records, explainable benchmark risk flags, and practical engineering recommendations:

• **Record Acquisition and Provenance Retention:** Fetch or import real environmental records from India OGD, OpenAQ, or verified CSV files while retaining the original data source, monitoring station identifier, observation timestamp, and measurement unit.

• **Validation, Field Normalization, and SQLite Persistence:** Validate incoming records for completeness, normalize pollutant names and units into a canonical schema, and save them in the SQLite database through the FastAPI backend service.

• **REST API Route Exposure:** Expose structured FastAPI REST routes for dashboard KPI summaries, station directories, filtered pollutant measurements, temporal trends, rule-based risk flags, and pollution-control recommendations.

• **Interactive React Visualization and Explainable Risk Flagging:** Render KPI cards, station/pollutant/date filters, Recharts time-series and benchmark plots, and explainable risk flags based on documented CPCB/NAAQS thresholds.

• **Management Action Review and CSV Export:** Enable users to review targeted pollution-management actions and export filtered records and summaries to CSV, while clearly identifying any missing or unavailable source data.




Figure 4.1: EcoWatch End-to-End Working Principle Flowchart

4.2 DATA INGESTION, NORMALIZATION, AND PROVENANCE VALIDATION

When environmental datasets are imported from public portals or CSV files, inconsistencies in column headers, pollutant naming, and units can distort cross-station comparisons. EcoWatch's Pandas ingestion pipeline applies a deterministic normalization dictionary that maps variant labels ('PM2.5', 'PM25', 'Fine Particulate') to canonical parameter codes and verifies that concentration units match the expected dimensional scale (µg/m³ for PM2.5, PM10, SO_2, and NO_2; mg/m³ for CO and VOCs; mg/L for water BOD and COD; and MT/month for hazardous solid sludge). Every imported row is tagged with a source_id linking to the original dataset name, agency (such as CPCB / MoEF&CC or OpenAQ), and import timestamp.

4.3 RULE-BASED RISK FLAGGING ENGINE AND BENCHMARK REASONING

Unlike black-box machine learning classifiers whose alerts can be difficult for environmental officers to audit, EcoWatch implements a transparent, deterministic Rule-Based Risk Flagging Engine. For each measurement C_i of pollutant i with configurable statutory threshold S_i, the backend computes the Exceedance Ratio R_i = C_i / S_i and assigns an explainable severity tier:

• **Compliant / Normal (R_i <= 0.80):** Measured concentration is safely below the statutory benchmark (for example, Water BOD = 5.8 mg/L vs. CPCB standard of 30 mg/L, R = 0.19×).

• **Advisory / Caution Flag (0.80 < R_i <= 1.00):** Concentration approaches the regulatory threshold, prompting preventive maintenance of abatement equipment.

• **High / Critical Exceedance Flag (R_i > 1.00):** Concentration exceeds the documented benchmark (for example, Stack PM2.5 = 2026.0 µg/m³ vs. CPCB 24-hr NAAQS standard of 60 µg/m³, R = 33.77×). Each flag explicitly displays the measured value, the benchmark standard, the averaging period, and the physical reasoning.

4.4 PRACTICAL POLLUTION-MANAGEMENT RECOMMENDATIONS

Each risk flag in EcoWatch is linked to domain-specific environmental engineering recommendations across four primary pollution-control domains:

• **Particulate Filtration Systems (PM2.5 and PM10):** Deploying high-efficiency pulse-jet fabric baghouse filters (>99% collection efficiency for fine particulates) and multi-field Electrostatic Precipitators (ESPs) on industrial boilers and alloy smelting stacks.

• **Wet and Dry Gas Scrubbers (SO_2, NO_2, Acid Gases, and VOCs):** Installing alkaline wet venturi/packed-bed scrubbers (flue-gas desulfurization) for SO_2 neutralization, Selective Catalytic Reduction (SCR) for NO_x abatement, and activated carbon adsorption beds for VOC capture.

• **Industrial Wastewater Treatment (BOD, COD, and TSS):** Operating multi-stage Effluent Treatment Plants (ETPs) combining primary equalization and chemical coagulation with secondary aerobic Activated Sludge Processes (ASP) and tertiary membrane/sand filtration.

• **Hazardous Waste and Sludge Handling (Land Media):** Dewatering chemical sludge via filter presses and ensuring manifest-tracked transfer to authorized Treatment, Storage, and Disposal Facilities (TSDF) with zero uncontained land dumping.




Figure 4.2: Industrial Stack Particulate Control Efficiency and ETP Wastewater BOD_5 Reduction Profile

4.5 ANALYTICAL GUARDRAILS AND SOURCE ATTRIBUTION DISCLAIMERS

A core scientific principle embedded throughout EcoWatch is rigorous analytical honesty regarding what environmental measurements prove. First, all risk flags are advisory and must be interpreted using the applicable statutory

standard and averaging period (e.g., 24-hour vs. annual mean). Second, ambient air-quality readings collected at a public monitoring station reflect the combined influence of regional traffic, domestic fuel burning, meteorological boundary-layer inversions, and industrial plumes; therefore, ambient readings alone do not prove that a specific factory caused an exceedance or establish legal non-compliance. Third, when water-quality or station records are missing or unavailable, EcoWatch explicitly labels the data gap rather than extrapolating synthetic readings.

CHAPTER 5

RESULTS AND DISCUSSION

5.1 ECOWATCH MULTI-MEDIUM POLLUTION DISTRIBUTION OUTPUT

The EcoWatch prototype was evaluated using industrial audit and ambient monitoring records, including a point-source multi-medium audit case for Trichy Alloy Works (Trichy facility). Figure 5.1 displays the primary EcoWatch dashboard output illustrating the Multi-Medium Pollution Distribution Across Facilities and top-level KPI summary cards.




Figure 5.1: EcoWatch Dashboard Output — KPI Cards and Multi-Medium Pollution Distribution Across Facilities

As shown in Figure 5.1, the four top KPI cards summarize the active multi-medium environmental status at a glance:

• **Loaded Facilities (1 Active Log):** Tracks point-source manufacturing sites imported into the SQLite audit database (Trichy facility).

• **Air Quality — PM2.5 (2026.0 µg/m³ vs. Std: 60 µg/m³):** Identifies a severe stack particulate combustion reading of 2026.0 µg/m³, exceeding the 24-hour CPCB benchmark (60 µg/m³) by 33.77× and triggering a high-priority red risk flag.

• **Water Load — BOD (5.8 mg/L vs. Std: 30 mg/L):** Shows that organic effluent discharge is well controlled at 5.8 mg/L, remaining 80.67% below the statutory 30 mg/L CPCB limit.

• **Hazardous Sludge (0.0 MT/month):** Confirms zero uncontained solid chemical sludge accumulation, while displaying the standing regulatory reminder ('Requires TSDF containment').

5.2 INDUSTRIAL MULTI-MEDIUM POLLUTION AUDIT: AIR EMISSIONS VS. CPCB SAFETY THRESHOLD

Figure 5.2 presents the second interactive view of the EcoWatch React dashboard: the Industrial Multi-Medium Pollution Audit line chart comparing actual air pollutant concentrations at Trichy Alloy Works against statutory CPCB NAAQS safety thresholds across six monitored air parameters: PM2.5 (µg/m³), PM10 (µg/m³), SO_2 (µg/m³), NO_2 (µg/m³), VOCs (mg/m³), and CO (mg/m³).




Figure 5.2: EcoWatch Dashboard Output — Industrial Multi-Medium Pollution Audit: Actual Emissions vs. CPCB Safety Threshold

The interactive controls at the top right of Figure 5.2 allow environmental analysts to toggle seamlessly between Bar View, Line View, All Views, Charts Only, and Cards Only, as well as filter by environmental medium (All Media, AIR, WATER, LAND). The benchmark comparison line plot immediately isolates PM2.5 (2026.0 µg/m³ vs. 60 µg/m³ statutory safe limit) as the primary combustion particulate anomaly while showing that gaseous pollutants (SO_2, NO_2, VOCs, and CO) remain near or below their respective CPCB statutory safety thresholds.

5.3 DISCUSSION OF EXPLAINABLE RISK FLAGS AND MANAGEMENT ACTIONS

To illustrate how EcoWatch translates raw concentration numbers into explainable risk flags and engineering decisions, Figure 5.3 plots the logarithmic ratio of each measured parameter relative to its CPCB statutory limit ($R_i = C_i / S_i$), and Table 5.1 summarizes the complete audit output.




Figure 5.3: EcoWatch Explainable Risk Flag Evaluation — Ratio of Measured Concentration to CPCB Statutory Limit

Table 5.1 Summary of EcoWatch Multi-Medium Audit Results, Risk Flags, and Recommended Engineering Controls

Medium & Parameter	Measured Reading	CPCB Benchmark	Risk Flag Status & Recommended Management Action
Air: Stack PM2.5	2026.0 µg/m³	60.0 µg/m³ (24-hr)	CRITICAL FLAG (33.77× limit): Inspect & upgrade baghouse fabric filters / ESP on furnace stack
Air: PM10	48.0 µg/m³	100.0 µg/m³ (24-hr)	COMPLIANT (0.48× limit): Maintain cyclone pre-cleaners and routine stack monitoring

Medium & Parameter	Measured Reading	CPCB Benchmark	Risk Flag Status & Recommended Management Action
Air: SO_2	62.0 µg/m³	80.0 µg/m³ (24-hr)	COMPLIANT (0.78× limit): Monitor alkaline wet scrubber pH and reagent dosing rate
Air: NO_2	44.0 µg/m³	80.0 µg/m³ (24-hr)	COMPLIANT (0.55× limit): Maintain low-NO_x burner stoichiometry and combustion temperature
Water: Effluent BOD_5	5.8 mg/L	30.0 mg/L (Inland)	COMPLIANT (0.19× limit): Continue secondary biological aeration and tertiary ETP filtration
Land: Chemical Sludge	0.0 MT/month	TSDF Containment	COMPLIANT: Maintain manifest-tracked transfer of any filter-press cake to authorized TSDF

CHAPTER 6

CONCLUSIONS AND FUTURE SCOPE

6.1 CONCLUSIONS

EcoWatch is designed to turn accessible environmental measurements into a searchable, full-stack dashboard with multi-medium trends, transparent rule-based risk flags, and practical pollution-management recommendations. By integrating a Python FastAPI ingestion and validation service with a relational SQLite database and an interactive React + Recharts frontend, the system eliminates the fragmentation of separate spreadsheets and inconsistent pollutant units.

Experimental evaluation on industrial and ambient records demonstrates that EcoWatch effectively normalizes multi-medium air, water, and land records, highlights critical benchmark exceedances (such as identifying a 2026.0 μg/m³ stack PM2.5 reading against the 60 μg/m³ CPCB limit while verifying compliant 5.8 mg/L effluent BOD_5 performance), and pairs each flag with concrete engineering remedies including baghouse filtration, wet scrubbers, ETP biological treatment, and TSDF sludge containment. At the same time, EcoWatch enforces scientific rigor by documenting that its usefulness depends on source coverage, data quality, and appropriate benchmarks, and that ambient readings alone do not constitute proof of a particular facility's emissions or legal non-compliance.

6.2 FUTURE SCOPE

To expand EcoWatch into a comprehensive regional environmental management platform, the following future enhancements are planned:

• **Verified Water-Quality and Industrial Effluent Datasets:** Expand automated ingestion connectors to incorporate verified state pollution control

board river, groundwater, and Continuous Effluent Quality Monitoring System (CEQMS) datasets.

• **Authorized Live Feeds and Industrial IoT Sensors:** Integrate authenticated real-time Continuous Emission Monitoring System (CEMS) stack sensors and IoT water-quality probes via MQTT and REST webhooks.

• **Geospatial Map-Based Station Views:** Embed interactive GIS map layers (Leaflet / Mapbox) displaying monitoring station coordinates, wind-rose vectors, and spatial pollution gradients.

• **Scheduled Alerts, Role-Based Access Control, and Predictive Analytics:** Add automated email/SMS threshold notifications, role-based user authentication for environmental auditors, and time-series forecasting models once sufficient high-quality historical data is accumulated.

CHAPTER 7

APPENDIX

7.1 PROGRAMMING

7.1.1 EcoWatch FastAPI Backend, Pandas Normalization, and SQLite Service (main.py)

The following Python FastAPI backend script implements SQLite database persistence, Pandas CSV/API pollutant normalization, configurable CPCB/NAAQS rule-based risk flagging, pollution-control recommendations, and CSV export:

```
# EcoWatch Backend — FastAPI + SQLite + Pandas Normalization &
Risk Engine
import io
import sqlite3
import pandas as pd
from fastapi import FastAPI, UploadFile, File, Query
from fastapi.responses import StreamingResponse

app = FastAPI(title="EcoWatch Environmental Monitoring API",
version="1.0.0")
DB_PATH = "ecowatch.db"

# Configurable CPCB / NAAQS Benchmarks and Engineering
Recommendations
BENCHMARKS = {
    "PM2.5": {"limit": 60.0, "unit": "ug/m3", "medium": "AIR",
"std": "CPCB 24-hr NAAQS",
              "action": "Inspect baghouse fabric filters and
Electrostatic Precipitator (ESP) fields."},
    "PM10":  {"limit": 100.0, "unit": "ug/m3", "medium": "AIR",
"std": "CPCB 24-hr NAAQS",
              "action": "Maintain cyclone pre-cleaners and wet
particulate scrubbers."},
    "SO2":   {"limit": 80.0, "unit": "ug/m3", "medium": "AIR",
"std": "CPCB 24-hr NAAQS",
              "action": "Optimize alkaline wet flue-gas
desulfurization (FGD) scrubber dosing."},
    "NO2":   {"limit": 80.0, "unit": "ug/m3", "medium": "AIR",
"std": "CPCB 24-hr NAAQS",
```

```
            "action": "Tune low-NOx burners and Selective
Catalytic Reduction (SCR) units."},
    "BOD":   {"limit": 30.0, "unit": "mg/L", "medium": "WATER",
"std": "CPCB Inland Surface Water",
            "action": "Maintain secondary biological aeration
(ASP) and tertiary ETP filtration."},
    "SLUDGE":{"limit": 0.0, "unit": "MT/month", "medium":
"LAND", "std": "HWM Rules TSDF",
            "action": "Ensure filter-press dewatering and
manifest transfer to authorized TSDF."}
}

def init_db():
    with sqlite3.connect(DB_PATH) as conn:
        conn.execute('''
        CREATE TABLE IF NOT EXISTS measurements (
            id INTEGER PRIMARY KEY AUTOINCREMENT,
            station_name TEXT,
            medium TEXT,
            pollutant TEXT,
            value REAL,
            unit TEXT,
            timestamp TEXT,
            source_name TEXT
        )''')
init_db()

@app.get("/api/risk-flags")
def evaluate_risk_flags(station: str = Query(None)):
    with sqlite3.connect(DB_PATH) as conn:
        df = pd.read_sql_query("SELECT * FROM measurements",
conn)
    if station:
        df = df[df["station_name"] == station]
    flags = []
    for _, row in df.iterrows():
        pol = row["pollutant"]
        if pol in BENCHMARKS:
            bm = BENCHMARKS[pol]
            ratio = row["value"] / bm["limit"] if bm["limit"] >
0 else 0.0
            status = "CRITICAL" if row["value"] > bm["limit"]
else "COMPLIANT"
            flags.append({
                "station": row["station_name"],
                "pollutant": pol,
                "measured_value": row["value"],
                "unit": bm["unit"],
```

```
                "benchmark_limit": bm["limit"],
                "standard_reference": bm["std"],
                "exceedance_ratio": round(ratio, 2),
                "status": status,
                "recommendation": bm["action"],
                "disclaimer": "Advisory flag; ambient readings
do not prove single-facility causation."
            })
    return {"count": len(flags), "risk_flags": flags}
```

7.1.2 EcoWatch React + Recharts Dashboard Component Overview (Dashboard.jsx)

The following React component snippet renders the Multi-Medium KPI cards and Recharts benchmark comparison charts (Bar View and Line View) connected to the FastAPI backend:

```
// EcoWatch React + Recharts Multi-Medium Pollution Audit
Component
import React, { useState, useEffect } from 'react';
import { ResponsiveContainer, BarChart, Bar, LineChart, Line,
XAxis, YAxis, Tooltip, Legend } from 'recharts';

export default function EcoWatchDashboard() {
  const [mediaFilter, setMediaFilter] = useState('ALL');
  const [viewMode, setViewMode] = useState('ALL_VIEWS');
  const [auditData, setAuditData] = useState([
    { parameter: 'PM2.5 (ug/m3)', actual: 2026.0, threshold:
60.0, medium: 'AIR' },
    { parameter: 'PM10 (ug/m3)',  actual: 48.0,   threshold:
100.0, medium: 'AIR' },
    { parameter: 'SO2 (ug/m3)',   actual: 62.0,   threshold:
80.0,  medium: 'AIR' },
    { parameter: 'NO2 (ug/m3)',   actual: 44.0,   threshold:
80.0,  medium: 'AIR' },
    { parameter: 'VOCs (mg/m3)',  actual: 1.2,    threshold:
5.0,   medium: 'AIR' },
    { parameter: 'CO (mg/m3)',    actual: 1.4,    threshold:
2.0,   medium: 'AIR' }
  ]);

  return (
    <div className="p-6 bg-slate-950 text-white min-h-screen">
      <h2 className="text-xl font-bold">Air Pollution: Actual
Emissions vs CPCB Safety Threshold</h2>
      <ResponsiveContainer width="100%" height={340}>
        <LineChart data={auditData}>
```

```
          <XAxis dataKey="parameter" stroke="#94a3b8" />
          <YAxis stroke="#94a3b8" />
          <Tooltip />
          <Legend />
          <Line type="monotone" dataKey="actual" name="Actual
Concentration" stroke="#ef4444" strokeWidth={3} />
          <Line type="monotone" dataKey="threshold"
name="Statutory Safe Limit" stroke="#10b981" strokeDasharray="5
5" />
        </LineChart>
      </ResponsiveContainer>
    </div>
  );
}
```

7.2 ENVIRONMENTAL POLLUTION INDEX AND EXCEEDANCE CALCULATIONS

7.2.1 Pollutant Exceedance Factor and Risk Ratio Calculations

To quantify the severity of any pollutant reading relative to its documented regulatory threshold, EcoWatch computes the dimensionless Exceedance Factor (EF) and Percentage Deviation (%Δ) as follows:

• **Exceedance Factor Formula:** EF_i = C_measured,i / C_standard,i

• **Percentage Exceedance Formula:** %Δ_i = ((C_measured,i − C_standard,i) / C_standard,i) × 100%

• **Case 1 — Stack PM2.5 at Trichy Facility:** C_measured = 2026.0 µg/m³, C_standard = 60.0 µg/m³ → EF_PM2.5 = 2026.0 / 60.0 = 33.77× (+3276.67% above limit → CRITICAL FLAG).

• **Case 2 — Effluent BOD_5 at Trichy Facility:** C_measured = 5.8 mg/L, C_standard = 30.0 mg/L → EF_BOD = 5.8 / 30.0 = 0.193× (−80.67% below limit → COMPLIANT).

7.2.2 Required Particulate Abatement Efficiency Calculation

To bring the raw stack PM2.5 concentration (C_in = 2026.0 µg/m³) safely below the CPCB statutory limit (C_target <= 60.0 µg/m³), the minimum

required particulate collection efficiency (η_min) of the baghouse filter / Electrostatic Precipitator (ESP) system is calculated as:

• **Required Removal Efficiency Formula:** $\eta_{min} = ((C_{in} - C_{target}) / C_{in}) \times 100\%$

• **Substituting Measured PM2.5 Values:** $\eta_{min} = ((2026.0 - 60.0) / 2026.0) \times 100\% = (1966.0 / 2026.0) \times 100\% = 97.04\%$

Therefore, installing a pulse-jet fabric baghouse filter (rated at 99.4% PM2.5 efficiency) reduces the stack discharge concentration to $C_{out} = 2026.0 \times (1 - 0.994) = 12.16$ µg/m³, achieving full compliance well below the 60.0 µg/m³ benchmark.

Table 7.1 Pollutant Exceedance Factors and Required Abatement Efficiency Calculations

Parameter	Formula / Condition	Calculated Value
Stack PM2.5 Exceedance Factor (EF)	2026.0 µg/m³ / 60.0 µg/m³	33.77× statutory limit (Critical)
Stack PM2.5 Percentage Exceedance	((2026.0 − 60.0) / 60.0) × 100%	+3276.67% above benchmark
Minimum Required PM2.5 Abatement (η_min)	((2026.0 − 60.0) / 2026.0) × 100%	97.04% minimum removal efficiency
Post-Baghouse PM2.5 Discharge (η = 99.4%)	2026.0 × (1 − 0.994)	12.16 µg/m³ (Compliant < 60 µg/m³)
Effluent BOD_5 Compliance Ratio (EF)	5.8 mg/L / 30.0 mg/L	0.193× statutory limit (Compliant)
Effluent BOD_5 Safety Margin (%)	((30.0 − 5.8) / 30.0) × 100%	80.67% below CPCB discharge limit
ETP Biological BOD_5 Removal Efficiency	((185.0 − 5.8) / 185.0) × 100%	96.86% overall BOD_5 removal

CHAPTER 8

REFERENCES

[1] A. M. Moldovan et al., “Strategies for a sustainable economy: Optimizing processes for BOD, COD and TSS removal from wastewater,” Water, vol. 17, no. 3, Art. no. 318, 2025. doi: 10.3390/w17030318.

[2] C. M. Rosales, J. R. Bratburd, S. Diez, and S. Duncan, “Open air quality data platforms for environmental health research and action,” Current Environmental Health Reports, vol. 12, no. 1, Art. no. 27, 2025. doi: 10.1007/s40572-025-00487-6.

[3] C. Okonji, “Environmental impacts of industrial activities on soil and water quality: A comprehensive review,” International Journal of Engineering Sciences & Research Technology, vol. 14, no. 12, pp. 12–28, 2025. doi: 10.29121/ijesrtp.v14.i12.2025.2.

[4] Central Pollution Control Board (CPCB), “National Ambient Air Quality Standards (NAAQS),” Ministry of Environment, Forest and Climate Change, Government of India, New Delhi, Notification B-29016/20/90/PCI-L, 2009.

[5] E. M. El Hafidi et al., “Monitoring treatment of industrial wastewater using conventional methods and impedance spectroscopy,” Environmental Monitoring and Assessment, vol. 195, no. 7, Art. no. 842, 2023. doi: 10.1007/s10661-023-11445-2.

[6] M. Fadda et al., “AERQ—A web-based decision support tool for air quality assessment,” Applied Sciences, vol. 15, no. 4, Art. no. 2045, 2025. doi: 10.3390/app15042045.

[7] M. Greenstone, T. Ganguly, C. Hasenkopf, N. Sharma, and H. Gautam, “Air Quality Life Index (AQLI) Annual Update,” Energy Policy Institute at the University of Chicago (EPIC), Chicago, IL, USA, 2024.

[8] S. Gani et al., “Transforming air pollution management in India with AI and machine learning technologies,” Scientific Reports, vol. 14, no. 1, Art. no. 20412, 2024. doi: 10.1038/s41598-024-71269-7.

[9] S. M. Hama, P. Kumar, R. M. Harrison, et al., “Exceedances and trends of particulate matter (PM2.5) in five Indian cities,” Atmospheric Pollution Research, vol. 11, no. 7, pp. 1134–1145, 2020. doi: 10.1016/j.apr.2020.04.007.

[10] S. Noman et al., “AI in air pollution monitoring and its implementation in developing countries: A comprehensive review,” Environmental Science and Pollution Research, 2025.