harmonisation

Harmonisation score

User manual

---

situation-report - github.com/Jaegerfeld/situation-report

For portfolio and process owners — Version 0.36.0

Contents

Contents 2

1 What it is about 3

2 Getting started 3

3 The workspace 3

4 The GUI 4

5 Answers and arithmetic 4

6 Reading the matrix 5

7 Deliberate limits and tips 5

8 Change, AI reading, conference pre-read 6

1 What it is about

A group with several brands or units often runs the same end-to-end process in several variants. Harmonise or not – and how deep? A harmonisation score answers that in a structured way: three dimensions (business value, transparency, IT and operations) with eight questions per process, feeding a board-level situational picture. The harmonisation module implements that structure.

- Question catalogue as data – the bundled example is an illustration; your own questions go into the same file.
- Assessments per process, versioned as one file each, with a value and an evidence level per question.
- Decision matrix for the board: score, confidence and spread per dimension – next to the columns the board fills in.

> A finding, not a judgement. The tool recommends neither what to harmonise nor how deep. It computes the finding and records what the board decided. There is no harmonisation proposal, no ranking and no overall score – the judgement line stays with people.

2 Getting started

- GUI: `python -m harmonisation` – without arguments the window opens.

Command line: a workspace folder in, the matrix as HTML out:

```
python -m harmonisation C:\Lagebild\harmo --lang en --browser
python -m harmonisation C:\Lagebild\harmo --example # create the example
```

3 The workspace

A workspace is a folder with four parts, all JSON with a schema_version. The GUI creates it ready-filled via “Create example…”; afterwards you replace catalogue and processes with your own.

File	Content
catalogue.json	Question catalogue: dimensions with their questions; text per language, English as fallback.
processes.json	End-to-end processes: id, name, owner, brands or units involved.
assessments/*.json	One file per assessment: process, assessor, date, answers with evidence level, note.
decisions.json	The board's decision per process: standardise, brand-specific or open – and the depth in the board's wording (optional).

> Every question is phrased so that strong agreement speaks for harmonisation. Only then can the values of a dimension be added up. Check this when you enter your own questions.

4 The GUI

At the top the workspace with Browse, Create example and Reload; on the right the flag to switch languages. Below, three tabs; at the bottom the matrix language and the button that generates it and opens it in the browser. Next to it the “Since” field with the button for the change; in the row below the checkbox for the AI reading and the provider choice.

- Processes: the list of processes; add new ones with id, name, owner and brands.
- Assessment: choose process, assessor and date; per question click a value 0–4 or “?” (unknown) and set the evidence level; saving writes the file into the assessments folder.
- Decision: per process the board's decision, the depth in its wording, date and body.

5 Answers and arithmetic

The score is deliberately simple so that any board can recompute it.

Quantity	Meaning
Value per question	0 “does not apply” to 4 “fully applies”. “Unknown” is a permitted answer – a situational picture that cannot show ignorance fakes certainty.
Evidence	documented (document, measurement, system) · estimated (the assessor's judgement) · hearsay.
Score per dimension	Mean of the answered questions, scaled to 0–100; plus “n of 8 answered”.
Confidence	Share of documented answers over all questions of the dimension: high from two thirds, medium from one third, otherwise low. “Unknown” lowers the confidence, not the score.
Several assessments	Median as the score, spread (highest minus lowest assessment) next to it. Two people who see the same process very differently are a finding, not noise.
Overall score	There is none. Three numbers side by side are more honest than one that nets three different things.

6 Reading the matrix

Colour key and legend come before the first table. The score is shaded in blue – a finding, not a traffic light. Only the confidence carries traffic-light colours.

Column	Content
Process	Name, owner, brands.
Per dimension	Score, number of assessments, questions answered, spread, confidence badge. “No assessment” while nothing is recorded.
Board decision	standardise · brand-specific · open, with date and body.
Depth	The board's own wording – deliberately free text, no preset scale.

Below the matrix follows the second reading: every assessment with every answer and its evidence level. Whoever doubts a number in the matrix finds there what it is made of.

7 Deliberate limits and tips

- No proposal, no ranking, no recommended depth – by design, not by omission.
- No AI in the core: the computation is deterministic, standard library only. The optional AI reading only phrases, labeled as a draft, and computes nothing.
- Have every process assessed by more than one person – only the spread shows where the picture is shared and where it is not.
- Answer “unknown” instead of guessing. Low confidence is a statement; a guessed value is a deception.

8 Change, AI reading, conference pre-read

Since step 2 the matrix has three connections. None of them changes the arithmetic – they show it differently or somewhere else.

Building block	What it does
Change between two states	“What has changed since the last assessment?” Assessments are dated, so `--since YYYY-MM-DD` recomputes the earlier state from today's files; `--delta FOLDER` compares against a second workspace. Per process and dimension score, confidence, spread and number of assessments old → new; plus new assessments (date only), board decisions, processes added or removed. “No changes” is said explicitly. A lower score is not a worsening but a different finding.
AI reading (draft)	`--narrate` (default: ollama, local) or the checkbox in the GUI. The model sees only a contract with every number of the matrix or the change – processes, dimensions, brands, never persons. Every number in the text must appear in the contract, otherwise the draft is discarded; the prompt forbids any recommendation on what to harmonise. The draft sits labeled directly below the table and additionally in `…reading.md` for editing; the operator evidence goes to llm_audit.jsonl.
Conference pre-read	In the portfolio module a solution carries the field `harmonisation` with the workspace folder (data-sources dialog, tenth field). The pre-read then shows the matrix as an annex after input 4 – a board view, not a fifth conference input.

```
python -m harmonisation C:\Lagebild\harmo --since 2026-09-20
python -m harmonisation C:\Lagebild\harmo --since 2026-09-20 --narrate
python -m harmonisation C:\Lagebild\harmo --narrate mock
```

If the AI fails, the page still stands. The deterministic matrix or change is always written; a missing draft is reported in the status line or by the command line's exit code 3.