

SituationReport

get_data

User Manual

Export Jira data for SituationReport

situation-report -- github.com/Jaegerfeld/situation-report

For Agile Coaches and PI Managers -- Version 0.22.0

1 Exporting Data from Jira Cloud

Note: The `get_data` module is still under development. This manual describes the manual export of Jira data via the Jira REST API. This is the same process that `get_data` will automate — the exported JSON files can be processed directly by `transform_data`.

This chapter explains how to export real issue data from Jira Cloud for SituationReport. The export produces the same JSON structure as the Testdata Generator — `transform_data` processes both identically.

1.1 What you need

Requirement	Details
Jira Cloud account	An account with read access to the desired project
API token	Personal token from id.atlassian.com — created once
Project key	The Jira project shortcode, e.g. 'ART_A' or 'SCRUM'
curl or browser	curl for automated queries; browser for quick tests

1.2 Creating an API token

The API token replaces your password for API calls and is created once:

Step	Action
1	Open https://id.atlassian.com in your browser (while logged into Jira)
2	Security → API tokens → Create API token
3	Enter a label, e.g. 'SituationReport', click 'Create'
4	Copy the token and store it safely — it is only shown once!

Security note: Treat the API token like a password. Store it in a password manager and do not share it.

1.3 Querying the Jira REST API

Jira Cloud offers two API variants. Use the current v3 API for new scripts; existing v2 scripts continue to work. `expand=changeLog` is required in both variants — without it, status transitions are missing and `transform_data` cannot compute time-in-stage values.

Current API (v3) – recommended

Endpoint: `POST /rest/api/3/search/jql`

Parameters are passed as a JSON request body. The response additionally includes `isLast` and `nextPageToken` for pagination (Section 1.5).

```
curl -X POST \
  "https://company.atlassian.net/rest/api/3/search/jql" \
```

```
-u "name@company.com:YourAPIToken" \
-H "Content-Type: application/json" \
-d '{"jql":"project=ART_A ORDER BY created ASC",
    "maxResults":100,
    "expand":["changelog"],
    "fields":["issuetype","created",
              "status","summary"]}' \
-o ART_A_page1.json
```

maxResults is limited to 100 issues per request with the v3 API. Use nextPageToken for projects with more than 100 issues (Section 1.5).

Older API (v2) – still supported

Endpoint: GET /rest/api/2/search

Parameters as URL query string. Supports up to 1,000 issues per request and offset-based pagination with startAt.

```
curl -u "name@company.com:YourAPIToken" \
     "https://company.atlassian.net/rest/api/2/search?
jql=project=ART_A+ORDER+BY+created+ASC\
&expand=changelog\
&maxResults=1000\
&fields=issuetype,created,status,project,summary,resolution" \
-o ART_A_page1.json
```

Tip: For new scripts, the v3 API is preferred. Existing v2 scripts do not need to be migrated.

1.4 Fields required by transform_data

Jira field	Required	Purpose
key	☐	Issue identifier (e.g. ART_A-001)
fields.issuetype.name	☐	Issue type for filtering (Feature, Bug, ...)
fields.created	☐	Issue creation date
fields.status.name	☐	Current status
changelog (expand=changelog)	☐	Status transitions with timestamps — MUST be set in the URL
fields.resolution	–	Optional — resolution type (e.g. 'Done', 'Won't Fix')
fields.summary	–	Optional — issue title

1.5 Pagination – more than 100 issues

API v3 – Cursor-based pagination (*nextPageToken*)

The v3 API returns at most 100 issues per request. Each response contains either a `nextPageToken` for the next page, or `"isLast": true` when all issues have been fetched. Pages must be retrieved sequentially — the token from the current response is used in the next request.

```
# Page 1 – no nextPageToken
curl -X POST \
  "https://company.atlassian.net/rest/api/3/search/jql" \
  -u "name@company.com:Token" \
  -H "Content-Type: application/json" \
  -d '{"jql":"project=ART_A ORDER BY created ASC",
      "maxResults":100,"expand":["changelog"],
      "fields":["issuetype","created",
               "status","summary"]}' \
  -o ART_A_page1.json

# Read nextPageToken from page 1:
#   cat ART_A_page1.json | grep nextPageToken
#   (or with jq: jq -r '.nextPageToken' ART_A_page1.json)

# Page 2 – insert nextPageToken
curl -X POST \
  "https://company.atlassian.net/rest/api/3/search/jql" \
  -u "name@company.com:Token" \
  -H "Content-Type: application/json" \
  -d '{"jql":"project=ART_A ORDER BY created ASC",
      "maxResults":100,"expand":["changelog"],
      "fields":["issuetype","created",
               "status","summary"],
      "nextPageToken":"<token from page 1>"}' \
  -o ART_A_page2.json

# Repeat until isLast:true appears in the response

# Merge all pages
python -m helper ART_A_page1.json ART_A_page2.json ... \
  --output ART_A_merged.json
```

Repeat until the response contains `"isLast": true`. The Helper merges all pages and removes duplicates automatically.

API v2 – Offset-based pagination (*startAt*) – Legacy

The v2 API supports up to 1,000 issues per request. With `startAt`, any page can be accessed directly. Important: `startAt` is only compatible with the v2 endpoint — not with the new v3 endpoint.

```
# Page 1 (issues 1-1,000)
curl -u "name@company.com:Token" \
  "https://company.atlassian.net/rest/api/2/search?\
jql=project=ART_A&expand=changelog&maxResults=1000&startAt=0" \
```

```

-o ART_A_page1.json

# Page 2 (issues 1,001-2,000)
curl -u "name@company.com:Token" \
  "https://company.atlassian.net/rest/api/2/search?\
jql=project=ART_A&expand=changelog&maxResults=1000&startAt=1000" \
  -o ART_A_page2.json

# Merge files with the Helper
python -m helper ART_A_page1.json ART_A_page2.json \
  --output ART_A_merged.json

```

Increment startAt by 1,000 until the response contains fewer than 1,000 issues.

1.6 From JSON export to workflow file

After exporting, create a workflow file that maps your actual Jira statuses. The following Python snippet extracts all status names from the export:

```

import json
data = json.loads(open('ART_A_page1.json').read())
statuses = set()
for issue in data['issues']:
    for h in issue['changelog']['histories']:
        for item in h['items']:
            if item['field'] == 'status':
                statuses.add(item['toString'])
print(sorted(statuses))

```

From the status names found, create a workflow.txt — arrange the statuses in logical order and set the <First> and <Closed> markers. The workflow file format is described in the transform_data User Manual.

2 Automatic fetch with get_data

get_data automates the export from chapter 1: it fetches the issues including changelog directly via REST, walks through all pages, removes duplicates and writes the same JSON file the manual export produces. Both acquisition paths are equal — in large organisations, approval for API access can take a long time; until then (and beyond) the manual path stays first-class.

```
# REST fetch (token ONLY via environment variable):
set JIRA_TOKEN=YourAPIToken
python -m get_data fetch --url https://company.atlassian.net \
  --project ART_A --email name@company.com --output ART_A.json

# Server/Data Center with PAT and the older API:
python -m get_data fetch --url https://jira.company.com \
  --project ART_A --auth bearer --api v2 --output ART_A.json

# Check an existing manual export (path 2):
python -m get_data check ART_A_merged.json
```

The check catches the classic export mistakes before transform_data stumbles: missing required fields, missing changelog (expand forgotten), duplicates — and forgotten follow-up pages (total larger than the issues in the file).

GUI: python -m get_data (or the Get Data card in the launcher) opens a window with both paths as a toggle: 'Jira REST fetch' (URL, project or JQL, API v3/v2, cloud/bearer auth, token field) and 'Existing export' (pick file → check).

Security: the token is never stored and never logged — the CLI reads it from an environment variable (default JIRA_TOKEN), the GUI keeps it in memory only.

3 Managing metric sources (sources)

Besides the raw Jira data, SituationReport also fetches external metrics (SLO/SLI, DORA, code quality) — via the pluggable sources framework. Three terms suffice: a provider translates a foreign system into normalised records; a fetch writes them as a register (JSON) the solution config references. The report never sees a vendor, and judgements (breached, tier low, ...) are made centrally — the same for every source.

3.1 Listing and fetching sources

```
python -m sources providers
python -m sources fetch --kind slo --config sources.json --output slo.json
```

providers is the inventory: shipped are file and csv (file paths, no API approval needed at all), prometheus (SLO/SLI), github and gitlab (DORA) and sonarqube (quality). Tokens come exclusively from environment variables (PROMETHEUS_TOKEN, GITHUB_TOKEN, GITLAB_TOKEN, SONAR_TOKEN) and are never stored or logged.

3.2 Swapping a source

Swapping means: change only the fetch config. Example — while the Prometheus approval is pending, a CSV file delivers; the day approval lands, {"provider": "csv", "path": "team_slos.csv"} becomes the Prometheus config — same fetch command, same register, report untouched; only the 'Data source' column shows the new origin.

3.3 Combining sources

```
{
  "sources": [
    {
      "provider": "prometheus", "base_url": "https://prom.intern",
      "services": [ ... ],
      {"provider": "csv", "path": "team_slos.csv"}
    }
  ]
}
```

Several sources fill ONE register; each row keeps its origin. Typical: most services in monitoring, two legacy systems in a spreadsheet.

3.4 Attaching a new source

A new source is ONE file in sources/providers/ with a PROVIDER object (provider_id, kinds, fetch()) — auto-discovery finds it without any further registration. The full step-by-step tutorial (CSV example from zero, REST pattern, tests) ships as sources_Tutorial_EN.pdf next to this manual and online under Tutorials → 'Attach a data source'; the living reference solution is sources/providers/csv_slo.py.

Rules of thumb: providers translate, they never judge; unmeasured values are None, not a guess; on 401/403 the error message names the missing approval and the file path as fallback.

4 Frequently Asked Questions (FAQ)

What happens if expand=changelog is missing?

transform_data finds no status transitions and outputs empty time values for all issues. The Excel files contain no usable data. Always include expand=changeLog in the URL.

I get an 'Unauthorized' error when calling curl.

Check: Is the email address correct? Is the API token correct? Are they separated by a colon? Does your account have read access to the project? Tip: Generate a new API token if the old one was lost or expired.

Can I merge multiple Jira projects?

Yes — either via JQL (jql=project in (ART_A, ART_B)) for a single export, or merge two separate exports with the Helper. Make sure the workflows of both projects are compatible.

How large can the JSON file get?

Rule of thumb: approximately 2–5 KB per issue (depending on changelog length). 1,000 issues ≈ 2–5 MB. For very large projects (10,000+ issues), use pagination and the Helper.

Should I use test data or real data?

For demos, training, and installation tests, synthetic test data from the Testdata Generator is the better choice — no privacy concerns, reproducible, and fully controlled. For real flow analyses and decisions, actual Jira data reflects the true workflow state.

5 Glossary

Term	Explanation
ART	Agile Release Train — a team-of-teams structure in SAFe
API	Application Programming Interface — programming interface
API token	Security key for accessing the Jira REST API; replaces the password in curl calls
Changelog	Jira log of all status changes for an issue (requires expand=changelog)
CFD	Cumulative Flow Diagram — shows the cumulative issue count per stage over time
Closed stage	The stage that marks an issue as completed (workflow.txt: <Closed>)
Cycle time	Time from the first active stage (<First>) to the closed stage
First stage	First active stage where cycle time measurement begins (workflow.txt: <First>)
Helper	SituationReport module for merging multiple Jira JSON files
Issue	A work item in Jira (Feature, Bug, Enabler, Story, ...)
JQL	Jira Query Language — query language for Jira searches, e.g. project=ART_A
JSON	JavaScript Object Notation — format of Jira API exports
Stage	One step in the workflow (corresponds to a Jira column or status name)
Workflow	Ordered sequence of stages that an issue passes through