

# SituationReport

## testdata\_generator

### User Manual

Generate synthetic Jira issue data for SituationReport

---

situation-report -- [github.com/Jaegerfeld/situation-report](https://github.com/Jaegerfeld/situation-report)

For Agile Coaches and PI Managers -- Version 0.24.0

# 1 What is the Testdata Generator?

---

The Testdata Generator creates synthetic Jira issue data in Jira REST API format. The generated files can be processed directly by `transform_data` — no real Jira instance required.

The generator simulates realistic workflow histories: issues traverse the defined stages, spend varying amounts of time in each stage, occasionally flow backwards, and close at a configurable rate.

Typical use cases:

- Test a new installation: Verify that `transform_data` and `build_reports` work correctly
- Demos and presentations: Realistic data without privacy concerns
- Training: Controlled learning environment with known data
- Development: Reproducible test data via the seed parameter

The Testdata Generator complements the Get Data module (still in development), which loads real data directly from Jira. For the manual export of real Jira data, see the Get Data User Manual.

## 2 Prerequisites and Start

---

### 2.1 Portable package (recommended)

The portable package includes Python already bundled — no separate installation required.

| Operating system | Start file                                     |
|------------------|------------------------------------------------|
| Windows          | TestdataGenerator.bat (double-click)           |
| macOS            | TestdataGenerator.command (right-click → Open) |
| Linux            | ./TestdataGenerator.sh                         |

*Note for Windows: If double-clicking shows an error about Python not being found, the ZIP file may have been blocked by Windows. Fix: right-click the ZIP → Properties → Security → Unblock → OK → extract again.*

### 2.2 From source code (Python required)

```
python -m testdata_generator
```

### 2.3 The user interface

After launch, the main window shows input fields for all parameters. Only the workflow file is required — all other fields have sensible defaults.

testdata\_generator 0.9.9

Hilfe

Workflow-Datei

Ausgabedatei (JSON)

Projekt-Key: TEST

Anzahl Issues: 100

Von (YYYY-MM-DD): 2025-01-01

Bis (YYYY-MM-DD): 2025-12-31

Issue-Typen (Typ:Gewicht ...)

Completion-Rate (0-1): 0.7

To-Do-Rate (0-1): 0.15

Backflow-Prob. (0-1): 0.1

Seed (leer = zufällig)

Ø Cycle Time (Tage, leer=auto)

Std.-Abw. (Tage, leer=auto)

Muster: ☒ Kein Muster ☐ Triangle ☐ Flat Triangle ☐ Cluster ☐ Batch

PI-Dauer (Wochen): 12

Generieren

Log

*Fig. 1: Testdata Generator user interface*

## 3 The Workflow File

The workflow file defines the stages of your Jira board and is the only required parameter. It uses the same format as `transform_data` — one file works for both modules.

### 3.1 Format

Each line describes a stage. Aliases (alternative status names in the Jira export) are separated by colons. Two special lines mark the start and end of active work:

```
CanonicalName:Alias1:Alias2
<First>FirstActiveStage
<Closed>ClosedStage
```

| Line                        | Meaning                                                               |
|-----------------------------|-----------------------------------------------------------------------|
| CanonicalName:Alias1:Alias2 | Stage with one or more alternative Jira status names                  |
| StageName (no :)            | Stage without aliases                                                 |
| StageName                   | First active stage — where processing begins (cycle time starts here) |
| StageName                   | Closed stage — marks an issue as completed                            |

### 3.2 ART\_A example workflow

The bundled example workflow\_ART\_A.txt models a typical SAFe ART workflow:

```
Funnel:New:Open:To Do
Analysis:In Analysis:Estimated
Program Backlog:Ready for Dev:Backlog
Implementation:In Implementation:In Review:In Progress
Blocker
Validating on Staging:QA
Deploying to Production:Ready for Development
Releasing:Completed
Done:Canceled
<First>Analysis
<Closed>Releasing
```

*Notes: 'Funnel' has four aliases — all four Jira status names are normalised to 'Funnel'. Analysis is the first active stage (cycle time begins here). Releasing is the closed stage.*

## 4 Parameter Reference

All parameters are available both in the GUI and on the command line.

| Parameter                | Default                            | Description                                                          |
|--------------------------|------------------------------------|----------------------------------------------------------------------|
| --workflow FILE          | (required)                         | Workflow definition file (.txt)                                      |
| --output FILE.json       | _generated.json                    | Output file path                                                     |
| --project KEY            | TEST                               | Jira project key for generated issues                                |
| --issues N               | 100                                | Number of issues to generate                                         |
| --from-date YYYY-MM-DD   | 2025-01-01                         | Earliest creation date                                               |
| --to-date YYYY-MM-DD     | 2025-12-31                         | Latest transition date                                               |
| --issue-types TYPE:W ... | Feature:0.6 Bug:0.3<br>Enabler:0.1 | Issue types with weights (sum need not equal 1)                      |
| --completion-rate FLOAT  | 0.7                                | Fraction of issues reaching the closed stage (0–1)                   |
| --todo-rate FLOAT        | 0.15                               | Fraction of open issues staying in early stages (0–1)                |
| --backflow-prob FLOAT    | 0.1                                | Probability of a backward transition at each step (0–1)              |
| --seed INT               | (random)                           | Seed for reproducible output (optional)                              |
| --mean-cycle-days FLOAT  | (none)                             | Target mean cycle time in days (lognormal); enables CT control       |
| --std-cycle-days FLOAT   | (30 % of mean)                     | Standard deviation of cycle time in days                             |
| --pattern PATTERN        | none                               | Flow anti-pattern: none / triangle / flat_triangle / cluster / batch |
| --pi-duration-weeks INT  | 12                                 | PI cycle length in weeks (for cluster/batch)                         |
| --pattern-strength 0-100 | 50                                 | Pattern intensity 0–100 (0=subtle, 50=default, 100=strong)           |

### Tip: Reproducible results

With a fixed seed (e.g. `--seed 42`), the generator always produces the same JSON file for the same parameters — ideal for demos where all participants should see identical results.

## 4b Flow Anti-Pattern Modes

Since version 0.9.9 the Testdata Generator can simulate typical flow anti-patterns from Vacanti and Singh. Combine `--mean-cycle-days` with `--pattern`. The GUI provides radio buttons and sliders for all pattern settings.

| Pattern       | Scatter plot appearance               | Description                                                                                                                                                                                     |
|---------------|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| none          | Even point cloud                      | Random cycle time without trend — default behaviour                                                                                                                                             |
| triangle      | Triangle: right angle bottom right    | Cycle time rises linearly over time (multiplier $\sim 1-4\times$ at default strength, higher with <code>--pattern-strength</code> ). Indicates a process that is becoming progressively slower. |
| flat_triangle | Triangle, rise flattens at the end    | Like triangle but the increase is damped by $\tanh(2.5\times t)$ . Shows a process deterioration that is levelling off.                                                                         |
| cluster       | Vertical clusters of points at PI end | Cycle time stays stable (lognormal), but most issues are delivered in the last 2 weeks before the PI end. Deadline-driven behaviour.                                                            |
| batch         | Columns of variable height at PI end  | Like cluster but with highly variable cycle time ( $0.1\times$ to $3\times$ mean). Shows that both short and very long issues are pushed to the PI end together.                                |

### Cycle time control

When `--mean-cycle-days` is provided, cycle times are sampled from a lognormal distribution with the given mean.

| Parameter                        | Meaning                                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------------------------------|
| <code>--mean-cycle-days</code>   | Mean cycle time in days (e.g. 20). Required for all patterns except none.                                     |
| <code>--std-cycle-days</code>    | Standard deviation in days (default: 30 % of mean). Higher values produce a wider spread in the scatter plot. |
| <code>--pi-duration-weeks</code> | Length of one PI cycle in weeks (default 12). Only relevant for cluster and batch.                            |

## Examples

```
# Triangle pattern: CT rises from 20d to 80d
python -m testdata_generator \
  --workflow workflow.txt --issues 300 \
  --pattern triangle \
  --mean-cycle-days 20 --std-cycle-days 6 \
  --completion-rate 0.8 --seed 1 \
  --output triangle.json

# Cluster of Dots: deliveries at PI end (12-week PI)
python -m testdata_generator \
  --workflow workflow.txt --issues 300 \
  --pattern cluster \
  --mean-cycle-days 30 --pi-duration-weeks 12 \
  --completion-rate 0.8 --seed 2 \
  --output cluster.json

# Batch Transfers: PI end + high CT variance
python -m testdata_generator \
  --workflow workflow.txt --issues 300 \
  --pattern batch \
  --mean-cycle-days 30 --pi-duration-weeks 12 \
  --completion-rate 0.8 --seed 3 \
  --output batch.json
```

Note: `--pattern` requires `--mean-cycle-days`. Without `--mean-cycle-days` the pattern is ignored.



## 5 ART\_A – Complete Example

---

This example shows the full pipeline from generator to finished report using the fictional ART\_A project.

### Step 1: Generate test data

```
python -m testdata_generator \  
    --workflow testdata_generator/workflow_ART_A.txt \  
    --project ART_A \  
    --issues 200 \  
    --from-date 2025-01-01 \  
    --to-date 2025-12-31 \  
    --issue-types Feature:0.6 Bug:0.2 Enabler:0.2 \  
    --completion-rate 0.75 \  
    --backflow-prob 0.08 \  
    --seed 42 \  
    --output ART_A_generated.json
```

Result: ART\_A\_generated.json with 200 issues — approximately 150 closed and 50 open.  
Reproducible with seed 42.

### Step 2: Process with transform\_data

```
python -m transform_data ART_A_generated.json \  
    --workflow testdata_generator/workflow_ART_A.txt
```

### Step 3: Create report with build\_reports

```
python -m build_reports
```

Expected output (seed 42, 200 issues):

- Issue keys: ART\_A-0001 to ART\_A-0200
- Issue types: ~120 Feature, ~40 Bug, ~40 Enabler
- ~150 issues with status 'Releasing' or 'Done'
- Creation dates distributed across 2025
- Occasional backward transitions (~8 %)

## 5b The Portfolio Scenario

With `--scenario portfolio` the generator creates a complete demo portfolio in one step: two solutions with three ARTs each, including every artifact of the processing chain.

In the GUI: the 'Demo portfolio' section at the bottom of the window generates the scenario into a folder of your choice at the click of a button (the seed field is honoured, default 42); 'Open Portfolio Report' renders the portfolio report, 'Open Delta Briefing' the 'what changed?' briefing from `snapshots/snapshot_prev/now.json` — no command line needed.

```
python -m testdata_generator --scenario portfolio \
    --output demo/ --seed 42
```

The target folder then contains:

| Artifact          | Content                                                                                                                                                                                        |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| workflows/        | two workflow files (Alpha and Beta stages)                                                                                                                                                     |
| raw/              | six Jira JSON exports (one generator run per ART)                                                                                                                                              |
| solutions/<name>/ | per solution: solution.json (Beta with its own stage_map), arts/ (IssueTimes/CFD/Transitions per ART) and registers/ with the nine registers under standard names (risks.json ... themes.json) |
| snapshots/        | report snapshots for the delta briefing (prev/now)                                                                                                                                             |
| portfolio.json    | portfolio config covering both solutions                                                                                                                                                       |
| pi_config.json    | PI intervals across the data window                                                                                                                                                            |
| README.md         | description of the built-in stories                                                                                                                                                            |

The data is placed relative to the generation date so the portfolio report's quality traffic light rates it as current. Three stories are built in:

**Built-in stories:**

- ART Alpha-3 is the outlier (about three times the cycle time) — highlighted red in Solution Alpha's comparison report.
- ART Beta-3 delivers weak data (no CFD, few started issues, data 60 days old) — confidence 'low' in the quality table.
- Solution Beta pools via its own stage\_map (Vorlauf/Umsetzung/Fertig); Solution Alpha uses the default path.
- ROAM board: two owned risks are deliberately old (45/50 days) — the aging highlight fires.
- NFR & runway: Beta's API NFR is violated and one runway element is an overdue gap — the dashboard shows red.
- Capability map: Beta's data-insights capability is critical, one Alpha capability has no ART (uncovered).
- Dependency heatmap: Alpha-1 → Alpha-3 blocked and overdue; Beta-1 → Alpha-1 as a cross-solution integration.
- Decision log: Beta's open assumption has passed its review date — flagged red as 'review due'.
- Delta briefing: snapshots/snapshot\_prev/now.json ship along — --delta shows throughput, Beta-3's confidence decay, AD-1's escalation, new risk BR-2, newly overdue items.
- SLO & DORA: Beta's sync API breaches its SLO, and ART Beta-3 is low tier in the delivery picture too (CFR 38 %, coverage 31 %).
- Flow-problem backlog (VSC): FP-A1/FP-B1 survive 3 resp. 4 conferences (red); --conference renders the pre-read.
- Strategic themes & roadmap: one orphan theme, EP-A9 a zombie; in the delta: EP-A9 loses its theme, EP-B2 moves P2 → P1.

The folder is directly usable: `python -m portfolio demo/portfolio.json` builds the portfolio report; the solution configs also work individually. The same seed yields identical data on the same day.

## 6 Frequently Asked Questions (FAQ)

---

### Difference between test data and real data?

For demos, training, and installation tests, test data is the better choice — no privacy concerns, reproducible, and fully controlled. For real flow analyses and decisions, actual data reflects the true workflow state.

*For the manual export of real Jira data: See the Get Data User Manual.*

## 7 Glossary

---

| Term       | Explanation                                                          |
|------------|----------------------------------------------------------------------|
| ART        | Agile Release Train — a team-of-teams structure in SAFe              |
| API        | Application Programming Interface — programming interface            |
| CFD        | Cumulative Flow Diagram — cumulative issue count per stage over time |
| Cycle time | Time from the first active stage to the closed stage                 |
| Helper     | SituationReport module for merging multiple Jira JSON files          |
| Issue      | A work item in Jira (Feature, Bug, Enabler, Story, ...)              |
| JSON       | JavaScript Object Notation — format of Jira API exports              |
| Seed       | Starting value for the random generator — same seed = same output    |
| Stage      | One step in the workflow (corresponds to a Jira column)              |
| Workflow   | Ordered sequence of stages that an issue passes through              |