

Package ‘CohortDiagnostics’

May 25, 2021

Type Package

Title Diagnostics for OHDSI Cohorts

Version 2.1.0

Date 2021-05-24

Maintainer Gowtham Rao <rao@ohdsi.org>

Description Diagnostics for cohorts that use the OMOP Common Data Model and the OHDSI tools.

Depends DatabaseConnector (>= 4.0.0),
FeatureExtraction (>= 3.1.1),
R (>= 4.0.0)

Imports Andromeda,
checkmate,
CirceR,
clock,
digest,
dplyr (>= 1.0.0),
methods,
ParallelLogger (>= 2.0.0),
pool,
readr (>= 1.4.0),
RJSONIO,
rlang,
ROhdsiWebApi (>= 1.2.0),
SqlRender (>= 1.7.0),
stringr,
tidyr (>= 1.0.0)

Suggests DT,
Eunomia,
ggiraph,
ggplot2,
htmltools,
knitr,
lubridate,
plotly,
purrr,
RColorBrewer,
rmarkdown,
RSQLite (>= 2.2.1),
scales,

shiny,
shinydashboard,
shinyWidgets,
testthat,
withr,
zip

Remotes ohdsi/Eunomia,
ohdsi/FeatureExtraction,
ohdsi/ROhdsiWebApi,
ohdsi/CirceR

License Apache License

VignetteBuilder knitr

URL <https://ohdsi.github.io/CohortDiagnostics>, <https://github.com/OHDSI/CohortDiagnostics>

BugReports <https://github.com/OHDSI/CohortDiagnostics/issues>

RoxygenNote 7.1.1

Encoding UTF-8

Language en-US

R topics documented:

checkInputFileEncoding	2
createResultsDataModel	3
getCohortCounts	3
getResultsDataModelSpecifications	4
instantiateCohortSet	4
launchCohortExplorer	7
launchDiagnosticsExplorer	8
preMergeDiagnosticsFiles	9
runCohortDiagnostics	9
uploadResults	13
Index	14

checkInputFileEncoding
<i>Check character encoding of input file</i>

Description

For its input files, CohortDiagnostics only accepts UTF-8 or ASCII character encoding. This function can be used to check whether a file meets these criteria.

Usage

checkInputFileEncoding(fileName)

Arguments

fileName The path to the file to check

Value

Throws an error if the input file does not have the correct encoding.

```
createResultsDataModel
```

Create the results data model tables on a database server.

Description

Create the results data model tables on a database server.

Usage

```
createResultsDataModel(connection = NULL, connectionDetails = NULL, schema)
```

Arguments

connection An object of type connection as created using the [connect](#) function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.

connectionDetails An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package. Can be left NULL if connection is provided.

schema The schema on the postgres server where the tables will be created.

Details

Only PostgreSQL servers are supported.

```
getCohortCounts
```

Count the cohort(s)

Description

Computes the subject and entry count per cohort

Usage

```
getCohortCounts(
  connectionDetails = NULL,
  connection = NULL,
  cohortDatabaseSchema,
  cohortTable = "cohort",
  cohortIds = c()
)
```

Arguments

connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.
connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
cohortDatabaseSchema	Schema name where your cohort table resides. Note that for SQL Server, this should include both the database and schema name, for example 'scratch.dbo'.
cohortTable	Name of the cohort table.
cohortIds	The cohort Id(s) used to reference the cohort in the cohort table. If left empty, all cohorts in the table will be included.

Value

A tibble with cohort counts

getResultsDataModelSpecifications

Get specifications for Cohort Diagnostics results data model

Description

Get specifications for Cohort Diagnostics results data model

Usage

```
getResultsDataModelSpecifications()
```

Value

A tibble data frame object with specifications

instantiateCohortSet *Instantiate a set of cohort*

Description

This function instantiates a set of cohort in the cohort table, using definitions that are fetched from a WebApi interface. Optionally, the inclusion rule statistics are computed and stored in the inclusionStatisticsFolder.

Usage

```

instantiateCohortSet(
  connectionDetails = NULL,
  connection = NULL,
  cdmDatabaseSchema,
  vocabularyDatabaseSchema = cdmDatabaseSchema,
  tempEmulationSchema = NULL,
  oracleTempSchema = NULL,
  cohortDatabaseSchema = cdmDatabaseSchema,
  cohortTable = "cohort",
  cohortIds = NULL,
  packageName = NULL,
  cohortToFile = "settings/CohortsToCreate.csv",
  baseUrl = NULL,
  cohortSetReference = NULL,
  generateInclusionStats = FALSE,
  inclusionStatisticsFolder = NULL,
  createCohortTable = TRUE,
  incremental = FALSE,
  incrementalFolder = NULL
)

```

Arguments

- | | |
|--------------------------|--|
| connectionDetails | An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided. |
| connection | An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes. |
| cdmDatabaseSchema | Schema name where your patient-level data in OMOP CDM format resides. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'. |
| vocabularyDatabaseSchema | Schema name where your OMOP vocabulary data resides. This is commonly the same as cdmDatabaseSchema. Note that for SQL Server, this should include both the database and schema name, for example 'vocabulary.dbo'. |
| tempEmulationSchema | Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created. |
| oracleTempSchema | DEPRECATED by DatabaseConnector: use tempEmulationSchema instead. |
| cohortDatabaseSchema | Schema name where your cohort table resides. Note that for SQL Server, this should include both the database and schema name, for example 'scratch.dbo'. |
| cohortTable | Name of the cohort table. |
| cohortIds | Optionally, provide a subset of cohort IDs to restrict the construction to. |

packageName	The name of the package containing the cohort definitions. Can be left NULL if baseUrl and cohortSetReference have been specified.
cohortToCreateFile	The location of the cohortToCreate file within the package. Is ignored if baseUrl and cohortSetReference have been specified. The cohortToCreateFile must be .csv file that is expected to be read into a dataframe object identical to requirements for cohortSetReference argument. This csv file is expected to be encoded in either ASCII or UTF-8, if not, an error message will be displayed and process stopped.
baseUrl	The base URL for the WebApi instance, for example: "http://server.org:80/WebAPI". Can be left NULL if packageName and cohortToCreateFile have been specified.
cohortSetReference	A data frame with four columns, as described in the details. Can be left NULL if packageName and cohortToCreateFile have been specified.
generateInclusionStats	Compute and store inclusion rule statistics?
inclusionStatisticsFolder	The folder where the inclusion rule statistics are stored. Can be left NULL if generateInclusionStats = FALSE.
createCohortTable	Create the cohort table? If incremental = TRUE and the table already exists this will be skipped.
incremental	Create only cohorts that haven't been created before?
incrementalFolder	If incremental = TRUE, specify a folder where records are kept of which definition has been executed.

Details

Currently two ways of executing this function are supported, either (1) [Package Mode] embedded in a study package, assuming the cohort definitions are stored in that package using the `ROhdsiWebApi::insertCohortDefinition` or (2) [WebApi Mode] By using a WebApi interface to retrieve the cohort definitions.

When using this function in Package Mode: Use the `packageName` and `cohortToCreateFile` to specify the name of the study package, and the name of the cohortToCreate file within that package, respectively

When using this function in WebApi Mode: use the `baseUrl` and `cohortSetReference` to specify how to connect to the WebApi, and which cohorts to fetch, respectively.

Note: if the parameters for both Package Mode and WebApi Mode are provided, then Package mode is preferred.

The `cohortSetReference` argument must be a data frame with the following columns:

referentConceptId A standard omop concept id that serves as the referent phenotype definition for the cohort Id.

cohortId The cohort Id is the id used to identify a cohort definition. This is required to be unique. It will be used to create file names. It is recommended to be $(\text{referentConceptId} * 1000) + \text{a number between 3 to 999}$

webApiCohortId Cohort Id in the webApi/atlas instance. It is a required field to run Cohort Diagnostics in WebApi mode. It is discarded in package mode.

cohortName The full name of the cohort. This will be shown in the Shiny app.

logicDescription A human understandable brief description of the cohort definition. This logic does not have to a fully specified description of the cohort definition, but should provide enough context to help user understand the meaning of the cohort definition

Value

A data frame with cohort counts

launchCohortExplorer *Launch the CohortExplorer Shiny app*

Description

Launch the CohortExplorer Shiny app

Usage

```
launchCohortExplorer(
  connectionDetails,
  cdmDatabaseSchema,
  cohortDatabaseSchema,
  cohortTable,
  cohortId,
  sampleSize = 100,
  subjectIds = NULL
)
```

Arguments

connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package.
cdmDatabaseSchema	Schema name where your patient-level data in OMOP CDM format resides. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'.
cohortDatabaseSchema	Schema name where your cohort table resides. Note that for SQL Server, this should include both the database and schema name, for example 'scratch.dbo'.
cohortTable	Name of the cohort table.
cohortId	The ID of the cohort.
sampleSize	Number of subjects to sample from the cohort. Ignored if subjectIds is specified.
subjectIds	A vector of subject IDs to view.

Details

Launches a Shiny app that allows the user to explore a cohort of interest.

launchDiagnosticsExplorer

Launch the Diagnostics Explorer Shiny app

Description

Launch the Diagnostics Explorer Shiny app

Usage

```
launchDiagnosticsExplorer(
  dataFolder = "data",
  dataFile = "PreMerged.RData",
  connectionDetails = NULL,
  resultsDatabaseSchema = NULL,
  vocabularyDatabaseSchema = NULL,
  vocabularyDatabaseSchemas = resultsDatabaseSchema,
  aboutText = NULL,
  runOverNetwork = FALSE,
  port = 80,
  launch.browser = FALSE
)
```

Arguments

dataFolder	A folder where the premerged file is stored. Use the preMergeDiagnosticsFiles function to generate this file.
dataFile	(Optional) The name of the .RData file with results. It is commonly known as the Premerged file.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package, specifying how to connect to the server where the CohortDiagnostics results have been uploaded using the uploadResults function.
resultsDatabaseSchema	The schema on the database server where the CohortDiagnostics results have been uploaded.
vocabularyDatabaseSchema	(Deprecated) Please use vocabularyDatabaseSchemas.
vocabularyDatabaseSchemas	(optional) A list of one or more schemas on the database server where the vocabulary tables are located. The default value is the value of the resultsDatabaseSchema. We can provide a list of vocabulary schema that might represent different versions of the OMOP vocabulary tables. It allows us to compare the impact of vocabulary changes on Diagnostics.
aboutText	Text (using HTML markup) that will be displayed in an About tab in the Shiny app. If not provided, no About tab will be shown.
runOverNetwork	(optional) Do you want the app to run over your network?
port	(optional) Only used if runOverNetwork = TRUE.
launch.browser	Should the app be launched in your default browser, or in a Shiny window. Note: copying to clipboard will not work in a Shiny window.

Details

Launches a Shiny app that allows the user to explore the diagnostics

```
preMergeDiagnosticsFiles
```

Premerge Shiny diagnostics files

Description

This function combines diagnostics results from one or more databases into a single file. The result is a single file that can be used as input for the Diagnostics Explorer Shiny app.

It also checks whether the results conform to the results data model specifications.

Usage

```
preMergeDiagnosticsFiles(dataFolder, tempFolder = tempdir())
```

Arguments

dataFolder	folder where the exported zip files for the diagnostics are stored. Use the runCohortDiagnostics function to generate these zip files. Zip files containing results from multiple databases may be placed in the same folder.
tempFolder	A folder on the local file system where the zip files are extracted to. Will be cleaned up when the function is finished. Can be used to specify a temp folder on a drive that has sufficient space if the default system temp space is too limited.

```
runCohortDiagnostics
```

Run cohort diagnostics

Description

Runs the cohort diagnostics on all (or a subset of) the cohorts instantiated using the `ROhdsiWebApi::insertCohortDefinition` function. Assumes the cohorts have already been instantiated.

Characterization: If `runTemporalCohortCharacterization` argument is `TRUE`, then the following default covariateSettings object will be created using `RFeatureExtraction::createTemporalCovariateSettings`. Alternatively, a covariate setting object may be created using the above as an example.

Usage

```
runCohortDiagnostics(
  packageName = NULL,
  cohortToCreateFile = "settings/CohortsToCreate.csv",
  baseUrl = NULL,
  cohortSetReference = NULL,
  connectionDetails = NULL,
  connection = NULL,
  cdmDatabaseSchema,
  oracleTempSchema = NULL,
```

```

tempEmulationSchema = NULL,
cohortDatabaseSchema,
vocabularyDatabaseSchema = cdmDatabaseSchema,
cohortTable = "cohort",
cohortIds = NULL,
inclusionStatisticsFolder = file.path(exportFolder, "inclusionStatistics"),
exportFolder,
databaseId,
databaseName = databaseId,
databaseDescription = databaseId,
cdmVersion = 5,
runInclusionStatistics = TRUE,
runIncludedSourceConcepts = TRUE,
runOrphanConcepts = TRUE,
runTimeDistributions = TRUE,
runVisitContext = TRUE,
runBreakdownIndexEvents = TRUE,
runIncidenceRate = TRUE,
runTimeSeries = TRUE,
runCohortOverlap = TRUE,
runCohortCharacterization = TRUE,
covariateSettings = createDefaultCovariateSettings(),
runTemporalCohortCharacterization = TRUE,
temporalCovariateSettings = createTemporalCovariateSettings(useConditionOccurrence =
  TRUE, useDrugEraStart = TRUE, useProcedureOccurrence = TRUE, useMeasurement = TRUE,
  temporalStartDays = c(-365, -30, 0, 1, 31), temporalEndDays = c(-31, -1, 0, 30, 365)),
minCellCount = 5,
incremental = FALSE,
incrementalFolder = file.path(exportFolder, "incremental")
)

```

Arguments

packageName	The name of the package containing the cohort definitions. Can be left NULL if baseUrl and cohortSetReference have been specified.
cohortToCreateFile	The location of the cohortToCreate file within the package. Is ignored if baseUrl and cohortSetReference have been specified. The cohortToCreateFile must be .csv file that is expected to be read into a dataframe object identical to requirements for cohortSetReference argument. This csv file is expected to be encoded in either ASCII or UTF-8, if not, an error message will be displayed and process stopped.
baseUrl	The base URL for the WebApi instance, for example: "http://server.org:80/WebAPI". Can be left NULL if packageName and cohortToCreateFile have been specified.
cohortSetReference	A data frame with four columns, as described in the details. Can be left NULL if packageName and cohortToCreateFile have been specified.
connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package. Can be left NULL if connection is provided.

connection	An object of type connection as created using the connect function in the DatabaseConnector package. Can be left NULL if connectionDetails is provided, in which case a new connection will be opened at the start of the function, and closed when the function finishes.
cdmDatabaseSchema	Schema name where your patient-level data in OMOP CDM format resides. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'.
oracleTempSchema	DEPRECATED by DatabaseConnector: use tempEmulationSchema instead.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
cohortDatabaseSchema	Schema name where your cohort table resides. Note that for SQL Server, this should include both the database and schema name, for example 'scratch.dbo'.
vocabularyDatabaseSchema	Schema name where your OMOP vocabulary data resides. This is commonly the same as cdmDatabaseSchema. Note that for SQL Server, this should include both the database and schema name, for example 'vocabulary.dbo'.
cohortTable	Name of the cohort table.
cohortIds	Optionally, provide a subset of cohort IDs to restrict the diagnostics to.
inclusionStatisticsFolder	The folder where the inclusion rule statistics are stored. Can be left NULL if runInclusionStatistics = FALSE.
exportFolder	The folder where the output will be exported to. If this folder does not exist it will be created.
databaseId	A short string for identifying the database (e.g. 'Synpuf').
databaseName	The full name of the database. If NULL, defaults to databaseId.
databaseDescription	A short description (several sentences) of the database. If NULL, defaults to databaseId.
cdmVersion	The version of the OMOP CDM. Default 5. (Note: only 5 is supported.)
runInclusionStatistics	Generate and export statistic on the cohort inclusion rules?
runIncludedSourceConcepts	Generate and export the source concepts included in the cohorts?
runOrphanConcepts	Generate and export potential orphan concepts?
runTimeDistributions	Generate and export cohort time distributions?
runVisitContext	Generate and export index-date visit context?
runBreakdownIndexEvents	Generate and export the breakdown of index events?
runIncidenceRate	Generate and export the cohort incidence rates?

runTimeSeries Generate and export the cohort prevalence rates?

runCohortOverlap Generate and export the cohort overlap? Overlaps are checked within cohortIds that have the same phenotype ID sourced from the CohortSetReference or cohortToCreateFile.

runCohortCharacterization Generate and export the cohort characterization? Only records with values greater than 0.0001 are returned.

covariateSettings Either an object of type covariateSettings as created using one of the createCovariateSettings function in the FeatureExtraction package, or a list of such objects.

runTemporalCohortCharacterization Generate and export the temporal cohort characterization? Only records with values greater than 0.001 are returned.

temporalCovariateSettings Either an object of type covariateSettings as created using one of the createTemporalCovariateSettings function in the FeatureExtraction package, or a list of such objects.

minCellCount The minimum cell count for fields contains person counts or fractions.

incremental Create only cohort diagnostics that haven't been created before?

incrementalFolder If incremental = TRUE, specify a folder where records are kept of which cohort diagnostics has been executed.

Details

Currently two ways of executing this function are supported, either (1) [Package Mode] embedded in a study package, assuming the cohort definitions are stored in that package using the `ROhdsiWebApi::insertCohortD` or (2) [WebApi Mode] By using a WebApi interface to retrieve the cohort definitions.

When using this function in Package Mode: Use the `packageName` and `cohortToCreateFile` to specify the name of the study package, and the name of the cohortToCreate file within that package, respectively

When using this function in WebApi Mode: use the `baseUrl` and `cohortSetReference` to specify how to connect to the WebApi, and which cohorts to fetch, respectively.

Note: if the parameters for both Package Mode and WebApi Mode are provided, then Package mode is preferred.

The `cohortSetReference` argument must be a data frame with the following columns:

referentConceptId A standard omop concept id that serves as the referent phenotype definition for the cohort Id.

cohortId The cohort Id is the id used to identify a cohort definition. This is required to be unique. It will be used to create file names. It is recommended to be $(\text{referentConceptId} * 1000) + \text{a number between 3 to 999}$

webApiCohortId Cohort Id in the webApi/atlas instance. It is a required field to run Cohort Diagnostics in WebApi mode. It is discarded in package mode.

cohortName The full name of the cohort. This will be shown in the Shiny app.

logicDescription A human understandable brief description of the cohort definition. This logic does not have to a fully specified description of the cohort definition, but should provide enough context to help user understand the meaning of the cohort definition

uploadResults	<i>Upload results to the database server.</i>
---------------	---

Description

Requires the results data model tables have been created using the [createResultsDataModel](#) function.

Set the POSTGRES_PATH environmental variable to the path to the folder containing the psql executable to enable bulk upload (recommended).

Usage

```
uploadResults(  
  connectionDetails = NULL,  
  schema,  
  zipFileName,  
  forceOverWriteOfSpecifications = FALSE,  
  purgeSiteDataBeforeUploading = TRUE,  
  tempFolder = tempdir()  
)
```

Arguments

connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package.
schema	The schema on the postgres server where the tables have been created.
zipFileName	The name of the zip file.
forceOverWriteOfSpecifications	If TRUE, specifications of the phenotypes, cohort definitions, and analysis will be overwritten if they already exist on the database. Only use this if these specifications have changed since the last upload.
purgeSiteDataBeforeUploading	If TRUE, before inserting data for a specific databaseId all the data for that site will be dropped. This assumes the input zip file contains the full data for that data site.
tempFolder	A folder on the local file system where the zip files are extracted to. Will be cleaned up when the function is finished. Can be used to specify a temp folder on a drive that has sufficient space if the default system temp space is too limited.

Index

checkInputFileEncoding, [2](#)
connect, [3–5](#), [11](#)
createConnectionDetails, [3–5](#), [7](#), [8](#), [10](#), [13](#)
createResultsDataModel, [3](#), [13](#)

getCohortCounts, [3](#)
getResultsDataModelSpecifications, [4](#)

instantiateCohortSet, [4](#)

launchCohortExplorer, [7](#)
launchDiagnosticsExplorer, [8](#)

preMergeDiagnosticsFiles, [8](#), [9](#)

runCohortDiagnostics, [9](#), [9](#)

uploadResults, [8](#), [13](#)