



Presentation for use with the textbook **Data Structures and Algorithms in Java, 6th edition**, by M. T. Goodrich, R. Tamassia, and M. H. Goldwasser, Wiley, 2014

Trees




What is a Tree

- ❑ In computer science, a tree is an abstract model of a hierarchical structure
- ❑ A tree consists of nodes with a parent-child relation
- ❑ Applications:
 - Organization charts
 - File systems
 - Programming environments



Tree Terminology

- ❑ Root: node without parent (A)
- ❑ Internal node: node with at least one child (A, B, C, F)
- ❑ External node (a.k.a. leaf): node without children (E, I, J, K, G, H, D)
- ❑ Ancestors of a node: parent, grandparent, grand-grandparent, etc.
- ❑ Depth of a node: number of ancestors
- ❑ Height of a tree: maximum depth of any node (3)
- ❑ Descendant of a node: child, grandchild, grand-grandchild, etc.
- ❑ Subtree: tree consisting of a node and its descendants



Tree ADT

- We use positions to abstract nodes
- Generic methods:
 - integer `size()`
 - boolean `isEmpty()`
 - Iterator `iterator()`
 - Iterable `positions()`
- Accessor methods:
 - position `root()`
 - position `parent(p)`
 - Iterable `children(p)`
 - Integer `numChildren(p)`

◆ Query methods:

- boolean `isInternal(p)`
- boolean `isExternal(p)`
- boolean `isRoot(p)`

◆ Additional update methods may be defined by data structures implementing the Tree ADT

Java Interface


Methods for a Tree interface:

```
1  /** An interface for a tree where nodes can have an arbitrary number of children. */
2  public interface Tree<E> extends Iterable<E> {
3      Position<E> root();
4      Position<E> parent(Position<E> p) throws IllegalArgumentException;
5      Iterable<Position<E>> children(Position<E> p)
6                               throws IllegalArgumentException;
7      int numChildren(Position<E> p) throws IllegalArgumentException;
8      boolean isInternal(Position<E> p) throws IllegalArgumentException;
9      boolean isExternal(Position<E> p) throws IllegalArgumentException;
10     boolean isRoot(Position<E> p) throws IllegalArgumentException;
11     int size();
12     boolean isEmpty();
13     Iterator<E> iterator();
14     Iterable<Position<E>> positions();
15 }
```

Binary Trees


- A binary tree is a tree with the following properties:
 - Each internal node has at most two children (exactly two for **proper** binary trees)
 - The children of a node are an ordered pair
- We call the children of an internal node **left child** and **right child**
- Alternative recursive definition: a binary tree is either
 - a tree consisting of a single node, or
 - a tree whose root has an ordered pair of children, each of which is a binary tree

- Applications:
 - arithmetic expressions
 - decision processes
 - searching




Arithmetic Expression Tree

- Binary tree associated with an arithmetic expression
 - internal nodes: operators
 - external nodes: operands
- Example: arithmetic expression tree for the expression $(2 \times (a - 1) + (3 \times b))$



Decision Tree


- Binary tree associated with a decision process
 - internal nodes: questions with yes/no answer
 - external nodes: decisions
- Example: dining decision



Properties of Proper Binary Trees


□ Notation

- n number of nodes
- e number of external nodes
- i number of internal nodes
- h height



◆ Properties:

- $e = i + 1$
- $n = 2e - 1$
- $h \leq i$
- $h \leq (n - 1)/2$
- $e \leq 2^h$
- $h \geq \log_2 e$
- $h \geq \log_2 (n + 1) - 1$




BinaryTree ADT

- The **BinaryTree** ADT extends the Tree ADT, i.e., it inherits all the methods of the Tree ADT
- Additional methods:
 - position **left**(p)
 - position **right**(p)
 - position **sibling**(p)
- The above methods return **null** when there is no left, right, or sibling of p, respectively
- Update methods may be defined by data structures implementing the BinaryTree ADT

Preorder Traversal

- A traversal visits the nodes of a tree in a systematic manner
- In a preorder traversal, a node is visited before its descendants
- Application: print a structured document


Algorithm *preOrder(v)*
visit(v)
for each child *w* of *v*
preorder(w)



Postorder Traversal


- In a postorder traversal, a node is visited after its descendants
- Application: compute space used by files in a directory and its subdirectories

Algorithm *postOrder*(*v*)
 for each child *w* of *v*
 postOrder (*w*)
 visit(*v*)



Breadth-First Traversal


- Visit all positions at depth d before we visit the positions at depth $d+1$



Inorder Traversal


- In an inorder traversal a node is visited after its left subtree and before its right subtree
- Application: draw a binary tree
 - $x(v)$ = inorder rank of v
 - $y(v)$ = depth of v

```
Algorithm inOrder( $v$ )  
  if  $left(v) \neq null$   
    inOrder( $left(v)$ )  
  visit( $v$ )  
  if  $right(v) \neq null$   
    inOrder( $right(v)$ )
```



Print Arithmetic Expressions

- Specialization of an inorder traversal
 - print operand or operator when visiting node
 - print “(“ before traversing left subtree
 - print “)” after traversing right subtree



Algorithm *printExpression(v)*

```
if left(v) ≠ null
    print("(")
    inOrder(left(v))
    print(v.element())
if right(v) ≠ null
    inOrder(right(v))
    print(")")
```

$((2 \times (a - 1)) + (3 \times b))$

Evaluate Arithmetic Expressions

- Specialization of a postorder traversal
 - recursive method returning the value of a subtree
 - when visiting an internal node, combine the values of the subtrees

Algorithm *evalExpr(v)*

if *isExternal*(v)

return *v.element*()


else

x \leftarrow *evalExpr*(*left*(v))

y \leftarrow *evalExpr*(*right*(v))



\diamond \leftarrow operator stored at v

return *x* \diamond *y*





Linked Structure for Trees

- A node is represented by an object storing
 - Element
 - Parent node
 - Sequence of children nodes
- Node objects implement the Position ADT




Linked Structure for Binary Trees

- A node is represented by an object storing
 - Element
 - Parent node
 - Left child node
 - Right child node
- Node objects implement the Position ADT



Array-Based Representation of Binary Trees

- Nodes are stored in an array A



Node v is stored at $A[\text{rank}(v)]$

- $\text{rank}(\text{root}) = 0$
- if node is the left child of $\text{parent}(\text{node})$,
 $\text{rank}(\text{node}) = 2 \cdot \text{rank}(\text{parent}(\text{node})) + 1$
- if node is the right child of $\text{parent}(\text{node})$,
 $\text{rank}(\text{node}) = 2 \cdot \text{rank}(\text{parent}(\text{node})) + 2$

