

## Supplementary Material for CVPR 2023 paper #11206

Anonymous CVPR submission

Paper ID 11206

### 1. Summary

This material presents the supplementary paper from the main paper due to the space limitation. In Section 2, the detailed calculation process of gradient for coefficients are presented. Additional details for ASAP architecture that were omitted from the main manuscript are presented in Section 3. In Section 4, hyperparameters of ASAP and baselines for both node classification and graph classification and more results on brain network classification on ADNI data are shown.

### 2. Gradients of Polynomial Coefficients with Scale

In this section, we are going to show the detailed derivation of gradient  $\frac{\partial c_{s,n}}{\partial s}$  for the three polynomials, i.e., Chebyshev, Hermite and Laguerre.

**Chebyshev Polynomial.** The expansion coefficient for Chebyshev polynomial is given as

$$c_{s,n}^T = (2 - \delta_{n0})(-1)^n e^{-\frac{sb}{2}} I_n \left( \frac{sb}{2} \right), \quad (1)$$

and the derivative of  $c_{s,n}^T$  with respect to  $s$  is obtained as

$$\begin{aligned} \frac{\partial c_{s,n}^T}{\partial s} &= 2(-1)^n e^{-\frac{sb}{2}} \left( \frac{-b}{2} \right) I_n \left( \frac{sb}{2} \right) + 2(-1)^n e^{-\frac{sb}{2}} I_n \left( \frac{sb}{2} \right) \frac{b}{2} \\ &= 2(-1)^n e^{-\frac{sb}{2}} \left( -\frac{b}{2} I_n \left( \frac{sb}{2} \right) + \frac{b}{2} I'_n \left( \frac{sb}{2} \right) \right) \\ &= (-1)^n b e^{-\frac{sb}{2}} \left( I'_n \left( \frac{sb}{2} \right) - I_n \left( \frac{sb}{2} \right) \right) \\ &= (-1)^n b e^{-\frac{sb}{2}} \left( I_{n-1} \left( \frac{sb}{2} \right) - \frac{n}{\frac{sb}{2}} I_n \left( \frac{sb}{2} \right) - I_n \left( \frac{sb}{2} \right) \right) \\ &= (-1)^n b e^{-\frac{sb}{2}} \left( I_{n-1} \left( \frac{sb}{2} \right) - \left( \frac{2n}{sb} + 1 \right) I_n \left( \frac{sb}{2} \right) \right) \\ &\quad \left( \because I'_n(x) = I_{n-1}(x) - \frac{n}{x} I_n(x) \right). \end{aligned} \quad (2)$$

**Hermite Polynomial.** The expansion coefficient for Hermite polynomial is written as

$$c_{s,n}^H = \frac{1}{n!} \left( \frac{-s}{2} \right)^n e^{\frac{s^2}{4}}, \quad (3)$$

108 and the derivative of  $c_{s,n}^H$  with respect to  $s$  is computed as 162  
 109  
 110 
$$\frac{\partial c_{s,n}^H}{\partial s} = \frac{n}{n!} \left(\frac{-s}{2}\right)^{n-1} \left(\frac{-1}{2}\right) e^{\frac{s^2}{4}} + \frac{1}{n!} \left(\frac{-s}{2}\right)^n e^{\frac{s^2}{4}} \frac{s}{2}$$
 163  
 111  
 112 
$$= \frac{1}{n!} e^{\frac{s^2}{4}} \left(\frac{-s}{2}\right)^n \left(\frac{-n}{2} \left(\frac{-s}{2}\right)^{-1} + \frac{s}{2}\right)$$
 164  
 113  
 114 
$$= \frac{1}{n!} e^{\frac{s^2}{4}} \left(\frac{-s}{2}\right)^n \left(\frac{n}{s} + \frac{s}{2}\right)$$
 165  
 115  
 116 
$$= \frac{1}{n!} e^{\frac{s^2}{4}} \left(\frac{-s}{2}\right)^n \frac{n s}{s 2 s} + \frac{1}{n!} e^{\frac{s^2}{4}} \left(\frac{-s}{2}\right)^n \frac{s}{2}$$
 166  
 117  
 118 
$$= \frac{s e^{\frac{s^2}{4}}}{2n!} \left(\frac{-s}{2}\right)^n \left(\frac{2n}{s^2} + 1\right).$$
 167  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215

**Laguerre Polynomial.** The expansion coefficient for Laguerre polynomial is written as

$$c_{s,n}^L = \frac{s^n}{(s+1)^{n+1}}, \quad (5)$$

and the derivative of  $c_{s,n}^L$  with respect to  $s$  is calculated as

$$\begin{aligned} \frac{\partial c_{s,n}^L}{\partial s} &= \frac{ns^{n-1}(s+1)^{n+1} - s^n(n+1)(s+1)^n}{\{(s+1)^{n+1}\}^2} \\ &= \frac{ns^{n-1}(s+1)^{n+1} - s^n(n+1)(s+1)^n}{(s+1)^{2n}(s+1)^2} \\ &= \frac{ns^{n-1}(s+1) - s^n(n+1)}{(s+1)^n(s+1)^2} \\ &= \frac{ns^n + ns^{n-1} - ns^n - s^n}{(s+1)^{n+2}} \\ &= \frac{ns^{n-1} - s^n}{(s+1)^{n+2}} \\ &= \frac{\left(\frac{n}{s} - 1\right)s^n}{(s+1)^{n+2}} \\ &= \frac{s^{n-1}(n-s)}{(s+1)^{n+2}}. \end{aligned} \quad (6)$$

### 3. ASAP Architecture

**Readout for Graph Classification.** The  $f_R(\cdot)$  with weights  $W_R$  takes  $H_K$  from the convolution layers as an input and returns  $h_G$ . In our model architecture,  $h_G$  is chosen as 2-layer Multi-layer perceptron (MLP) as

$$h_G = \sigma_{R_2}(\sigma_{R_1}(H_K W_{R_1}) W_{R_2}) \quad (7)$$

where  $R_1$  and  $R_2$  correspond to first and second layer for MLP structure, respectively.  $W_{R_1}$  and  $W_{R_2}$  denote weights and Rectified Linear Unit (ReLU) was used for the non-linear activation functions  $\sigma_{R_1}$  and  $\sigma_{R_2}$  for each layer. To make our model end-to-end trainable, the derivative of  $h_G$  with respect to  $H_K$  is computed as

$$h'_G = \sigma'_{R_2}(\sigma_{R_1}(H_K W_{R_1}) W_{R_2}) W_{R_2} \sigma'_{R_1}(H_K W_{R_1}) W_{R_1}. \quad (8)$$

216

Table 1. Hyperparameters for classification tasks.

270

217

271

218

272

219

273

220

274

221

275

222

276

223

277

224

278

225

279

226

280

227

281

228

282

229

283

230

284

231

285

232

286

233

287

234

288

235

289

236

290

237

291

238

292

239

293

240

294

241

295

242

296

Task	Dataset	Model	Hidden Units	Learning Rate	Dropout Rate	Regularization ( $\alpha$ )	Scale's Learning Rate ( $\beta_s$ )	ASAP-C (b)
Node Classification	Cora	ASAP & Exact	64	0.01	0.5	0.1	1	1.48
	Citeseer	ASAP & Exact	32	0.01	0.5	1	10	1.50
	Pubmed	ASAP & Exact	64	0.1	0.5	1	10	1.65
	Amazon Computer	GAT	32	0.01	0.5	-	-	-
		GDC	32	0.0001	0.5	-	-	-
		GraphHeat	32	0.01	0.5	-	-	-
		ASAP & Exact	32	0.001	0.5	1	1	1.60
	Amazon photo	GAT	32	0.01	0.5	-	-	-
		GDC	16	0.0001	0.5	-	-	-
		GraphHeat	32	0.01	0.5	-	-	-
		ASAP & Exact	32	0.01	0.5	1	10	1.59
	Coauthor CS	GAT	32	0.01	0.5	-	-	-
		GDC	16	0.0001	0.5	-	-	-
		GraphHeat	32	0.01	0.5	-	-	-
		ASAP & Exact	32	0.01	0.5	1	1	1.41
Graph Classification	Cortical Thickness	SVM (Linear)	-	-	-	-	-	-
		MLP (2-layers)	16	0.01	0.5	-	-	-
		GCN	16	0.01	0.5	-	-	-
		GAT	16	0.01	0.1	-	-	-
		GDC	16	0.01	0.5	-	-	-
		GraphHeat	32	0.01	0.5	-	-	-
		ASAP & Exact	16	0.01	0.5	1	1	1.20
	FDG	SVM (Linear)	-	-	-	-	-	-
		MLP (2-layers)	16	0.01	0.5	-	-	-
		GCN	16	0.01	0.5	-	-	-
		GAT	16	0.01	0.1	-	-	-
		GDC	16	0.01	0.5	-	-	-
		GraphHeat	16	0.01	0.5	-	-	-
		ASAP & Exact	16	0.01	0.5	1	1	1.20

## 4. Experiments

In the main experiments, we compared the performances between ASAP and baselines on node classification and graph classification. For node classification, standard benchmarks (Cora, Citeseer and Pubmed) and additional datasets (Amazon Computers, Amazon Photo, and Coauthor CS) were used to validate the performance of ASAP. For graph classification, the ADNI dataset containing a number of subjects with brain network was used to classify AD-specific labels. Hyperparameters should be set so that the model can properly learn data in each experiment. Table 1 shows the detailed parameters of ASAP and baselines for the main experiments.

The trained scales on the brain network classification with Exact and ASAP are visualized in Fig. 1 and Fig. 2 containing additional interpretable results visualized from various views. In Table 2, based on Exact, smallest scales that appear in common across Exact and ASAPs are listed. 7 ROIs were detected in Exact and ASAPs, 6 ROIs were detected in 3 models,




Figure 1. Visualization of learned scales on the cortical and sub-cortical regions of a brain. This visualization shows the scale of each ROI through the classification result using Cortical Thickness feature.




Figure 2. Visualization of learned scales on the cortical and sub-cortical regions of a brain. This visualization shows the scale of each ROI through the classification result using FDG feature.

Table 2. ROIs with the smallest trained scales for AD classification. (L) and (R) denote left and right hemisphere.

# of common models	ROI	Cortical Thickness				# of common models	ROI	FDG			
		Exact	ASAP-C	ASAP-H	ASPA-L			Exact	ASAP-C	ASAP-H	ASPA-L
4	(R) S.pericallosal	0.035	0.097	0.033	0.050	4	(L) G&S.paracentral	0.034	0.052	0.049	0.066
	(R) Lat.Fis.ant.Horizont	0.048	0.074	0.039	0.037		(L) G.front.inf.Orbital	0.036	0.071	0.060	0.043
	(L) Lat.Fis.ant.Horizont	0.049	0.083	0.038	0.051		(R) G.precuneus	0.041	0.044	0.034	0.051
	(L) G&S.paracentral	0.059	0.034	0.046	0.044		(R) S.orital.med.ofact	0.047	0.078	0.054	0.059
	(L) G&S.ocipital.inf	0.062	0.071	0.043	0.055		(R) G.cingul.Post.ventral	0.055	0.056	0.055	0.051
	(R) Lat.Fis.ant.Vertical	0.064	0.108	0.046	0.041		(R) S.oc.temp.lat	0.055	0.065	0.045	0.063
	(L) G.cingul.Post.ventral	0.068	0.127	0.035	0.066		(R) G.oc.temp.med.Lingual	0.055	0.076	0.043	0.040
3	(L) S.suborbital	0.036	-	0.054	0.060	3	(L) Sub.put	0.058	0.077	0.047	0.060
	(L) S.temporal.inf	0.045	0.129	0.039	0.057		(L) S.postcentral	0.061	0.069	0.060	0.018
	(L) S.ocipital.ant	0.050	0.119	-	0.064		(R) G.front.inf.Orbital	0.063	0.093	0.069	0.050
	(R) S.precentral.inf.part	0.054	0.052	-	0.057		(R) S.intrapariet.&P.trans	0.046	0.095	-	0.054
	(R) S.oc.temp.med&Lingual	0.055	-	0.052	0.062		(L) G.cuneus	0.049	-	0.044	0.062
	(L) G.temp.sup.G.T.transv	0.068	0.104	0.049	-		(R) S.temporal.sup	0.049	-	0.028	0.056
2	(R) G.parietal.sup	0.035	-	0.056	-	2	(R) S.calcarine	0.053	0.059	-	0.047
	(R) Lat.Fis.post	0.049	0.067	-	-		(R) G&S.paracentral	0.055	-	0.051	0.048
	(L) Lat.Fis.ant.Vertical	0.059	-	-	0.040		(R) G.cuneus	0.057	-	0.057	0.066
	(R) S.suborbital	0.064	-	-	0.048		(R) G&S.cingul.Mid.Ant	0.062	0.041	-	-
	RMSE for all ROIs	-	<b>0.5358</b>	<b>0.4193</b>	<b>0.4072</b>		RMSE for all ROIs	-	<b>0.5827</b>	<b>0.2904</b>	<b>0.2899</b>

and only 2 ROIs were in 2 models for cortical thickness feature. Using FDG, 10 ROIs were detected in every model, 6 ROIS were detected in 3 models, and 2 ROIs were detected in 2 models. In addition, similar ROIs overall showed similar values of scale in all models.