

unicon — interpret or compile Unicon programs

Unicon Project

Unicon Technical Report: 11

2014-07-28

Abstract

Manual page for unicon, iconc, and iconc — tools that convert Unicon and Icon source programs into executable form.

Unicon Project

<http://unicon.org>

University of Idaho

Department of Computer Science
Moscow, ID, 83844, USA

1 NAME

unicon - interpret or compile Unicon programs

2 SYNOPSIS

```
| unicon [ option ... ] file ... [ -x arg ... ] | iconc [ option ... ] file ... [ -x arg ... ] | iconc [ option ... ] file ... [ -x arg ... ]
```

3 DESCRIPTION

The programs unicon, iconc and iconc convert Unicon and Icon source programs into executable form. By default unicon, like iconc, translates quickly and provides interpretive (virtual machine) execution. Unicon with the -C option uses iconc, which takes longer to compile but produces programs that execute faster. iconc and iconc for the most part can be used interchangeably. Unicon is a superset that supports Icon programs, while adding classes, packages, and various other features.

This manual page describes unicon, and the versions of iconc and iconc that come with unicon. This page is gratefully based on the Icon Project manual page for icon. Where there are differences in usage between unicon, iconc and iconc, these are noted.

File Names: Files whose names end in .icn are assumed to be Unicon source files. The .icn suffix may be omitted; if it is not present, it is supplied. The character - can be used to indicate an Unicon source file given in standard input. Several source files can be given on the same command line; if so, they are combined to produce a single program.

The name of the executable file is the base name of the first input file, formed by deleting the suffix, if present. stdin is used for source programs given in standard input.

Processing: As noted in the synopsis above, unicon, iconc and iconc accept options followed by file names, optionally followed by -x and arguments. If -x is given, the program is executed automatically and any following arguments are passed to it.

unicon: The processing performed by unicon consists of *class and package preprocessing* followed by invocation of iconc (or iconc, if -C is given) to produce code and/or executable output.

icont: The processing performed by icont consists of two phases: *translation* and *linking*. During translation, each Icon source file is translated into an intermediate language called *ucode*. A ucode file is produced for each source file, with a base name taken from the source file and the suffix *.u*. During linking, one or more ucode files are combined to produce a single *icode* file. The ucode files are deleted after the icode file is created.

Processing by unicon or icont can be terminated after translation by the *-c* option. In this case, the ucode files are not deleted. The names of *.u* files from previous translations can be given on the unicon or icont command line. These files are included in the linking phase after the translation of any source files. Ucode files that are explicitly named are not deleted.

iconc: The processing performed by iconc consists of two phases: *code generation* and *compilation and linking*. The code generation phase produces C code, consisting of a *.c* and a *.h* file, with the base name of the first source file. These files are then compiled and linked to produce an executable binary file. The C files normally are deleted after compilation and linking.

Processing by iconc can be terminated after code generation by the *-c* option. In this case, the C files are not deleted.

4 OPTIONS

The following options are recognized by unicon, icont, and iconc:

<i>-c</i>	Stop after producing intermediate files and do not delete them (unicon and icont only).
<i>-e file</i>	Redirect standard error output to <i>file</i> .
<i>-f s</i>	Enable full string invocation.
<i>-o name</i>	Name the output file <i>name</i> .
<i>-s</i>	Suppress informative messages. Normally, both informative messages and error messages are printed.
<i>-t</i>	Arrange for <i>&trace</i> to have an initial value of -1 when the program is executed and for <i>&trace</i> to be set to 0 when the program terminates.
<i>-u</i>	Issue warning messages for undeclared identifiers in the program.
<i>-v i</i>	Set verbosity level of informative messages to <i>i</i> .

-E Direct the results of preprocessing to standard output and inhibit further processing.

The following options are recognized only by unicon:

\ -C Have unicon generate code using iconc instead of icon

-version

Print the version of Unicon and exit.

-features

Print the features compiled into this implementation Unicon and exit.

The following additional options are recognized only by unicon and iconc:

\ -G Bundle a graphics-enabled VM (MS Windows)

| **The following additional options are recognized only by by unicon -C**
and iconc:

| **-f *string***

Enable features as indicated by the letters in *string*:

a	all, equivalent to delns
d	enable debugging features: display(), name(), variable(), error trace back, and the effect
e	enable error conversion
l	enable large-integer arithmetic
n	produce code that keeps track of line numbers and file names in the source code
s	enable full string invocation

-n *string*

Disable specific optimizations. These are indicated by the letters in *string*:

a	all, equivalent to cest
c	control flow optimizations other than switch statement optimizations
e	expand operations in-line when reasonable (keywords are always put in-line)
s	optimize switch statements associated with operation invocations
t	type inference

-p *arg*

Pass *arg* on to the C compiler used by iconc

-r *path*

Use the run-time system at *path*, which must end with a slash.

-CC *prg*

Have iconc use the C compiler given by *prg*

5 ENVIRONMENT VARIABLES

| **When an Unicon program is executed, several environment variables are**
examined to determine certain execution parameters. Values in parentheses are the default values.

| BLKSIZE (1% of physical memory)

The initial size of the allocated block region, in bytes.

COEXPSIZE (2000)

The size, in words, of each co-expression block.

DBLIST

The location of data bases for iconc to search before the standard one.

The value of DBLIST should be a semicolon-separated string of the form *p1;p2;... pn* where the *pi* name directories.

ICONCORE

If set, a core dump is produced for error termination.

ICONX

The location of iconx, the executor for icode files, is built into an icode file when it is produced. This location can be overridden by setting the environment variable ICONX. If ICONX is set, its value is used in place of the location built into the icode file.

IPATH

The location of ucode files specified in link declarations for iconc. IPATH is a semicolon-separated list of directories. The current directory is always searched first, regardless of the value of IPATH.

LPATH

The location of source files specified in preprocessor \$include directives and in link declarations for iconc. LPATH is otherwise similar to IPATH.

MSTKSIZE (50000)

The size, in words, of the main interpreter stack for iconc.

NOERRBUF

By default, &errout is buffered. If this variable is set, &errout is not buffered.

QLSIZE (5000)

The size, in bytes, of the region used for pointers to strings during garbage collection.

STRSIZE (1% of physical memory)

The initial size of the string space, in bytes.

TRACE

The initial value of &trace. If this variable has a value, it overrides the translation-time -t option.

6 FILES

| unicon Unicon translator | iconc Icon translator | iconc Icon compiler | iconx
Icon executor

7 SEE ALSO

Programming with Unicon, Clinton Jeffery, Shamim Mohamed, Ray Pereda and Robert Parlett, <http://unicon.org>, 2008.

The Icon Programming Language, Ralph E. Griswold and Madge T. Griswold, Peer-to-Peer Communications, Inc., Third Edition, 1996.

Version 9.3 of Icon, Ralph E. Griswold, Clinton L. Jeffery, and Gregg M. Townsend, IPD278, Department of Computer Science, The University of Arizona, 1996.

Version 9 of the Icon Compiler, Ralph E. Griswold, IPD237, Department of Computer Science, The University of Arizona, 1995.

8 LIMITATIONS AND BUGS

The icode files for the interpreter do not stand alone; the Icon run-time system (iconx) must be present.

Stack overflow is checked using a heuristic that is not always effective.

| **"unicon -C" and iconc are not yet ported to MS Windows. They run out of**

| **memory on large programs if limited swap or virtual memory address**
space is available, such as 32-bit platforms. A few features of Unicon, such as ODBC database access, are not yet supported under "unicon -C" and iconc.