EXPERIMENT – 4

AIM:

Develop a game-playing agent using minimax and alpha-beta pruning for Tic-Tac-Toe or a similar turn-based game.

OBJECTIVE:

To develop a game-playing agent for Tic-Tac-Toe using the Minimax algorithm with Alpha-Beta pruning, and to observe how pruning reduces the number of game-tree nodes evaluated while preserving the same optimal decision.

PROCEDURE:

1. Represent the Tic-Tac-Toe board as a 9-cell list and implement a function to detect a winner across all rows, columns and diagonals.
2. Implement the Minimax recursive evaluation function that assigns +10/-10 (adjusted by depth) for an AI win/loss and 0 for a draw at terminal states.
3. Extend Minimax with Alpha-Beta pruning: maintain alpha (best already guaranteed for the maximizer) and beta (best already guaranteed for the minimizer), and prune a branch when beta <= alpha.
4. Implement best_move() which tries every empty cell for the AI and picks the move with the highest minimax score.
5. Count nodes_evaluated on each AI turn to measure the effect of pruning as the game tree shrinks.
6. Simulate a full game: the AI (X) plays optimally via Minimax while the opponent (O) follows a fixed scripted sequence of moves.
7. Print the board after every move along with the number of nodes evaluated, and report the final result (win/loss/draw).

PROGRAM / CODE:

```
# ================================================================
 # PRACTICAL 4
 # Minimax with Alpha-Beta Pruning - Tic-Tac-Toe
 # ================================================================
 HUMAN = "O"
 AI = "X"
 EMPTY = " "
 def print_board(board):
     rows = []
     for r in range(3):
         rows.append(" | ".join(board[r * 3:r * 3 + 3]))
     print(("\n" + "-" * 9 + "\n").join(rows))
 def winner(board):
     lines = [
         (0, 1, 2), (3, 4, 5), (6, 7, 8),
         (0, 3, 6), (1, 4, 7), (2, 5, 8),
         (0, 4, 8), (2, 4, 6)
     ]
     for a, b, c in lines:
         if board[a] != EMPTY and board[a] == board[b] == board[c]:
             return board[a]
     return None
 def is_full(board):
     return EMPTY not in board
 nodes_evaluated = 0
 def minimax(board, depth, alpha, beta, maximizing):
     global nodes_evaluated
     nodes_evaluated += 1
     win = winner(board)
     if win == AI:
         return 10 - depth
```


Name: c.jagadesh **Enrollment No: 92400118512**

```
    if win == HUMAN:
        return depth - 10
    if is_full(board):
        return 0
    if maximizing:
        best = float("-inf")
        for i in range(9):
            if board[i] == EMPTY:
                board[i] = AI
                score = minimax(board, depth + 1, alpha, beta, False)
                board[i] = EMPTY
                best = max(best, score)
                alpha = max(alpha, best)
                if beta <= alpha:
                    break
        return best
    else:
        best = float("inf")
        for i in range(9):
            if board[i] == EMPTY:
                board[i] = HUMAN
                score = minimax(board, depth + 1, alpha, beta, True)
                board[i] = EMPTY
                best = min(best, score)
                beta = min(beta, best)
                if beta <= alpha:
                    break
        return best
def best_move(board):
    best_score = float("-inf")
    move = None
    for i in range(9):
        if board[i] == EMPTY:
            board[i] = AI
            score = minimax(board, 0, float("-inf"), float("inf"), False)
            board[i] = EMPTY
            if score > best_score:
                best_score = score
                move = i
    return move
def scripted_human_move(board):
    """A fixed sequence representing a human/opponent playing sensibly."""
    for i in [4, 0, 2, 6, 8, 1, 3, 5, 7]:
        if board[i] == EMPTY:
            return i
if __name__ == "__main__":
    board = [EMPTY] * 9
    turn = AI
    move_no = 0
    print("=" * 55)
    print("   MINIMAX + ALPHA-BETA PRUNING - TIC-TAC-TOE")
    print("=" * 55)
    while True:
        move_no += 1
        print(f"\nMove {move_no} ({turn}'s turn)")
         if turn == AI:
             nodes_evaluated = 0
             pos = best_move(board)
             board[pos] = AI
             print(f"AI plays position {pos} (nodes evaluated: {nodes_evaluated})")
         else:
             pos = scripted_human_move(board)
             board[pos] = HUMAN
             print(f"Opponent plays position {pos}")
         print_board(board)
         w = winner(board)
         if w:
             print(f"\nResult: {w} WINS!")
             break
         if is_full(board):
             print("\nResult: DRAW")
             break
         turn = HUMAN if turn == AI else AI
```


Name: c.jagadesh **Enrollment No: 92400118512**

```
    print("=" * 55)
```

OUTPUT:

```
=======================================================
    MINIMAX + ALPHA-BETA PRUNING - TIC-TAC-TOE
=======================================================
Move 1 (X's turn)
AI plays position 0   (nodes evaluated: 34202)
X |   |
---------
  |   |
---------
  |   |
Move 2 (O's turn)
Opponent plays position 4
X |   |
---------
  | O |
---------
  |   |
Move 3 (X's turn)
AI plays position 1   (nodes evaluated: 1630)
X | X |
---------
  | O |
---------
  |   |
Move 4 (O's turn)
Opponent plays position 2
X | X | O
---------
  | O |
---------
  |   |
Move 5 (X's turn)
AI plays position 6   (nodes evaluated: 97)
X | X | O
---------
  | O |
---------
X |   |
Move 6 (O's turn)
Opponent plays position 8
X | X | O
---------
  | O |
---------
X |   | O
Move 7 (X's turn)
AI plays position 3   (nodes evaluated: 10)
X | X | O
---------
X | O |
---------
X |   | O
Result: X WINS!
=======================================================
```

RESULT:

The Minimax algorithm with Alpha-Beta pruning was successfully implemented for Tic-Tac-Toe. On the AI's first move (empty board, the largest possible search tree), Minimax evaluated 34,202 nodes even with pruning; as the game progressed and the board filled up, the number of nodes evaluated per move fell sharply (1,630 → 97 → 10) because there were fewer empty cells and more branches were pruned early once a guaranteed win/loss bound was found. Playing against a fixed opponent sequence, the AI played optimally at every turn and won the game, confirming that Alpha-Beta pruning returns exactly the same decision as plain Minimax while exploring a fraction of the game tree, which is

essential for making game-tree search practical even in a game as small as Tic-Tac-Toe.