

Politecnico di Milano

COMPUTER SCIENCE AND ENGINEERING

Software Engineering 2

Project Plan

PowerEnJoy

Authors:
Francesco Fabiani
Jagadesh Manivannan
Niccolò Pozzolini

Professors: Elisabetta Di Nitto Luca Mottola

Contents

1	Inti	roduction	2
	1.1	Revision history	2
	1.2	Purpose and scope	2
	1.3	Definitions, acronyms, abbreviations	2
	1.4	Reference documents	4
2		0 /	5
	2.1	Size estimation	5
	2.2	Cost and effort estimation	
		2.2.1 Scale drivers	
		2.2.2 Cost drivers	7
		2.2.3 Effort equation	
		2.2.4 Schedule estimation	16

Chapter 1

Introduction

1.1 Revision history

Version	Date	Authors	Summary
1.0	22/01/2017	Fabiani, Manivannan, Pozzolini	Initial release

Table 1.1: Changelog of this document

1.2 Purpose and scope

The Project Plan (PP) document is intended to describe the best strategies for the management of PowerEnJoy with regards to all the aspects of the project, such as costs, schedule of the activities, resource allocation and effort estimation.

The product described is PowerEnJoy, a car-sharing service which offers to its users exclusively electric cars. It includes the common functionalities of its category: permitting to registered users to obtain the position of all the available cars, reserving one within a certain amount of time and continuously displaying the up-to-the-minute cost of the ride are just few of them. Moreover, PowerEnJoy stimulates users to behave virtuously towards the ecosystem by applying various types of discounts under specific conditions.

1.3 Definitions, acronyms, abbreviations

• ACAP: Analyst Capability

Chapter 1. Introduction

- *APEX*: Applications Experience
- API: Application Programming Interface
- BCE: Business Controller Entity
- Car: electric vehicle provided by the service
- *CPLX*: Product Complexity
- DB: Database
- DBMS: Database Management System
- DD: Design Document
- DOCU: Documentation Match to Life-Cycle Needs
- ER: Entity-Relationship
- GPS: Global Positioning System
- Guest or Guest user: person not registered to the service
- ITPD: Integration Test Plan Document
- LTEX: Language and Tool Experience
- MVC: Model View Controller
- OS: Operating System, related both to desktop and mobile platforms
- PCAP: Programmer Capability
- PCON: Personnel Continuity
- PIN: Personal Identification Number
- *PLEX*: Platform Experience
- PP: Project Plan
- PVOL: Platform Volatility
- RASD: Requirements Analysis and Specification Document
- Registered user: see User
- RELY: Required Software Reliability

Chapter 1. Introduction

- REST: Representational State Transfer
- RESTful: that follows the REST principles
- RUSE: Developed for Reusability
- Safe area: set of parking spots where a user can leave a car without penalization
- STOR: Main Storage Constraint
- User: person with a valid driving license registered to the service
- *UX*: User eXperience
- W3C: World Wide Web Consortium

1.4 Reference documents

The PP document has been composed following the guidelines reported in the Requirements Analysis and Specification Document delivered for this project. Moreover, the part describing the cost estimation follows the indications described in the second revision of the procedural software cost estimation model named Constructive Cost Model (COCOMO II), developed by Barry W. Boehm.

With regards to the course named Software Engineering 2 and held by professors Luca Mottola and Elisabetta Di Nitto (Politecnico di Milano, a. y. 2016/17), the document conforms to the guidelines provided during the lectures and within the material of the course.

Chapter 2

Project size, cost and effort estimation

2.1 Size estimation

2.2 Cost and effort estimation

In this section we are going to use the COCOMO II approach to estimate the cost and effort needed to develop the PowerEnJoy application.

2.2.1 Scale drivers

In order to evaluate the values of the scale drivers, we refer to the following official COCOMO II table:

Scale factors	Very low	Low	Nominal	High	Very high	Extra high
PREC	thoroughly	largely	somewhat	generally	largely fa-	thoroughly
	unprece-	unprece-	unprece-	familiar	miliar	familiar
	dented	dented	dented			
SF_j	6.20	4.96	3.72	2.48	1.24	0.00
FLEX	rigorous	occasional	some	general	some con-	general
		relaxation	relaxation	conformity	formity	goals
SF_j	5.0	4.05	3.04	2.03	1.01	0.00
RESL	little	some	often	generally	mostly	full (100%)
	(20%)	(40%)	(60%)	(75%)	(90%)	
SF_j	7.07	5.65	4.24	2.83	1.41	0.00

Chapter 2. Project size, cost and effort estimation

TEAM	very diffi-	some diffi-	basically	largely co-	highly co-	seamless
	cult inter-	cult inter-	coop-	operative	operative	interac-
	actions	actions	erative			tions
			interac-			
			tions			
SF_j	5.48	4.38	3.29	2.19	1.10	0.00
PMAT	Level 1	Level 1 up-	Level 2	Level 3	Level 4	Level 5
	lower	per				
SF_j	7.80	6.24	4.68	3.12	1.56	0.00

Table 2.1: Scale Factor values (SF_i) for COCOMO II Models

A brief description for each scale driver:

- *Precedentedness*: this factor determines or reveals the level of exposure or experience in development of large scale projects or similar kind of projects that out team has done before. Since we have developed few projects like this, we can set this value to be Nominal.
- Development flexibility: it determines the degree of flexibility in the development process with respect to the external specification and requirements. In our project, the functionalities and requirements are clear and well defined with no specific mention about the technology. Hence this value would be low.
- Architecture/Risk resolution: it determines the level of awareness and reactivity with respect to risks. Since we have an extremely good risk management plan, we consider this value to be very high.
- Team cohesion: it determines if all the Stakeholders are able to work in a team and share same vision and commitment. Since our team is highly co-operative, the value is very high.
- Process maturity: we have a done an extremely fair work to meet our goals successfully in this project. Since we had prior experience in successfully dealing these kind of projects, the value is set to Level 4.

The results of our evaluation is the following:

Chapter 2. Project size, cost and effort estimation

Scale Driver	Factor	Value
Precedentedness (PREC)	Nominal	3.72
Development flexibility (FLEX)	Low	4.05
Risk resolution (RESL)	Very high	1.41
Team cohesion (TEAM)	Very high	1.10
Process maturity (PMAT)	Level 4	1.56
Total		11.84

2.2.2 Cost drivers

Product factors

• Required Software Reliability (RELY):

The software application is developed in such a way that the main aim is to reserve and take a ride in the Cars in the city. Any malfunctioning could lead to important financial loss. Considering this, the RELY cost driver is set to high.

	RELY cost drivers										
RELY de-	slightly	easily re-	moderate	high finan-	risk to hu-						
scriptors	inconve-	coverable	recov-	cial loss	man life						
	nience	losses	erable								
			losses								
Rating	Very low	Low	Nominal	High	Very high	Extra high					
level											
Effort mul-	0.82	0.92	1.00	1.10	1.26	n/a					
tipliers											

• Database size (DATA):

This factor considers the effective size of our database. We do'nt know this value exactly. But based on the lower and upper bound values of the SLOC, which is 10.000-15.000 SLOC, we can estimate roughly that our system can reach a 3GB database size. Since it is distributed over 10.000-15.000 SLOC, the ratio D/P (measured as testing DB bytes/program SLOC) is between 209 and 314, resulting in the DATA cost driver being high.

Chapter 2. Project size, cost and effort estimation

DATA cost drivers									
DATA de-		$\frac{D}{P} < 10$	$10 \leq \frac{D}{P} <$	$100 \le \frac{D}{P} <$	$\frac{D}{P} \ge 1000$				
scriptors		_	100	1000					
Rating	Very low	Low	Nominal	High	Very high	Extra high			
level									
Effort mul-	n/a	0.90	1.00	1.14	1.28	n/a			
tipliers									

• Product complexity (CPLX):

This factor is related to the complex logics involved in implementing the product as a whole. Hence, we set it to very high according to the CPLX cost driver table.

	CPLX cost drivers									
Rating	Very low	Low	Nominal	High	Very high	Extra high				
level										
Effort mul-	0.73	0.87	1.00	1.17	1.34	1.74				
tipliers										

• Developed for Reusability (RUSE):

In our project, we use many individual piece of codes that can be made reusable for other services or functions. Hence the RUSE cost driver is set to nominal.

	RUSE cost drivers										
RUSE descriptors		None	Across project	Across program	Across product line	Across multiple product					
Rating level	Very low	Low	Nominal	High	Very high	Extra high					
Effort multipliers	n/a	0.95	1.00	1.07	1.15	1.24					

• Documentation Match to Life-Cycle Needs (DOCU):

This factor describes the relationship between the documentation and the application requirements. The product life-cycle needs are explicitly mentioned clearly in the documentation. Hence the DOCU cost driver is set to nominal.

	DOCU cost drivers								
DOCU de-	Many life-	Some life-	Right	Excessive	Very ex-				
scriptors	cycle needs	cycle needs	sized to	for life-	cessive for				
	uncovered	uncovered	life-cycle	cycle needs	life-cycle				
			needs		needs				
Rating	Very low	Low	Nominal	High	Very high	Extra high			
level									
Effort mul-	0.81	0.91	1.00	1.11	1.23	n/a			
tipliers									

Platform factors

• Execution Time Constraint (TIME):

This factor describes the approximated value of CPU usage with respect to the hardware specifications. Our PowerEnJoy application has vast functionalities as a software and hence the TIME cost driver is set to be very high.

	TIME cost drivers										
TIME de-			$\leq 50\%$ use	70% use of	85% use of	90% use of					
scriptors			of available	available	available	available					
			execution	execution	execution	execution					
			time	time	time	time					
Rating	Very low	Low	Nominal	High	Very high	Extra high					
level											
Effort mul-	n/a	n/a	1.00	1.11	1.29	1.63					
tipliers											

• Main Storage Constraint (STOR):

This factor describes the approximated storage space with respect to the hardware specifications. Our PowerEnJoy application has

vast functionalities as a software. Keeping this in mind, the disk drives can store up to enough terabytes and hence the STOR cost driver is set to be high.

	STOR cost drivers										
STOR de-			$\leq 50\%$ use	70% use of	85% use of	90% use of					
scriptors			of available	available	available	available					
			storage	storage	storage	storage					
Rating	Very low	Low	Nominal	High	Very high	Extra high					
level											
Effort mul-	n/a	n/a	1.00	1.05	1.17	1.46					
tipliers											

• Platform Volatility (PVOL):

This factor describes the change in the basic or fundamental platform in which the system is designed. We do'nt change the platform often except for very few major releases or updated requested by the client. This will be done approximately for every 5months to be in sync with the latest evolving or trending technologies. Hence, the PVOL cost driver is set to nominal.

	PVOL cost drivers							
PVOL de-		Major	Major	Major	Major			
scriptors		change	change	change	change			
		every	every	every	every			
		12 months;	6 months;	2 months;	2 weeks;			
		minor	minor	minor	minor			
		change	change	change	change			
		every	every	every	every			
		1 month	2 weeks	1 week	2 days			
Rating	Very low	Low	Nominal	High	Very high	Extra high		
level								
Effort mul-	n/a	0.87	1.00	1.15	1.30	n/a		
tipliers								

• Analyst Capability (ACAP):

This factor describes the potential analysis that has been done with respect to the potential implementation in real world. Since we have done a regressive analysis, the ACAP cost driver is set to be high.

	ACAP cost drivers							
ACAP de-	15th per-	35th per-	55th per-	75th per-	90th per-			
scriptors	centile	centile	centile	centile	centile			
Rating	Very low	Low	Nominal	High	Very high	Extra high		
level								
Effort mul-	1.42	1.19	1.00	0.85	0.71	n/a		
tipliers								

• Programmer Capability (PCAP):

This factor describes the ability of the programmer to do a work without much difficulty. Our project has not been implemented yet our programmers have executed several projects like this successfully and hence the PCAP cost driver is set to be high.

	PCAP cost drivers							
PCAP de-	15th per-	35th per-	55th per-	75th per-	90th per-			
scriptors	centile	centile	centile	centile	centile			
Rating	Very low	Low	Nominal	High	Very high	Extra high		
level								
Effort mul-	1.34	1.15	1.00	0.88	0.76	n/a		
tipliers								

• Applications Experience (APEX):

Our team members are quite experienced with this kind of project development and hence the APEX cost driver is set to be high.

Chapter 2. Project size, cost and effort estimation

	APEX cost drivers								
APEX de-	$\leq 2 \text{ months}$	6 months	1 years	3 years	6 years				
scriptors									
Rating	Very low	Low	Nominal	High	Very high	Extra high			
level									
Effort mul-	1.22	1.10	1.00	0.88	0.81	n/a			
tipliers									

• Platform Experience (PLEX):

Our team has a good and stable experience in Java EE platform and also a good knowledge about the integration with UI, Database and other tiers. Hence the PLEX cost driver is set to be high.

PLEX cost drivers								
PLEX de-	$\leq 2 \text{ months}$	6 months	1 years	3 years	6 years			
scriptors								
Rating	Very low	Low	Nominal	High	Very high	Extra high		
level								
Effort mul-	1.19	1.09	1.00	0.91	0.85	n/a		
tipliers								

• Language and Tool Experience (LTEX):

As we have mentioned before, since the knowledge of our programmers are good enough on this kind of project and Java EE platform, they possess a good standard of using tools in the development environment, server side and client side integration, etc. Hence the LTEX cost driver is set to be high.

	LTEX cost drivers								
LTEX de-	$\leq 2 \text{ months}$	6 months	1 years	3 years	6 years				
scriptors									
Rating	Very low	Low	Nominal	High	Very high	Extra high			
level									
Effort mul-	1.20	1.09	1.00	0.91	0.84	n/a			
tipliers									

• Personnel Continuity (PCON):

This factor describes the personnel turnover annually. Since our project is a short term project, the PCON cost driver is set to be very low.

	PCON cost drivers							
PCON de-	48%/year	24%/year	12%/year	6%/year	3%/year			
scriptors								
Rating	Very low	Low	Nominal	High	Very high	Extra high		
level								
Effort mul-	1.29	1.12	1.00	0.90	0.81	n/a		
tipliers								

Project factors

• Use of Software Tools (TOOL):

Our application environment is complete and well integrated, so we will set this parameter as high.

	TOOL cost drivers						
TOOL de-	edit, code,	simple,	basic life-	strong,	strong,		
scriptors	debug	front-end,	cycle tools,	mature	mature,		
		back-end	mod-	life-cycle	proactive		
		CASE,	erately	tools,	life-cycle		
		little inte-	integrated	mod-	tools, well		
		gration		erately	integrated		
				integrated	with pro-		
					cesses,		
					methods,		
					reuse		
Rating	Very low	Low	Nominal	High	Very high	Extra high	
level							
Effort mul-	1.17	1.09	1.00	0.90	0.78	n/a	
tipliers							

• Multisite Development (SITE):

Our application is designed in such a way that it relies on wideband electronic communication at extremely good speeds (e.g. 3G, 4G) for connection. Hence the SITE cost driver is set to be very high.

	SITE cost drivers							
SITE col-	interna-	multi-city	multi-city	same city	same	fully collo-		
location	tional	and multi-	or multi-	or metro	building or	cated		
descriptors		company	company	area	complex			
SITE commu- nications descriptors	some phone, mail	individual phone, FAX	narrow band email	wideband electronic communi- cation	wideband electronic commu- nication, occasional video conference	interactive multime- dia		
Rating	Very low	Low	Nominal	High	Very high	Extra high		
level								
Effort mul-	1.22	1.09	1.00	0.93	0.86	0.80		
tipliers								

General factor

• Required Development Schedule (SCED):

The efforts was distributed or split equally in our project for all the documentation, yet there were certain time consuming process in analysing and development of the RASD and the DD documents for precision. Hence, the SCED cost driver is set to be high.

SCED cost drivers								
SCED de-	75% of	85% of	100% of	130% of	160% of			
scriptors	nominal	nominal	nominal	nominal	nominal			
Rating	Very low	Low	Nominal	High	Very high	Extra high		
level								
Effort mul-	1.43	1.14	1.00	1.00	1.00	n/a		
tipliers								

Results

Overall our results are expressed in the following table:

Cost Driver	Factor	Value
Required software reliability (RELY)	High	1.10
Database size (DATA)	High	1.14
Product complexity (CPLX)	Very high	1.34
Required reusability (RUSE)	Nominal	1.00
Documentation match to life-cycle needs (DOCU)	Nominal	1.00
Execution time constraint (TIME)	Very high	1.29
Main storage constraint (STOR)	High	1.11
Platform volatility (PVOL)	Nominal	1.00
Analyst capability (ACAP)	High	0.85
Programmer capability (PCAP)	High	0.88
Application experience (APEX)	High	0.88
Platform Experience (PLEX)	High	0.91
Language and Tool Experience (LTEX)	High	0.91
Personnel continuity (PCON)	Very low	1.12
Usage of Software Tools (TOOL)	High	0.90
Multisite development (SITE)	Very high	0.86
Required development schedule (SCED)	High	1.00
Total	•	1.13694

2.2.3 Effort equation

This final equation gives us the effort estimation measured in Person-Months (PM):

$$Effort = A \times EAF \times KSLOC^E$$

where:

A = 2.94 (for COCOMO II)

EAF = 1.13694 (product of all cost drivers)

$$E = B + 0.01 \times \sum_{i} SF[i] = B + 0.01 * 11.84 = 0.91 + 0.1464 = 1.0284$$

(exponent derived from the scale drivers, with B = 0.91 for COCOMO II)

With this parameters we can compute the effort value, which has a lower bound of:

$$Effort = A \times EAF \times KSLOC^{E} = 2.94 \times 1.13694 \times dash^{1.0284}$$
$$= 4 \text{ PM} \approx dash \text{ PM}$$

and an upper bound of:

$$Effort = A \times EAF \times KSLOC^{E} = 2.94 \times 1.13694 \times dash^{1.0284}$$
$$= 4 \text{ PM} \approx dash \text{ PM}$$

2.2.4 Schedule estimation

Regarding the final schedule, we are going to use the following formula:

$$Duration = 3.67 \times Effort^F$$

As a lower bound, we consider

$$F = 0.28 + 0.2 \times (E - B) = 0.28 + 0.2 \times 0.1464 = 0.30928$$

$$Effort = 56.957 \text{ PM}$$

$$Duration = 3.67 \times 56.957^{0.30928} = 12.81 \text{ months}$$

while as an upper bound, we consider

$$F = 0.28 + 0.2 \times (E - B) = 0.28 + 0.2 \times 0.1464 = 0.30928$$

$$Effort = 84.737 \text{ PM}$$

$$Duration = 3.67 \times 84.737^{0.30928} = 14.49 \text{ months}$$