

# Rajalakshmi Engineering College

Name: JAGADISH S A

Email: 241501071@rajalakshmi.edu.in

Roll no: 241501071

Phone: 9245831133

Branch: REC

Department: I AI & ML FA

Batch: 2028

Degree: B.E - AI & ML

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 4\_MCQ\_Updated

Attempt : 2

Total Mark : 20

Marks Obtained : 20

### Section 1 : MCQ

1. Which one of the following is an application of Queue Data Structure?

**Answer**

All of the mentioned options

**Status : Correct**

**Marks : 1/1**

2. After performing this set of operations, what does the final list look to contain?

InsertFront(10);

InsertFront(20);

InsertRear(30);

DeleteFront();

InsertRear(40);

```
InsertRear(10);
DeleteRear();
InsertRear(15);
display();
```

**Answer**

10 30 40 15

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code?

```
#include <stdio.h>
#include <stdlib.h>
#define MAX_SIZE 5
typedef struct {
    int* arr;
    int front;
    int rear;
    int size;
} Queue;
Queue* createQueue() {
    Queue* queue = (Queue*)malloc(sizeof(Queue));
    queue->arr = (int*)malloc(MAX_SIZE * sizeof(int));
    queue->front = -1;
    queue->rear = -1;
    queue->size = 0;
    return queue;
}
int isEmpty(Queue* queue) {
    return (queue->size == 0);
}
int main() {
    Queue* queue = createQueue();
    printf("Is the queue empty? %d", isEmpty(queue));
    return 0;
}
```

**Answer**

Is the queue empty? 1

**Status :** Correct

**Marks :** 1/1

4. Which of the following can be used to delete an element from the front end of the queue?

**Answer**

```
public Object deleteFront() throws emptyDEQException{if(isEmpty())throw new  
emptyDEQException("Empty");else{Node temp = head.getNext();Node cur =  
temp.getNext();Object e = temp.getEle();head.setNext(cur);size--;return e;}}
```

**Status :** Correct

**Marks :** 1/1

5. Insertion and deletion operation in the queue is known as

**Answer**

Enqueue and Dequeue

**Status :** Correct

**Marks :** 1/1

6. The process of accessing data stored in a serial access memory is similar to manipulating data on a

**Answer**

Queue

**Status :** Correct

**Marks :** 1/1

7. In what order will they be removed If the elements "A", "B", "C" and "D" are placed in a queue and are deleted one at a time

**Answer**

ABCD

**Status :** Correct

**Marks :** 1/1

8. In a linked list implementation of a queue, front and rear pointers are tracked. Which of these pointers will change during an insertion into a non-empty queue?

**Answer**

Only rear pointer

**Status : Correct**

**Marks : 1/1**

9. What are the applications of dequeue?

**Answer**

All the mentioned options

**Status : Correct**

**Marks : 1/1**

10. What does the front pointer in a linked list implementation of a queue contain?

**Answer**

The address of the first element

**Status : Correct**

**Marks : 1/1**

11. In linked list implementation of a queue, the important condition for a queue to be empty is?

**Answer**

FRONT is null

**Status : Correct**

**Marks : 1/1**

12. Front and rear pointers are tracked in the linked list implementation of a queue. Which of these pointers will change during an insertion into the EMPTY queue?

**Answer**

Both front and rear pointer

**Status :** Correct

**Marks :** 1/1

13. Which of the following properties is associated with a queue?

**Answer**

First In First Out

**Status :** Correct

**Marks :** 1/1

14. Which operations are performed when deleting an element from an array-based queue?

**Answer**

Dequeue

**Status :** Correct

**Marks :** 1/1

15. What will the output of the following code?

```
#include <stdio.h>
#include <stdlib.h>
typedef struct {
    int* arr;
    int front;
    int rear;
    int size;
} Queue;
Queue* createQueue() {
    Queue* queue = (Queue*)malloc(sizeof(Queue));
    queue->arr = (int*)malloc(5 * sizeof(int));
    queue->front = 0;
    queue->rear = -1;
    queue->size = 0;
    return queue;
}
int main() {
```

```
Queue* queue = createQueue();  
printf("%d", queue->size);  
return 0;  
}
```

**Answer**

0

**Status : Correct**

**Marks : 1/1**

16. The essential condition that is checked before insertion in a queue is?

**Answer**

Overflow

**Status : Correct**

**Marks : 1/1**

17. When new data has to be inserted into a stack or queue, but there is no available space. This is known as

**Answer**

overflow

**Status : Correct**

**Marks : 1/1**

18. What is the functionality of the following piece of code?

```
public void function(Object item)  
{  
    Node temp=new Node(item,trail);  
    if(isEmpty())  
    {  
        head.setNext(temp);  
        temp.setNext(trail);  
    }  
    else  
    {  
        Node cur=head.getNext();
```

```

while(cur.getNext()!=trail)
{
    cur=cur.getNext();
}
cur.setNext(temp);
}
size++;
}

```

**Answer**

Insert at the rear end of the dequeue

**Status :** Correct

**Marks :** 1/1

19. What will be the output of the following code?

```

#include <stdio.h>
#define MAX_SIZE 5
typedef struct {
    int arr[MAX_SIZE];
    int front;
    int rear;
    int size;
} Queue;

void enqueue(Queue* queue, int data) {
    if (queue->size == MAX_SIZE) {
        return;
    }
    queue->rear = (queue->rear + 1) % MAX_SIZE;
    queue->arr[queue->rear] = data;
    queue->size++;
}

int dequeue(Queue* queue) {
    if (queue->size == 0) {
        return -1;
    }
    int data = queue->arr[queue->front];
    queue->front = (queue->front + 1) % MAX_SIZE;
}

```

```
    queue->size--;  
    return data;  
}  
int main() {  
    Queue queue;  
    queue.front = 0;  
    queue.rear = -1;  
    queue.size = 0;  
    enqueue(&queue, 1);  
    enqueue(&queue, 2);  
    enqueue(&queue, 3);  
    printf("%d ", dequeue(&queue));  
    printf("%d ", dequeue(&queue));  
    enqueue(&queue, 4);  
    enqueue(&queue, 5);  
    printf("%d ", dequeue(&queue));  
    printf("%d ", dequeue(&queue));  
    return 0;  
}
```

**Answer**

1 2 3 4

**Status : Correct**

**Marks : 1/1**

20. A normal queue, if implemented using an array of size MAX\_SIZE, gets full when

**Answer**

Rear = MAX\_SIZE - 1

**Status : Correct**

**Marks : 1/1**