

```
In [1]: x1 = input('Enter the first number')
        y1 = input('Enter the Second number')
        z = x1+y1
        print(z)
```

1213

```
In [2]: x1 = int(input('Enter the first number'))
        y1 = int(input('Enter the Second number'))
        z = x1+y1
        print(z)
```

25

```
In [4]: x1 = input('Input a Stting')[0]
        x1
```

Out[4]: 'a'

```
In [6]: #18th class input()
```

```
In [8]: exp = input('Enter a value')
        print(exp)
```

2+3-1+10

```
In [9]: exp1 = int(input('Enter a value'))
        print(exp1) # will get value error
```

```
-----
ValueError                                Traceback (most recent call last)
Cell In[9], line 1
----> 1 exp1 = int(input('Enter a value'))
      2 print(exp1)

ValueError: invalid literal for int() with base 10: '1+3+5-1'
```

```
In [10]: exp1 = eval(input('Enter a value'))
         print(exp1) # work as we used eval;
```

5

```
In [12]: #write a python program to add two numbers

a = 10
b = 20
c = a + b
print(c)
```

30

```
In [14]: #write a calculator app for me in python

import tkinter as tk
from tkinter import ttk

root = tk.Tk()
root.title("Calculator")
root.geometry("300x200")
```

```
label = tk.Label(root, text="Calculator")
label.pack()

root.mainloop()
```

In [15]: *#write a front end code for me for the calculator app*

```
import tkinter as tk
from tkinter import ttk

root = tk.Tk()
root.title("Calculator")
root.geometry("300x200")

label = tk.Label(root, text="Calculator")
label.pack()

root.mainloop()
```

In []:

In []:

In []:

In []:

In []:

In []: