Back to the case

Edition compass · Case 03 · Rätselhaft! · Joint version 1.1 · 27 October 2026 · Material

From source to corpus

Sources and internal work

▼ Example and Tip

Example: An accepted TEI book is in source/; the unified version and the input of a rhyme study are separated.

Tip: Document the relationships. Publish a clearly identified corpus stock for new users.

→

Determine publication concept

▼ Example and Tip

Example: docs/publikationskonzept.md lists target groups, scope, structure, review and release path.

Tip: Create this file before the first public data level and maintain it like the data with Git.

→

Check and curate data

▼ Example and Tip

Example: The converter gets two puzzles, but loses two solutions. An inventory comparison reports the loss, although the puzzle counting succeeds.

Tip: Connect schema/weiss check with inventory comparison and targeted source reading.

→

GitHub: Data, rules, examples

▼ Example and Tip

Example: README leads from data/tei via docs/auszeichnung.md to the first call in examples/.

Tip: Let an external person try this way without personal introduction.

→
Release and Archive

▼ Example and Tip

Example: Tag v1.1, release notes and archived package denote the same verified version.

Tip: Check package, metadata and version proof. One day alone is not independent archiving.

→
Local research and reporting

▼ Example and Tip

Example: Elif downloads v1.0, performs an evaluation and reports a missing solution reference as an issue.

Tip: Ask for data version and affected identification so that the findings can be understood.

Separate tool repos provide converters, tests and analyses. Tested data levels are taken over into a separate public history. Internal work history is not published unnoticed.

Git data

file versions, commit relationships and transferred references. Check tags and required additional objects explicitly.

Additional received

Relevant issues and decisions, attachments, test procedures, CI configuration, roles, accesses and contact paths.

Received releases, complete packages and an actual rebuild limit dependencies. The archive does not automatically replace a running host.