100 DAYS QUALITY MANAGEMENT CHALLENGE DAY 89

Integrated Petroleum Quality Engineering

Product Quality Testing, Process Control and Root Cause Analysis

Organisation Focus: Bharat Petroleum Corporation Limited (BPCL) | **Author:** Jagriti Singh

1. INTRODUCTION

Petroleum products ranging from High-Speed Diesel (HSD) and Motor Spirit (MS) to Aviation Turbine Fuel (ATF) and industrial lubricants must stringently adhere to precise chemical and physical specifications defined by standards organizations (such as the Bureau of Indian Standards - BIS). These specifications govern properties like flash point, viscosity, sulfur content, density, and distillation parameters.

Quality assurance in petroleum engineering ensures operational safety, compliance with environmental emission norms, engine efficiency, and customer trust. Continuous product quality testing acts as a critical line of defense, validating that processing units operate within target control limits and identifying contamination or operational drift before product offloading or distribution.

2. PRACTICAL EDUCATIONAL CASE STUDY

Hypothetical Case Scenario: Flash Point Deviation in Diesel Fuel

During routine laboratory testing of a newly refined batch of High-Speed Diesel (HSD) prior to storage tank transfer, the tested sample exhibited a **Flash Point of 31°C**, falling below the minimum standard safety limit of **35°C**.

1. **What the Problem Is:** The HSD batch failed the minimum flash point quality specification, indicating an unexpected concentration of volatile light-end hydrocarbons in the fuel mixture.
2. **Why It Matters:** A low flash point significantly elevates the fire hazard risk during fuel storage, transportation, and handling. Furthermore, it indicates off-specification product performance that could lead to engine vapor lock or early auto-ignition.
3. **What the Engineer Should Check First:** The quality engineer must immediately re-sample and re-test the product using a calibrated Pensky-Martens Closed Cup tester to rule out testing, sampling, or lab-instrument error. Concurrently, quarantine the storage batch to prevent blending with clean fuel.
4. **How to Investigate Possible Causes:** Conduct a structured review across the supply chain: check the distillation column operating conditions (stripping steam rates, top/draw-off temperatures), inspect pipeline manifolds and valve alignments for cross-contamination from lighter fractions (e.g., petrol/naphtha), and inspect sampling containers for residual solvent residues.
5. **What Corrective Action May Be Appropriate:** Adjust the distillation unit operating parameters (increasing stripping column reboiler temperature or stripping steam flow to drive off light components). For the quarantined off-spec batch, re-process it through the stripper unit or perform controlled blending under lab supervision with a heavy component batch.
6. **How to Verify Whether the Action Worked:** Draw multi-level representative samples (top, middle, bottom) from the treated/reprocessed batch and conduct composite laboratory testing to confirm the flash point comfortably exceeds 35°C across all levels.

3. IMPORTANT QUALITY TOOLS

To systematically manage and resolve quality deviations in petroleum refining, four primary quality engineering tools are applied:

1. Check Sheet

Purpose: A structured, real-time data collection form designed to record event frequencies, inspection results, or defect occurrences for easy pattern analysis.

Case Study Example: A laboratory operator uses a daily check sheet to log testing parameters (flash point, density, viscosity) across different shift times and refinery sampling points to spot recurring off-spec trends.

2. Root Cause Analysis (RCA)

Purpose: A structured problem-solving methodology aimed at identifying the fundamental, underlying systemic reason for a failure rather than merely addressing visible symptoms.

Case Study Example: An RCA team analyzes the low flash point issue by evaluating raw crude feed variability, process column parameters, valve maintenance records, and operator sampling logs.

3. Five Whys

Purpose: An iterative interrogative technique used to dig into cause-and-effect relationships by asking "Why?" repeatedly (typically 5 times) until the root human or process cause is reached.

Case Study Example: *Why low flash point?* Excess light-ends in HSD. → *Why excess light-ends?* Diesel stripper column temperature was low. → *Why was temperature low?* Steam control valve stuck. → *Why was valve stuck?* Lack of scheduled preventive lubrication. → *Why was it missed?* Maintenance check-sheet lacked specific valve lube intervals (Root Cause).

4. Failure Mode and Effects Analysis (FMEA)

Purpose: A proactive risk assessment tool used to identify potential failure modes, evaluate their severity, occurrence, and detection ratings (RPN), and prioritize mitigation actions.

Case Study Example: An FMEA on the distillation transfer process identifies "Valve leaking lighter naphtha into diesel line" as a failure mode with high severity, prompting installation of double block-and-bleed valves.

4. KEY ENGINEERING LEARNINGS

- **Product Testing Compliance:** Routine standardized quality testing is non-negotiable for ensuring operational safety, regulatory compliance, and customer satisfaction.
- **Measurement Reliability:** Laboratory test equipment calibration and standardized sampling protocols are critical to eliminate false-positive or false-negative off-spec reports.
- **Structured Problem Investigation:** Isolating symptoms from true root causes requires systematic evaluation across process variables, equipment mechanics, and human factors.
- **Targeted Corrective Action:** Effective corrective actions address the underlying systemic cause (such as maintenance schedules or control loops) rather than short-term fixes like batch re-blending alone.
- **Rigorous Verification:** No quality issue is considered closed until post-correction multi-point sampling confirms product stability and protocol effectiveness over time.

5. TECHNICAL INTERVIEW QUESTIONS & ANSWERS

Q1: What is the significance of the flash point parameter in petroleum quality testing?

> The flash point indicates the lowest temperature at which a liquid produces sufficient vapor to form an ignitable mixture with air. It is a critical safety specification for fuel storage, handling, and fire risk classification.

Q2: How does kinematic viscosity impact engine fuel system performance?

> Viscosity determines fuel flow characteristics and atomization quality in fuel injectors. Excessive viscosity causes poor atomization and incomplete combustion, while very low viscosity leads to injector pump wear and internal fuel leakage.

Q3: Why is repeatability and reproducibility important in laboratory fuel testing?

> Repeatability ensures consistent results by the same operator on the same instrument, while reproducibility ensures consistency across different operators and laboratories, guaranteeing measurement reliability across facilities.

Q4: How does a Check Sheet assist in refinery quality assurance processes?

> A Check Sheet provides standardized, systematic real-time data collection of quality parameters or process failures, allowing engineers to identify defect frequencies, shift patterns, and equipment-specific trends.

Q5: What is the primary objective of Root Cause Analysis (RCA) in quality engineering?

> The primary objective of RCA is to identify the fundamental, underlying systemic breakdown that caused an off-spec event or failure, enabling actions that prevent recurrence rather than treating symptoms.

Q6: How does the "Five Whys" methodology prevent superficial problem-solving?

> By repeatedly asking "Why?" following each logical effect, the technique drills past immediate physical symptoms to uncover systemic human, management, or procedural weaknesses.

Q7: What are the three core evaluation criteria used to calculate Risk Priority Number (RPN) in FMEA?

> The three criteria are Severity (impact of failure), Occurrence (likelihood of occurrence), and Detection (probability of detecting the failure before impact), multiplied as RPN = S × O × D.

Q8: What immediate step should a Quality Engineer take when a fuel sample fails quality testing?

> Quarantine the affected batch/tank immediately to prevent blending or shipment, and re-sample/re-test using calibrated equipment to verify test accuracy.

Q9: How can cross-contamination occur in petroleum storage and piping systems?

> Cross-contamination occurs through passing or leaking isolation valves, shared piping manifolds without proper flushing, or improper line flushing during product grade switching.

Q10: What is the difference between corrective action and preventive action (CAPA)?

> Corrective action eliminates the root cause of an existing non-conformity to prevent recurrence, whereas preventive action proactively identifies potential risks to prevent occurrence in the first place.

Q11: Why is multi-level sampling (top, middle, bottom) necessary for petroleum storage tanks?

> Liquid petroleum in large tanks can stratify due to temperature or density differences; multi-level sampling ensures the composite sample is truly representative of the entire volume.

Q12: How does stripping steam flow rate affect the flash point in a distillation column draw?

> Increasing the stripping steam flow rate strips out volatile light-end hydrocarbons from the stream, thereby raising the flash point of the bottom/side product to meet specification.

Q13: What role does statistical process control (SPC) play in petroleum quality management?

> SPC utilizes control charts to monitor process parameters over time, helping engineers distinguish between common cause variability and special cause anomalies before off-spec product is produced.

Q14: How do you verify whether a corrective action was successful following an off-spec event?

> Verification is achieved by re-sampling the corrected product, analyzing key quality parameters against standard limits, and monitoring process trends over time to confirm process stability.

Q15: Why is instrument calibration critical for quality laboratory accreditation?

> Calibration links test measurements to certified standard reference materials, ensuring test accuracy, legal metrology compliance, and international test result acceptance.

6. REFERENCES & DISCLAIMER

- Bharat Petroleum Corporation Limited (BPCL) Official Website: www.bharatpetroleum.in
- ISO 9001:2015 Quality Management Systems Requirements
- Juran, J.M., & De Feo, J.A. (2010). *Juran's Quality Handbook: The Complete Guide to Performance Excellence* (6th ed.). McGraw-Hill.

Disclaimer: This is an independent educational case study based on a hypothetical scenario. It does not represent an actual BPCL incident, internal procedure, or official BPCL publication. This work is not affiliated with or endorsed by BPCL.