# Rajalakshmi Engineering College

Name: CHEMBETI JAHNAVI

Email: 240701089@rajalakshmi.edu.in

Roll no: 240701089 Phone: 6300874727

**Branch: REC** 

Department: I CSE AG

Batch: 2028

Degree: B.E - CSE



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

REC\_DS using C\_Week 5\_COD\_Question 4

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

#### 1. Problem Statement

John, a computer science student, is learning about binary search trees (BST) and their properties. He decides to write a program to create a BST, display it in post-order traversal, and find the minimum value present in the tree.

Help him by implementing the program.

### **Input Format**

The first line of input consists of an integer N, representing the number of elements to insert into the BST.

The second line consists of N space-separated integers data, which is the data to be inserted into the BST.

#### **Output Format**

The first line of output prints the space-separated elements of the BST in postorder traversal.

The second line prints the minimum value found in the BST.

Refer to the sample output for formatting specifications.

```
Sample Test Case
 Input: 3
 5 10 15
 Output: 15 10 5
 The minimum value in the BST is: 5
 Answer
 #include <stdio.h>
 #include <stdlib.h>
 struct Node {
   int data:
   struct Node* left;
   struct Node* right;
 };
struct Node* createNode(int data) {
   struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
   newNode->data = data;
   newNode->left = newNode->right = NULL;
   return newNode;
 }
 // You are using GCC
 struct Node* insert(struct Node* root, int data) {
   //Type your code here
   if(root==NULL)
    return createNode(data);
   if(data<root->data)
```

```
root->left=insert(root->left,data);
  else
    root->right=insert(root->right,data);
  return root;
void displayTreePostOrder(struct Node* root) {
  //Type your code here
  if(root!=NULL)
    displayTreePostOrder(root->left);
    displayTreePostOrder(root->right);
    printf("%d ",root->data);
}
int findMinValue(struct Node* root) {
  //Type your code here
  if(root==NULL)
    return -1;
  struct Node* current = root;
  while(current->left!=NULL)
    current=current->left;
  return current->data;
}
int main() {
  struct Node* root = NULL;
  int n, data;
  scanf("%d", &n);
  for (int i = 0; i < n; i++) {
  scanf("%d", &data);
    root = insert(root, data);
```

```
240101089
displayTreePostOrder(root);
printf("\n");
        int minValue = findMinValue(root);
printf("The minimum value in the BST is: %d", minValue);
        return 0;
      }
      Status: Correct
                                                                                      Marks: 10/10
240/0/089
                                                               240701089
```

2407070889

2,40707089

240707089

240101089