

GE23131-Programming Using C-2024

Status Finished

Started Monday, 23 December 2024, 5:33 PM

Completed Friday, 6 December 2024, 9:41 AM

Duration 17 days 7 hours

Question **1**

Correct

Marked out of 3.00

🚩 [Flag question](#)

Write a program that prints a simple chessboard.

Input format:

The first line contains the number of inputs T.
The lines after that contain a different values for size of the chessboard

Output format:



Output format.

Print a chessboard of dimensions size * size.
Print a W for white spaces and B for black spaces.

Input:

2

3

5

Output:

WBW

BWB

WBW

WBWBW

BWBWB

WBWBW

BWBWB

WBWBW

Answer: (penalty regime: 0 %)

1	#include<stdio.h>
2	int main()
3 ▾	{




```

4      int T,d,i=0,i1,i2,o;
5      char c;
6      scanf("%d",&T);
7      while (i<T)
8      {
9          scanf("%d",&d);
10         i1=0;
11         while(i1<d)
12         {
13             o=1;
14             i2=0;
15             if (i1%2==o)
16             {
17                 o=0;
18             }
19             while (i2<d)
20             {
21                 c='W';
22                 if (i2%2==o)
23                 {
24                     c='B';
25                 }
26                 printf("%c",c);
27                 i2++;
28             }
29             i1+=1;
30             printf("\n");
31         }
32         i=i+1;
33     }
34 }

```

	Input	Expected	Got	
✓	2	WBW	WBW	✓
	3	BWB	BWB	
	5	WBW	WBW	
		WBWBW	WBWBW	
		BWBWB	BWBWB	
		WBWBWB	WBWBWB	

WBWBW

WBWBW

Passed all tests! ✓

Question 2

Correct

Marked out of 5.00

🚩 [Flag question](#)

Let's print a chessboard!

Write a program that takes input:

The first line contains T, the number of test cases

Each test case contains an integer N and also the starting character of the chessboard

Output Format

Print the chessboard as per the given examples

Sample Input / Output

Input:



3 B

Output:

WB

BW

BWB

WBW

BWB

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int T,d,i,i1,i2,o,z;
5      char c,s;
6      scanf("%d",&T);
7      for(i=0;i<T;i++)
8      {
9          scanf("%d %c",&d,&s);
10         for(i1=0;i1<d;i1++)
11         {
12             z=(s=='W') ?0:1;
13             o=(i1%2==z) ?0:1;
14             for(i2=0;i2<d;i2+
15             {
16                 c=(i2%2==o) ?
17                 printf("%c",c
18             }
19             printf("\n");
20         }
21     }
22     return 0;
23 }
```

	Input	Expected	Got	
✓	2	WB	WB	✓
	2 W	BW	BW	
	3 B	BWB	BWB	
		WBW	WBW	
		BWB	BWB	

Passed all tests! ✓

Question **3**

Correct

Marked out of 7.00

🚩 [Flag question](#)

Decode the logic and print the Pattern that corresponds to given input.

If N= 3

then pattern will be :

10203010011012

**4050809

****607

First line print Case #i where i is the test case number

In the subsequent line, print the pattern

Test Case 1

3

3

4

5

Output

Case #1

10203010011012

**4050809

****607

Case #2

1020304017018019020

**50607014015016

****809012013

*****10011

Case #3

102030405026027028029030

**6070809022023024025



```

1  #include<stdio.h>
2  int main()
3  {
4      int n,v,p3,c,in,i,i1,i2,t
5      scanf("%d",&t);
6      for(ti=0;ti<t;ti++)
7      {
8          v=0;
9          scanf("%d",&n);
10         printf("Case #%d\n",t
11         for(i=0;i<n;i++)
12         {
13             c=0;
14             if (i>0)
15             {
16                 for (i1=0;i1<
17             }
18             for(i1=i;i1<n;i1+
19             {
20                 if (i>0) c++;
21                 printf("%d0",
22             }
23             if(i==0)
24             {
25                 p3=v+(v*(v-1)
26                 in=p3;
27             }
28             in=in-c;
29             p3=in;
30             for(i2=i;i2<n;i2+
31             {
32                 printf("%d",p
33                 if(i2!=n-1)pr
34             }printf("\n");
35         }
36     }
37 }


```


	Input	Expected
✓	3	Case #1
	3	10203010011012
	4	**4050809
	5	****607
		Case #2
		1020304017018019020
		**50607014015016
		****809012013
		*****10011
		Case #3
		102030405026027028029030
		**6070809022023024025
		****10011012019020021
		*****13014017018
		*****15016

Passed all tests! ✓

Finish review

Quiz navigation



Show one page at a time

Finish review

GE23131-Programming Using C-2024

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Friday, 13 December 2024, 9:53 AM
Duration	10 days 7 hours

Question **1**

Correct

Marked out of 3.00

🚩 [Flag question](#)

The k -digit number N is an Armstrong number if and only if the k -th power of each digit sums to N .

Given a positive integer N , return true if and only if it is an Armstrong number.

Example 1:

Input:



3 3.

Example 2:

Input:

123

Output:

false

Explanation:

123 is a 3-digit number, and $123 \neq 1^3 + 2^3 + 3^3 = 36$.

Example 3:

Input:

1634

Output:



Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  #include<math.h>
3  int main()
4  {
5      int n;
6      scanf("%d",&n);
7      int x=0,n2=n;
8      while (n2!=0)
9      {
10         x++;
11         n2=n2/10;
12     }
13     int sum=0;
14     int n3=n,n4;
15     while (n3!=0)
16     {
17         n4=n3%10;
18         sum=sum+pow(n4,x);
19         n3=n3/10;
20     }
21     if (n==sum)
22     {
23         printf("true");
24     }
25     else
26     {
27         printf("false");
28     }
29     return 0;
30 }
```

	Input	Expected	Got	
✓	153	true	true	✓
✓	123	false	false	✓

Question 2

Correct

Marked out of 5.00

🚩 [Flag question](#)

Take a number, reverse it and add it to the original number until the obtained number is a palindrome. Constraints $1 \leq \text{num} \leq 999999999$

Sample Input 1 32 Sample Output 1 55

Sample Input 2 789 Sample Output 2 66066

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int rn,n,nt=0,i=0;
5      scanf("%d",&n);
6      do
7      {
8          nt=n;rn=0;
9          while(n!=0)
10         {
11             rn=rn*10+n%10;
12             n=n/10;
13         }
14         n=nt+rn;
15         i++;
16     }
17     while (rn!=nt||i==1);
18     printf("%d",rn);
19     return 0;
20 }
```



	Input	Expected	Got	
✓	32	55	55	✓
✓	789	66066	66066	✓

Passed all tests! ✓

Question 3

Correct

Marked out of 7.00

🚩 [Flag question](#)

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th lucky number is 34 and so on. Note that 13, 40 etc., are not lucky as they have other numbers in it.

The program should accept a number 'n' as input and display the nth lucky number as output.

Sample Input 1:


```

1  #include<stdio.h>
2  int main()
3  {
4      int rn,n,nt=0,i=0;
5      scanf("%d",&n);
6      do
7      {
8          nt=n;rn=0;
9          while(n!=0)
10         {
11             rn=rn*10+n%10;
12             n=n/10;
13         }
14         n=nt+rn;
15         i++;
16     }
17     while (rn!=nt||i==1);
18     printf("%d",rn);
19     return 0;
20 }

```

	Input	Expected	Got	
✓	32	55	55	✓
✓	789	66066	66066	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 7.00

🚩 [Flag question](#)

Question 3

Correct

Marked out of 7.00

🚩 [Flag question](#)

A number is considered lucky if it contains either 3 or 4 or 3 and 4 both in it. Write a program to print the nth lucky number. Example, 1st lucky number is 3, and 2nd lucky number is 4 and 3rd lucky number is 33 and 4th lucky number is 34 and so on. Note that 13, 40 etc., are not lucky as they have other numbers in it.

The program should accept a number 'n' as input and display the nth lucky number as output.

Sample Input 1:

3

Sample Output 1:

33



Sample Input 2:

34

Sample Output 2:

33344

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n=1,i=0,nt,co=0,e;
5      scanf("%d",&e);
6      while (i<e)
7      {
8          nt=n;
9          while (nt!=0)
10         {
11             co=0;
12             if (nt%10!=3 && n
13             {
14                 co=1;
15                 break;
```

```

15         break;
16     }
17     nt=nt/10;
18 }
19 if (co==0)
20 {
21     i++;
22 }
23 n++;
24 }
25 printf("%d",--n);
26 return 0;
27 }

```

	Input	Expected	Got	
✓	34	33344	33344	✓

Passed all tests! ✓

Finish review

Quiz navigation



Show one page at a time

Finish review

