```java
class Thread1 implements Runnable
{
    Thread t;
    String name;
    int time;
    Thread1(String name,int time)
    {
        this.name=name;
        this.time=time;
        t=new Thread( target: this,name);
        t.start();
    }
    public void run()
    {
        try
        {
            for (int n=5;n>0;n--)
            {
                System.out.println(name);
                Thread.sleep(time);
            }
        }
        catch(InterruptedException ie)
        {
            System.out.println("Thread "+name+" got interrupted");
        }
        System.out.println("Thread "+name+" quitting");
```

```java
        }
    public void run()
    {
        try
        {
            for (int n=5;n>0;n--)
            {
                System.out.println(name);
                Thread.sleep(time);
            }
        }
        catch(InterruptedException ie)
        {
            System.out.println("Thread "+name+" got interrupted");
        }
        System.out.println("Thread "+name+" quitting");
    }
}
public class Week11labProgram {
    public static void main(String[] args)
    {
        Thread1 t1=new Thread1( name: "BMS College of Engineering", time: 10000);
        Thread1 t2=new Thread1( name: "CSE", time: 2000);
    }
}
```

```
"C:\Program Files\Java\jdk1.8.0_261\bin\java.exe" ...
 BMS College of Engineering
 CSE
 CSE
 CSE
 CSE
 CSE
 BMS College of Engineering
 Thread CSE quitting
 BMS College of Engineering
 BMS College of Engineering
 BMS College of Engineering
 Thread BMS College of Engineering quitting

Process finished with exit code 0
```