Ex.No:8
25.9.26

NMAP on TryHackMe Platform.

Aim:

To discover live hosts in a network using Nmap ARP, ICMP, TCP and UDP ping scans.

Procedure:

1. Start the TryHackMe Nmap Live Host directory lab and AttackBox.
2. Identify the target subnet.
3. Perform ARP, ICMP, TCP and UDP host-discovery scans.
4. Record the hosts reported as "Host is up".
5. Compare results of different recovery methods.

i) ARP Scan:

Sudo nmap -PR -sn <subnet>/24

Protocol = ARP / Link

Broadcasts ARP requests; reply confirms a live host. Works only on the local subnet.

ii) ICMP Echo:

Sudo nmap -PE -sn <Subnet>/24>

Protocol = ICMP / network.

Sends Echo request and checks reply

UDP Ping:

Sudo nmap -PU -sn <Subnet"/24"

UDP / Transport

ICMP "Port Unreachable" response indicates a live host.

The TCP/IP diagram in the guide shows ARP at the Link layer, ICMP at Network layer and TCP/UDP at the Transport layer.

Nmap options:

-sn = host discovery only, no port scan

-Pn = skip host discovery and treat hosts as online

-n = disable reverse DNS

-R = perform reverse DNS lookup.

-sL = list targets without scanning

Result:

Live hosts in the given network were successfully identified using different Nmap host-discovery techniques.













