

REST - Get country based on country code

Country.xml

```
<?xml version="1.0" encoding="UTF-8"?>

<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xmlns:util="http://www.springframework.org/schema/util"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           https://www.springframework.org/schema/beans/spring-beans.xsd
           http://www.springframework.org/schema/util
           https://www.springframework.org/schema/util/spring-util.xsd">

    <bean id="india" class="com.cognizant.springlearn.Country">
        <property name="code" value="IN"/>
        <property name="name" value="India"/>
    </bean>

    <bean id="us" class="com.cognizant.springlearn.Country">
        <property name="code" value="US"/>
        <property name="name" value="United States"/>
    </bean>

    <bean id="germany" class="com.cognizant.springlearn.Country">
        <property name="code" value="DE"/>
        <property name="name" value="Germany"/>
    </bean>

    <bean id="japan" class="com.cognizant.springlearn.Country">
        <property name="code" value="JP"/>
        <property name="name" value="Japan"/>
    </bean>

    <util:list id="countryList">
        <ref bean="india"/>
```

```
<ref bean="us"/>

<ref bean="germany"/>

<ref bean="japan"/>

</util:list>

</beans>
```

CountryService.java

```
package com.cognizant.springlearn.service;

import com.cognizant.springlearn.Country;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;
import org.springframework.stereotype.Service;
import java.util.List;

@Service

public class CountryService {

    public Country getCountry(String code) {

        ApplicationContext context =

            new ClassPathXmlApplicationContext("country.xml");

        List<Country> countryList =

            context.getBean("countryList", List.class);

        for (Country country : countryList) {

            if (country.getCode().equalsIgnoreCase(code)) {

                ((ClassPathXmlApplicationContext) context).close();

                return country;

            }

        }

        ((ClassPathXmlApplicationContext) context).close();

        return null;

    }

}
```

```
}
```

CountryController.java

```
package com.cognizant.springlearn.controller;

import com.cognizant.springlearn.Country;

import com.cognizant.springlearn.service.CountryService;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.web.bind.annotation.*;

@RestController

public class CountryController {

    @Autowired

    private CountryService countryService;

    @GetMapping("/countries/{code}")

    public Country getCountry(@PathVariable String code) {

        return countryService.getCountry(code);

    }

}
```

Pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-
4.0.0.xsd">
    <modelVersion>4.0.0</modelVersion>
    <parent>
        <groupId>org.springframework.boot</groupId>
        <artifactId>spring-boot-starter-parent</artifactId>
        <version>4.1.0</version>
        <relativePath/> <!-- lookup parent from repository -->
    </parent>
    <groupId>com.cognizant</groupId>
    <artifactId>spring-learn</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name/>
    <description/>
    <url/>
```

```
<licenses>
  <license/>
</licenses>
<developers>
  <developer/>
</developers>
<scm>
  <connection/>
  <developerConnection/>
  <tag/>
  <url/>
</scm>
<properties>
  <java.version>21</java.version>
</properties>
<dependencies>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-webmvc</artifactId>
  </dependency>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-web</artifactId>
  </dependency>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-devtools</artifactId>
    <scope>runtime</scope>
    <optional>true</optional>
  </dependency>
  <dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-webmvc-test</artifactId>
    <scope>test</scope>
  </dependency>
</dependencies>

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
    </plugin>
  </plugins>
</build>

</project>
```

SpringLearnApplication.java

```
package com.cognizant.spring_learn;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class SpringLearnApplication {

    public static void main(String[] args) {
        SpringApplication.run(SpringLearnApplication.class, args);
    }

}
```

