

Spring Core – Load Country from Spring Configuration XML

SpringLearnApplication.java

```
package com.cognizant.spring_learn;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;
public class SpringLearnApplication {
    private static final Logger LOGGER =
        LoggerFactory.getLogger(SpringLearnApplication.class);

    public static void main(String[] args) {
        displayCountry();
    }
    public static void displayCountry() {
        ApplicationContext context =
            new ClassPathXmlApplicationContext("country.xml");
        Country country =
            context.getBean("country", Country.class);
        LOGGER.debug("Country : {}", country);
        ((ClassPathXmlApplicationContext) context).close();
    }
}
```

Country.java

```
package com.cognizant.spring_learn;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
public class Country {
    private static final Logger LOGGER =
        LoggerFactory.getLogger(Country.class);
    private String code;
    private String name;
    public Country() {
        LOGGER.debug("Inside Country Constructor.");
    }
    public String getCode() {
        LOGGER.debug("Inside getCode()");
        return code;
    }
    public void setCode(String code) {
        LOGGER.debug("Inside setCode()");
        this.code = code;
    }
    public String getName() {
        LOGGER.debug("Inside getName()");
```

```

        return name;
    }
    public void setName(String name) {
        LOGGER.debug("Inside setName()");
        this.name = name;
    }
    @Override
    public String toString() {
        return "Country{" +
            "code='" + code + '\'' +
            ", name='" + name + '\'' +
            '}';
    }
}

```

country.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="
        http://www.springframework.org/schema/beans
        https://www.springframework.org/schema/beans/spring-beans.xsd">
    <bean id="country"
        class="com.cognizant.spring_learn.Country">
        <property name="code" value="IN"/>
        <property name="name" value="India"/>
    </bean>

</beans>

```

Logback.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration>
    <root level="DEBUG">
        <appender-ref ref="STDOUT"/>
    </root>
    <appender name="STDOUT"
        class="ch.qos.logback.core.ConsoleAppender">
        <encoder>
            <pattern>%d %-5level %logger - %msg%n</pattern>
        </encoder>
    </appender>
</configuration>

```

Pom.xml

```

<?xml version="1.0" encoding="UTF-8"?>

```

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"

  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-
4.0.0.xsd">

  <modelVersion>4.0.0</modelVersion>

  <parent>

    <groupId>org.springframework.boot</groupId>

    <artifactId>spring-boot-starter-parent</artifactId>

    <version>4.1.0</version>

    <relativePath/> <!-- lookup parent from repository -->

  </parent>

  <groupId>com.cognizant</groupId>

  <artifactId>spring-learn</artifactId>

  <version>0.0.1-SNAPSHOT</version>

  <name/>

  <description/>

  <url/>

  <licenses>

    <license/>

  </licenses>

  <developers>

    <developer/>

  </developers>

  <scm>

    <connection/>

    <developerConnection/>

    <tag/>

    <url/>
```

```
</scm>

<properties>

  <java.version>21</java.version>

</properties>

<dependencies>

  <dependency>

    <groupId>org.springframework.boot</groupId>

    <artifactId>spring-boot-starter-webmvc</artifactId>

  </dependency>

  <dependency>

    <groupId>org.springframework.boot</groupId>

    <artifactId>spring-boot-devtools</artifactId>

    <scope>runtime</scope>

    <optional>true</optional>

  </dependency>

  <dependency>

    <groupId>org.springframework.boot</groupId>

    <artifactId>spring-boot-starter-webmvc-test</artifactId>

    <scope>test</scope>

  </dependency>

</dependencies>

<build>

  <plugins>

    <plugin>

      <groupId>org.springframework.boot</groupId>

      <artifactId>spring-boot-maven-plugin</artifactId>

    </plugin>

  </plugins>
```

</build>

</project>

