

[attributes \(/reference/attributes\)](#)

[case \(/reference/case\)](#)

[code \(/reference/code\)](#)

[comments \(/reference/comments\)](#)

[conditionals \(/reference/conditionals\)](#)

[doctype \(/reference/doctype\)](#)

[extends \(/reference/extends\)](#)

[filters \(/reference/filters\)](#)

[includes \(/reference/includes\)](#)

[inheritance \(/reference/inheritance\)](#)

[iteration \(/reference/iteration\)](#)

[mixins \(/reference/mixins\)](#)

[plain text \(/reference/plain-text\)](#)

[tags \(/reference/tags\)](#)

Includes

Includes allow you to insert the contents of one jade file into another.

```
//– index.jade
doctype html
html
  include ./includes/head.jade
  body
    h1 My Site
    p Welcome to my super lame site.
    include ./includes/foot.jade
```

```
//– includes/head.jade
head
  title My Site
  script(src='/javascripts/jquery.js')
  script(src='/javascripts/app.js')
```

```
//– includes/foot.jade
#footer
  p Copyright (c) foobar
```

```
<!doctype html>
<html>
  <head>
    <title>My Site</title>
    <script src='/javascripts/jquery.js'></script>
    <script src='/javascripts/app.js'></script>
  </head>
  <body>
    <h1>My Site</h1>
    <p>Welcome to my super lame site.</p>
    <div id="footer">
      <p>Copyright (c) foobar</p>
    </div>
  </body>
</html>
```

Including Plain Text

Including files that are not jade just includes the raw text.

```
// - index.jade
doctype html
html
  head
    style
      include style.css
  body
    h1 My Site
    p Welcome to my super lame site.
    script
      include script.js
```

```
/* style.css */
h1 { color: red; }
```

```
// script.js
console.log('You are awesome');
```

```
<!doctype html>
<html>
  <head>
    <style>
      /* style.css */
      h1 { color: red; }
    </style>
  </head>
  <body>
    <h1>My Site</h1>
    <p>Welcome to my super lame site.</p>
    <script>
      // script.js
      console.log('You are awesome');
    </script>
  </body>
</html>
```

Including Filtered Text

You can combine filters with includes to filter things as you include them.

```
//- index.jade
doctype html
html
  head
    title An Article
  body
    include:markdown article.md
```

```
# article.md
```

This is an article written in markdown.

```
<!doctype html>
<html>
  <head>
    <title>An Article</title>
  </head>
  <body>
    <h1>article.md</h1>
    <p>This is an article written in markdown.</p>
  </body>
</html>
```