

Backup restore MI

06 May 2025 18:39

Create storage account and SQL managed instance should be in same region
Storage account contributor and contributor on subscription and RG
Sysadmin in MI and Source instance

We can migrate SQL authentication login for windows auth you can use EntraID

Check database recovery model

```
SELECT name, recovery_model_desc FROM sys.databases
```

Move login to Managed instance prior to restoring backup:

[Transfer logins and passwords between instances - SQL Server | Microsoft Learn](#)

Step 1: SP on source:



Transfer
Login SP b...
Run: Exec sp_help_revlogin --save it and run the output to managed instance

---once migration is completed --Retrieve jobs and execute in Target

---OnPrem

USE master

```
CREATE CREDENTIAL [https://storageacc1crossregion.blob.core.windows.net/migration-crossregion]-- ---this name must match the container path, start with https and must not contain a trailing forward slash.
```

```
WITH IDENTITY='SHARED ACCESS SIGNATURE' -- this is a mandatory string and do not change it.
```

```
, SECRET = '<SASToken>' -- this is the shared access signature token
```

BACKUP DATABASE [AdventureWorksLT2016] TO

```
URL = N'https://storageacc1crossregion.blob.core.windows.net/migration-crossregion/adventureworkslt2016\_backup\_2025\_04\_29\_135135.bak' WITH NOFORMAT,  
NOINIT, NAME = N'AdventureWorksLT2016-Full Database Backup', NOSKIP, NOREWIND,  
NOUNLOAD, STATS = 10
```

```
GO
```

---SQL MI

USE master

```
CREATE CREDENTIAL [https://storageacc1crossregion.blob.core.windows.net/migration-crossregion]-- ---this name must match the container path, start with https and must not contain a trailing forward slash.
```

```
WITH IDENTITY='SHARED ACCESS SIGNATURE' -- this is a mandatory string and do not change it.
```

```
, SECRET = '<SASToken>' -- this is the shared access signature token
```

RESTORE DATABASE [AdventureWorksLT2016] FROM URL =

```
N'https://storageacc1crossregion.blob.core.windows.net/migration-crossregion/adventureworkslt2016\_backup\_2025\_04\_29\_135135.bak'
```

Backup on source: --one time full and log. No new backup should be

[SQL Server Backup \(hallengren.com\)](http://hallengren.com) :

Run this script on source:

Backup status:

```
select percent_complete,* from sys.dm_exec_requests where percent_complete >0
```

Schedule job Full once and then log at every 15 min

---User database ----

```
EXECUTE [dbo].[DatabaseBackup]
@Databases = 'User_Databases',
@DirectoryStructure = '{DatabaseName}',
@BackupType = 'FULL',
@Compress='Y',
@Url='<SAS URL>',
@BlockSize=65536,
@MaxTransferSize=4194304,
@Checksum = 'Y',
@LogToTable = 'Y'
```

---selective database ---- change the database with db names

```
@Databases = 'DB1, DB2',
```

----Log backup----

```
EXECUTE [dbo].[DatabaseBackup]
@Databases = 'USER_DATABASES',
@DirectoryStructure = '{DatabaseName}',
@BackupType = 'LOG',
@Compress='Y',
@Url='https://jaideep.blob.core.windows.net/testbackups',
@BlockSize=65536,
@MaxTransferSize=4194304,
@Checksum = 'Y',
@LogToTable = 'Y'
```

Share this query to disable all the hallengren jobs-----

```
USE msdb
go
SELECT
    j.job_id, j.name AS job_name, j.description AS job_description,
    j.date_created, j.enabled
FROM    dbo.sysjobs j
LEFT JOIN  dbo.sysjobsteps js ON j.job_id = js.job_id
Where description like '%ola.hallengren%'
ORDER BY  j.name, js.step_id;
```

-----Automate Restore for all the -----

```
DECLARE @restoreCommand NVARCHAR(MAX)

DECLARE restore_cursor CURSOR FOR
SELECT
    CASE b.type
        WHEN 'D' THEN 'RESTORE DATABASE ['
        WHEN 'I' THEN 'RESTORE DATABASE ['
        WHEN 'L' THEN 'RESTORE LOG ['
    END
    + b.database_name + ']' FROM URL = N''' + bm.physical_device_name + '''
    + CHAR(10) AS restore_cmd
FROM msdb.dbo.backupset b
```

```

JOIN msdb.dbo.backupmediafamily bm ON b.media_set_id = bm.media_set_id
WHERE b.is_snapshot = 0
      AND b.is_copy_only = 0
      AND b.backup_start_date >= '20250512' and bm.physical_device_name like '%
https://sqlmippstorageaccount.blob.core.windows.net/testduration%'

```

```
ORDER BY b.database_name, b.backup_start_date ASC
```

```
OPEN restore_cursor
```

```
FETCH NEXT FROM restore_cursor INTO @restoreCommand
```

```
WHILE @@FETCH_STATUS = 0
```

```
BEGIN
```

```
    PRINT @restoreCommand -- For debugging; replace with EXEC if ready
    -- EXEC sp_executesql @restoreCommand -- Uncomment to actually restore

```

```
    FETCH NEXT FROM restore_cursor INTO @restoreCommand
END
```

```
CLOSE restore_cursor
DEALLOCATE restore_cursor
```

```
RESTORE DATABASE [CDADB] FROM URL =
N'https://sqlmippstorageaccount.blob.core.windows.net/testduration/CDADB/PPSDB\$ag\_MENDIX\_CDADB\_FULL\_20250512\_111920.bak'

```

```
Transfer Login
```

```
Transfer Jobs
```

```
----Validate jobs owner-----
```

```
select s.name,l.name
from msdb..sysjobs s
left join master.sys.syslogins l on s.owner_sid = l.sid

```

```
---Disable all jobs -----
```

```
USE msdb;
```

```
GO
```

```
-- Disable all enabled jobs
```

```
UPDATE dbo.sysjobs
```

```
SET enabled = 0
```

```
WHERE enabled = 1;
```

```
-- Confirm which jobs were disabled
```

```
SELECT name AS JobName, 'Disabled' AS Status
```

```
FROM dbo.sysjobs
```

```
WHERE enabled = 0;
```

Transfer Linked Server

Need to transfer using object details and then rename the sql auth account.