Homework 4 writeup solutions


Name: Jaiden Atterbury - Section B

Problem 1

Part a

```
In [70]: import numpy as np
         import matplotlib.pyplot as plt
         from mpl toolkits.mplot3d import Axes3D
         import scipy.optimize
         # i.
         f = lambda x, y: (x ** 2 + y - 11) ** 2 + (x + y ** 2 - 7) ** 2
         fp = lambda p: f(p[0], p[1])
         # ii.
         x = np.linspace(-7, 7, 40)
         y = np.linspace(-7, 7, 40)
         X, Y = np.meshgrid(x, y)
         # iii. and iv.
         fig = plt.figure(1)
         ax = plt.axes(projection='3d')
         surface = ax.plot_surface(X, Y, f(X,Y), cmap = "viridis", linewidth=1, cstri
         fig.colorbar(surface)
         ax.view init(30,30)
         ax.set xlabel("x-axis")
         ax.set_ylabel("y-axis")
         ax.set_zlabel("z-axis")
         ax.set_title("Plot of Himmelblau's function")
```

Out[70]: Text(0.5, 0.92, 'Plot of Himmelblau's function')



Part b

```
In [51]: fig2 = plt.figure(2)
ax2 = plt.axes()

# i.
x = np.linspace(-7, 7, 100)
y = np.linspace(-7, 7, 100)
X, Y = np.meshgrid(x, y)


# ii. and iii.
surface = plt.contour(X, Y, f(X,Y), np.logspace(-1, 3, 22), cmap = "viridis"

# iv.
plt.xlabel("x-axis")
plt.ylabel("y-axis")

# v.
fig2.colorbar(surface)

# vi.
plt.title("Contour Plot of Himmelblau's function")
```

Out[51]: Text(0.5, 1.0, 'Contour Plot of Himmelblau's function')



Part c

Based on the plot again, we can see 4 approximate locations of minima.

```
In [52]: min_1 = np.array([-3.7, -3.5])
    min_2 = np.array([3.5, -1.8])
    min_3 = np.array([3, 2])
    min_4 = np.array([-3, 3.7])

f_min_1 = scipy.optimize.fmin(fp, min_1)
    f_min_2 = scipy.optimize.fmin(fp, min_2)
    f_min_3 = scipy.optimize.fmin(fp, min_3)
    f_min_4 = scipy.optimize.fmin(fp, min_4)
```

Optimization terminated successfully.

Current function value: 0.000000

Iterations: 30

Function evaluations: 57

Optimization terminated successfully.

Current function value: 0.000000

Iterations: 27

Function evaluations: 51

Optimization terminated successfully.

Current function value: 0.000000

Iterations: 23

Function evaluations: 47

Optimization terminated successfully.


Current function value: 0.000000

Iterations: 34

Function evaluations: 67

Once we have found the minima, we can plot them.


```
In [4]: ax2.plot(f_min_1[0], f_min_1[1], "y*", markersize = 15)
ax2.plot(f_min_2[0], f_min_2[1], "y*", markersize = 15)
ax2.plot(f_min_3[0], f_min_3[1], "y*", markersize = 15)
ax2.plot(f_min_4[0], f_min_4[1], "y*", markersize = 15)
fig2
```



Part d

```
In [5]: gradf_xy = lambda x, y: np.array([4*x**3 - 42*x + 4*x*y + 2 * y *** 2 - 14,
                                           4*y**3 - 26*y + 4*x*y + 2 * x ** 2 - 22]
        gradf_p = lambda p: gradf_xy(p[0], p[1])
        p = np.array([-3, -2])
        tol = 10 ** -7
        iterations = 0
        for k in range(2000):
            grad = gradf_p(p)
            if abs(np.linalg.norm(grad)) < tol:</pre>
                break
            phi = lambda t: p - t * grad
            f_of_phi = lambda t: fp(phi(t))
            tstar = scipy.optimize.fminbound(f_of_phi, 0, 1)
            p = phi(tstar)
            iterations += 1
        ax2.plot(p[0], p[1], "gs", markersize=5, label="Grad descent")
        ax2.legend()
        fig2
```





Problem 2

Part a

```
In [13]: import time # Import the timing algorithm,
         p = np.array([2, 3])
         tol = 1e-9
         iterations = 0
         start = time.time()
         for k in range(8000):
             grad = gradf p(p)
             if abs(np.linalq.norm(grad)) < tol:</pre>
                  break
             phi = lambda t: p - t * grad
             f_of_phi = lambda t: fp(phi(t))
             tstar = scipy.optimize.fminbound(f_of_phi, 0, 1)
             p = phi(tstar)
             iterations += 1
         end = time.time()
         print("The above commands took " + str(end - start) +" seconds to complete."
         print("Number of iterations:", iterations)
```

The above commands took 0.015858173370361328 seconds to complete. Number of iterations: 16

Part b-d

```
In [71]: def grad_desc_step(p, tol, tstep):
             iterations = 0
             start = time.time()
             for k in range(8000):
                 grad = gradf p(p)
                 if abs(np.linalg.norm(grad)) < tol:</pre>
                      break
                 p = p - tstep*grad
                 iterations += 1
             end = time.time()
             return np.array([p, iterations, end-start])
         print(grad desc step(np.array([2,3]), 1e-9, 0.01)
         print(grad_desc_step(np.array([2,3]), 1e-9, 0.02))
         print(grad_desc_step(np.array([2,3]), 1e-9, 0.025))
         [array([3., 2.]) 81 0.0036668777465820312]
         [array([3., 2.]) 55 0.001712799072265625]
```

[array([3.23482283, 2.12502178]) 8000 0.19936585426330566]

Part e - the results

	Number Iterations	Time	Converged (Yes/No)
tstep = 0.01	81	0.0029239654541015625	Yes
tstep = 0.02	55	0.0020339488983154297	Yes
tstep = 0.025	8000	0.20737195014953613	No
fminbound	16	0.015858173370361328	Yes

Part f - discussion

- I found that the Gradient Descent algorithm did **not** always converge. The only case out of the four cases tested where the algorithm did not converge was the method with tstep of 0.025. The reason why this method did not converge was because the tstep of 0.025 was too large. Since this tstep was too large, we end up following the path of the negative gradient for too long, and thus skip over the minimum on each successive iteration of the algorithm.
- I found that Gradient Descent converged fastest with the method where we used the tstep of 0.02. In particular, the algorithm converged in a time of only 0.002 seconds.
- I found that Gradient Descent converged with the fewest iterations when using the fminbound method. In particular, the fminbound method took only 16 iterations to converge. However, the total time elapsed was 0.0159 seconds which was slower than both of the tstep methods that converged.
- As seen above, my answer for which algorithm converged fastest and which
 algorithm converged in the least amount of iterations was different. One reason why
 the tstep alogrithm may be slightly faster than the fminbound algorithm for this
 particular function and intial guess is because when using the tstep algorithm, there
 are less lines of code to run, and more importantly we don't have to solve an
 optimization problem (fminbound) on each iteration of our algorithm.
- **Optional:** The optimum tstep to make this algorithm converge the fastest according to my calculations is 0.0184375.