

1. Balanced strings are those that have an equal quantity of 'L' and 'R' characters.

Given a balanced string *s*, split it in the maximum amount of balanced strings.

Return the maximum amount of split balanced strings.

Example 1:

Input:

RLRRLRLRL

Output:

4

Explanation: *s* can be split into "RL", "RRLL", "RL", "RL", each substring contains same number of 'L' and 'R'.

Example 2:

Input:

RLLLLRRRLR

Output:

3

Explanation: *s* can be split into "RL", "LLLRRR", "LR", each substring contains same number of 'L' and 'R'.

Example 3:

Input:

LLLLRRRR

Output:

1

Explanation: *s* can be split into "LLLLRRRR".

Constraints:

$1 \leq s.length \leq 1000$

s[*i*] is either 'L' or 'R'.

s is a balanced string.

Program:

def BalancedStrings(*s*,*l*=0,*r*=0,*count*=0):

```

for i in s :

    if i=='L' :

        l+=1

    elif i=='R' :

        r+=1

    if l==r :

        count+=1

return count

```

	Test	Expected	Got	
✓	print(BalancedStrings('RLRRLLRLRL'))	4	4	✓
✓	print(BalancedStrings('RLLLLRRRLR'))	3	3	✓

Passed all tests! ✓

2. You are given an $m \times n$ integer matrix `matrix` with the following two properties:

- Each row is sorted in non-decreasing order.
- The first integer of each row is greater than the last integer of the previous row.

Given an integer `target`, return `True` if `target` is in `matrix` or `False` otherwise.

You must write a solution in $O(\log(m * n))$ time complexity.

Example 1:

1	3	5	7
10	11	16	20
23	30	34	60

Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 3
Output: True

Example 2:

1	3	5	7
10	11	16	20
23	30	34	60

Input: matrix = [[1,3,5,7],[10,11,16,20],[23,30,34,60]], target = 13
Output: False

Program:

```
def searchMatrix(matrix:list[list[int]], target: int) -> bool:
```

```
    for i in range(len(matrix)):
```

```
        for j in range(len(matrix)):
```

```
            if matrix[i][j]==target:
```

```
                return True
```

```
    return False
```

	Test	Expected	Got	
✓	print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 13))	False	False	✓
✓	print(searchMatrix([[1,3,5,7],[10,11,16,20],[23,30,34,60]], 3))	True	True	✓

Passed all tests! ✓

3. An list contains N numbers and you want to determine whether two of the numbers sum to a given number K. For example, if the input is 8, 4, 1, 6 and K is 10, the answer is yes (4 and 6). A number may be used twice.

Input Format

The first line contains a single integer n , the length of list

The second line contains n space-separated integers, list[i].

The third line contains integer k.

Output Format

Print Yes or No.

Sample Input

7

0 1 2 4 6 5 3

1

Sample Output

Yes

Program:

```
a=int(input())
```

```
p=input()
```

```
b=list(map(int,p.split()))
```

```
count=0
```

```
c=int(input())
```

```
for i in range(len(b)):
```

```
    for j in range(i+1,len(b)):
```

```
        if (b[i]+b[j])==c:
```

```
            print("Yes")
```

```
            count=1
```

```
break
```

```
if count==1:
```

```
    break
```

```
if count==0:
```

```
    print("No")
```

	Input	Expected	Got	
✓	5 8 9 12 15 3 11	Yes	Yes	✓
✓	6 2 9 21 32 43 43 1 4	No	No	✓
✓	6 13 42 31 4 8 9 17	Yes	Yes	✓

Passed all tests! ✓

4. Given an array `nums` containing `n` distinct numbers in the range `[0, n]`, return *the only number in the range that is missing from the array*.

Example 1:

Input: `nums = [3,0,1]`

Output: 2

Explanation: `n = 3` since there are 3 numbers, so all numbers are in the range `[0,3]`. 2 is the missing number in the range since it does not appear in `nums`.

Example 2:

Input: `nums = [0,1]`

Output: 2

Explanation: `n = 2` since there are 2 numbers, so all numbers are in the range `[0,2]`. 2 is the missing number in the range since it does not appear in `nums`.

Example 3:

Input: `nums = [9,6,4,2,3,5,7,0,1]`

Output: 8

Explanation: `n = 9` since there are 9 numbers, so all numbers are in the range `[0,9]`. 8 is the missing number in the range since it does not appear in `nums`.

program:

```
def missingNumber(n):
```

```

count=0

flag=0

p=len(n)-1

for i in range(p):

    count+=1

    if count not in n:

        flag=1

    if flag==1:

        break

if flag==1:

    return count

else:

    return n[p]+1

```

	Test	Expected	Got	
✓	print(search([-1,0,3,5,9,12],9))	4	4	✓
✓	print(search([-1,0,3,5,9,12],2))	-1	-1	✓

Passed all tests! ✓

5. Given an array of integers **nums** which is sorted in ascending order, and an integer **target**, write a function to search **target** in **nums**. If **target** exists, then return its index. Otherwise, return **-1**.

You must write an algorithm with $O(\log n)$ runtime complexity.

Example 1:

Input: nums = [-1,0,3,5,9,12], target = 9

Output: 4

Explanation: 9 exists in nums and its index is 4

Example 2:

Input: nums = [-1,0,3,5,9,12], target = 2

Output: -1

Explanation: 2 does not exist in nums so return -1

Constraints:

- $1 \leq \text{nums.length} \leq 10^4$
- $-10^4 < \text{nums}[i], \text{target} < 10^4$
- All the integers in **nums** are **unique**.
- **nums** is sorted in ascending order.

Programdef search(num: list[int], target: int) -> int:

count=0

flag=0

for i in range(len(num)):

if num[i]==target:

count=i

flag=1

break

if flag==1:

return count

else:

return -1

	Test	Expected	Got	
✓	print(missingNumber([3,0,1]))	2	2	✓
✓	print(missingNumber([0,1]))	2	2	✓
✓	print(missingNumber([9,6,4,2,3,5,7,0,1]))	8	8	✓

Passed all tests! ✓

6. Write a Python program for binary search.

For example:

Input	Result
1,2,3,5,8 6	False
3,5,9,45,42 42	True

Program:

```
a=list(map(int,input().split(',')))
```

```
b=int(input())
```

```
c=0
```

```
flag=0
```

```
d=len(a)
```

```
a.sort()
```

```
while c<d:
```

```
    p=(c+d)//2
```

```
    if a[p]==b:
```

```
        print("True")
```

```
        flag=1
```

```
        break
```

```
    elif b<a[p]:
```

```
        d=p
```

```
    else:
```

```
        c=p+1
```



```
if flag==0:
```

```
    print("False")
```

	Input	Expected	Got	
✓	1,2,3,5,8 6	False	False	✓
✓	3,5,9,45,42 42	True	True	✓
✓	52,45,89,43,11 11	True	True	✓

Passed all tests! ✓

7. Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element $a[i]$ is a peak element if

$A[i-1] \leq A[i] \geq a[i+1]$ for middle elements. $[0 < i < n-1]$

$A[i-1] \leq A[i]$ for last element $[i=n-1]$

$A[i] \geq A[i+1]$ for first element $[i=0]$

Input Format

The first line contains a single integer n , the length of A .

The second line contains n space-separated integers, $A[i]$.

Output Format

Print peak numbers separated by space.

Sample Input

5

8 9 10 2 6

Sample Output

10 6

Program:

```
a=int(input())
```

```
b=list(map(int,input().split()))
```

```
c=[]
```

```
d=len(b)-1
```

```
if a>1:
```

```
    if b[0]>b[1]:
```

```
        c.append(b[0])
```

```
    if b[d]>b[d-1]:
```

```
        c.append(b[d])
```

```
for i in range(1,d-1):
```

```
    m=i-1
```

```
    n=i+1
```

```
    if b[i]>b[m] and b[i]>b[n]:
```

```
        c.append(b[i])
```

```
c.sort(reverse=True)
```

```
print(*c)
```

	Input	Expected	Got	
✓	7 15 7 10 8 9 4 6	15 10 9 6	15 10 9 6	✓
✓	4 12 3 6 8	12 8	12 8	✓

Passed all tests! ✓

8. Two string values S1, S2 are passed as the input. The program must print first N characters present in S1 which are also present in S2.

Input Format:

The first line contains S1.

The second line contains S2.

The third line contains N.

Output Format:

The first line contains the N characters present in S1 which are also present in S2.

Boundary Conditions:

$2 \leq N \leq 10$

$2 \leq \text{Length of S1, S2} \leq 1000$

Example Input/Output 1:

Input:

```
abcbde  
cdefghbb  
3
```

Output:

```
bcd
```

Note:

b occurs twice in common but must be printed only once.

Program:

```
a=input()
```

```

b=input()

c=int(input())

d=""

count=0

for i in a:

    if count>=c:

        break

    if i in b and i not in d:

        d+=i

        count+=1

print(d)

```

	Input	Expected	Got	
✓	abcbde cdefghbb 3	bcd	bcd	✓

Passed all tests! ✓

9. String should contain only the words are not palindrome.

Sample Input 1

Malayalam is my mother tongue

Sample Output 1

is my mother tongue

program:

```
w=input().split(' ')
```

```
u=""
```

```

for i in w:

    i=i.lower()

    if i!=i[::-1]:

        u+=i+" "

print(u)

```

	Input	Expected	Got	
✓	Malayalam is my mother tongue	is my mother tongue	is my mother tongue	✓

Passed all tests! ✓

10. Given two Strings s1 and s2, remove all the characters from s1 which is present in s2.

Constraints

1<= string length <= 200

Sample Input 1

```

experience
enc

```

Sample Output 1

```

xpri

```

program:

```

a=input()

```

```

b=input()

```

```

c=""

```

```

for i in a:

```

```

    if i not in b:

```

```

        c+=i

```

print(c)

	Input	Expected	Got	
✓	experience enc	xpri	xpri	✓

Passed all tests! ✓