

ACTIVIDAD 04 – CONFIGURACIÓN DNS IV

(Definición de las zonas)

La portede no se numero



Deberic estar más grand

Jaime García Pedrote

• cat del fichero de zonas de S1-Alias:

```
ß jgarcia@s1–jgarcia:~$ sudo cat /etc/bind/named.conf.local
       // Do any local configuration here
        Consider adding the 1918 zones here, if they are not used in your
      // organization
//include "/etc/bind/zones.rfc1918";
      zone "alumno–5.ca" {
                type master;
               notify yes;
                allow–transfer { 172.16.5.2; };
file "/etc/bind/db.alumno–5.ca";
      zone "5.16.172.in–addr.arpa" {
                type master;
               notify yes;
                allow–transfer { 172.16.5.2; };
file "/etc/bind/db.alumno–5.ca.rev";
      zone "aula–5.org" {
                type slave;
               masters { 172.16.5.2 };
allow-notify { 172.16.5.2; };
file "/etc/bind/db.aula-5.org";
      jgarcia@s1−jgarcia:~$
```

• cat del fichero de zonas de S2-Alias:

```
jgarcia@s2-jgarcia:/etc/bind$ sudo cat named.conf.local
//
// Do any local configuration here
//
// Consider adding the 1918 zones here, if they are not used in your
// organization
//include "/etc/bind/zones.rfc1918";

zone "alumno-5.ca" {
    type slave;
        masters { 172.16.5.1; };
        allow-notify { 172.16.5.1; };
        file "db.alumno-5.ca";

};

zone "5.16.172.in-addr.arpa" {
        type slave;
        masters { 172.16.5.1; };
        allow-notify { 172.16.5.1; };
        file "db.alumno-5.ca.rev";
};

zone "aula-5.org" {
        type master;
        notify yes;
        allow-transfer { 172.16.5.1; };
        file "/etc/bind/db.aula-5.org";
};

jgarcia@s2-jgarcia:/etc/bind$
```

Jaime García Pedrote