Jai Jain

1BM18CS040

Century

Page No.

Date :

B- Trees

```
def B-Tree Insertion (T, K) :
    root = self. root
    if ( len (root. keys) == (2* self. t) - 1) :
        p = Node ()
        root = p
        p. child. insert (0, root)
        self. split - child (p, 0)
        self. insert_non full (temp, k)
    else :
        Self. insert_non_full (root, k)

def insert_non full (self, x, k) :
    i = len (x. keys) - 1
    if (x. leaf) :
        x. keys [i+1] = x. keys [i]
    while (i >= 0) and k[0] < x. keys [i]
        x. keys [i+1] = x. keys [i]
        i = i
        x. keys [i+1] = k
    else :
        while i >= 0 and k[0] < x. keys [i][0]
            i - = 1
        i + = 1
    if (len (x. child. keys) == 2 (* self. t) - 1 :
        self. split. child (x, i)
        if (x [0]) > x. keys ([i] [0] :
            i + = 1
        self. insert - non_full (x child [i], k)
```

```
def split(Node p)
{
    temp1 = Node()
    temp2 = Node()
    mid = max/2 - 1
    insert non-full (p[mid])

    while (i=0, i<mid; i++)
        insert non-full (p[i], temp1)
    while (i=mid, i<max; i++)
        insert non-full (p[i], temp2)
    p.parent ⟶ mid node = temp1
    p.parent ⟶ node = temp2
```