

CC Lecture 12

Prepared for: 7th Sem, CE, DDU

Prepared by: Niyati J. Buch

Runtime Environment

(topics covered so far)

- Parameter passing methods
- Static storage allocation
- Dynamic stack storage allocation
 - Activation record structure
 - Offset calculation for overlapped storage

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
  begin R; end  
begin P; end
```

- P is nested in RTST
- Q and R are nested in P
- Q and R are at same level
- Q calls R and R calls Q
- P calls R
- Main program RTST calls P

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```

- Activation records are created at procedure entry time and are destroyed at exit time
- How to access variables declared in various procedures?

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```

- **Call sequence**

RTST -> P -> R -> Q -> R

- Main program *RTST* cannot access variables of *P*, *Q* and *R*.
- *P* can access its own and main program variables but not of *Q* and *R*
- *Q* cannot access variables of *R* but can access variables of *P* and main
- *R* cannot access variables of *Q* but can access variables of *P* and main

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```

- **Call sequence**

RTST -> **P** -> R -> Q -> R


- When **P** is called, activation record of P is made
- Base pointer + offset can be used to access local variables of P
- But what about variables of main??
- Can base pointer be use in this case??

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```

- **Call sequence**

RTST -> P -> R -> Q -> R




- The **DL chain** chains all the activation records in order to maintain a stack structure.
- To access the variables of RTST, the **SL field** of the activation record has to be put into a register, and the contents of that activation of that register will now point to the beginning of the activation record for RTST.
- Consider this particular value and then access the variables of RTST using the offset.

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```

- **Call sequence**

RTST -> P -> R -> Q -> R



For variables of *RTST*:

SL field of *P* → register → beginning of *RTST* + offset

For variables of *P*:


Base is beginning of *P* + offset

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```

- **Call sequence**

RTST -> P -> R -> Q -> R



For variables of R: Base

For variables of P: use SL


For variables of RTST: one more level of indirection using SL

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
  begin R; end  
begin P; end
```

- Call sequence**

RTST -> P -> R -> Q -> R



No static link from $Q \rightarrow R$, as Q cannot access variables of R


But SL from $Q \rightarrow P$, as Q can access variables of P and RTST

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
  begin R; end  
begin P; end
```

- **Call sequence**

RTST -> P -> R -> Q -> R




No SL: $R \rightarrow Q$ and $R \rightarrow R$

Allocation of nested procedure

```
1. program RTST;  
2. procedure P;  
3.     procedure Q;  
        begin R; end  
3.     procedure R;  
        begin Q; end  
        begin R; end  
begin P; end
```

- **Call sequence**

RTST(1) -> P(2) -> R(3) -> Q(3) -> R(3)




Allocation of nested procedure

How SL is determined?

- Skip $L1 - L2 + 1$ records starting from the caller's AR and establish the static link to the AR reached
- $L1 = \text{caller}$ and $L2 = \text{Callee}$

$RTST(1) \rightarrow P(2) \rightarrow R(3) \rightarrow Q(3) \rightarrow R(3)$

- for $P(2) \rightarrow R(3)$, $2 - 3 + 1 = 0$;
hence the SL of R points to P
- for $R(3) \rightarrow Q(3)$, $3 - 3 + 1 = 1$;
skipping 1 link starting from R,
we get P;
SL of Q points to P




Creation of activation record happens in callee code

- The creation of activation record takes place after the callee assumes control, because the exact size of the activation record will be known to the callee function.
- It will not be known to the caller.
- Callee functions can possibly be compiled separately.
- So, the total area for the variables of the function, its temporaries will not be known to the caller.
- Callers will only the size of the parameter list.
- So, the complete creation of the activation record really happens in the callee code.

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
  begin R; end  
begin P; end
```




- Call sequence

RTST -> P -> R -> Q ← R

Return from R

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```




- **Call sequence**

RTST -> P -> R \leftarrow Q

Return from Q

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```




- Call sequence

RTST -> P ← R

Return from R

Allocation of nested procedure

```
program RTST;  
  procedure P;  
    procedure Q;  
      begin R; end  
    procedure R;  
      begin Q; end  
    begin R; end  
  begin P; end
```



- Call sequence

RTST ← P

Return from P


Static vs. Dynamic link

- **Static link:**
 - to access the global variables in the various activation records.
- **Dynamic link:**
 - to maintain the stack of activation records.

Display Stack

- It is **data structure** to be used instead of **static link**.
- A stack of pointers which point to the activation records of procedures which are right now executing is maintained instead of static link.
- The most recent procedure which is activated its activation record pointer is on the top of the stack.
- The display stack structure must reflect the scope of the various functions and procedures appropriately.

Display Stack of Activation Records (without SL)



Pop $L1-L2+1$ records off the display of the caller and push the pointer to AR of callee ($L1$ – caller, $L2$ – Callee)

The popped pointers are stored in the AR of the caller and restored to the DISPLAY after the callee returns

What about languages that don't support nested procedures?

- Example:- C language
- No requirement for static link
- Two links are needed
 1. To the beginning of the activation record
 2. To the static area containing global variables
- Dynamic link structure will handle the allocation and deallocation of the stack.

Static (lexical) scope	Dynamic scope
<p data-bbox="112 168 761 215">C, C++, Java, Pascal, Python</p> <p data-bbox="112 305 948 629">The name resolution depends on the location in the source code and the lexical context, which is defined by where the named variable or function is defined.</p> <p data-bbox="112 725 948 982">A global identifier refers to the identifier with that name that is declared in the closest enclosing scope of the program text.</p> <p data-bbox="112 1072 948 1258">Uses the static (unchanging) relationship between blocks in the program text.</p>	<p data-bbox="989 168 1508 215">Lisp, Perl, Logo, LaTeX</p> <p data-bbox="989 305 1825 629">The name resolution depends upon the program state when the name is encountered which is determined by the execution context or calling context.</p> <p data-bbox="989 725 1825 911">A global identifier refers to the identifier associated with the most recent activation record.</p> <p data-bbox="989 1072 1825 1329">Uses the actual sequence of calls that are executed in the dynamic (changing) execution of the program.</p>

Example 1 (C-like structure is used)

```
int x = 1, y = 0;
int g(int z){
    return x+z;
}
int f(int y) {
    int x;
    x = y+1;
    return g(y*x);
}
y = f(3);
```

After the call to g

Static scope

x = 1

So, y = 1 + 12 = **13**

Dynamic scope

x = 4

So, y = 4 + 12 = **16**

x	1
y	0

outer block

y	3
x	4

f(3)

z	12
---	----

g(12)

Stack of activation records
after the call to g

Example 2 (C-like structure is used)

```
float r = 0.25;
void show() {
    printf("%f",r);
}
void small() {
    float r = 0.125;
    show();
}

int main (){
    show();
    small();
    printf("\n");
    show();
    small();
    printf("\n");
}
```

Output Static Scope	Output Dynamic Scope
?	?

Example 2 (C-like structure is used)

```
float r = 0.25;
void show() {
    printf("%f",r);
}
void small() {
    float r = 0.125;
    show();
}

int main (){
    show();
    small();
    printf("\n");
    show();
    small();
    printf("\n");
}
```

Output Static Scope	Output Dynamic Scope
0.25 0.25	0.25 0.125
0.25 0.25	0.25 0.125

Implementing Dynamic scope

1. Deep access method
2. Shallow access method


Deep Access Method

- The idea is to keep a stack of active variables.
- Use control links instead of access links and to find a variable, search the stack from top to bottom looking for most recent activation record that contains the space for desired variables.
- Since search for nonlocal variables is made “deep” in the stack, the method is called deep access.
- Here, a symbol table should be used at runtime.

Shallow Access Method

- The idea is to keep a central storage and allot one slot for every variable name.
- If the names are not created at runtime then the storage layout can be fixed at compile time.
- Else, when new activation procedure occurs, then that procedure changes the storage entries for its local at entry and exit.
- Shallow access allows fast access but has a overhead of handling procedure entry and exit.

Deep Access Example



Calling Sequence

Main \rightarrow R \rightarrow Q \rightarrow R


Currently, R is being accessed. (Base)

In R, if we don't find x, we search in Q then again R and then in main.

Deep Access Method

- Dynamic link is used as static link.
- Activation records are searched on the stack to find the first activation record containing the non-local name to be found.
- The time required to access global variables is much more than the time required to access local variables.
- The time to access a global variable will depend on the sequence of calls that are made (hence can't be determined at compile-time).
- Needs some information on the identifiers to be maintained at runtime within the ARs.

Shallow Access Example



Calling Sequence

Main → R → Q → R

Direct and quick access to global variables, but some overhead is incurred when activations begin and end.

Shallow Access Method

- Variables declared in the procedures are stored in a unique static storage area.
- There is exactly one fixed amount of storage for each unique name.
- If same name is declared in various procedures with different type then maximum storage required of the given types is allocated in the static storage area.
- The advantage is every name has a unique address and it is static so there is no need to use a stack pointer to access.
- But, there is an overhead of storing and restoring at begin and end of the activation record.

Runtime Environment

- Parameter passing methods
- Static storage allocation
- Dynamic stack storage allocation
 - Activation record structure
 - Offset calculation for overlapped storage
 - **Allocation of nested procedure**
 - **Display stack structure (without static link)**
 - **Static and Dynamic scope**
 - **Deep Access Method for dynamic scope**
 - **Shallow Access Method for dynamic scope**