

Comment Hoodor 4	Description	Designator	Footprint UDD1V4	LibRef Hondor 4	Quantity
Header 4 Header 10	Header, 4-Pin Header, 10-Pin	4-pin .156 MTA 10-pin MTA	HDR1X4 HDR1X10	Header 4 Header 10	
ricader 10	Header, 8 Pins, 0.100	10-piii Wii A	TIDICIATO	ricader to	
HDR8PIN_2X4_100	in, Dual Row, AMP: 103328-4 or equivalent	Board_Console, Kiwi_to_Console	HDR8PIN_2X5_100	19156	
HDR5PIN	Header, 5 Pins, 2.50mm, Vertical, Through hole, single row, Shrouded, JST: B05B-XASK-1-A	Board_Resistance, HD3, Resistance motor, USB_to_RS485_Adapt er, USB_to_RS- 485_Adapter_from_R aspberryPi3b	HDR5PIN_JST_XA_2.5 MM	342211	
HDR2PIN	row, Shrouded, JST: B02B-XASK-1-A	Board_Tach	HDR2PIN_JST_XA_2.5 MM	342208	
HDR4PIN	Header, 4 Pins, 2.50mm, Vertical, Through hole, single row, Shrouded, JST: B04B-XASK-1-A	CONN,JST,VH,.156,(4 11732)	HDR4PIN_JST_XA_2.5 MM	342210	
HDR12PIN100SHRD	Header, 12 Pins, 0.100 in., Shrouded, Ting Zi:018-W012IP no alternates, Header, 12 pins Pins, 0.1 in., Shrouded, AMP: 3-644861-2	HD1, HD?, MC5100_EXT_48W	HDR12PIN100SHRD	293272, 1763	
HDR2PIN	Header, 2 Pins, 2.50mm, Right Angle, Through hole, single row, Shrouded, CJT: A2508WR-F-2P	HD4, RaspberryPi3b, VIN_5VDC_to_12VDC		342769	
HDR4PIN100SHRD	Header, 4 pin Pins, 0.100 in., Shrouded, AMP: 644486-4	HD?	HDR4PIN100SHRD	1768	
HDR5PIN100SHRD	Header, 5 pin Pins, 0.100 in., Shrouded, AMP: 644486-5 Header, 9 Pins Pins,	HD?	HDR5PIN100SHRD	1770	
HDR9PIN100SHRD	0.1 in, Shrouded, AMP: 644486-9	HD?	HDR9PIN100SHRD	2327	
HDR-DC-PWR_CUI-PJ- 102AH	stack: PJ-060A or exact equivalent	HD?	HDR-DC_POWER	19154	
HDR12PIN2_5MMSHR D	Header, 12 Pins, 2.5mm, Shrouded, Hsuan Mao: 7600- 12PST or equivalent	J8 pin 40 = pin 1, J8 pin 17 = pin 1	HDR12PIN2_5MMSHR D	10696	
Black_to_Multimeter	Socket	J?	PIN1	Socket	
DC POWER JACK	Low Voltage Power	J?	KLD-0202	PWR2.5	
Plug AC Female	Supply Connector IEC Mains Power Outlet, EN60 320-2-2 F Class I, PC Flange Rear Mount, Chassis Socket	13.	IEC7-2H3	Plug AC Female	
Red_to_Multimeter	Socket	J?	PIN1	Socket	
HDR8PIN	Header, 8 Pins, 2.50mm, Vertical, Through hole, single row, Shrouded, JST: B08B-XASK-1-A	JST_to_Console, JST_to_Console?, to_EQF1259_Boston1, to_EQF1259_TREAD1	HDR8PIN_JST_XA_2.5 MM	342214	
HDR4PIN100SLDR	Header, 4 pin Pins, 0.100 in., Solder, Part of the PCB, NOT a component	JST_to_Tablet_	4PIN100SLDR	6327	
HDR_10PIN_DUALRO W	Header, 10 Pins, 2.50mm, Vertical, Through hole, dual row, Shrouded, JST: B10B-XADSS-N-A	Kiwi_to_Motor_Contr oller, SWITCH BOX	HDR_2.5MM_10PIN_J ST_XAD	343791	
DRW# 378026	Header, 3-Pin	P? P?	MHDR1X3	MHDR1X3	<u> </u>
To PSoC 4BLE RESISTOR_SMT	Header, 3-Pin Resistor, 9.09K, ThickFilm, 1%, 0603, 1/10W, Any	P? R?	HDR1X3 0603	Header 3 311405	
HDR8PIN_1.5mm_DR _VERT	Header, 8 Pins, 1.5mm, Shrouded, AMP: 292207-8	Raspberry_Pi_3b	HDR8PIN_1.5mm_DR _8PIN_VERT	16901	
Header 8	Header, 8-Pin	Red_DIN	HDR1X8	Header 8	
SW-DPDT	Double-Pole, Double- Throw Switch	RUN/COMMUNICATI ON	DPDT-6	SW-DPDT	
o-3A/c-4A	Single-Pole, Single- Throw Switch	S?	SPST-2	SW-SPST	
SW-DPST	Double-Pole, Single- Throw Switch Header, 10 Pins,	S?	DPST-4	SW-DPST	
HDR10PIN	2.50mm, Vertical, Through hole, single row, Shrouded, JST: B10B-XASK-1-A Header, 12 Pins,	to_Console	HDR10PIN_JST_XA_2. 5MM	342216	
HDR12PIN100SLDR	0.100in., Solder, Part of PCB, not a component	to_EQF1259_Boston2	12PIN-SLDR-HDR2	6330	
		Yellow_DIN	HDR1X6	Header 6	