

Uni Software Defined Infrastructure Notes

Felix Pojtinger

December 6, 2021

Contents

1	Introduction	2
1.1	Contributing	2
1.2	License	2
2	Hosts	3
3	User	3
4	SSH	3
5	UFW	3
6	APT	4
7	Traefik	4
8	Cockpit	8
9	DNS	8
9.1	Manager	8
9.2	Worker	10
9.3	Exercises	11
10	LDAP	12
11	Apache	16
12	MariaDB	19

1 Introduction

1.1 Contributing

These study materials are heavily based on [professor Goik's "Software Defined Infrastructure" lecture at HdM Stuttgart](#).

Found an error or have a suggestion? Please open an issue on GitHub (github.com/pojntfx/uni-sdi-notes):



Figure 1: QR code to source repository

If you like the study materials, a GitHub star is always appreciated :)

1.2 License



Figure 2: AGPL-3.0 license badge

Uni Software Defined Infrastructure Notes (c) 2021 Felix Pojtinger and contributors

SPDX-License-Identifier: AGPL-3.0

2 Hosts

Add the following A and AAAA records to a public DNS server (with root domain alphahorizon.io):

felixs-sdi1	10800	IN	A	138.68.70.72
felixs-sdi1	10800	IN	AAAA	2a03:b0c0:3:d0::e34:5001
*.felixs-sdi1	10800	IN	A	138.68.70.72
*.felixs-sdi1	10800	IN	AAAA	2a03:b0c0:3:d0::e34:5001
felixs-sdi2	10800	IN	A	159.223.25.154
felixs-sdi2	10800	IN	AAAA	2a03:b0c0:3:d0::1092:b001
*.felixs-sdi2	10800	IN	A	159.223.25.154
*.felixs-sdi2	10800	IN	AAAA	2a03:b0c0:3:d0::1092:b001

3 User

```
ssh root@felixs-sdi1.alphahorizon.io
adduser pojntfx
usermod -aG sudo pojntfx
su pojntfx
```

4 SSH

```
sudo apt update
sudo apt install -y openssh-server
sudo systemctl enable --now ssh
mkdir -p ~/.ssh
chmod 700 ~/.ssh
curl 'https://github.com/pojntfx.keys' | tee -a ~/.ssh/authorized_keys
chmod 600 ~/.ssh/authorized_keys
exit
```

5 UFW

```
ssh pojntfx@felixs-sdi1.alphahorizon.io
sudo apt update
sudo apt install -y ufw
sudo systemctl enable --now ufw
sudo ufw default deny incoming
sudo ufw default allow outgoing
sudo ufw allow OpenSSH
sudo ufw enable
```

6 APT

```
sudo apt update
sudo apt install -y unattended-upgrades

sudo vi /etc/apt/apt.conf.d/50unattended-upgrades # Now replace/add the following:
Unattended-Upgrade::Origins-Pattern {
    "origin=*";
}
Unattended-Upgrade::Automatic-Reboot "true";
Unattended-Upgrade::Automatic-Reboot-Time "02:00";

sudo dpkg-reconfigure unattended-upgrades # Answer with yes
sudo systemctl enable --now unattended-upgrades
sudo unattended-upgrades --debug # Test the configuration; this will install the available u
sudo reboot # If required
```

7 Traefik

```
$ sudo apt update
$ sudo apt install -y docker.io
$ sudo systemctl enable --now docker
$ sudo mkdir -p /etc/traefik
$ sudo tee /etc/traefik/traefik.yaml<<'EOT'
entryPoints:
  dnsTcp:
    address: ":53"

  dnsUdp:
    address: ":53/udp"

  web:
    address: ":80"

  websecure:
    address: ":443"

  websecurealt:
    address: ":8443"

providers:
  file:
    filename: /etc/traefik/services.yaml
    watch: true
```

```

api:
  dashboard: true

certificatesResolvers:
  letsencrypt:
    acme:
      email: felix@pojtinger.com
      storage: /var/lib/traefik/acme.json
      httpChallenge:
        entryPoint: web

log:
  level: INFO
EOT
$ sudo tee /etc/traefik/services.yaml<<'EOT'
udp:
  routers:
    dns:
      entryPoints:
        - dnsUdp
      service: dns
  services:
    dns:
      loadBalancer:
        servers:
          - address: localhost:54

tcp:
  routers:
    dns:
      entryPoints:
        - dnsTcp
      rule: HostSNI(`*`)
      service: dns
    ssh:
      entryPoints:
        - websecurealt
      rule: HostSNI(`*`)
      service: ssh
    sshOverTLS:
      entryPoints:
        - websecure
      rule: HostSNI(`ssh.felixs-sdi1.alphahorizon.io`)
      service: ssh
    tls:
      certResolver: letsencrypt

```

```

        domains:
          - main: ssh.felixs-sdi1.alphahorizon.io
ldap:
  entryPoints:
    - websecure
  rule: HostSNI(`ldap.felixs-sdi1.alphahorizon.io`)
  service: ldap
  tls:
    certResolver: letsencrypt
    domains:
      - main: ldap.felixs-sdi1.alphahorizon.io
services:
  dns:
    loadBalancer:
      servers:
        - address: localhost:54
  ssh:
    loadBalancer:
      servers:
        - address: localhost:22
  ldap:
    loadBalancer:
      servers:
        - address: localhost:389

http:
  routers:
    cockpit:
      rule: Host(`cockpit.felixs-sdi1.alphahorizon.io`)
      tls:
        certResolver: letsencrypt
        domains:
          - main: cockpit.felixs-sdi1.alphahorizon.io
      service: cockpit
      entryPoints:
        - websecure
  apache:
    rule: Host(`apache.felixs-sdi1.alphahorizon.io`) || HostRegexp(`^{subdomain:[a-z]+}.ap`)
    tls:
      certResolver: letsencrypt
      domains:
        - main: apache.felixs-sdi1.alphahorizon.io
        - main: marx.apache.felixs-sdi1.alphahorizon.io
        - main: kropotkin.apache.felixs-sdi1.alphahorizon.io
        - main: secure.apache.felixs-sdi1.alphahorizon.io
    service: apache

```

```

    entryPoints:
      - websecure
phpmyadmin:
  rule: Host(`phpmyadmin.felixs-sdi1.alphahorizon.io`)
  tls:
    certResolver: letsencrypt
    domains:
      - main: phpmyadmin.felixs-sdi1.alphahorizon.io
  service: apache
  entryPoints:
    - websecure
dashboard:
  rule: Host(`traefik.felixs-sdi1.alphahorizon.io`)
  tls:
    certResolver: letsencrypt
    domains:
      - main: traefik.felixs-sdi1.alphahorizon.io
  service: api@internal
  entryPoints:
    - websecure
  middlewares:
    - dashboard

middlewares:
  dashboard:
    basicauth:
      users:
        - "admin:$apr1$wBh8VM6G$bhz82XpyH3mX4ha9XBbcL1" # htpasswd -nb admin asdf

services:
  cockpit:
    loadBalancer:
      serversTransport: cockpit
      servers:
        - url: https://localhost:9090
  apache:
    loadBalancer:
      servers:
        - url: http://localhost:8080

serversTransports:
  cockpit:
    insecureSkipVerify: true
EOT
$ sudo docker run -d --restart=always --net=host -v /var/lib/traefik/:/var/lib/traefik -v /etc/passwd:/etc/passwd
$ sudo ufw allow 'DNS'

```

```
$ sudo ufw allow 'WWW'
$ sudo ufw allow 'WWW Secure' # Now visit https://cockpit.felixs-sdi1.alphahorizon.io/
$ sudo ufw allow '8443/tcp'
$ ssh pojntfx@felixs-sdi1.alphahorizon.io # Connect using SSH without Traefik
$ ssh -p 8443 pojntfx@felixs-sdi1.alphahorizon.io # Connect using SSH over Traefik without T
$ ssh -o ProxyCommand="openssl s_client -connect ssh.felixs-sdi1.alphahorizon.io:443 -quiet"
```

8 Cockpit

```
echo 'deb http://deb.debian.org/debian bullseye-backports main' | sudo tee /etc/apt/sources
sudo apt update
sudo apt install -t bullseye-backports -y cockpit
```

9 DNS

9.1 Manager

```
sudo apt update
sudo apt install -y bind9 bind9utils
sudo systemctl enable --now named
```

```
sudo vi /etc/bind/named.conf.options # Now add the following at the end of the options block
listen-on port 54 { 127.0.0.1; };
listen-on-v6 port 54 { ::1; };
```

```
version "not currently available";
recursion yes;
querylog yes;
allow-transfer { none; };
allow-query { any; };
```

```
sudo tee -a /etc/bind/named.conf.local <<'EOT'
zone "example.pojtinger" {
    type master;
    file "/etc/bind/db.example.pojtinger";
    allow-query { any; };
    allow-transfer { 159.223.25.154; 2a03:b0c0:3:d0::1092:b001; };
};
```

```
zone "70.68.138.in-addr.arpa" {
    type master;
    file "/etc/bind/db.70.68.138";
    allow-query { any; };
    allow-transfer { 159.223.25.154; 2a03:b0c0:3:d0::1092:b001; };
};
```



```

zone "1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.0.c.0.b.3.0.a.2.ip6.arpa" {
    type master;
    file "/etc/bind/db.1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.0.c.0.b.3.0.a.2";
    allow-query { any; };
    allow-transfer { 159.223.25.154; 2a03:b0c0:3:d0::1092:b001; };
};
EOT

```

```

# Increase `1634570712` by one and reload after each change to propagate changes to the world
sudo tee /etc/bind/db.example.pojtinger <<'EOT'
$ORIGIN example.pojtinger.
$TTL 3600

```

```

example.pojtinger.      IN      SOA      ns1.example.pojtinger. hostmaster.example.pojtinger.
example.pojtinger.      IN      NS       ns1.example.pojtinger.
example.pojtinger.      IN      NS       ns2.example.pojtinger.

example.pojtinger.      IN      A        138.68.70.72
example.pojtinger.      IN      AAAA     2a03:b0c0:3:d0::e34:5001

ns1.example.pojtinger.  IN      A        138.68.70.72
ns1.example.pojtinger.  IN      AAAA     2a03:b0c0:3:d0::e34:5001

ns2.example.pojtinger.  IN      A        159.223.25.154
ns2.example.pojtinger.  IN      AAAA     2a03:b0c0:3:d0::1092:b001

example.pojtinger.      IN      MX       1          fb.mail.gandi.net.
www.example.pojtinger.  IN      CNAME    example.pojtinger.
EOT

```

```

# Increase `1634570724` by one and reload after each change to propagate changes to the world
sudo tee /etc/bind/db.70.68.138 <<'EOT'
$ORIGIN 70.68.138.in-addr.arpa.
$TTL 3600

```

```

@      IN      SOA      ns1.example.pojtinger. hostmaster.example.pojtinger.      ( 1634570724

@      IN      NS       ns1.example.pojtinger.
@      IN      NS       ns2.example.pojtinger.

72     IN      PTR      example.pojtinger.
EOT

```

```

# Increase `1634570724` by one and reload after each change to propagate changes to the world

```

```

sudo tee /etc/bind/db.1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.0.c.0.b.3.0.a.2 <<'EOT'
$ORIGIN 1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.0.c.0.b.3.0.a.2.ip6.arpa.
$TTL 3600

@      IN      SOA      ns1.example.pojtinger. hostmaster.example.pojtinger.    ( 1634570724

@      IN      NS       ns1.example.pojtinger.

@      IN      NS       ns2.example.pojtinger.

1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.0.c.0.b.3.0.a.2.ip6.arpa.      IN      PTR
EOT

sudo named-checkconf

sudo named-checkzone example.pojtinger /etc/bind/db.example.pojtinger
sudo named-checkzone 70.68.138.in-addr.arpa. /etc/bind/db.70.68.138
sudo named-checkzone 1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.0.c.0.b.3.0.a.2.ip6.arpa.

sudo systemctl reload named

```

9.2 Worker

```

sudo apt update
sudo apt install -y bind9 bind9utils
sudo systemctl enable --now named

sudo vi /etc/bind/named.conf.options # Now add the following at the end of the options block
listen-on port 54 { 127.0.0.1; };
listen-on-v6 port 54 { ::1; };

version "not currently available";
recursion yes;
querylog yes;
allow-transfer { none; };
allow-query { any; };

sudo tee -a /etc/bind/named.conf.local <<'EOT'
zone "example.pojtinger" {
    type slave;
    file "db.example.pojtinger";
    allow-query { any; };
    masters { 138.68.70.72; 2a03:b0c0:3:d0::e34:5001; };
};

zone "70.68.138.in-addr.arpa" {
    type slave;

```

```

        file "db.70.68.138";
        allow-query { any; };
        masters { 138.68.70.72; 2a03:b0c0:3:d0::e34:5001; };
};

zone "1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.c.0.b.3.0.a.2.ip6.arpa" {
    type slave;
    file "db.1.0.0.5.4.3.e.0.0.0.0.0.0.0.0.0.d.0.0.3.0.0.0.c.0.b.3.0.a.2";
    allow-query { any; };
    masters { 138.68.70.72; 2a03:b0c0:3:d0::e34:5001; };
};
EOT

sudo named-checkconf
sudo systemctl reload named

```

9.3 Exercises

Use the `dig` command to query A/CNAME/MX/NS records from various machines/domains of your choice. Then execute reverse lookups as well.

```

# Get A/AAA records from manager server
$ dig +noall +answer @138.68.70.72 example.pojtinger A
example.pojtinger.      3600    IN      A       138.68.70.72
$ dig +noall +answer @138.68.70.72 example.pojtinger AAAA
example.pojtinger.      3600    IN      AAAA    2a03:b0c0:3:d0::e34:5001

# Get A/AAAA records from worker server
$ dig +noall +answer @159.223.25.154 example.pojtinger A
example.pojtinger.      3600    IN      A       138.68.70.72
$ dig +noall +answer @159.223.25.154 example.pojtinger AAAA
example.pojtinger.      3600    IN      AAAA    2a03:b0c0:3:d0::e34:5001

# Get NS record
$ dig +noall +answer @159.223.25.154 example.pojtinger NS
example.pojtinger.      3600    IN      NS      ns1.example.pojtinger.
example.pojtinger.      3600    IN      NS      ns2.example.pojtinger.

# Get CNAME record
$ dig +noall +answer @159.223.25.154 www.example.pojtinger CNAME
www.example.pojtinger.  3600    IN      CNAME   example.pojtinger.

# Do IPv4 reverse lookup
$ dig +short @159.223.25.154 -x 138.68.70.72
example.pojtinger.

```

```
# Do IPv6 reverse lookup
$ dig +short @159.223.25.154 -x '2a03:b0c0:3:d0::e34:5001'
example.pojtinger.
```

Enable recursive queries to parent nameservers enabling your name-server to resolve external machines like `www.w3.org` by delegation.

```
# Get AAAA record for felix.pojtinger.com using parent nameservers
$ dig +noall +answer @159.223.25.154 felix.pojtinger.com AAAA
felix.pojtinger.com.      123      IN      CNAME   cname.vercel-dns.com.
```

**Provide a mail exchange record pointing to `mx1.hdm-stuttgart.de`.
Test this configuration using dig accordingly.**

```
# Get MX record
$ dig +noall +answer @159.223.25.154 example.pojtinger MX
example.pojtinger.      3600     IN      MX      1 fb.mail.gandi.net.
```

10 LDAP

```
sudo apt update
sudo apt install -y slapd ldap-utils certbot
```

```
sudo dpkg-reconfigure slapd # ldap.felixs-sdi1.alphahorizon.io, felixs-sdi1
```

```
curl ldaps://ldap.felixs-sdi1.alphahorizon.io:443 # Test the connection
```

```
socat tcp-listen:8389,fork openssl:ldap.felixs-sdi1.alphahorizon.io:443 # Run this on the 1
curl ldap://localhost:8389 # Test the proxy's connection
```

```
# Connect in Apache Directory Studio with the following info:
# Hostname: localhost
# Port: 8389
# Bind DN or user: cn=admin,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
# Bind password: The password from `sudo dpkg-reconfigure slapd`
```

```
# Connect with ldapwhoami like so:
ldapwhoami -H 'ldaps://ldap.felixs-sdi1.alphahorizon.io:443' -x # Anonymous
ldapwhoami -H 'ldaps://ldap.felixs-sdi1.alphahorizon.io:443' -W -D cn=admin,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
```

```
# Now add the objects:
ldapadd -H 'ldaps://ldap.felixs-sdi1.alphahorizon.io:443' -W -D cn=admin,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
version: 1
```

```
dn: dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: dcObject
```

```

objectClass: organization
objectClass: top
dc: ldap
o: felixs-sdi1

# We already set this up using `dpkg-reconfigure`
# dn: cn=admin,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
# objectClass: organizationalRole
# objectClass: simpleSecurityObject
# cn: admin
# userPassword:: e1NTSEF9cEhFKOVQT0cyZ3lSeU9nanZGcXNXT2I1ekdzR2w5Q0Q=
# description: LDAP administrator

dn: ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: organizationalUnit
objectClass: top
ou: departments

dn: ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: organizationalUnit
objectClass: top
ou: software

dn: ou=financial,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: organizationalUnit
objectClass: top
ou: financial

dn: ou=devel,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: organizationalUnit
objectClass: top
ou: devel

dn: ou=testing,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: organizationalUnit
objectClass: top
ou: testing

dn: uid=bean,ou=devel,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: inetOrgPerson
objectClass: organizationalPerson
objectClass: person
objectClass: top
cn: Audrey Bean
sn: Bean
givenName: Audrey

```

mail: bean@ldap.felixs-sdi1.alphahorizon.io
uid: bean
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=

dn: uid=smith,ou=devel,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=
objectClass: inetOrgPerson
objectClass: organizationalPerson
objectClass: person
objectClass: top
cn: Jane Smith
sn: Smith
givenName: Jane
mail: smith@ldap.felixs-sdi1.alphahorizon.io
uid: smith
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=

dn: uid=waibel,ou=financial,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: inetOrgPerson
objectClass: organizationalPerson
objectClass: person
objectClass: posixAccount
objectClass: top
cn: Jakob Waibel
gidNumber: 100
homeDirectory: /usr/jakob
sn: Waibel
uid: waibel
uidNumber: 1337
givenName: Jakob
mail: waibel@ldap.felixs-sdi1.alphahorizon.io
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=

dn: uid=simpson,ou=financial,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,dc=io
objectClass: inetOrgPerson
objectClass: organizationalPerson
objectClass: person
objectClass: top
cn: Homer Simpson
sn: Simpson
givenName: Homer
mail: simpson@ldap.felixs-sdi1.alphahorizon.io
uid: simpson
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=

dn: uid=pojtinger,ou=testing,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon
objectClass: inetOrgPerson

objectClass: organizationalPerson
objectClass: person
objectClass: top
cn: Felix Pojtinger
sn: Pojtinger
givenName: Felix
mail: pojtinger@ldap.felixs-sdi1.alphahorizon.io
uid: pojtinger
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=

dn: uid=simpson,ou=testing,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,
objectClass: inetOrgPerson
objectClass: organizationalPerson
objectClass: person
objectClass: top
cn: Maggie Simpson
sn: Simpson
givenName: Maggie
mail: simpson@ldap.felixs-sdi1.alphahorizon.io
uid: simpson
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=

dn: uid=aleimut,ou=devel,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,
objectClass: inetOrgPerson
objectClass: organizationalPerson
objectClass: person
objectClass: top
cn: Adelheit Aleimut
sn: Aleimut
givenName: Adelheit
mail: aleimut@ldap.felixs-sdi1.alphahorizon.io
uid: aleimut
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=

dn: uid=tibbie,ou=testing,ou=software,ou=departments,dc=ldap,dc=felixs-sdi1,dc=alphahorizon,
objectClass: inetOrgPerson
objectClass: organizationalPerson
objectClass: person
objectClass: posixAccount
objectClass: top
cn: Oswald Tibbie
gidNumber: 100
homeDirectory: /usr/oswald
sn: Tibbie
uid: tibbie
uidNumber: 1234

```
givenName: Oswald
mail: tibbie@ldap.felixs-sdi1.alphahorizon.io
userPassword:: e1NTSEF9NGxCMnc4dThQRXI5Rjd3VGZjN3ltNWkwUDk5N3d0eS8=
EOT
```

```
# And test if we can access using a user
ldapwhoami -H 'ldaps://ldap.felixs-sdi1.alphahorizon.io:443' -W -D uid=bean,ou=devel,ou=soft
```

11 Apache

```
sudo apt update
sudo apt install -y apache2
sudo vi /etc/apache2/ports.conf # Now replace/add the following:
Listen 8080
sudo systemctl restart apache2
sudo systemctl enable --now apache2
sudo systemctl status apache2
```

```
sudo tree -T "Example Index" -H '.' -o /var/www/html/index.html /var/www/html # Replace the
sudo mkdir -p /var/www/sdidoc
sudo tree -T "Example Index For sdidoc" -H '.' -o /var/www/sdidoc/index.html /var/www/html #
sudo tee /etc/apache2/sites-available/apache.felixs-sdi1.alphahorizon.io.conf <<'EOT'
<VirtualHost *:8080>
```

```
    ServerName felixs-sdi1.alphahorizon.io
    ServerAlias apache.felixs-sdi1.alphahorizon.io
```

```
    ServerAdmin webmaster@alphahorizon.io
    DocumentRoot /var/www/html
```

```
    ErrorLog ${APACHE_LOG_DIR}/error.log
    CustomLog ${APACHE_LOG_DIR}/access.log combined
```

```
<Directory "/var/www/html">
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
</Directory>
```

```
Alias /sdidoc /var/www/sdidoc
```

```
<Directory "/var/www/sdidoc">
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
</Directory>
```



```

</VirtualHost>
EOT
sudo a2dissite 000-default.conf
sudo a2ensite apache.felixs-sdi1.alphahorizon.io
sudo systemctl reload apache2

curl https://apache.felixs-sdi1.alphahorizon.io/ # Access the index
curl https://apache.felixs-sdi1.alphahorizon.io/sdidoc/ # Access the index in `/var/www/sdi1

sudo apt install -y apache2-doc # Install the docs package
curl https://apache.felixs-sdi1.alphahorizon.io/manual/en/index.html # Access the installed

sudo mkdir -p /var/www/marx.apache.felixs-sdi1.alphahorizon.io
echo '<h1>Marx</h1>' | sudo tee /var/www/marx.apache.felixs-sdi1.alphahorizon.io/index.html
sudo tee /etc/apache2/sites-available/marx.apache.felixs-sdi1.alphahorizon.io.conf <<'EOT'
<VirtualHost *:8080>
    ServerName felixs-sdi1.alphahorizon.io
    ServerAlias marx.apache.felixs-sdi1.alphahorizon.io

    ServerAdmin webmaster@alphahorizon.io
    DocumentRoot /var/www/marx.apache.felixs-sdi1.alphahorizon.io

    ErrorLog ${APACHE_LOG_DIR}/error.log
    CustomLog ${APACHE_LOG_DIR}/access.log combined

    <Directory "/var/www/marx.apache.felixs-sdi1.alphahorizon.io">
        Options Indexes FollowSymLinks
        AllowOverride None
        Require all granted
    </Directory>
</VirtualHost>
EOT
sudo a2ensite marx.apache.felixs-sdi1.alphahorizon.io
sudo systemctl reload apache2

curl https://marx.apache.felixs-sdi1.alphahorizon.io/ # Access the Marx site

sudo mkdir -p /var/www/kropotkin.apache.felixs-sdi1.alphahorizon.io
echo '<h1>Kropotkin</h1>' | sudo tee /var/www/kropotkin.apache.felixs-sdi1.alphahorizon.io/
sudo tee /etc/apache2/sites-available/kropotkin.apache.felixs-sdi1.alphahorizon.io.conf <<'EOT'
<VirtualHost *:8080>
    ServerName felixs-sdi1.alphahorizon.io
    ServerAlias kropotkin.apache.felixs-sdi1.alphahorizon.io

    ServerAdmin webmaster@alphahorizon.io
    DocumentRoot /var/www/kropotkin.apache.felixs-sdi1.alphahorizon.io

```

```

ErrorLog ${APACHE_LOG_DIR}/error.log
CustomLog ${APACHE_LOG_DIR}/access.log combined

<Directory "/var/www/kropotkin.apache.felixs-sdi1.alphahorizon.io">
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
</Directory>
</VirtualHost>
EOT
sudo a2ensite kropotkin.apache.felixs-sdi1.alphahorizon.io
sudo systemctl reload apache2

curl https://kropotkin.apache.felixs-sdi1.alphahorizon.io/ # Access the Kropotkin site

sudo mkdir -p /var/www/secure.apache.felixs-sdi1.alphahorizon.io
echo '<h1>Super secure content!</h1>' | sudo tee /var/www/secure.apache.felixs-sdi1.alphahorizon.io
sudo tee /etc/apache2/sites-available/secure.apache.felixs-sdi1.alphahorizon.io.conf <<'EOT'
<VirtualHost *:8080>
    ServerName felixs-sdi1.alphahorizon.io
    ServerAlias secure.apache.felixs-sdi1.alphahorizon.io

    ServerAdmin webmaster@alphahorizon.io
    DocumentRoot /var/www/secure.apache.felixs-sdi1.alphahorizon.io

    ErrorLog ${APACHE_LOG_DIR}/error.log
    CustomLog ${APACHE_LOG_DIR}/access.log combined

    <Directory "/var/www/secure.apache.felixs-sdi1.alphahorizon.io">
        Options Indexes FollowSymLinks
        AllowOverride None

        AuthType Basic
        AuthBasicProvider ldap
        AuthName "Please enter your LDAP username and password"
        AuthLDAPURL "ldap://localhost:389/ou=devel,ou=software,ou=departments,dc=ld
        Require valid-user
    </Directory>
</VirtualHost>
EOT
sudo a2enmod authnz_ldap
sudo a2ensite secure.apache.felixs-sdi1.alphahorizon.io
sudo systemctl reload apache2

ldapwhoami -H 'ldap://localhost:389' -W -D uid=bean,ou=devel,ou=software,ou=departments,dc=1

```

```
curl https://secure.apache.felixs-sdi1.alphahorizon.io/ # Try to access the secure site and see the error
curl -u bean:password https://secure.apache.felixs-sdi1.alphahorizon.io/ # Access the secure site
```

12 MariaDB

```
sudo apt update
sudo apt install -y mariadb-server
sudo mysql_secure_installation # Empty string, y, y, yourpassword, yourpassword, y, y, y, y

sudo mysql -u root -e 'GRANT ALL PRIVILEGES ON *.* TO 'phpmyadmin'@'localhost' WITH GRANT OPTION'

sudo apt install -y phpmyadmin libapache2-mod-php # apache2, y, yourpassword, yourpassword
sudo phpenmod mbstring

sudo a2disconf phpmyadmin

sudo tee /etc/apache2/sites-available/phpmyadmin.felixs-sdi1.alphahorizon.io.conf <<'EOT'
<VirtualHost *:8080>
    ServerName felixs-sdi1.alphahorizon.io
    ServerAlias phpmyadmin.felixs-sdi1.alphahorizon.io

    ServerAdmin webmaster@alphahorizon.io
    DocumentRoot /usr/share/phpmyadmin

    ErrorLog ${APACHE_LOG_DIR}/error.log
    CustomLog ${APACHE_LOG_DIR}/access.log combined

    <Directory "/usr/share/phpmyadmin">
        Options SymLinksIfOwnerMatch
        DirectoryIndex index.php

        # limit libapache2-mod-php to files and directories necessary by pma
        <IfModule mod_php7.c>
            php_admin_value upload_tmp_dir /var/lib/phpmyadmin/tmp
            php_admin_value open_basedir /usr/share/phpmyadmin:/usr/share/doc/phpmyadmin
        </IfModule>
    </Directory>

    # Disallow web access to directories that don't need it
    <Directory /usr/share/phpmyadmin/templates>
        Require all denied
    </Directory>
    <Directory /usr/share/phpmyadmin/libraries>
        Require all denied
```

```
        </Directory>
</VirtualHost>
EOT
sudo a2ensite phpmyadmin.felixs-sdi1.alphahorizon.io
sudo systemctl reload apache2

# Now visit https://phpmyadmin.felixs-sdi1.alphahorizon.io/ and login as root using yourpass
```