



HMER.EX6721 Check Valves

[Page Bottom](#)

Check Valves

[See General Information for Check Valves](#)

SHIELD FIRE SAFETY & SECURITY LTD

EX6721

REDBURN HOUSE

2A TONBRIDGE ROAD

ROMFORD, ESSEX RM3 8QE UNITED KINGDOM

Swing type, Model **SD-NRV250CV**, 3, 4, **6** and 8 in. sizes flanged end check valves rated pressure for 250 psig. Horizontal or vertical installation.

Swing-type check valves, Models SD-NRV-PN16, SD-NRV300FF-D, sizes 2 to 12 in. with rubber faced checks, rated for 300 psi, horizontal or vertical installation.

Swing-type check valve, Model SD-NRV200FF-D, sizes 2 to 12 in. with rubber faced checks, rated for 200 psi, horizontal or vertical installation.

[Last Updated](#) on 2014-06-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2014 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2014 UL LLC".