



SEE DRAWING NO. VM-15A-M FOR STANDARD MATERIALS OF CONSTRUCTION

VALVE SIZE	MODEL NUMBER	INLET SIZE	OUTLET SIZE	MAX. W.P. P.S.I.	ORIFICE SIZE
1/2"	15A	1/2" NPT	1/2" NPT	175	1/16"
3/4"	15A.2	3/4" NPT	1/2" NPT	175	1/16"
1"	15A.3	1" NPT	1/2" NPT	175	1/16"

- | | | | |
|----|-------------|----|----------------------------|
| 1 | BODY | 11 | ORIFICE BUTTON |
| 2 | COVER | 12 | PIVOT PIN |
| 3 | LEVER FRAME | 13 | RETAINING RING (NOT SHOWN) |
| 4 | SEAT | 14 | PIPE PLUG |
| 5 | FLOAT | 17 | FLOAT RETAINER |
| 6 | GASKET | 21 | LOCATOR |
| 7 | COVER BOLT | 34 | LOCK WASHER |
| 10 | FLOAT ARM | | |

AIR RELEASE VALVE

DATE 4-15-11

VAL-MATIC

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VMC-15A

AIR RELEASE VALVE

SERIES NO. 15A

STANDARD MATERIALS OF CONSTRUCTION

<u>PART NO.</u>	<u>PART NAME</u>	<u>MATERIAL</u>
1	BODY	CAST IRON ASTM A126, CLASS B
2	COVER	CAST IRON ASTM A126, CLASS B
3	LEVER FRAME	STAINLESS STEEL T316, ASTM A240
4	SEAT	STAINLESS STEEL T316, ASTM A276
5	FLOAT	STAINLESS STEEL T316, ASTM A240
6	GASKET	COMPRESSED NON-ASBESTOS FIBER
7	COVER BOLT	ALLOY STEEL SAE, GRADE 5
10	FLOAT ARM	STAINLESS STEEL T316, ASTM A240
11	ORIFICE BUTTON	VITON
12	PIVOT PIN	STAINLESS STEEL T316, ASTM A479
13	PIN RETAINER	STAINLESS STEEL PH 15-7 MO
14	PIPE PLUG	STEEL
17	FLOAT RETAINER	STAINLESS STEEL T316, ASTM F879
21	LOCATOR	STAINLESS STEEL T316, ASTM F593
34	LOCK WASHER	STAINLESS STEEL T316, ASTM A240

NOTE: ALL SPECIFICATIONS AS
LAST REVISED.

Revised 1-29-03

MATERIALS OF CONSTRUCTION

DATE 2/23/87

VAL-MATIC[®]

VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-15A-M