Retainable Interactive Computation: Operational Semantics, Algebraic Effects, and Crash-Consistent Recovery in the Agentic Lambda Abstraction Network (ALAN)

ALAN Research Monograph

October 2026

Abstract

Contemporary frameworks for autonomous and language-model-driven agents are overwhelmingly engineered as ad hoc orchestration libraries: they embed control flow inside opaque host-language closures, conflate probabilistic model completions with authoritative state transitions, and rely on the incidental survival of an operating-system process to carry residual computation forward. When a process fails mid-execution, or when a higher-order coordinator must supervise, bound, retry, or cancel a subordinate agent, the computation itself possesses no independent mathematical existence.

This monograph develops the theoretical foundations of **ALAN (Agentic Lambda Abstraction Network)**, a programming-language and computation-model architecture whose central thesis is that *agentic computation must be a first-class, retainable mathematical object*. Rather than treating agents as black-box callbacks connected by workflow arrows, ALAN formulates an agent as a version-bound, finite-step interactive transition system whose residual control, typed environment, correlation obligations, and pending effect intents are explicitly reified as serializable projections.

We situate ALAN at the intersection of five classical traditions in theoretical computer science and distributed systems: (I) Church, Turing, and Felleisen's theory of computability versus *macro-expressiveness* [4, 15, 5]; (II) Plotkin and Turi's *structural* and *mathematical operational semantics* [11, 14]; (III) Milner, Hewitt, and Agha's calculi of *mobile processes and actor configurations* [6, 8, 1]; (IV) Moggi, Plotkin, Pretnar, and Xia et al.'s *algebraic effects and coinductive Interaction Trees* [10, 12, 16]; and (V) Schneider, Lamport, and Chandy's theory of *fault-tolerant state machines, causal ordering, and consistent cuts* [7, 3, 13].

Synthesizing these five pillars, we present four groups of definitions, arguments and implementation evidence, with general congruence and dependent recovery simulations retained as open obligations: (1) the relative macro-expressiveness of supervision, coordination, and bounded snapshot-cursor iteration (Λ_{ALAN}); (2) a syntactic bimorphism lowering high-level interactions into standard Interaction Trees over a split-phase signature $E_{\mathrm{split}} = \mathsf{Emit} \uplus \mathsf{Receive}$, paired with a novel *Split-Phase Journaled Handler Algebra* ($\mathcal{H}_{\mathrm{journal}}$) whose per-intent state evolves monotonically over a four-stage consistent epistemic poset $\mathbb{O}_{\mathrm{eff}}^{\mathrm{cons}} = \{\bot_{\mathrm{unauth}}, \mathsf{Suppressed}(r), \mathsf{Unknown}, \mathsf{Known}(v)\}$ completed by an improper fault element $\top_{\mathrm{conflict}}$ into a five-kind bounded lattice $\widehat{\mathbb{O}}_{\mathrm{eff}}$; (3) the orthogonality of provenance, communication, and lifecycle authority graphs ($\mathcal{G}_{\mathrm{prov}} \perp \mathcal{G}_{\mathrm{comm}} \perp \mathcal{G}_{\mathrm{life}}$) and a proposed, unproved general congruence claim for budget-indexed, interface-scoped failure/divergence bisimulation ($\approx^{\Delta}_{I,\mathcal{B}}$) preserving dual mailbox-admission and continuation-consumption refusals; and (4) an FLP-style impossibility theorem for unconditional crash bisimulation across unreconciled non-idempotent in-flight effects, leading to the *Two-Regime Fundamental Theorem of Durable Interactive Recovery*, which separates retained-state and conservative-uncertainty safety from proposed symmetric and directed future simulations. Peer interference, resource/closure stability, endpoint coupling and scheduling require additional arguments; retry expenditure and external effects cannot be hidden to restore equivalence.

Contents

1 Introduction: The Ontological Crisis of Agentic Computation **3**
- 1.1 Orchestration Frameworks versus Models of Computation . . . 3
- 1.2 Durable Workflows versus Durable Computation . . . 3
- 1.3 Distinguishing Engineering Synthesis from Mathematical Contributions . . . 4

2 Pillar I: Computational Universality, Bounded Realizability, and Felleisen Expressiveness **5**
- 2.1 Beyond the Turing Tarpit . . . 5
- 2.2 Macro-Eliminability of Supervision and the Phase 1C Falsification . . . 6
- 2.3 Bounded Data-Dependent Iteration and Snapshot Cursors (Phase 1G) . . . 6

3 Pillar II: Structural and Mathematical Operational Semantics **8**
- 3.1 Small-Step Operational Semantics of Pure Local Reduction (δ_v) . . . 8
- 3.2 Global Transition Rules at the Runtime Boundary . . . 9

4 Pillar III: Dynamic Concurrency, Orthogonal Authority, and Compositional Congruence **9**
- 4.1 The Four-Tier Identity Hierarchy and Orthogonal Authority Graphs . . . 9
- 4.2 Two-Tier Injective Identity Algebra . . . 10
- 4.3 Bounded Template Invocations and Conditional Congruence . . . 10

5 Pillar IV: Algebraic Effects, Split-Phase Operational Handlers, and the Epistemic Effect Lattice **17**
- 5.1 Split-Phase ITree Lowering versus the Asynchronous Handler Algebra . . . 17
- 5.2 Separating Probabilistic Intelligence from Deterministic Execution . . . 18

6 Pillar V: Crash-Consistent Operational Semantics and the Two-Regime Fundamental Theorem **18**
- 6.1 Two-Tier Configurations, the Recovery Operator, and the Window-W_3 Impossibility Theorem . . . 18
- 6.2 The Two-Regime Fundamental Theorem of Durable Computation . . . 19

7 Conclusion **20**

1 Introduction: The Ontological Crisis of Agentic Computation

1.1 Orchestration Frameworks versus Models of Computation

The rapid proliferation of large language models (LLMs) has catalyzed an industry of software frameworks purporting to build "autonomous agents." Viewed through the lens of programming-language theory, however, nearly all contemporary agent frameworks are variations on a single, fragile idiom: *imperative host-language orchestration*. In such systems, an "agent" is a Python, TypeScript, or Go closure that loops over a mutable prompt buffer, invokes an external HTTP endpoint to sample tokens from a probabilistic model, parses tool-call strings from the completion, and executes arbitrary host callbacks in-place.

This architecture suffers from a foundational ontological confusion by conflating three layers that must be kept mathematically distinct:

1. **Probabilistic Epistemic Proposals:** A language model completion is not a computation step; it is an untrusted, nondeterministic external observation sampled from a stochastic oracle.

2. **Deterministic Residual Control:** The logic that validates an observation against a schema, updates local state, enforces budget ceilings, and selects the next branch of work is a pure, finite state transition.

3. **Authoritative World Transitions:** Admitting a message to a peer's inbox, mutating an external database, or incrementing the execution generation of a failed child computation are irreversible distributed commitments subject to partial failure, message reordering, and process death.

When a conventional agent framework embeds all three layers inside the call stack of a live OS process, the *continuation* of the agent—what remains to be done, which obligations are outstanding, and what authority the agent holds—is implicitly encoded in ephemeral instruction pointers, heap pointers, and open TCP sockets. If the executor process receives `SIGKILL` after dispatching an external tool request but before recording its receipt, the residual computation vanishes.

1.2 Durable Workflows versus Durable Computation

Even industrial "durable execution" engines (such as Temporal) address process crashes via event-sourced replay of host-language coroutines rather than reifying the computation itself. A decisive gulf separates *durable workflow bookkeeping* from *durable computation*:

- **First-Class Projections vs. Opaque Coroutines:** Workflow engines treat the program as an opaque host closure whose state is invisible except by re-executing host code from step 0. ALAN represents every computation as an explicit, version-bound instruction array P_v and serializable projection $\sigma = \langle pc, \rho, status, \kappa \rangle$.

- **Ordinary Supervision vs. Privileged Runtime Strata:** In workflow and actor engines, supervision and retry policies are privileged runtime mechanisms. In ALAN, a supervisor or coordinator is an ordinary program in the same calculus that consumes typed terminal observations and emits lifecycle intents through the same interpreter (`executor.Reduce`).

- **Split-Phase Effect Authority:** Rather than collapsing external activities into `Started/Completed`, ALAN factors every interaction across five distinct commit boundaries (Prepare → Commit → Authorize → Apply → Settle) with explicit epistemic outcomes (Suppressed vs. Unknown).

Foundational Work	Fundamental Contribution	Connection to ALAN
Church (1936) [4]; Turing (1936) [15]	λ-calculus and universal mechanical computation	Small, universal compositional core without privileged agent classes
Felleisen (1991) [5]	Rigorous distinction between computability and macro-expressiveness	Proving supervision is derived while typed outcome admission is essential
Plotkin (1981) [11]	Structural Operational Semantics (SOS)	ALAN's finite interpreter (`Reduce`) and global ledger transition rules
Turi & Plotkin (1997) [14]	Mathematical operational semantics & bialgebraic congruence	Compositional equivalence for nested agent networks
Milner, Parrow & Walker (1992) [8]; Hewitt (1973) [6]	Mobile processes (π-calculus) and actor configurations	Dynamic template invocation (`compose`), capability scoping, and identity
Moggi (1991) [10]; Plotkin & Pretnar (2009/2013) [12]	Computational monads and algebraic effect handlers	Separating pure reduction from durable intents and runtime adapter execution
Xia et al. (2020) [16]	Coinductive Interaction Trees (ITree)	Mathematical analogue to ALAN's retained interactive computations
Lamport (1978) [7]; Chandy & Lamport (1985) [3]	Causal happens-before ordering and consistent global cuts	Per-run observation serialization, generation routing, and replay cuts
Schneider (1990) [13]	Fault-tolerant deterministic state machines	Journaled replay and crash recovery extended to external uncertainty

Table 1: The intellectual lineage of ALAN across programming languages and distributed systems.

1.3 Distinguishing Engineering Synthesis from Mathematical Contributions

To situate this work precisely for a programming-languages audience, we distinguish what ALAN synthesizes from existing literature from where existing formalisms break down:

1. **Engineering Synthesis of Known Theory:** Representing local step execution (`Reduce`) as a deterministic transition function δ_v instantiates Plotkin's SOS [11]; lowering synchronous requests $\mathsf{Vis}(e, k)$ into split-phase Emit and $\mathsf{Receive}$ instructions is a standard free-monad homomorphism $\mathcal{S} : \mathsf{ITree}_{E,R} \to \mathsf{ITree}_{E_{\text{split}},R}$ [16]; and re-evaluating history rows under monotonically increasing epoch numbers $e \mapsto e + 1$ synthesizes Schneider's state-machine replay [13] and Burrows's fencing tokens [2].

2. **Specific Mathematical Contributions of This Work:**

   - *The Split-Phase Journaled Handler Algebra ($\mathcal{H}_{journal}$) and Consistent Epistemic Poset ($\mathbb{O}_{eff}^{cons}$):* Standard ITree interpretation (`interp`) applies a monadic handler $h : E_{\text{split}} \rightsquigarrow \mathsf{StateT}(\mathcal{D}, M)$ atomically inside the evaluation thread, which cannot model an effect in flight across a process crash or concurrent `CancelRun`. We formulate the asynchronous handler protocol over the four-stage consistent epistemic poset $\mathbb{O}_{\text{eff}}^{\text{cons}}$ completed by $\top_{\text{conflict}}$ into $\widehat{\mathbb{O}}_{\text{eff}}$ (where $\mathsf{Suppressed}(r)$ and $\mathsf{Known}(v)$ are strictly incomparable consistent elements whose join is $\top_{\text{conflict}}$) and prove the Cancellation–Authorization Dichotomy (Theorem 5.1).
   - *Relative Macro-Expressiveness of Supervision:* Using Felleisen's $\preceq_{\text{macro}}$ [5], we prove

both positive macro-eliminability of supervision and its exact negative boundary when typed terminal inbox admission is omitted (Theorem 2.3).

- *Inductive Congruence under Dual Refusals and Shared External Effects:* We show why standard weak bisimulation fails under hiding in the presence of asynchronous mailbox admission vs. synchronous continuation consumption, shared external endpoints $\mathcal{W}_\ell$, and shared root conservation envelopes $\mathcal{B}(r)$, and formulate an open conditional-congruence claim over $\mathcal{C}_{\mathrm{adm}}$ (Theorem 4.5), with interference, invocation and scheduler obligations still to be discharged.
- *Impossibility of Unconditional Crash Bisimulation and the Two-Regime Recovery Theorem:* We prove that no deterministic recovery operator without out-of-band world introspection can achieve symmetric forward bisimulation across an unreconciled non-idempotent Window-W_3 crash while guaranteeing at-most-once world mutation (Proposition 6.1), and distinguish conservative recovery safety from the stronger symmetric and directed simulation obligations (Theorem 6.2). The general peer/interference and reconciliation arguments remain open.

2 Pillar I: Computational Universality, Bounded Realizability, and Felleisen Expressiveness

2.1 Beyond the Turing Tarpit

Church [4], Turing [15], and Minsky's Theorem Ia [9] establish that two unbounded integer registers with increment-and-jump and decrement-and-branch-on-zero suffice to compute any partial recursive function. In an open, durable agent system, however, appealing to Turing completeness obscures two critical realities:

1. **Bounded Realizability:** Practical durable deployments enforce explicit resource ceilings $\mathcal{L} = (\mathit{MaxProgramBytes}, \mathit{MaxDataBytes}, \mathit{MaxObservationBytes}, \mathit{MaxOutputBytes})$ (each 1 MiB by default in `internal/executor/program.go`) and checked 64-bit integer arithmetic (`int64` overflow trapping to `ErrLimit`). Unbounded host callbacks violate finite-step scheduling.

2. **Computability vs. Macro-Expressiveness:** Following Felleisen [5], whole-program simulation via Gödel numbering is vacuous for language design because it destroys concurrency, local state isolation, and observational equivalence in contexts.

Definition 2.1 (Contextual Equivalence and Macro-Eliminability, after Felleisen [5])**.** Let $\mathcal{L} = (\mathsf{Syn}_{\mathcal{L}}, \mathsf{Conf}_{\mathcal{L}}, \longrightarrow_{\mathcal{L}}, \mathsf{Obs}_{\mathcal{L}})$ be an interactive calculus. Two terms $P, Q \in \mathsf{Syn}_{\mathcal{L}}$ are *contextually equivalent*, written $P \simeq_{\mathcal{L}} Q$, if $\mathsf{Obs}_{\mathcal{L}}(C[P]) = \mathsf{Obs}_{\mathcal{L}}(C[Q])$ for every closing context $C[\cdot]$. An extension $\mathcal{L}^+ = \mathcal{L} \cup \{F(\cdot_1, \ldots, \cdot_k)\}$ is *macro-expressible* in $\mathcal{L}$ ($\mathcal{L}^+ \preceq_{\mathrm{macro}} \mathcal{L}$) if there exists a homomorphic translation $\mathcal{T} : \mathsf{Syn}_{\mathcal{L}^+} \to \mathsf{Syn}_{\mathcal{L}}$ fixing $\mathcal{L}$-primitives such that $\mathcal{T}(F(t_1, \ldots, t_k)) = \Phi_F[\mathcal{T}(t_1), \ldots, \mathcal{T}(t_k)]$ for a fixed $\mathcal{L}$-context Φ_F and $\mathsf{Obs}_{\mathcal{L}^+}(P) = \mathsf{Obs}_{\mathcal{L}}(\mathcal{T}(P))$ for all closed P.

Theorem 2.2 (Inexpressibility of `Conditional` in Trace-Fixed Total `OneShot` Calculi)**.** *Let $\mathcal{L}_{\mathit{fixed}}$ be generated by atomic `OneShot` leaves L_i and sequential composition $P; Q$, where each leaf L_i is total, terminates normally without input-dependent failure or early exit, and emits a fixed nonempty sequence of observable effect labels $\vec{\alpha}(L_i) \in \mathsf{Act}^+$ independent of input data ρ. Let $\mathcal{L}^+_{\mathit{fixed}}$ adjoin $\mathsf{Conditional}(p, A, B)$ for a non-constant predicate $p(\rho) \in \{\mathsf{true}, \mathsf{false}\}$. Then $\mathcal{L}_{\mathit{fixed}} \prec_{\mathit{macro}} \mathcal{L}^+_{\mathit{fixed}}$.*

Proof. By structural induction on $M \in \mathsf{Syn}_{\mathcal{L}_{\mathrm{fixed}}}$, totality and normal termination of every leaf L_i ensure that in $P; Q$, P always emits its complete fixed trace $\vec{u}$ and passes control to Q, which

emits its complete fixed trace $\vec{v}$, making the concatenated trace $\pi(M, \rho) = \vec{u} \cdot \vec{v}$ independent of ρ. By contrast, $\mathsf{Conditional}(p, L_{\text{left}}, L_{\text{right}})$ with $\vec{\alpha}(L_{\text{left}}) \neq \vec{\alpha}(L_{\text{right}})$ emits input-dependent traces. (When leaves instead evaluate a pure reducer δ_v that selects residual control, `Conditional` is locally macro-eliminable via `branch` and `jump`.) □

2.2 Macro-Eliminability of Supervision and the Phase 1C Falsification

These supervision statements concern the core instruction calculus. The current public author constructors expose a smaller vocabulary: Phase 1K separately tests terminal-observation access through a raw public-runtime artifact and qualifies the ordinary authoring boundary. A host-side inspection result is not automatically an observation available to a retained program.

Theorem 2.3 (Macro-Eliminability of Bounded Supervision)**.** *In ALAN's core instruction calculus $\mathcal{L}_{ALAN}$ (`set`, `add`, `branch`, `jump`, `receive`, `emit`, `end`), a bounded supervisor $\mathsf{Supervise}(a_{child}, B_{retry}, obl, P_{init}, P_{succ})$ is locally macro-expressible without any privileged supervisor opcode or runtime role dispatch, if and only if the runtime boundary admits typed terminal observations (kind = "`terminal`", prov = "`runtime-terminal`") and correlated lifecycle intents/settlements (kind = "`lifecycle`").*

Proof. The constructive macro-expansion $\Phi_{\mathsf{Supervise}}$ is given by the 15-instruction inner supervisor in `internal/executor/examples.go` (`NestedProvision`, lines 52–69):

```
pc 0: receive(kind="message", prov="ordinary-message", src=Outer, gen=1, obl="inner-start") ->
    [started]
pc 1: emit(kind="message", target=Worker, gen=Ref("expected"), obl="worker-work", payload=
    P_init)
pc 2: receive(kind="terminal", prov="runtime-terminal", src=Worker, gen=Ref("expected"), obl=
    obl) -> [outcome]
pc 3: branch(Ref("outcome") == "succeeded", target=13, otherwise=4)
pc 4: branch(Ref("outcome") == "failed", target=5, otherwise=14)
pc 5: branch(Ref("spent") == Ref("limit"), target=14, otherwise=6)
pc 6: emit(dst="pending", kind="lifecycle", target=Worker, gen=Ref("expected"), obl=obl,
          payload={"operation": "Retry", "revision": Ref("revision")},
          updates={"spent": Offset("spent", +1)})
pc 7: receive(kind="lifecycle", prov="runtime-lifecycle", src=Worker, gen=Ref("expected"),
             obl=obl, op=Ref("pending")) -> [accepted, reason, successor, disposition]
pc 8: branch(Ref("accepted") == true, target=9, otherwise=14)
pc 9: set(dst="expected", A=Ref("successor"))
pc 10: set(dst="pending", A="")
pc 11: emit(kind="message", target=Worker, gen=Ref("expected"), obl="worker-work", payload=
    P_succ)
pc 12: jump(target=2)
pc 13: end(outcome="succeeded")
pc 14: end(outcome="failed")
```

At `pc = 6`, `emit` atomically commits the `Retry` intent, stores its canonical ID into `pending`, and increments `spent` by +1. Conversely, in the initial Phase 1 model where `DeliverTerminal` updated an external ledger without inserting a typed `"terminal"` inbox observation (Phase 1C regression in `docs/foundational/05-decisions.md`), no ordinary instruction at `pc = 2` could observe child failure, proving that typed outcome admission is an essential expressive boundary. □

2.3 Bounded Data-Dependent Iteration and Snapshot Cursors (Phase 1G)

Theorem 2.4 (Laminar Cursor Conservation and Strong Termination)**.** *Let P be any program passing `validateProgram(P)` under `CollectionSemanticVersion` (`internal/executor/collections.go`), with code length $L = |P.\texttt{Code}|$, maximum loop-snapshot capacity $M = \max_c c.\texttt{MaxItems}$, where c ranges over the `Collection` schemas of `foreach`*

instructions (set $M = 0$ if there are no loops), and actual finite loop nesting depth d. The public authoring compiler additionally enforces $d \leq$ `author.MaxNesting`; the raw program validator does not impose that cap. For any valid open projection σ_0:

1. ***Snapshot Invariance:*** *Mutations to ρ[`items`] inside a loop body leave the active cursor's cloned $\kappa[pc_{start}]$.Snapshot invariant.*

2. ***Cursor Well-Bracketedness:*** *At every reachable open projection σ, $\kappa[pc_{start}]$ exists iff $pc_{start} < \sigma.pc < P$.`Code`$[pc_{start}]$.`Otherwise`. Executing* ***`end`*** *clears all cursors, even when its program counter remains inside a loop interval.*

3. ***Strong Termination Bound:*** *Every sequence of successful local reductions has length at most $L \cdot (M+2)^d$. A maximal sequence ends with terminal status, a blocked `receive`, or a rejected reduction. Excluding rejection additionally requires that all executed operands, schemas, resource checks, and successor program counters are valid; `validateProgram(P)` alone does not establish this assumption. The bound counts successful instruction reductions, not unsuccessful receive polling or elapsed external waiting.*

Proof. (1) `foreach` stores a deep clone of the evaluated source list in its cursor. Subsequent `next` reductions read only this snapshot, clone it forward, and increment its index; body mutations to the source variable do not change it.

(2) `validateCollections` enforces laminar `foreach`–`loop` intervals, a matching `next` immediately after each header, and a matching `loop` immediately before its exit. It forbids backward `jump`/`branch` targets and entry from outside into a loop body. Thus a newly entered body has a cursor created by its `foreach`; an initially active loop has one by `validateCursors`. On an outward forward exit, `cleanCursors` deletes every exited cursor. It also clears all cursors on `end`, so the interval equivalence is asserted only for open projections.

(3) On a stretch of forward instructions, the natural-valued distance $L - \sigma.pc$ strictly decreases. The former coordinate $\sigma.pc$ had the wrong sign. Replacing it in the active-cursor tuple does not give a ranking that decreases at every instruction: `loop` jumps backward without changing any cursor index, and the following `next` increments it in a separate reduction. In the five-instruction program `foreach; next; set; loop; end`, with a one-element snapshot already bound, `set` at $2 \to 3$ increases the old tuple $(0, 2) \to (0, 3)$, while `loop` at $3 \to 1$ increases the sign-corrected tuple $(0, L-3) = (0, 2) \to (0, L-1) = (0, 4)$. Loop entry and exit also change the active tuple's dimension. We therefore use a structural instruction-count argument rather than assert a global per-step lexicographic rank.

For one activation with immutable snapshot length $n \leq M$, `next` binds at most n elements and performs at most one final exhaustion check; `loop` executes at most once per bound element. Induct on laminar loop depth: at depth zero all nonterminal steps advance the program counter, so each instruction executes at most once. At greater depth, the induction hypothesis makes each strictly nested loop activation finite; after collapsing those activations, each body pass contains only forward control flow up to the enclosing `loop` or an outward exit. Hence there are at most M body passes and $M + 1$ executions of `next` per activation. Outward branches and early `end` only shorten the traversal.

For an initially active loop, starting at `next` leaves at most $n - \mathit{Index}$ bindings. Starting inside its body requires $\mathit{Index} \geq 1$ by `validateCursors`, so the current partial pass plus the remaining passes number at most $1 + n - \mathit{Index} \leq n$. Each nested header is encountered at most once per enclosing body pass. Applying the bounds from outermost to innermost gives at most $(M + 1)^d$ executions of any fixed instruction, including exhaustion checks. Summing over the L instructions yields at most $L(M + 1)^d \leq L(M + 2)^d$ successful reductions. Failed checks and waiting without an eligible observation add none. This proves the bound without claiming successful completion or a bound on external waiting. □

Bounded adaptive application (Phase 1H). `examples/adaptive` uses the existing public authoring operations to accept seed work after initialization and derive each ordered successor frontier from the preceding round's returned outcomes. A single retained three-token `ForEach` controls at most three rounds, with at most eight application-accepted leaf items across the obligation. Each round emits its item invocations, consumes all required outcomes through their original operation handles, checks the complete candidate frontier for identity collisions and remaining capacity, and retains a one-row decision before emitting successor work. Application work IDs are distinct from runtime operation identities. The full accepted-frontier count is retained before its first item intent; runtime invocation, created-run and external-attempt charges remain separate facts.

The scalar policy maps returned observations 0/1/2 to zero/one/two ordered children, using the finite integer identity scheme in the application contract. The historical paired controlled cases used the same request and retained artifacts: changing only gamma's returned observation from 2 to 0 changed frontiers `[1,2,3] / [7,10,11] / [31]` into `[1,2,3] / [7]`. Direct and wrapped deployment use the identical adaptive artifact at maximum leaf depths 2 and 3. Additional rounds do not increase invocation depth. Request round/work limits persist under the shared root envelope of 32 accepted invocations, 64 created runs and 96 external reservations, with physical capacity 1 or 2; the fixed root run is separate provisioning cost.

Protocol success does not mean exhaustive application completion. Work- or round-limit stops return `complete=false` with the entire unperformed frontier; only exhaustion returns `complete=true`. A required unknown outcome blocks the round barrier and remains spent, even if a sibling has a known failure. Neither an unknown outcome nor an absent response is converted into observation zero or permission for replacement work. Root closure may prevent any application reply. The effectful profile directly reuses the existing two-member evidence helper, accepts questions of at most 512 UTF-8 bytes, and consumes only its returned disposition for branching; complete answers and citations remain inspectable in the original retained outcomes. It establishes no answer-quality or semantic-completeness claim.

These are bounded implementation results, not a general expressiveness or recovery proof. The source-bound Task2 report records passing controlled direct/nested and paired-result cases and byte/profile checks at manifest `fd7ab336...`; those results predate the rebase onto `56892cb...` and do not qualify the rebased source. Process recovery, unknown/closure schedules, isolated replay, independent faulty-application rejection, final suites and review are qualified separately by source-tagged records under `docs/foundational/phase1h`; only records matching the relevant source establish that source's tested status. Replay checks retained protocol consistency; the independent expected-work ledger checks whether the application follows the intended frontier policy.

3 Pillar II: Structural and Mathematical Operational Semantics

3.1 Small-Step Operational Semantics of Pure Local Reduction (δ_v)

Let $x = (a, g) \in \mathsf{RunID}$ be a logical execution identity, $n \in \mathbb{N}^+$ the next commit sequence, and $\sigma = \langle pc, \rho, status, \kappa \rangle$ an open projection ($status = \text{"}\texttt{open}\text{"}$). The pure single-step reducer δ_v (`executor.Reduce` in `internal/executor/program.go`) defines the judgment $P, x, n, \mathcal{L} \vdash \langle \sigma, o_{\text{opt}} \rangle \xrightarrow{\delta_v} \langle \sigma', \vec{\iota} \rangle$:

$$\textbf{(R-Receive)}\quad \frac{\begin{array}{c} I_{pc} = \mathsf{Receive}(\mathcal{M}, \beta) \quad o_{\text{opt}} = \mathsf{Some}(o) \quad o.Run = x \quad \|o\|_{\text{json}} \le \mathcal{L}.MaxObs \\ \langle o.Kind, o.Prov, o.Src, o.SrcGen, o.Obl, o.Op \rangle = \\ \langle \mathcal{M}.kind, \mathcal{M}.prov, [\![\mathcal{M}.e_{\text{src}}]\!]_\rho, [\![\mathcal{M}.e_{\text{gen}}]\!]_\rho, [\![\mathcal{M}.e_{\text{obl}}]\!]_\rho, [\![\mathcal{M}.e_{\text{op}}]\!]_\rho \rangle \\ \mathsf{schemaValid}_P(pc, o.Payload) \quad \rho' = \mathsf{bindPayload}(\rho, \beta, o.Payload) \end{array}}{P, x, n, \mathcal{L} \vdash \langle \sigma, \mathsf{Some}(o) \rangle \xrightarrow{\delta_v} \langle \mathsf{clean}_P(\langle pc + 1, \rho', \text{"}\texttt{open}\text{"}, \kappa \rangle), [] \rangle}$$

$$\textbf{(R-Emit)}\quad \frac{\begin{array}{c} I_{pc} = \mathsf{Emit}(dst_{\text{opt}}, \mathcal{E}, \Upsilon) \quad o_{\text{opt}} = \mathsf{None} \quad id = \texttt{json}([a, g, n, 0]) \\ \iota = \langle ID : id,\ Run : x,\ Seq : n,\ Ord : 0,\ Kind : \mathcal{E}.kind, \\ Target : [\![\mathcal{E}.e_{\text{target}}]\!]_\rho,\ Gen : [\![\mathcal{E}.e_{\text{gen}}]\!]_\rho,\ Obl : [\![\mathcal{E}.e_{\text{obl}}]\!]_\rho,\ Payload : [\![\Pi]\!]_\rho \rangle \\ \mathsf{authorIntentValid}_P(\iota) \quad \rho_1 = \rho[\forall (k \mapsto e_u) \in \Upsilon : k \mapsto [\![e_u]\!]_\rho] \\ \rho_2 = \rho_1[dst_{\text{opt}} \mapsto \mathsf{Str}(id)] \quad \|[\iota]\|_{\text{json}} \le \mathcal{L}.MaxOut \end{array}}{P, x, n, \mathcal{L} \vdash \langle \sigma, \mathsf{None} \rangle \xrightarrow{\delta_v} \langle \mathsf{clean}_P(\langle pc + 1, \rho_2, \text{"}\mathsf{open}\text{"}, \kappa \rangle), [\iota] \rangle}$$

Lemma 3.1 (Purity and Strong Determinism of δ_v)**.** *For any valid program P, run identity $x = (a, g)$, sequence $n \in \mathbb{N}^+$, limits $\mathcal{L}$, open projection σ, and optional observation o_{opt}, $\xrightarrow{\delta_v}$ is a partial function producing unique canonical JSON bytes for σ' and $\vec{\iota}$.*

3.2 Global Transition Rules at the Runtime Boundary

Embedding δ_v into a global configuration Γ yields the atomic commit and authorization transitions:

$$\textbf{(G-Commit)}\quad \frac{\begin{array}{c} p = \langle x = (a, g), e, n + 1, o_{\text{opt}}, \sigma', \vec{\iota} \rangle \in \Gamma.\mathsf{Prop} \quad \Gamma.\mathsf{Subj}[a] = \langle g_{\text{curr}}, owner, w, retired \rangle \\ g = g_{\text{curr}} \quad \neg retired \quad \Gamma.\mathsf{Runs}[x] = \langle P_v, e_{\text{curr}}, n_{\text{curr}}, \sigma \rangle \\ e = e_{\text{curr}} \quad n = n_{\text{curr}} \quad \sigma.status = \text{"}\mathsf{open}\text{"} \\ (o_{\text{opt}} = \mathsf{Some}(o) \implies o \in \Gamma.\mathsf{Obs}[x] \wedge o.consumed = \bot) \quad \neg\mathsf{scopeClosed}(\Gamma, x) \end{array}}{\Gamma \xrightarrow{\mathsf{Commit}(x, e, n+1)} \Gamma'}$$

$$\textbf{(G-Authorize)}\quad \frac{\begin{array}{c} \iota \in \Gamma.\mathsf{Int} \quad \iota.ID \notin \mathrm{dom}(\Gamma.\mathsf{Att}) \quad x = \iota.Run = (a, g) \\ \Gamma.\mathsf{Subj}[a] = \langle g_{\text{curr}}, owner, w_{\text{curr}}, retired \rangle \quad \Gamma.\mathsf{Runs}[x] = \langle P_v, e, n, \sigma \rangle \\ allowed \iff (g = g_{\text{curr}} \wedge \neg retired \wedge w_{\text{curr}} = \iota.revision \wedge \sigma.status = \text{"}\mathsf{open}\text{"} \\ \wedge \neg\mathsf{scopeClosed}(\Gamma, x) \wedge \mathsf{grant}(\Gamma.\mathsf{Perm}, \iota)) \end{array}}{\Gamma \xrightarrow{\mathsf{Authorize}(\iota.ID)} \Gamma\big[\mathsf{Att}[\iota.ID] \leftarrow \langle Allowed : allowed,\ Reason : reason \rangle\big]}$$

4 Pillar III: Dynamic Concurrency, Orthogonal Authority, and Compositional Congruence

4.1 The Four-Tier Identity Hierarchy and Orthogonal Authority Graphs

Unlike the π-calculus [8] or classical actor models [6, 1], ALAN separates identity into four tiers: (1) Retained Computation (P_v, σ); (2) Logical Subject $a \in \mathsf{Subj}$; (3) Logical Execution (Run) $x = (a, g) \in \mathsf{RunID}$; and (4) Physical Activation $(x, e) \in \mathsf{RunID} \times \mathbb{N}^+$, alongside ownership revision $w \in \mathbb{N}^+$.

Theorem 4.1 (Authority Non-Amplification and Graph Orthogonality — Invariant I3)**.** *In ALAN's operational semantics, the provenance graph $\mathcal{G}_{prov}$, communication/observation graph $\mathcal{G}_{comm}$, and lifecycle authority graph $\mathcal{G}_{life}$ are mutually orthogonal ($\mathcal{G}_{prov} \perp \mathcal{G}_{comm} \perp \mathcal{G}_{life}$): holding send or terminal-observation permissions in $\mathcal{G}_{comm}$ never enables an accepted lifecycle transition (`Retry`, `CancelRun`, `AbandonRun`, `RetireSubject`) in $\mathcal{G}_{life}$.*

4.2 Two-Tier Injective Identity Algebra

To eliminate receipt spoofing, transport domain shadowing, and cross-store operation key collisions, ALAN defines:

$$\mathsf{AdmKey}(d, \tau_{\text{raw}}) \triangleq \texttt{json}\big([\text{"}\texttt{admission}\text{"},\ d,\ \tau_{\text{raw}}]\big), \quad d \in \{\texttt{input}, \texttt{message}, \texttt{terminal}, \texttt{lifecycle}, \texttt{external}, \texttt{adapter}\}, \tag{1}$$

$$\mathsf{ExtKey}(\mathcal{N}_{256}, (a, g), n, k) \triangleq \texttt{json}\big([\text{"}\texttt{alan/external/v2}\text{"},\ \mathcal{N}_{256},\ a,\ g,\ n,\ k]\big), \quad \mathcal{N}_{256} \in \{0,1\}^{256}. \tag{2}$$

4.3 Bounded Template Invocations and Conditional Congruence

Theorem 4.2 (Root Resource Conservation and Waiting-Parent Slot Freedom)**.** *Let r be a composition root with envelope $\mathcal{B}(r) = \langle D_{\max}, I_{\max}, R_{\max}, E_{\max}, C_{phys} \rangle$ (`internal/executor/invocation.go`). Across arbitrary interleavings of local steps, template invocations, external adapter calls, root closures, and `SIGKILL` recoveries: (1) total created runs in r's tree never exceed $R_{\max}$, invocations never exceed $I_{\max}$, effect reservations never exceed $E_{\max}$, and depth never exceeds $D_{\max}$; and (2) a parent run suspended at `AwaitInvocation` occupies zero physical transport slots in C_{phys}.*

Definition 4.3 (Admissible Contexts, Dual Readiness, and Budget-Indexed Bisimulation $\approx^{\Delta}_{I,\mathcal{B}}$)**.** The grammar of admissible composition contexts $\mathcal{C}_{\text{adm}}(I_{\text{in}} \Rightarrow I_{\text{out}})$ is generated by:

$$C[\cdot] \ ::= \ [\cdot] \ \mid \ C[\cdot] \parallel_{\mathcal{I}} Q \ \mid \ Q \parallel_{\mathcal{I}} C[\cdot] \ \mid \ \mathsf{hide}\ H\ \mathsf{in}\ C[\cdot] \ \mid \ \mathsf{Invoke}_{T,r}(C[\cdot]), \qquad H \cap \mathcal{E}_{\text{ext}} = \emptyset.$$

Structural admissibility does not itself entitle a context to successful completion. Completion additionally requires contract-based accounting of prior spending, outstanding reservations, remaining candidate/peer/wrapper demand and depth at every reachable prefix. Insufficient capacity remains a valid refusal experiment.

Because mailbox admission (`AdmitMessage`/`DecideLifecycle`) is asynchronous with respect to a run's program counter while observation consumption (`Reduce` at `receive`) is synchronous with the 6-tuple guard $\mathcal{M}$, every configuration Γ exposes two refusal/readiness observables at interface I: *mailbox admission readiness* $\mathsf{AdmReady}_I(\Gamma) \subseteq \Sigma_{\text{in}}$ (which target subjects/generations are open vs. closed/retired) and *continuation consumption readiness* $\mathsf{WaitReady}_I(\Gamma) \subseteq \mathsf{Match}_I$ (which 6-tuple guards $\mathcal{M}$ are awaited by suspended `receive` instructions). External interactions are labeled by open transitions $\mathsf{extAuth}(r_{\text{root}}, g_{\text{root}}, \ell, \Pi, \Delta\mathcal{B}) \in \mathcal{E}^{\text{req}}_{\text{ext}}$ and environment-quantified responses $\mathsf{extSettle}(\iota.ID, v) \in \mathcal{E}^{\text{resp}}_{\text{ext}}$ $(\forall v \in \mathsf{Val})$.

A symmetric relation $\mathcal{R}$ is a *Budget-Indexed, Interface-Scoped Failure/Divergence Bisimulation* ($\approx^{\Delta}_{I,\mathcal{B}}$) if whenever $(\Gamma_1, \Gamma_2) \in \mathcal{R}$:

1. **Weak Transfer & Budget Preservation:** $\Gamma_1 \xrightarrow{\alpha}_H \Gamma_1'$ implies $\Gamma_2 \xRightarrow{\hat{\alpha}}_H \Gamma_2'$ with $(\Gamma_1', \Gamma_2') \in \mathcal{R}$ and equal root resource debits $\Delta\mathcal{B}(\Gamma_1 \to \Gamma_1') = \Delta\mathcal{B}(\Gamma_2 \Rightarrow \Gamma_2')$;
2. **Dual Refusal Preservation at Quiescence:** If Γ_1 is H-quiescent, $\Gamma_2 \xRightarrow{\epsilon}_H \Gamma_2'$ for an H-quiescent Γ_2' with $(\Gamma_1, \Gamma_2') \in \mathcal{R}$, $\Delta\mathcal{B} = \vec{0}$, $\mathsf{AdmReady}_I(\Gamma_1) = \mathsf{AdmReady}_I(\Gamma_2')$, and $\mathsf{WaitReady}_I(\Gamma_1) = \mathsf{WaitReady}_I(\Gamma_2')$;
3. **Divergence Sensitivity (Δ):** $\Gamma_1 \uparrow_H \iff \Gamma_2 \uparrow_H$.

Premise audit. Definition of $\approx^{\Delta}_{I,\mathcal{B}}$ requires symmetric weak transfer with equal debit on every matched step, zero-debit matching quiescence with dual readiness, and divergence sensitivity. It is stronger than schema compatibility or upper-bound contract refinement. Unequal-charge

local/helper implementations do not refute a theorem assuming it; equal final charges do not establish it. Parallel reasoning additionally needs relation stability under actual residual-budget, authority and closure interference.

Lemma 4.4 (Nonblocking Turn Structure; Confluence Obligation)**.** *For a finite workload while* `Store.Run` *continues without cancellation, operational-limit exhaustion or store error, its loop offers completion, internal delivery, external launch and ready-local-reduction opportunities. An unmatched receive does not itself hold a transport slot, and background transport does not hold the store mutex across network I/O.*

Code-level justification and limit. The ready-run scan rotates, but `selectReady` loads and scans observations; no constant-time skip or exact global turn bound is claimed. This supports nonblocking structure, not endpoint fairness or schedule equality. Local determinism and termination do not establish a diamond property for competing admissions, closure/authorization or shared endpoint updates. The former unique-quiescent-state inference is withdrawn; general confluence remains open. Interleaving semantics may preserve genuine nondeterminism.

Theorem 4.5 (Conditional Compositional Congruence; Open General Claim)**.** *The proposed implication is: for every context* $C[\cdot] \in \mathcal{C}_{adm}$, $\Gamma_A \approx^{\Delta}_{I_A,\mathcal{B}} \Gamma_{A'}$ *implies* $C[\Gamma_A] \approx^{\Delta}_{I_C,\mathcal{B}} C[\Gamma_{A'}]$*, under the originally stated hypotheses: (H1) private namespace separation, declared-port interaction and non-extrusion; (H2) root-correlated external provenance and equal matched debits; (H3) exact six-field correlation routing; (H4) nonblocking peer progress under explicit scheduling/environment assumptions; and (H5) a valid well-founded rank for relevant hidden interaction cycles.*

Status: unproved over the stated grammar. The label preserves the historical claim, not a certification. The former proof is retained in `docs/foundational/phase1i/evidence/manuscript/original-excerpts.md`. Missing arguments are:

1. **Parallel interference:** equal pre-step residual budgets do not prove that the component relation survives a peer debit, closure or authority change. Readiness, outstanding obligations and shared world-response coupling must also be preserved.
2. **Invocation:** admission/refusal, depth, member creation and charges require a separate induction case. A singleton wrapper costs one invocation, one created run and another depth; rejection creates no child/debit. It is not cost-free parallel/hiding syntax, and child/wrapper outcomes differ.
3. **Hiding/progress:** establish transfer, dual readiness and divergence for the actual hidden channels, without erasing shared charges, meaningful refusals, effects or unresolved obligations. The general loop-ranking obligation of Theorem 2.4 is not repaired here.
4. **Concrete scheduling:** abstract trace-set equality differs from a selected `Store.Run` trace. Pure steps, identity ordering and a volatile cursor lost on reopen may change the chosen interleaving. Fairness does not imply confluence or an identical contention winner.

Bounded behavioral contracts (Phase 1I). The frozen K1 contract separates schema compatibility, asymmetric local refinement and symmetric equivalence. Independently authored local and one-helper candidates preserve a request id and compute a Boolean complement, with explicit failure, missing-reply and pending modes. Five named templates (bare, sequential, parallel, hidden and one wrapper), finite payloads and residual allowances define 3,840 configurations per reference/candidate graph and 84 contract-fixed completion-entitled answer configurations. The reference $C[K1]$, local component relation and candidate products are checked separately. Artifact correspondence inspection, finite model checking, sampled runtime behavior and replay are distinct evidence categories.

Bounded negative result: root success fences a peer. An executed independent model extension reflecting `compositionScopeClosed` (`invocation.go:165--177`) exposes a missing assumption in the frozen parallel reference product. At request id 1/value 0, answer mode, invocation/run limits 3 and depth 2, a correct candidate result lets the root caller succeed before peer S admission; S is then refused with `scope_closed`. Initial completion entitlement is retained and no external `close_root` event occurs. This happens for K1 and both candidate graphs. It falsifies the frozen parallel completion premise/runtime correspondence, not an implication requiring a valid $C[K1]$ premise or the stronger exact-debit congruence premise. The source-specific boundary-extension census records all eight initially entitled parallel configurations failing and the other 76 completing in those finite graphs; the failures remain in scope. Earlier positive reference results used optimistic semantics omitting this ordinary-root-terminal guard. This is bounded model evidence; concrete runtime confirmation and final review are separately qualified.

Reference-model corrections preserve their original failures: collapsed helper/wrapper failure consumption and terminal freeze, and later premature payload visibility. Corrected graph results supersede those versions without rewriting their evidence. Preliminary source-specific checks live under `docs/foundational/phase1i/evidence/model`; they are neither a general theorem nor final runtime qualification. Weak-contract resource and equal-charge scheduling probes retain separate premises and traces. Phase1I qualification/review records govern the executed scope. Acyclic witnesses avoid the general loop-ranking obligation; pure own-state recovery does not establish effectful substitution. Replacing code beneath retained continuations is excluded.

Retained joining and report-source lifetime (Phase 1J). The separately frozen J1 experiment preserves A, B, S, the static root/peer topology, the peer's 32-step prefix, and the original resource allowances. Its root consumes the candidate outcome, retains it, and waits for a correlated ordinary report of the peer's actual S outcome before deciding either success or failure. The peer reports every known S outcome and then succeeds locally; this local status means reporting-program completion, not S success or guaranteed report delivery. An independent causal checker connects the report to the peer's original invocation handle and actually consumed observation. A valid-schema premature report can fool the trusting root while violating J1.

Within the eight original parallel answer configurations (two ids, two values, depth caps 2 or 3, invocation and created-run limits 3, zero effects), the independent finite products preserve the checked resource and root-lifetime obligations but admit a new completion counterexample for K1, A and B: S outcome consumption, report commitment, peer local Success, then first report authorization refused as `source_closed`. The report is an ordinary message, so the invocation-reply exemption does not apply; the root remains open at its required receive. Eventual service does not make a refused authorization successful. This is a bounded counterexample under the modeled local/service interleavings, not an observed failure of the unchanged `Store.Run` scheduler and not an impossibility theorem for every public join protocol.

Concrete delayed-peer samples using unchanged `Store.Run` at physical capacity one demonstrate the intended intermediate state: candidate outcome consumed, S still unadmitted, root open at its join receive. They complete with dynamic charges $A = (2, 2, 0)$, $B = (3, 3, 0)$, plus the two fixed runs, while the original C0 failure persists even with larger capacity. Four acknowledged process-kill/fresh-open samples retain the unfinished join or original committed report and complete. These sampled results and their adverse controls are separately qualified in `docs/foundational/phase1j/02-qualification.md`. They support the causal value of retaining the root in those executions; they do not establish all-schedule completion. The next exposed obligation concerns the source authority needed by required ordinary communication until authorization is retained. The general congruence, compiler and effectful-recovery obligations remain open. The structured-loop termination bound was corrected separately in

the preceding manuscript revision; J1's finite graph rank neither relies on nor replaces that structural argument.

Required communication and safe termination (Phase 1K). With frozen J1 candidate B, request id 1/value 0, answer mode, invocation/created-run limits 3, depth 2 and zero effects, a supported public driver realizes the modeled report-source race using genuine original instructions and observations. First authorization after peer termination is refused as `source_closed`; the original report receives a refused admission and the root remains pending. In the paired execution, first authorization is retained while the peer is open, the peer then terminates before admission, and the same report is admitted and consumed by the still-open root, allowing aggregate success. Both executions spend three dynamic invocations/created runs plus two fixed runs. These samples and source inspection support H-auth under an admission-open receiver, stable identities/routes/grants and valid payload: later source termination alone does not invalidate an already allowed first authorization. Consumption additionally requires eligible receiver service. Dispatch acknowledgment can record refused admission and supplies no proof of consumption.

The unchanged automatic runner is qualified separately. At the recorded fresh and preauthorization-restart boundaries, the report is the sole pending internal delivery, peer is open just after Send and root is open. The runner services one internal delivery before its next local commit, excluding the late-first-authorization ordering from that exact boundary. Both samples complete. This conditional source/record result supplies no general drain-all barrier or arbitrary-context scheduler guarantee. Three acknowledged SIGKILL/fresh-Open samples preserve the original database and identities: committed report without authorization; allowed authorization with terminal peer before admission; and refused authorization plus refused admission and dispatcher acknowledgment before retry. The allowed disposition survives reopening and source closure; reattempting the same refused authorization/delivery identities preserves the refusal and pending state. Activation renewal does not replace logical work or refund charges. These are single-host process-crash samples, not a distributed recovery theorem.

The single frozen J2 candidate has the peer wait for a correlated ordinary ACK and lets the root commit that ACK before its final decision. Its independent K1 local/helper product at request id 1/value 0 in answer mode, under the same resource limits, contains 1,408 states and 2,886 edges, with two complete maximal states and two ACK-refusal pending maximal states. The adverse order is report consumption, ACK commitment, root local Success, then first ACK authorization refused while the peer waits. Root local success is distinct from aggregate completion. This bounded model result falsifies the candidate's completion claim under the declared interleavings; no extra handshake round was added.

The exact authored J2 peer fails compilation: its received ACK handle has kind `string`, while its retained S handle has kind `request:invocation:peer`, and the required equality comparison rejects those different kinds. Both roots and the original A/B/S artifacts support partial correspondence checks, but no complete J2 peer artifact, deployment or concrete runtime trace exists. A collection conversion would change the frozen prefix and was not implemented. The failed construction and intended policy tests remain evidence, rather than being replaced by a weakened correlation check. This is a specific authoring obstruction, not a universal non-expressibility result.

Current `author.Send` exposes no retained authorization/admission result, and ordinary `Receive` does not express a terminal wait. A separate external consumer nevertheless provisions a raw `alan/1d/v1` receiver through the public runtime, delivers an authentic observation from a genuinely terminated peer along its frozen route, and verifies actual selected consumption. Thus the constructor and raw-runtime surfaces differ. If a separately qualified peer program could reach successful End only after consuming the correlated ACK, a matching authentic terminal

observation with outcome `succeeded` could supply a stable fact about that consumption; the probe alone does not establish this complete protocol. Invoking the peer would instead change topology/accounting and use invocation-outcome settlement. Exact evidence, rejected oracle histories, source identities and remaining correspondence obligations are recorded in `docs/foundational/phase1k/02-qualification.md`.

Executable substitution under invocation ownership (Phase 1L). A different context C_{inv} uses one public parent definition parameterized by the unchanged A or B candidate. It commits candidate and original S invocations before its first await, then consumes both original outcomes before any normal decision. Status and presence guard payload reads; success requires the candidate's preserved id and Boolean complement, S's original id and zero result, parent/aggregate success and resource compliance. Bound parent artifacts differ at three candidate-binding leaves and their catalogues differ; the builder, guards, result policy and allowance agree. This changes the static-peer context rather than repairing its I/J/K counterexamples. Both candidates receive invocation/created-run limits 3, depth 2 and zero effects, with one fixed parent. A spends two dynamic invocations/created runs and B spends three; this is common-envelope guarantee preservation, not exact-debit equivalence.

An independently derived finite reference checks $C_{\text{inv}}[K1]$ first, preserving K1's local/helper choices, then both replacements over four answer inputs (id in $\{1, 2\}$, value in $\{0, 1\}$). The reference/A/B products contain respectively 1,952/926/1,706 states, 4,276/2,006/3,678 edges and 8/4/4 terminal maximal states; every maximum satisfies the required guarantee, with no recorded failure or cutoff. Every edge is checked before deduplication, and an intrinsic rank under explicit eventual-service assumptions bounds strict progress; maxima count states, not all interleaving traces. Checked finite artifact correspondence and current-source local refinement support this bounded implication, not a general compiler or congruence theorem. Separately, eight automatic concrete samples at physical capacity one complete with actual original outcome consumption; selected public B executions expose both child completion orders while parent consumption remains candidate then S. Atomic runtime settlement is expanded into ordered abstract publication/delivery events, so the model's split intermediate states are not automatically real checkpoints.

Focused controls preserve truthful wrong-id failure while rejecting component conformance and the guarantee, retain actual insufficient-budget refusal, and distinguish failure, absence and pending outcomes. Preserved reference-checker and raw-validator counterexamples required correction and independent rereview; they are evidence-validation defects, not observed runtime substitution failures. One acknowledged B process-crash predicate per normal/race profile has both invocations committed, the candidate outcome consumed once, and admitted S still at its unconsumed request with no produced outcome. Actual SIGKILL and fresh-process opening of the same database complete original work without duplicate consumption or refunded spending. These are single-host samples under stable identities/grants, no cancellation, sufficient operational bounds and eventual eligible service; arbitrary context grammars, universal scheduling, general compiler correctness and effectful/distributed recovery remain open. Exact scope, identities, decisive evidence and review dispositions are in `docs/foundational/phase1l/02-qualification.md`.

Consuming order and reason policies (Phase 1M). Two further alternative parents retain one owner and the original A/B/helper/S components. Both commit candidate then S and consume S then candidate before any normal decision. C_{se} retains the strict answer policy and guarantee G_{answer}; C_{reason} classifies actual consumed status, reason and presence under G_{outcome}. After validating original S as succeeded/`member_succeeded`, present, with original id/zero, correct candidate success selects `answer`, failed/absent `member_failed` selects `candidate_failed`, and failed/absent `missing_reply` selects `candidate_missing_reply`;

other completed evidence selects defensive `invalid_outcome`. Presence guards prevent absent-payload reads. The absent child's reason stays `missing_reply` while the deliberately failing parent/root has `member_failed`. No requested-mode branch replaces observed evidence, and errors still require both joins.

The independently frozen K1-first models retain both local/helper choices. Under common invocation/created-run limits 3, depth 2, zero effects and one fixed parent, C_{se} checks four answer inputs per product (id in $\{1,2\}$, value in $\{0,1\}$): reference/A/B have 1,996/944/1,784 states, 4,376/2,046/3,842 edges and 8/4/4 terminal maxima. C_{reason} adds fail/absent/pending, sixteen configurations per product: 6,072/2,680/6,460 states, 12,880/5,414/13,636 edges, 24/12/12 terminal and 8/4/4 intended pending maxima. Every maximum satisfies its selected guarantee; the reason model's twelve answer configurations separately satisfy G_{answer}. All-mode local refinement and separate open-progress checks support replacement conformance. Every incoming edge is checked before deduplication without failure pruning or cutoff; rank and eventual eligible service qualify progress. Dynamic spending remains two or three under the same allowance, not exact-debit equivalence.

Separately, each context has eight automatic concrete answer samples at capacity one. Public S-first schedules expose both original publication orders and an open parent with S consumed while candidate work is still required, either unproduced or retained-unconsumed. Reason samples authenticate selected envelopes, actual committed classification/branch, terminal execution and the designated unmatched pending receive; pending has no candidate outcome or completed classification. A classification Set and selected decision share one committed step, expanded into two ordered abstract events; executing End occurs later. No durable cut between classification and decision follows. Truthful wrong-id and observation-versus-request controls reject component/profile conformance without rewriting evidence. Finite artifact correspondence and operational bounds supplement these single-host samples under stable identities/authority, valid bindings, no cancellation and eventual service. General congruence, arbitrary contexts, universal compiler/scheduler correctness and new effectful/distributed recovery remain open; Phase 1L's recovery retains its original scope. Exact identities, controls and review dispositions are in `docs/foundational/phase1m/02-qualification.md`.

Callable owning joins and consuming callers (Phase 1N). A new ordinary public join $J[X]$ owns the unchanged candidate and S invocations, commits candidate then S, and consumes S then candidate before normal classification. The sole fixed root O invokes J and consumes that original public outcome. J replies with a bounded record containing the original application id, classification and zero-or-one original answer records; O guards presence, correlation, cardinality and status/reason/tag consistency before committing its decision. Candidate `failed/missing_reply` becomes a present `candidate_missing_reply` diagnostic on J's deliberately failed `failed/member_failed` outcome. Candidate failure has its distinct `candidate_failed` diagnostic. Missing J reports are not diagnoses: Success without a required reply publishes `failed/missing_reply`, whereas Failure without a reply retains `failed/member_failed`; O rejects either absent response as `invalid_join_outcome`. Neither classifier substitutes requested mode for selected evidence.

The common allowance is four invocations/created runs, depth three, zero effects and one fixed root. J's prior admission costs $(1,1,0)$, leaving residual allowance three; candidate/S enter at depth two and B's original helper at three. Only accepted original S admission maps to the local environment's arbitrary-time debit. A spends $(3,3,0)$ and B $(4,4,0)$; this preserves a common envelope, not exact-debit equivalence. No outer sibling adds another interfering debit.

A reviewed restricted conditional constructor argument (ARG-1) supplies $J[X] \preceq J[K1]$ for candidates in the declared e/helper event semantics, given a relation preserving original identity/protocol/outcome, source closure, ledger, depth and future-demand facts; matching single events or public-field-preserving private stutters; bilateral environment/caller readiness; equal

authorization sidecars; and separate all-mode progress/nondivergence. A weak matching-path variant additionally requires stable intermediate guards and no nonmatching protocol events. The public environment supplies stable bindings/authority, an open eligible caller, sufficient finite limits, no cancellation/retirement or pending release, and eventual eligible service. The independent $J[K1] \models K_{\text{join}}$ premise then gives contract preservation; adding fixed O control yields G_{outer}. This is a source-level conditional argument, not a machine-checked generic theorem. At Phase 1N's close, ARG-2 remained open: arbitrary weak refinement of unchanged K1 had no proved normalization/extension to the stronger intermediate-guard, caller-readiness and authorization-sidecar premises. Neither the original exact-debit definition nor the open general congruence claim changes.

The independently frozen K1-first reference and A/B products cover sixteen inputs each (id in $\{1, 2\}$, value in $\{0, 1\}$ and answer/fail/absent/pending), retaining K1's local/helper alternatives in every mode. Their respective state counts are 6,376/2,864/6,644, edge counts 13,232/5,622/13,844, terminal maxima 24/12/12 and designated pending maxima 8/4/4. All recorded property/rank failures, refusals, stuck states, cutoffs and cycles are zero. Separate aligned local relations and open-progress checks support the finite lifted A/B instances of ARG-1; they do not prove ARG-2. K_{join} and G_{outer} project the same products, not two independent censuses. Pending maxima retain the actual unmatched candidate receive, completed original S consumption, open J awaiting e and open O awaiting J, without a diagnostic or terminal publication. Every incoming edge is checked before deduplication; zero successors establish finite maximality. Finite artifact/guard correspondence and operational bounds are separate evidence.

Concrete normal/race profiles each include eight automatic answer samples, six representative A/B fail/absent/pending samples, one supported late-reply execution and four genuine controls at physical capacity one. In the supported B/absent execution, J commits its diagnostic Send, executes Failure, and only then obtains its first reply authorization and admission; its original failed outcome retains the diagnostic, which O actually selects before committing the matching failure. The permitted closed-source exception is the original entry-member reply bound to the actual caller/generation/obligation with unchanged revision, template and schema checks; invocation authorization receives no such exception. No host-fabricated observation or authoritative-state edit supplies this schedule. The additive raw mapping and independent audit authenticate original emitted handles, selected histories, actual instructions/cursors, report transport and outer decisions. Classification plus ghost decision share one Set commit; End/freeze and publication/delivery have explicit atomic groups, so abstract intermediate states are not automatically durable cuts.

Genuine no-report controls make O reject absent J evidence; a genuine false report passes provenance and O's faithful public policy while failing constructor truth; a deliberate-failure component under an absent request preserves truthful classification while failing K1 mode conformance. These are distinct failed premises, not conforming substitution counterexamples. Detached decoder attacks and incomplete-prefix claims are separately rejected. Shared protocol formats, historical machinery and runtime/replay dependencies limit independence; pure replay checks retained consistency. Runtime review and final manuscript qualification are tracked in `docs/foundational/phase1n/06-review.md`; exact evidence and scope are in `docs/foundational/phase1n/03-qualification.md`. Arbitrary contexts/candidates without the supplied relation, recursive tree closure, universal compiler/scheduler correctness, exact-debit equivalence and effectful/distributed recovery remain open; historical recovery retains its original predicates and source identities.

Weak refinement and original-state accounting (Phase 1O). The reviewed source argument distinguishes the stronger P_{stage} projection, which already compares original-state choice/ticket/demand stages, from P_{boundary}. Within A_{op} with fixed operational owner fram-

ing, and under the separate progress and E_N premises, the former retains its weak relation and derives the remaining ARG-1 bridge duties. For the latter, unrestricted ARG-2 remains open under both event-visible F_{event} and fact-visible F_{fact} readings. For an original candidate $X \in A_{\text{op}}$ with fixed operational owner framing, an additional $\mathsf{Account}_N(X; \alpha, \lambda)$ certificate, together with a supplied W_N^{σ} weak relation and separate $\mathsf{Progress}_N$, yields a suitable relation $R_g \subseteq \mathsf{States}(X) \times \mathsf{States}(K1)$ under E_N. The fixed maps α on original states and λ on original edges check initial tickets, faithful accounting, ordered updates, branch/mode legality and every original edge/atomic group. They do not assume reference-demand equality, ARG-1 readiness or progress. This is a sufficient representation condition; neither its necessity nor its existence for every boundary-projection candidate is established.

The preserved R1 rejection identifies the missing inference: lawful history accounts can assign possible and excluded helper demand to the same original state. Operational transfer through a history extension does not alone make demand an observation on that state. Preserving every accounted demand through a projection requires and suffices for demand to be constant on its reachable fibers; the full state-accounting record above is a stronger sufficient condition. The corrected argument does not silently add history to X's state domain. The merge is a diagnostic of the failed representation argument, not a conforming candidate counterexample, a nonexistence result or a demonstrated specification gap.

Fixed reference choices preserve current constructor/protocol guards; this differs from endpoint demand equality. Fixed owner framing and mandatory facts supply immediate caller matches, while eventual finite original S service opens J's selection gate. Given the coarse relation, compatible legal first-authorization histories admit the retained-record extension, preserving each run's own raw provenance. These derived portions do not supply E_N's stable identity/authority/bindings, open eligible callers, no closure/retirement/release, eventual eligible service or adequate operational limits. J's prior debit remains $(1, 1, 0)$ within full I=R4, and original S remains the sole q debit. Progress remains separate from safety. Full-domain W, Progress and Account, when supplied, restrict configuration-wise to the residual profile; a profile certificate does not qualify the full contract. Conditional ARG-1 lifting still requires the independent $J[K1]$ reference/product premises for K_{join} and G_{outer} preservation.

This is a source-reviewed argument, not a machine-checked theorem. Corrected finite certificate checks address only declared machinery, accounting, normalization, demand/current-guard and legal-history clauses. In the declared $F_{\text{fact}}/P_{\text{boundary}}$ fragment, both supplied weak relations pass; the premature R_w has eight endpoint-demand inequalities and normalized R_g has no named strong-clause failure. These are supplied-witness results, not whole-candidate conformance, runtime execution or existence search. The corrected argument, preserved rejection and scope boundaries are recorded in `docs/foundational/phase1o/02-arg2.md`, `docs/foundational/phase1o/03-finite-contract.md` and `docs/foundational/phase1o/05-qualification.md`. Arbitrary-context congruence, universal compiler/runtime correctness, recovery and exact-debit equivalence gain no new theorem.

5 Pillar IV: Algebraic Effects, Split-Phase Operational Handlers, and the Epistemic Effect Lattice

5.1 Split-Phase ITree Lowering versus the Asynchronous Handler Algebra

At the pure syntax and local reduction level (δ_v), factoring $\mathsf{Vis}(e : E(A), k : A \to X)$ into `emit` and `receive` is a syntactic bimorphism $\mathcal{S} : \mathsf{ITree}_{E,R} \to \mathsf{ITree}_{E_{\text{split}},R}$ over $E_{\text{split}} = \mathsf{Emit} \uplus \mathsf{Receive}$:

$$\mathcal{S}\big(\mathsf{Vis}(e,k)\big) \triangleq \mathsf{Vis}\Big(\mathsf{Emit}(e),\ \lambda id.\ \mathsf{Vis}\big(\mathsf{Receive}(id),\ \lambda a.\ \mathcal{S}(k(a))\big)\Big).$$

However, in Xia et al. [16], `interp` applies a monadic handler $h : E_{\text{split}} \rightsquigarrow \mathsf{StateT}(\mathcal{D}, M)$ synchronously inside the evaluator's thread, which cannot represent effects interrupted across the

four distributed crash windows W_1 (post-reduce, pre-commit), W_2 (post-commit, pre-authorize vs. cancel), W_3 (post-authorize, in-flight transport), and W_4 (post-receipt, pre-settlement).

ALAN's mathematical contribution in Pillar IV is therefore the *Split-Phase Journaled Handler Algebra* ($\mathcal{H}_{\text{journal}}$), which interprets each committed intent $\iota \in \mathcal{D}.\mathsf{Int}$ as an asynchronous coalgebraic protocol evolving over a four-stage *consistent epistemic poset* $(\mathbb{O}_{\text{eff}}^{\text{cons}}, \sqsubseteq_{\text{info}})$:

$$\mathbb{O}_{\text{eff}}^{\text{cons}} \triangleq \{\bot_{\text{unauth}}\} \uplus \{\mathsf{Suppressed}(r) \mid r \in \mathsf{Reason}_{\text{deny}}\} \uplus \{\mathsf{Unknown}\} \uplus \{\mathsf{Known}(v) \mid v \in \mathsf{Val}\},$$

with covering relations $\bot_{\text{unauth}} \sqsubset_{\text{info}} \mathsf{Suppressed}(r)$ and $\bot_{\text{unauth}} \sqsubset_{\text{info}} \mathsf{Unknown} \sqsubset_{\text{info}} \mathsf{Known}(v)$. Crucially, $\mathsf{Suppressed}(r)$ and $\mathsf{Known}(v)$ are *strictly incomparable* in $\mathbb{O}_{\text{eff}}^{\text{cons}}$. Adjoining an improper top fault element $\top_{\text{conflict}}$ completes $\mathbb{O}_{\text{eff}}^{\text{cons}}$ into the five-kind bounded algebraic lattice $\widehat{\mathbb{O}}_{\text{eff}} = \mathbb{O}_{\text{eff}}^{\text{cons}} \uplus \{\top_{\text{conflict}}\}$, where $\mathsf{Suppressed}(r) \sqcup \mathsf{Known}(v) = \top_{\text{conflict}}$ (`corrupt("receipt without authorization")` at `external.go:496`) and $\mathsf{Known}(v_1) \sqcup \mathsf{Known}(v_2) = \top_{\text{conflict}}$ for $v_1 \neq v_2$ (`ErrConflict` at `external.go:322`).

Theorem 5.1 (The Cancellation–Authorization Dichotomy)**.** *For any committed intent $\iota \in \Gamma.\mathsf{Int}$ of run $x = (a, g)$ and concurrent closure $c \in \{\mathsf{CancelRun}(a, g, w), \mathsf{RetireSubject}(a, w)\}$:*

1. *If $c \prec \mathsf{Authorize}(\iota)$ in the store's serialization order, ι transitions to the maximal consistent state $\mathsf{Suppressed}(\texttt{source_closed})$ and non-execution of ι in $\mathcal{W}$ is guaranteed under trusted dispatch.*

2. *If $\mathsf{Authorize}(\iota) \prec c$, ι transitions to $\mathsf{Unknown}$ (refinable to $\mathsf{Known}(v)$ upon late receipt arrival from the pre-cancellation attempt), and no new mutating attempt for ι may ever be launched after c, even with an idempotency key.*

5.2 Separating Probabilistic Intelligence from Deterministic Execution

In `examples/evidence/evidence.go` and `examples/investigation/investigation.go`, LLM invocations (`evidence-model`) are compiled into split-phase `author.Request` and `author.Await` steps surrounded by pure deterministic guards: budget enforcement (`model_spent < model_limit`), tool-name verification (`plan_tool == "lookup"`), deterministic span-exclusion copying across revision rounds, and byte-exact citation provenance verification across `document`, `version`, `snippet`, `start`, and `end`.

6 Pillar V: Crash-Consistent Operational Semantics and the Two-Regime Fundamental Theorem

6.1 Two-Tier Configurations, the Recovery Operator, and the Window-W_3 Impossibility Theorem

We decompose a single-host ALAN configuration into $\Gamma = \langle \mathcal{D}, \mathcal{V}, \mathcal{W} \rangle$, where $\mathcal{D}$ is the durable SQLite WAL/FULL store, $\mathcal{V}$ is the volatile activation state, and $\mathcal{W}$ is the external world state. Let $\mathsf{Commit}(\langle \mathcal{D}, \mathcal{V}, \mathcal{W} \rangle) = \langle \mathcal{D}, \emptyset_{\mathcal{V}}, \mathcal{W} \rangle$ and $\mathsf{Crash}(\Gamma) \ni \langle \mathcal{D}, \emptyset_{\mathcal{V}}, \mathcal{W}' \rangle$. Upon recovery, $\mathsf{Recover}$ validates ledger integrity and increments activation epochs $e \mapsto e + 1$ for open runs. When an authorized non-idempotent external attempt or adapter attempt has no recorded receipt ($\iota \in \mathsf{Unresolved}_{\text{non-idem}}(\mathcal{D})$), ALAN *neither re-transmits the request nor fabricates a synthetic inbox observation* (`"unknown outcome has no result"` at `adapters.go:314`); instead, the waiting run remains quiescently suspended at `receive` while $\iota.ID$ is surfaced in `RunReport.UnknownExternal` / `UnknownAdapters` (`external_test.go:175--226`).

Proposition 6.1 (Impossibility of Unconditional Symmetric Crash Bisimulation in Non-Idempotent Window W_3)**.** *Let $\iota \in \mathsf{Unresolved}_{non\text{-}idem}(\mathcal{D})$ be an authorized in-flight intent in Window*

W_3 targeting a non-idempotent endpoint $\mathcal{W}_\ell^{non\text{-}idem}$ without an out-of-band read-only receipt-lookup channel, and let $k(v)$ be a continuation whose observable output depends on v. No deterministic recovery operator $\mathsf{Recover}(\langle \mathcal{D}, \emptyset_{\mathcal{V}}, \mathcal{W}' \rangle)$ *can simultaneously guarantee (1) At-Most-Once World Safety (*$\#\mathsf{Apply}_\ell \leq 1$ *across* $\mathcal{W}' \in \{\mathcal{W}, \mathsf{apply}(\mathcal{W}, \alpha)\}$*) and (2) Unconditional Symmetric Forward Bisimulation with the uninterrupted execution where the live socket in $\mathcal{V}$ delivers v to $k(v)$.*

Proof. Because $\mathcal{D}$ is identical whether the request dropped before reaching $\mathcal{W}_\ell$ ($\mathcal{W}' = \mathcal{W}$) or mutated $\mathcal{W}_\ell$ just before the response socket died ($\mathcal{W}' = \mathsf{apply}(\mathcal{W}, \alpha)$), re-dispatching α violates (1) in the latter case ($\#\mathsf{Apply}_\ell = 2$), whereas withholding re-dispatch leaves k without v, violating (2) in the realization where the live socket returned v. □

6.2 The Two-Regime Fundamental Theorem of Durable Computation

Let $\approx_{\text{obs}}$ require logical store identity modulo activation epochs and symmetric future $\approx^{\Delta}_{I,\mathcal{B}}$ behavior. Identity and epoch-independent local reduction are necessary evidence, not an automatic proof: shared resource/closure interference, admissible response coupling and concrete scheduling remain obligations even with no unknown non-idempotent attempt.

Directed epistemic prefix/safety simulation $\preccurlyeq_{\text{ep}}$ requires historical identity at a matched committed cut and conservative information, no automatic retransmission of an unknown non-idempotent attempt, and explicit peer/reconciliation obligations. A peer's lack of an await dependency is insufficient for symmetric comparison: resource, authority, closure and shared-world interference must be absent or accounted for by a stable relation. While no later logical closure intervenes, affected runs await authentic evidence with the original unknown handle and reservation; no value is fabricated. Late evidence may advance $\mathsf{Unknown}$ to $\mathsf{Known}(v)$, but rejoining $\approx_{\text{obs}}$ also requires matched continuations, world, authority and residual resources. Closure may prevent consumption without invalidating retained evidence. Conservative safety alone does not establish the full simulation.

The supervisory public-output reconvergence condition (Markdown Definition 6.5) is application-specific, not a separately checkable substitution proof. Retry debits and root-correlated external actions remain visible. Hiding a private generation or `spent` register cannot supply exact-debit equivalence; "modulo retry debit" would need a separately defined observation relation and is not claimed here.

Theorem 6.2 (Two-Regime Durable Computation; Qualified Claim and Open Simulation Obligations)**.** *For a reachable configuration under a fixed semantic version:*

1. ***Part I (Historical Replay Completeness and Zero-Effect Soundness):*** *read-only* `Replay` *reconstructs historical projections and intents without dispatching effects or mutating the retained store.*

2. ***Part II (Proposed Symmetric Future Relation):*** *when* $\mathsf{Unresolved}_{non\text{-}idem}(\mathcal{D}) = \emptyset$*, recovery preserves the retained logical cut subject to the version/epoch protocol. The stronger* $\text{Recover}(\Gamma_{crash}) \approx_{\text{obs}} \mathsf{Commit}(\Gamma)$ *remains a proof obligation under matched admissible responses, authorized endpoint reconciliation, interference-stable resource/closure relations and an explicit schedule interpretation. Idempotence or receipt availability alone does not establish it.*

3. ***Part III (Conservative Unknown Safety and Proposed Directed Simulation):*** *recovery of an authorized non-idempotent/adapter attempt without a result retains its original uncertainty and spent reservation, fabricates no observation and does not automatically retransmit it. Full* $\text{Recover}(\Gamma_{crash}) \preccurlyeq_{\text{ep}} \Gamma$ *additionally requires the peer/reconciliation obligations above. No outer exact-debit bisimulation after retry follows from hiding; expenditure, effects and authority/generation observations must be accounted for.*

Replay argument and recovery limits. Part I's historical induction uses determinism of the reducer, immutable programs/observations and the read-only replay guard. For Part II, retaining projections/handles/charges and changing activation authority yields the same local successor only for the same selected observation and valid authority. Volatile ready-run position and in-flight workers are not retained semantic state. Idempotent retransmission requires current authorization and the endpoint contract; prior source authorization does not bypass final reservation/closure checks. Selected pure process cuts do not prove the general simulation.

For Part III, unknown-attempt eligibility and settlement rules support no-repeat/no-fabrication safety. Lemma 4.4 permits enabled peers to progress despite an unmatched receive, not identical peer histories under shared competition. Surviving live late transport and fresh-process unknown recovery are distinct environments. Neither late evidence nor abandonment/retry restores exact-debit equivalence merely by hiding. The general peer/reconciliation/retry simulation argument remains open.

Under an endpoint contract that deduplicates identical immutable keys and parameters, execution-scoped keys support at-most-once logical mutation within a generation across permitted physical retries. This endpoint-dependent safety fact is separate from the open future-simulation claim and does not authorize retransmission after closure.

Theorem 6.3 (Impossibility of Blind Cross-Generation Business Deduplication)**.** *Across a supervisor-initiated* `Retry` *from* $x_1 = (a, g)$ *to* $x_2 = (a, g+1)$*, the execution-scoped external keys* $\mathsf{ExtKey}(\mathcal{N}_{256}, (a, g), n, 0) \neq \mathsf{ExtKey}(\mathcal{N}_{256}, (a, g+1), n, 0)$ *are distinct. Consequently, computation recovery and outbox idempotence cannot prevent duplicate external mutation across generations unless the application threads a generation-invariant business key or reconciles* Unknown *prior to retry (witnessed by* `business:order-7` *in Phase 1C).*

7 Conclusion

ALAN demonstrates that the path beyond fragile agent orchestration is neither adding more prompt wrappers nor inventing privileged workflow node types. By uniting Felleisen's expressive minimality, Plotkin and Turi's mathematical operational semantics, Milner and Hewitt's concurrent topologies, Xia et al.'s Interaction Trees, and Schneider and Lamport's fault-tolerant state machines into a single crash-consistent calculus, ALAN makes agentic computation a rigorous, retainable, and composable mathematical object.

Qualification boundary. General congruence (Theorem 4.5) and dependent recovery simulation (Theorem 6.2) retain explicit proof obligations. Phase 1I checks bounded contract-relative guarantees, not equivalence of all conforming agents. Shared retry expenditure and external effects remain observable. The general loop-ranking argument and whole-dissertation formalization remain separate work; the bounded witnesses do not repair them.

References

[1] Gul Agha, Ian A. Mason, Scott Smith, and Carolyn Talcott. A foundation for actor computation. *Journal of Functional Programming*, 7(1):1–72, 1997.

[2] Mike Burrows. The Chubby lock service for loosely-coupled distributed systems. In *Proceedings of the 7th USENIX Symposium on Operating Systems Design and Implementation (OSDI '06)*, pages 335–350, 2006.

[3] K. Mani Chandy and Leslie Lamport. Distributed snapshots: Determining global states of distributed systems. *ACM Transactions on Computer Systems (TOCS)*, 3(1):63–75, 1985.

[4] Alonzo Church. An unsolvable problem of elementary number theory. *American Journal of Mathematics*, 58(2):345–363, 1936.

[5] Matthias Felleisen. On the expressive power of programming languages. *Science of Computer Programming*, 17(1–3):35–75, 1991.

[6] Carl Hewitt, Peter Bishop, and Richard Steiger. A universal modular ACTOR formalism for artificial intelligence. In *Proceedings of the 3rd International Joint Conference on Artificial Intelligence (IJCAI '73)*, pages 235–245, 1973.

[7] Leslie Lamport. Time, clocks, and the ordering of events in a distributed system. *Communications of the ACM*, 21(7):558–565, 1978.

[8] Robin Milner, Joachim Parrow, and David Walker. A calculus of mobile processes, I and II. *Information and Computation*, 100(1):1–77, 1992.

[9] Marvin L. Minsky. Recursive unsolvability of Post's problem of "Tag" and other topics in theory of Turing machines. *Annals of Mathematics*, 74(3):437–455, 1961.

[10] Eugenio Moggi. Notions of computation and monads. *Information and Computation*, 93(1):55–92, 1991.

[11] Gordon D. Plotkin. A structural approach to operational semantics. *Journal of Logic and Algebraic Programming*, 60–61:17–139, 2004. Originally published as Technical Report DAIMI FN-19, Aarhus University, 1981.

[12] Gordon D. Plotkin and Matija Pretnar. Handling algebraic effects. *Logical Methods in Computer Science*, 9(4:23):1–36, 2013. Conference version in ESOP 2009, LNCS 5502, pp. 80–94.

[13] Fred B. Schneider. Implementing fault-tolerant services using the state machine approach: A tutorial. *ACM Computing Surveys*, 22(4):299–319, 1990.

[14] Daniele Turi and Gordon D. Plotkin. Towards a mathematical operational semantics. In *Proceedings of the 12th Annual IEEE Symposium on Logic in Computer Science (LICS '97)*, pages 280–291, 1997.

[15] Alan M. Turing. On computable numbers, with an application to the Entscheidungsproblem. *Proceedings of the London Mathematical Society*, 42(1):230–265, 1936.

[16] Li-yao Xia, Yannick Zakowski, Paul He, Chung-Kil Hur, Gregory Malecha, Benjamin C. Pierce, and Steve Zdancewic. Interaction trees: Representing recursive and impure programs in Coq. *Proceedings of the ACM on Programming Languages*, 4(POPL):1–32, 2020.