## JakeMate14

## Contents

L	Estructuras de Datos  1.1 Segment tree	1
2	Graphs	2
3	Math	2
1	Geometry	2
5	Strings	2
3	Flow	2
7	Other	2

## 1 Estructuras de Datos

## 1.1 Segment tree

```
1 struct segtree {
       int size;
       vector<ll> vv;
       void build(vector<int> &nums) {
           size = 1;
           while (size < nums.size()) size *= 2;</pre>
           vv.assign(2 * size, 0);
           build(nums, 0, 0, size);
       }
10
11
       void build(vector<int> &nums, int x, int lx, int rx) {
12
           if (rx - 1x == 1) {
13
               if (lx < nums.size()) {</pre>
14
                    vv[x] = nums[lx];
16
           } else {
17
               int m = (lx + rx) / 2;
18
               build(nums, 2 * x + 1, lx, m);
19
               build(nums, 2 * x + 2, m, rx);
20
               vv[x] = vv[2 * x + 1] + vv[2 * x + 2];
21
           }
22
       }
23
24
       void set(int i, int v) {
25
           set(i, v, 0, 0, size);
26
       }
27
28
       void set(int i, int v, int x, int lx, int rx) {
29
           if (rx - lx == 1) {
30
               vv[x] = v;
31
           } else {
32
               int m = (lx + rx) / 2;
33
               if (i < m) {
34
                    set(i, v, 2*x+1, lx, m);
35
               } else {
36
                    set(i, v, 2*x+2, m, rx);
37
38
39
                vv[x] = vv[2*x+1] + vv[2*x+2];
```

```
40
       }
41
^{42}
       11 sum(int 1, int r) {
43
           return sum(1, r, 0, 0, size);
44
       }
45
46
       11 sum(int 1, int r, int x, int lx, int rx) {
47
            if (r <= lx) return 0;</pre>
48
            if (1 \ge rx) return 0;
49
            if (lx \ge l \&\& rx \le r) return vv[x];
50
            int m = (lx + rx) / 2;
51
           11 s1 = sum(1, r, 2*x+1, lx, m);
52
           11 s2 = sum(1, r, 2*x+2, m, rx);
53
           return s1 + s2;
54
       }
55
56 };
```

- 2 Graphs
- 3 Math
- 4 Geometry
  - 5 Strings
  - 6 Flow
  - 7 Other
- 7.1 Template

```
#include<bits/stdc++.h>

#define endl '\n'

#define IO ios::sync_with_stdio(false); cin.tie(0); cout.tie(0);

#define YES cout<<"Yes\n";

#define NO cout<<"No\n";

#define pb push_back

#define all(v) v.begin(), v.end()

#define sortall(f) sort(all(f))</pre>
```

```
#define forn(i,n) for(ll i=0;i<n;i++)</pre>
11
   const int MX = 0;
12
13
   using namespace std;
14
15
   typedef long long 11;
   void sol(){
18
19
20
   int main(){
22
       ΙO
       int t=1;//cin>>t;
23
24
        while(t--)
25
            sol();
26
27 }
```