

Descongelen a Victor Moreno

Contents

1 Estructuras de Datos	2		
1.1 Unordered Map	2	3.13 Max Matching	16
1.2 Segment tree Recursivo	2	3.14 LCA	16
1.3 Segment Tree Iterativo	2	3.15 Centroid	17
1.4 Segment Tree Lazy Recursivo	3	4 Flow	18
1.5 Segment Tree Lazy Iterativo	4	4.1 Dinics	18
1.6 Rope	5	4.2 Flow's Utilities	18
1.7 Ordered Set	5	4.3 Min cost-Max Flow	19
1.8 Union Find	5	4.4 Hungarian	20
1.9 Segment Tree Persistente	5	4.5 Edmonds-Karps	20
1.10 Sparse Table	6	5 Geometria	21
1.11 Wavelet Tree	6	5.1 Puntos y lineas	21
1.12 Trie	7	5.2 Circulos	23
1.13 Treap	7	5.3 Poligonos	24
1.14 Segment Tree Dinamico	8	6 Matematicas	26
2 Strings	8	6.1 Exponenciacion Binaria	26
2.1 Aho Corasick	8	6.2 GCD y LCD	26
2.2 Dynamic Aho Corasick	9	6.3 Euclides extendido e inverso modular	26
2.3 Hashing	10	6.4 Fibonacci	26
2.4 KMP	10	6.5 Criba de Primos	27
2.5 Manacher	11	6.6 Triangulo de Pascal	27
2.6 Suffix Automaton	11	6.7 Cambio de bases	27
3 Graph	11	6.8 Factorizacion	28
3.1 Structs for Graphs	11	7 Varios	28
3.2 Dijkstra	12	7.1 String a vector int	28
3.3 Bellman-Ford	12	7.2 Generar permutaciones	28
3.4 Floyd Warshall	13	7.3 2-Sat	28
3.5 Transitive Closure	13	7.4 Bits	29
3.6 Is bipartite?	13	7.5 Matrix	29
3.7 Topological Sort	14	7.6 Mo's Algorithm	29
3.8 Has Cycle?	14	7.7 PBS	30
3.9 Articulation Bridges	14	7.8 Dates	30
3.10 SCC Kosaraju's	15	8 Template	30
3.11 Kruskal	15		
3.12 Kuhn's Algorithm	15		

1 Estructuras de Datos

1.1 Unordered Map

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 using namespace __gnu_pbds;
3
4 struct custom_hash {
5     static uint64_t splitmix64(uint64_t x) {
6         // http://xorshift.di.unimi.it/splitmix64.c
7         x += 0x9e3779b97f4a7c15;
8         x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
9         x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
10        return x ^ (x >> 31);
11    }
12
13    size_t operator()(uint64_t x) const {
14        static const uint64_t FIXED_RANDOM = chrono::steady_clock::now()
15            .time_since_epoch().count();
16        return splitmix64(x + FIXED_RANDOM);
17    }
18 };
19 gp_hash_table<int, int, custom_hash> m1;
20
21 //Function count
22 m1.find(x) != m1.end()

```

1.2 Segment tree Recursivo

```

1 // Point updates, range query
2 const int N = 4e5+5;
3 int st[N], arr[N];
4 void build(int l, int r, int i) {
5     if (l == r) {st[i] = arr[l]; return;}
6     int m = l+r>>1;
7     build(l, m, 2*i+1);
8     build(m+1, r, 2*i+2);
9     st[i] = st[2*i+1] + st[2*i+2]; // !#
10 }
11 void update(int l, int r, int idx, int x, int i) {
12     if (l == r) {st[i] += x; return;}
13     int m = l+r>>1;

```

```

14     if (idx <= m) update(l, m, idx, x, i*2+1);
15     else update(m+1, r, idx, x, i*2+2);
16     st[i] = st[i*2+1] + st[i*2+2];
17 }
18 int query(int l, int r, int a, int b, int i) {
19     if (a > r || b < l) return 0;
20     if (a <= l && r <= b) return st[i];
21     int m = l+r>>1;
22     return query(l, m, a, b, 2*i+1) + query(m+1, r, a, b, 2*i+2);
23 } // idx=0, l=0, r=n-1
24
25 // Range update, point query
26 // Use same build function above, but comment #!
27 void update(int l, int r, int a, int b, int x, int i) {
28     if (a > r || b < l) return;
29     if (a <= l && r <= b) {st[i] += x; return;}
30     int m = l+r>>1;
31     update(l, m, a, b, x, i*2+1);
32     update(m+1, r, a, b, x, i*2+2);
33 }
34 ll query(int l, int r, int idx, int i) {
35     if (idx > r || idx < l) return 0;
36     if (idx <= l && r <= idx) return st[i];
37     int m = l+r>>1;
38     return query(l, m, idx, 2*i+1) + query(m+1, r, idx, 2*i+2) + st[i];
39 }

```

1.3 Segment Tree Iterativo

```

1 //Para procesar queries de tipo k-esimo es necesario crear un arbol
2 // binario perfecto (llenar con 0's)
3 template<typename T>
4 struct SegmentTree{
5     int N;
6     vector<T> ST;
7
8     //Creacion a partir de un arreglo O(n)
9     SegmentTree(int N, vector<T> & arr): N(N){
10         ST.resize(N << 1);
11         for(int i = 0; i < N; ++i)
12             ST[N + i] = arr[i]; //Dato normal
13             ST[N + i] = creaNode(); //Dato compuesto
14         for(int i = N - 1; i > 0; --i)

```

```

14     ST[i] = ST[i << 1] + ST[i << 1 | 1];          //Dato normal
15     ST[i] = merge(ST[i << 1] , ST[i << 1 | 1]); //Dato compuesto
16 }
17
18 //Actualizacion de un elemento en la posicion i
19 void update(int i, T value){
20     ST[i += N] = value;          //Dato normal
21     ST[i += N] = creaNodo(); //Dato compuesto
22     while(i >= 1)
23         ST[i] = ST[i << 1] + ST[i << 1 | 1];          //Dato normal
24         ST[i] = merge(ST[i << 1] , ST[i << 1 | 1]); //Dato compuesto
25 }
26
27 //query en [l, r]
28 T query(int l, int r){
29     T res = 0; //Dato normal
30     nodo resl = creaNodo(), resr = creaNodo(); //Dato compuesto
31     for(l += N, r += N; l <= r; l >= 1, r >= 1){
32         if(l & 1)         res += ST[l++]; //Dato normal
33         if(!(r & 1))       res += ST[r--]; //Dato normal
34
35         if(l & 1)         resl = merge(resl, ST[l++]); //Dato compuesto
36         if(!(r & 1))       resr = merge(ST[r--], resr); //Dato compuesto
37     }
38     return res;          //Dato normal
39     return merge(resl, resr); //Dato compuesto
40 }
41
42 //Para estas querys es necesario que el st tenga el tam de la
43     siguiente potencia de 2
44 //ll nT = 1;
45 // while(nT<n) nT<=1;
46 //vector<int> a(nT,0);
47
48 //Encontrar k-esimo 1 en un st de 1's
49 int Kth_One(int k) {
50     int i = 0, s = N >> 1;
51     for(int p = 2; p < 2 * N; p <= 1, s >= 1) {
52         if(k < ST[p]) continue;
53         k -= ST[p++]; i += s;
54     }
55     return i;
56 }

```

```

56
57 //i del primer elemento >= k en todo el arr
58 int atLeastX(int k){
59     int i = 0, s = N >> 1;
60     for(int p = 2; p < 2 * N; p <= 1, s >= 1) {
61         if(ST[p] < k) p++, i += s;
62     }
63     if(ST[N + i] < k) i = -1;
64     return i;
65 }
66
67 //i del primer elemento >= k en [l,fin]
68 //Uso atLeastX(k,l,1,nT)
69 int atLeastX(int x, int l, int p, int s) {
70     if(ST[p] < x or s <= 1) return -1;
71     if((p < 1) >= 2 * N)
72         return (ST[p] >= x) - 1;
73     int i = atLeastX(x, l, p < 1, s >> 1);
74     if(i != -1) return i;
75     i = atLeastX(x, l - (s >> 1), p < 1 | 1, s >> 1);
76     if(i == -1) return -1;
77     return (s >> 1) + i;
78 }
79 };

```

1.4 Segment Tree Lazy Recursivo

```

1  const int N = 2e5+10;
2  ll st[4*N+10], lazy[4*N+10], arr[N];
3  void build(int l, int r, int i) {
4      lazy[i] = 0;
5      if (l == r) {st[i] = arr[l]; return;}
6      int m = l+r>>1;
7      build(l, m, 2*i+1);
8      build(m+1, r, 2*i+2);
9      st[i] = st[2*i+1] + st[2*i+2];
10 }
11 void push(int l, int r, int i) {
12     if (!lazy[i]) return;
13     st[i] += (r-l+1) * lazy[i];
14     if (l != r) {
15         lazy[2*i+1] += lazy[i];
16         lazy[2*i+2] += lazy[i];

```

```

17     }
18     lazy[i] = 0;
19 }
20 void update(int l, int r, int a, int b, ll x, int i) {
21     push(l, r, i);
22     if (a > r || b < l) return;
23     if (a <= l && r <= b) {
24         lazy[i] += x;
25         push(l, r, i);
26         return;
27     }
28     int m = l+r>>1;
29     update(l, m, a, b, x, 2*i+1);
30     update(m+1, r, a, b, x, 2*i+2);
31     st[i] = st[2*i+1] + st[2*i+2];
32 }
33 ll query(int l, int r, int a, int b, int i) {
34     if (a > r || b < l) return 0;
35     push(l, r, i);
36     if (a <= l && r <= b) return st[i];
37     int m = l+r>>1;
38     return query(l, m, a, b, 2*i+1) + query(m+1, r, a, b, 2*i+2);
39 } // i=0, l=0, r=n-1, x=value, a,b=range query

```

1.5 Segment Tree Lazy Iterativo

```

1 //Lazy propagation con incremento de u en rango y minimo
2 //Hay varias modificaciones necesarias para suma en ambos
3 template<typename T>
4 struct SegmentTreeLazy{
5     int N,h;
6     vector<T> ST, d;
7
8     //Creacion a partir de un arreglo
9     SegmentTreeLazy(int n, vector<T> &a): N(n){
10         //En caso de inicializar en cero o algo similar, revisar que la
            construccion tenga su respectivo neutro mult y 1
11         ST.resize(N << 1);
12         d.resize(N);
13         h = 64 - __builtin_clzll(n);
14
15         for(int i = 0; i < N; ++i)
16             ST[N + i] = a[i];

```

```

17     //Construir el st sobre la query que se necesita
18     for(int i = N - 1; i > 0; --i)
19         ST[i] = min(ST[i << 1], ST[i << 1 | 1]);
20 }
21
22 //Modificar de acuerdo al tipo modificacion requerida, +,*,|,^,etc
23 void apply(int p, T value) {
24     ST[p] += value;
25     if(p<N) d[p]+= value;
26 }
27
28 // Modifica valores de los padres de p
29 //Modificar de acuerdo al tipo modificacion requerida, +,*,|,^,etc y a
    la respectiva query
30 void build(int p){
31     while(p>1){
32         p >>= 1;
33         ST[p] = min(ST[p << 1], ST[p << 1 | 1]) + d[p];
34         //ST[p] = (ST[p << 1] & ST[p << 1 | 1]) | d[p]; Ejemplos con
            bitwise
35     }
36 }
37
38 // Propagacion desde la raiz a p
39 void push(int p){
40     for (int s = h; s > 0; --s) {
41         int i = p >> s;
42         if (d[i] != 0) {
43             apply(i << 1, d[i]);
44             apply(i << 1 | 1, d[i]);
45             d[i] = 0; //Tener cuidado si estoy haciendo multiplicaciones
46         }
47     }
48 }
49
50 // Sumar v a cada elemento en el intervalo [l, r)
51 void increment(int l, int r, T value) {
52     l += N, r += N;
53     int l0 = l, r0 = r;
54     for (; l < r; l >>= 1, r >>= 1) {
55         if(l & 1) apply(l++, value);
56         if(r & 1) apply(--r, value);
57     }

```

```

58     build(l0);
59     build(r0 - 1);
60 }
61
62 // min en el intervalo [l, r)
63 T range_min(int l, int r) {
64     l += N, r += N;
65     push(l);
66     push(r - 1);
67     T res = LLONG_MAX;
68     //T res = (1 << 30) - 1;    Requerir operacion and
69     for (; l < r; l >>= 1, r >>= 1) {
70         if(l & 1) res = min(res, ST[l++]);
71         //if(res >= mod) res -= mod;
72         if(r & 1) res = min(res, ST[--r]);
73         //if(res >= mod) res -= mod;
74     }
75     return res;
76 }
77
78 };

```

1.6 Rope

```

1 #include <ext/rope>
2 using namespace __gnu_cxx;
3 rope<int> s;
4 // Sequence with O(log(n)) random access, insert, erase at any position
5 // s.push_back(x);
6 // s.insert(i,r) // insert rope r at position i
7 // s.erase(i,k) // erase subsequence [i,i+k)
8 // s.substr(i,k) // return new rope corresponding to subsequence [i,i+k)
9 // s[i] // access ith element (cannot modify)
10 // s.mutable_reference_at(i) // acces ith element (allows modification)
11 // s.begin() and s.end() are const iterators (use mutable_begin(),
    mutable_end() to allow modification)

```

1.7 Ordered Set

```

1 #include<ext/pb_ds/assoc_container.hpp>
2 #include<ext/pb_ds/tree_policy.hpp>
3 using namespace __gnu_pbds;
4 typedef tree<int,null_type,less<int>,rb_tree_tag,
    tree_order_statistics_node_update> ordered_set;

```

```

5 // find_by_order(i) -> iterator to ith element
6 // order_of_key(k) -> position (int) of lower_bound of k

```

1.8 Union Find

```

1 vector<pair<int,int>>ds(MAX,{-1,0});
2 // Solo siu requieres los elementos del union find, utiliza
3 // dsex en caso contrario borrarlo
4 list<int>dsex[MAX];
5 void init(int n){
6     for(int i=0;i<n;i++)dsex[i].push_back(i);
7 }
8 int find(int x){
9     if(-1==ds[x].first) return x;
10    return ds[x].first=find(ds[x].first);
11 }
12 bool unionDs(int x, int y){
13     int px=find(x),py=find(y);
14     int &rx=ds[px].second,&ry=ds[py].second;
15     if(px==py) return false;
16     else{
17         if(rx>ry){
18             ds[py].first=px;
19         }
20         else{
21             ds[px].first=py;
22             if(rx==ry) ry+=1;
23         }
24     }
25     return true;
26 }

```

1.9 Segment Tree Persistente

```

1 #define inf INT_MAX
2 const int MAX=5e5+2;
3 typedef pair<ll, ll> item;
4 struct node{
5     item val;
6     node *l, *r;
7     node(): l(nullptr),r(nullptr),val({inf,inf}){};
8     node(node *_l,node *_r):l(_l),r(_r){
9         val=min(l->val,r->val);
10    }

```

```

11     node(ll value,ll pos):r(nullptr),l(nullptr){
12         val=make_pair(value,pos);
13     }
14 };
15 pair<ll,ll>all;
16 vector<node*>versions(MAX,nullptr);
17 node* build(int l,int r){
18     if(l==r)return new node(inf,l);
19     int m=(l+r)/2;
20     return new node(build(l,m),build(m+1,r));
21 }
22
23 node* update(node *root,int l,int r,int pos,int val){
24     if(l==r){
25         return new node(val,pos);}
26     int m=(l+r)/2;
27     if(pos<=m) return new node(update(root->l,l,m,pos,val),root->r);
28     return new node(root->l,update(root->r,m+1,r,pos,val));
29 }
30 item query(node *root,int l,int r,int a,int b){
31     if(a>r || b<l) return all;
32     if(a<=l && r<=b) return root->val;
33     int m=(l+r)/2;
34     return min(query(root->l,l,m,a,b),query(root->r,m+1,r,a,b));
35 }

```

1.10 Sparse Table

```

1 //Se usa para RMQ porque se puede hacer en O(1), no acepta updates
2 vector<int>lg;
3 vector<vector<int>>st;
4 int *nums;
5 void init(int n){
6     int logn=(int) log2(n)+1;
7     lg.assign(n+1,0);
8     st.assign(logn,vector<int>(n+1));
9     for(int i=0;i<n;i++) st[0][i]=nums[i];
10    lg[1]=0;
11    for(int i=2;i<=n;i++) lg[i]=lg[i/2]+1;
12    for(int i=1;i<logn;i++)
13        for(int j=0;j+(1<<i)<n;j++)st[i][j]=min(st[i-1][j],st[i-1][j
14        +(1<<(i-1))]);

```

```

15 int query(int a,int b){
16     int logn=lg[(b-a+1)];
17     cout<<st[logn][a]<<endl;
18     return min(st[logn][a],st[logn][b-(1<<logn)+1]);
19 }

```

1.11 Wavelet Tree

```

1 // indexed in 1
2 // from pointer to first element and to to end
3 // x and y The minimum element and y the max element
4 // If you need only one function or more erase the others
5 // If you need to construct other function you only required to
6 // understand the limit, this
7 // are the same
8 struct wavelet_tree{
9     wavelet_tree *l, *r;
10    vector<int> b;
11    wavelet_tree(int *from, int *to, int x, int y){
12        lo = x, hi = y;
13        if(lo == hi or from >= to) return;
14        int mid = (lo+hi)/2;
15        auto f = [mid](int x){ return x <= mid;};
16        b.reserve(to-from+1);
17        b.pb(0);
18        for(auto it = from; it != to; it++)
19            b.push_back(b.back() + f(*it));
20        auto pivot = stable_partition(from, to, f);
21        l = new wavelet_tree(from, pivot, lo, mid);
22        r = new wavelet_tree(pivot, to, mid+1, hi);
23    }
24    //kth smallest element in [l, r]
25    int kth(int l, int r, int k){
26        if(l > r) return 0;
27        if(lo == hi) return lo;
28        int inLeft = b[r] - b[l-1];
29        int lb = b[l-1];
30        int rb = b[r];
31        if(k <= inLeft) return this->l->kth(lb+1, rb, k);
32        return this->r->kth(lb, rb-rb, k-inLeft);
33    }
34    //count of nos in [l, r] Less than or equal to k

```

```

35 int LTE(int l, int r, int k) {
36     if(l > r or k < lo) return 0;
37     if(hi <= k) return r - l + 1;
38     int lb = b[l-1], rb = b[r];
39     return this->l->LTE(lb+1, rb, k) + this->r->LTE(l-lb, r-rb, k);
40 }
41 //count of nos in [l, r] equal to k
42 int count(int l, int r, int k) {
43     if(l > r or k < lo or k > hi) return 0;
44     if(lo == hi) return r - l + 1;
45     int lb = b[l-1], rb = b[r], mid = (lo+hi)/2;
46     if(k <= mid) return this->l->count(lb+1, rb, k);
47     return this->r->count(l-lb, r-rb, k);
48 }
49 };

```

1.12 Trie

```

1 struct trie{
2     int len,id;
3     int children[26];
4     trie(int _id){
5         len=0,id=_id;
6         for(int i=0;i<26;i++)children[i]=-1;
7     }
8 };vector<trie>Trie;Trie.push_back(trie());
9 void inserString(string str,int root){
10     int aux=root;
11     for(int i=0;i<str.size();i++){
12         int index=str[i]-'a';
13         if(Trie[aux].children[index]==-1){
14             Trie.push_back(trie(Trie.size()));
15             Trie[aux].children[index]=Trie.size()-1;
16         }
17         aux=Trie[aux].children[index];
18     }
19     Trie[aux].len=str.size();
20 }
21 bool existInTrie(string str,int root){
22     int aux=root;
23     for(int i=0;i<str.size();i++){
24         int index=str[i]-'a';
25         if(Trie[aux].children[index]==-1) return false;

```

```

26         aux=Trie[aux].children[index];
27     }
28     return Trie[aux].len;
29 }

```

1.13 Treap

```

1 struct Node {
2     int val=0;
3     ll weight, len=1,lazy=0,sum=0;
4     Node *l, *r;
5     Node(int c) : val(c),weight(rand()), l(NULL), r(NULL) {}
6 } *treap;
7 int size(Node *root) { return root ? root->len : 0; }
8 ll sum(Node *root){ return root? root->sum:0;}
9 void pushDown(Node *&root){
10     if(!root || !root->lazy) return;
11     if(root->l) root->l->lazy+=root->lazy;
12     if(root->r) root->r->lazy+=root->lazy;
13     ll num=root->lazy;num*=size(root);
14     root->sum+=num;root->lazy=0;
15 }
16 void recal(Node *&root){
17     if(!root) return;
18     root->len=1+size(root->l)+size(root->r);
19     root->sum=sum(root->l)+sum(root->r)+root->val;
20     root->val+=root->lazy;
21     pushDown(root);
22 }
23 void split(Node *root, Node *&l, Node *&r, int val) {
24     recal(root);
25     if (!root) l = r = NULL;
26     else if (size(root->l) < val) {
27         split(root->r, root->r, r, val - size(root->l) - 1); l = root; recal
28         (l);
29     } else {
30         split(root->l, l, root->l, val); r = root; recal(r);
31     }
32     recal(root);
33 }
34 void merge(Node *&root, Node *l, Node *r) {
35     recal(l);recal(r);
36     if (!l || !r){root = (!l)?r:l;}

```

```

36 else if (l->weight < r->weight) {
37     merge(l->r, l->r, r); root = l;
38 } else {
39     merge(r->l, l, r->l); root = r;
40 }
41 root->len=1+size(root->l)+size(root->r);
42 }
43 // Not necessary functions indexed in 1
44 void insert(Node *&root, Node *nNode, int pos){
45     Node *l=NULL, *r=NULL, *aux=NULL;
46     split(root, l, r, pos-1);
47     merge(aux, l, nNode);
48     merge(root, aux, r);
49 }
50 void delateRange(Node *&root, int l, int r){
51     Node *l1, *r1, *l2, *r2, *aux2;
52     split(root, l1, r1, l-1);
53     split(r1, r1, r2, r-l+1);
54     merge(root, l1, r2);
55 }
56 // queries if you dont need this you can delete recal and push-down
57 // rembember change the size
58 ll query(Node *&root, int l, int r){
59     Node *l1, *r1, *l2, *r2;
60     split(root, l1, r1, l-1);
61     split(r1, r1, l2, r-l+1);
62     ll res=sum(r1);
63     merge(root, l1, r1); merge(root, root, l2);
64     return res;
65 }
66 void update(Node *&root, int l, int r, ll add){
67     Node *l1, *r1, *l2, *r2, *aux;
68     split(root, l1, r1, l-1);
69     split(r1, r1, r2, r-l+1);
70     r1->lazy+=add;
71     merge(l1, l1, r1); merge(root, l1, r2);
72 }
73 // debugging
74 ostream &operator<<(ostream &os, Node *n) {
75     if (!n) return os;
76     os << n->l;
77     os << n->val;
78     os << n->r;

```

```

79     return os;
80 }

```

1.14 Segment Tree Dinamico

```

1 struct dinamicStree{
2     int l,r;
3     dinamicStree *left=NULLptr,*right=NULLptr;
4     ll sum=0;
5     dinamicStree(int l1,int r1){
6         l=l1,r=r1;
7     }
8 };
9 void updateD(int l,int r,int idx,ll x,dinamicStree *node){
10     if(l==r){ node->sum+=x;return;}
11     int m=(l+r)>>1;
12     ll sum=0;
13     if(idx<=m){
14         node->left=(node->left==NULLptr?new dinamicStree(l,m):node->left
15             );
16         updateD(l,m,idx,x,node->left);
17     }
18     else{
19         node->right=(node->right==NULLptr?new dinamicStree(m+1,r):node->
20             right);
21         updateD(m+1,r,idx,x,node->right);
22     }
23     node->sum=(node->left!=NULLptr?node->left->sum:0)+(node->right!=
24         NULLptr?node->right->sum:0);
25 }
26 ll queryD(int a,int b,dinamicStree *node){
27     if(node==NULLptr) return 0;
28     if(a>node->r || b<node->l) return 0;
29     if(a<=node->l && node->r<=b) return node->sum;
30     return queryD(a,b,node->left)+queryD(a,b,node->right);
31 }

```

2 Strings

2.1 Aho Corasick

```

1 int K, I = 1;
2 struct node {

```



```

3     int fail, ch[26] = {};
4     vector<int> lens;
5 } T[500005];
6
7 void add(string s) {
8     int x = 1;
9     for (int i = 0; i < s.size(); i++) {
10         if (T[x].ch[s[i] - 'a'] == 0)
11             T[x].ch[s[i] - 'a'] = ++I;
12         x = T[x].ch[s[i] - 'a'];
13     }
14     T[x].lens.PB(s.size());
15 }
16
17 void build() {
18     queue<int> Q;
19     int x = 1;
20     T[1].fail = 1;
21     for (int i = 0; i < 26; i++) {
22         if (T[x].ch[i])
23             T[T[x].ch[i]].fail = x, Q.push(T[x].ch[i]);
24         else
25             T[x].ch[i] = 1;
26     }
27     while (!Q.empty()) {
28         x = Q.front(); Q.pop();
29         for (int i = 0; i < 26; i++) {
30             if (T[x].ch[i])
31                 T[T[x].ch[i]].fail = T[T[x].fail].ch[i], Q.push(T[x].ch[i]);
32             else
33                 T[x].ch[i] = T[T[x].fail].ch[i];
34         }
35     }
36 }

```

2.2 Dynamic Aho Corasick

```

1 const int MX = 300005, SIG = 26, LMX = 19;
2
3 struct aho_corasick {
4     struct Node {
5         Node *sig[SIG], *fail;

```

```

6         int finish, cnt;
7         Node () : fail(this), finish(0), cnt(0) {
8             for (int i = 0; i < SIG; i++)
9                 sig[i] = this;
10        }
11        Node (Node *root) : fail(root), finish(0), cnt(0) {
12            for (int i = 0; i < SIG; i++)
13                sig[i] = root;
14        }
15    };
16    Node *root;
17    aho_corasick() { reset(); }
18    void reset () {
19        root = new Node;
20    }
21    void insert (string &s, int ind) {
22        Node *u = root;
23        for (char c : s) {
24            c -= 'a';
25            if (u->sig[c] == root) {
26                u->sig[c] = new Node(root);
27                u->sig[c]->finish = -1;
28            }
29            u = u->sig[c];
30        }
31        u->finish = ind;
32        u->cnt++;
33    }
34    Node* getFail (Node *u, int c) {
35        while (u != root && u->sig[c] == root)
36            u = u->fail;
37        return u->sig[c];
38    }
39    void build () {
40        queue<Node*> q;
41        for (int i = 0; i < SIG; i++)
42            if (root->sig[i] != root)
43                q.push(root->sig[i]);
44        while (q.size()) {
45            Node *u = q.front();
46            q.pop();
47            for (int i = 0; i < SIG; i++) {
48                Node *v = u->sig[i];

```

```

49     if (v != root) {
50         v->fail = getFail(u->fail, i);
51         v->cnt += v->fail->cnt;
52         q.push(v);
53     }}}}
54 int match (string &t) {
55     Node *u = root;
56     int res = 0;
57     for (int i = 0; i < t.size(); i++) {
58         char c = t[i] - 'a';
59         if (u->sig[c] != root)
60             u = u->sig[c];
61         else
62             u = getFail(u->fail, c);
63         res += u->cnt;
64     }
65     return res;
66 }
67 };
68
69 typedef vector<string*> vs;
70 struct dynamic_aho_corasick {
71     aho_corasick ac[LMX];
72     vs s[LMX];
73     int exi;
74     dynamic_aho_corasick () : exi(0) {}
75     int insert (string &str) {
76         int j = 0;
77         while (exi & (1 << j)) j++;
78         s[j].push_back(new string(str));
79         for (int i = 0; i < j; i++) {
80             for (string *t : s[i]) s[j].push_back(t);
81             s[i].clear();
82             ac[i].reset();
83         }
84         for (string *t : s[j])
85             ac[j].insert(*t, 1);
86         ac[j].build();
87         exi++;
88     }
89     int match (string &t) {
90         int res = 0;
91         for (int i = 0; i < LMX; i++)

```

```

92         if (exi & (1 << i))
93             res += ac[i].match(t);
94         return res;
95     }
96 };

```

2.3 Hashing

```

1 struct Hash{
2     const int mod=1e9+123;
3     const int p=257;
4     vector<int> prefix;
5     static vector<int> pow;
6     Hash(string str){
7         int n=str.size();
8         while(pow.size()<=n){
9             pow.push_back(1LL*pow.back()*p%mod);
10        }
11        vector<int> aux(n+1);
12        prefix=aux;
13        for(int i=0;i<n;i++){
14            prefix[i+1]=(prefix[i]+1LL*str[i]*pow[i])%mod;
15        }
16    }
17    inline int getHashInInerval(int i,int len,int MxPow){
18        int hashing=prefix[i+len]-prefix[i];
19        if(hashing<0) hashing+=mod;
20        hashing=1LL*hashing*pow[MxPow-(len+i-1)]%mod;
21        return hashing;
22    }
23 };
24 vector<int> Hash::pow{1};

```

2.4 KMP

```

1 vector<int> kmp(string s){
2     int n=s.size();
3     vector<int> pi(n);
4     for(int i=1;i<n;i++){
5         int j=pi[i-1];
6         while(j>0 && s[i]!=s[j])j=pi[j-1];
7         if(s[i]==s[j]) j++;
8         pi[i]=j;
9     }

```

```

10     return pi;
11 }

```

2.5 Manacher

```

1 vector<int> manacher_odd(string s) {
2     int n = s.size();
3     s = "$" + s + "^";
4     vector<int> p(n + 2);
5     int l = 1, r = 1;
6     for(int i = 1; i <= n; i++) {
7         p[i] = max(0, min(r - i, p[l + (r - i)]));
8         while(s[i - p[i]] == s[i + p[i]]) {
9             p[i]++;
10        }
11        if(i + p[i] > r) {
12            l = i - p[i], r = i + p[i];
13        }
14    }
15    return vector<int>(begin(p) + 1, end(p) - 1);
16 }
17 vector<int> manacher_even(string s){
18     string even;
19     for(auto c:s){
20         even+='#'+c;
21     }
22     even+='#';
23     return manacher_odd(even);
24 }

```

2.6 Suffix Automaton

```

1 struct node{
2     map<char,int>edges;
3     int link,length,terminal=0;
4     node(int link,int length): link(link),length(length){};
5 };vector<node>sa;
6 // init in main with sa.push_back(node(-1,0));
7 int last=0;
8 // add one by one chars in order
9 void addChar(char s, int pos){
10     sa.push_back(node(0,pos+1));
11     int r=sa.size()-1;
12     int p=last;

```

```

13     while(p >= 0 && sa[p].edges.find(s) == sa[p].edges.end()) {
14         sa[p].edges[s] = r;
15         p = sa[p].link;
16     }
17     if(p != -1) {
18         int q = sa[p].edges[s];
19         if(sa[p].length + 1 == sa[q].length) {
20             sa[r].link = q;
21         } else {
22             sa.push_back(node(sa[q].link,sa[p].length+1));
23             sa[sa.size()-1].edges=sa[q].edges;
24             int qq = sa.size()-1;
25             sa[q].link = qq;
26             sa[r].link= qq;
27             while(p >= 0 && sa[p].edges[s] == q) {
28                 sa[p].edges[s] = qq;
29                 p = sa[p].link;
30             }
31         }
32     }
33     last = r;
34 }
35 // Not necessary functions
36 void findTerminals(){
37     int p = last;
38     while(p > 0) {
39         sa[p].terminal=1;
40         p = sa[p].link;
41     }
42 }

```

3 Graph

3.1 Structs for Graphs

```

1 struct edge{
2     int source, dest, cost;
3     edge(): source(0), dest(0), cost(0){}
4     edge(int dest, int cost): dest(dest), cost(cost){}
5     edge(int source, int dest, int cost): source(source), dest(dest), cost
        (cost){}
6     bool operator==(const edge & b) const{
7         return source == b.source && dest == b.dest && cost == b.cost;

```

```

8   }
9   bool operator<(const edge & b) const{
10      return cost < b.cost;
11   }
12   bool operator>(const edge & b) const{
13      return cost > b.cost;
14   }
15 };

16
17 struct path{
18     int cost = inf;
19     deque<int> vertices;
20     int size = 1;
21     int prev = -1;
22 };

23
24 struct graph{
25     vector<vector<edge>> adjList;
26     vector<vb> adjMatrix;
27     vector<vi> costMatrix;
28     vector<edge> edges;
29     int V = 0;
30     bool dir = false;
31     graph(int n, bool dir): V(n), dir(dir), adjList(n), edges(n),
32         adjMatrix(n, vb(n)), costMatrix(n, vi(n)){
33         for(int i = 0; i < n; ++i)
34             for(int j = 0; j < n; ++j)
35                 costMatrix[i][j] = (i == j ? 0 : inf);
36     }
37     void add(int source, int dest, int cost){
38         adjList[source].emplace_back(source, dest, cost);
39         edges.emplace_back(source, dest, cost);
40         adjMatrix[source][dest] = true;
41         costMatrix[source][dest] = cost;
42         if(!dir){
43             adjList[dest].emplace_back(dest, source, cost);
44             adjMatrix[dest][source] = true;
45             costMatrix[dest][source] = cost;
46         }
47     }
48     void buildPaths(vector<path> & paths){
49         for(int i = 0; i < V; i++){
50             int u = i;

```

```

50         for(int j = 0; j < paths[i].size; j++){
51             paths[i].vertices.push_front(u);
52             u = paths[u].prev;
53         }
54     }
55 }
56 };

```

3.2 Dijkstra

```

1 vector<path> dijkstra(int start){
2     priority_queue<edge, vector<edge>, greater<edge>> cola;
3     vector<path> paths(V);
4     cola.emplace(start, 0);
5     paths[start].cost = 0;
6     while(!cola.empty()){
7         int u = cola.top().dest; cola.pop();
8         for(edge & current : adjList[u]){
9             int v = current.dest;
10            int nuevo = paths[u].cost + current.cost;
11            if(nuevo == paths[v].cost && paths[u].size + 1 < paths[v].
12                size){
13                paths[v].prev = u;
14                paths[v].size = paths[u].size + 1;
15            }else if(nuevo < paths[v].cost){
16                paths[v].prev = u;
17                paths[v].size = paths[u].size + 1;
18                cola.emplace(v, nuevo);
19                paths[v].cost = nuevo;
20            }
21        }
22    }
23    buildPaths(paths); // !# - Copy function from above
24    return paths;
25 }

```

3.3 Bellman-Ford

```

1 vector<path> bellmanFord(int start){
2     vector<path> paths(V, path());
3     vi processed(V);
4     vb inQueue(V);
5     queue<int> Q;
6     paths[start].cost = 0;

```

```

7   Q.push(start);
8   while(!Q.empty()){
9       int u = Q.front(); Q.pop(); inQueue[u] = false;
10      if(paths[u].cost == inf) continue;
11      ++processed[u];
12      if(processed[u] == V){
13          cout << "Negative_cycle\n";
14          return {};
15      }
16      for(edge & current : adjList[u]){
17          int v = current.dest;
18          int nuevo = paths[u].cost + current.cost;
19          if(nuevo == paths[v].cost && paths[u].size + 1 < paths[v].size){
20              paths[v].prev = u;
21              paths[v].size = paths[u].size + 1;
22          }else if(nuevo < paths[v].cost){
23              if(!inQueue[v]){
24                  Q.push(v);
25                  inQueue[v] = true;
26              }
27              paths[v].prev = u;
28              paths[v].size = paths[u].size + 1;
29              paths[v].cost = nuevo;
30          }
31      }
32  }
33  buildPaths(paths); // !# - Copy function from above
34  return paths;
35 }

```

3.4 Floyd Warshall

```

1   vector<vi> floyd(){
2       vector<vi> tmp = costMatrix;
3       for(int k = 0; k < V; ++k)
4           for(int i = 0; i < V; ++i)
5               for(int j = 0; j < V; ++j)
6                   if(tmp[i][k] != inf && tmp[k][j] != inf)
7                       tmp[i][j] = min(tmp[i][j], tmp[i][k] + tmp[k][j]);
8       return tmp;
9   }

```

3.5 Transitive Closure

```

1   vector<vb> transitiveClosure(){
2       vector<vb> tmp = adjMatrix;
3       for(int k = 0; k < V; ++k)
4           for(int i = 0; i < V; ++i)
5               for(int j = 0; j < V; ++j)
6                   tmp[i][j] = tmp[i][j] || (tmp[i][k] && tmp[k][j]);
7       return tmp;
8   }
9
10  vector<vb> transitiveClosureDFS(){
11      vector<vb> tmp(V, vb(V));
12      function<void(int, int)> dfs = [&](int start, int u){
13          for(edge & current : adjList[u]){
14              int v = current.dest;
15              if(!tmp[start][v]){
16                  tmp[start][v] = true;
17                  dfs(start, v);
18              }
19          }
20      };
21      for(int u = 0; u < V; u++)
22          dfs(u, u);
23      return tmp;
24  }

```

3.6 Is bipartite?

```

1   bool isBipartite(){
2       vi side(V, -1);
3       queue<int> q;
4       for (int st = 0; st < V; ++st){
5           if(side[st] != -1) continue;
6           q.push(st);
7           side[st] = 0;
8           while(!q.empty()){
9               int u = q.front();
10              q.pop();
11              for (edge & current : adjList[u]){
12                  int v = current.dest;
13                  if(side[v] == -1) {
14                      side[v] = side[u] ^ 1;
15                      q.push(v);
16                  }else{

```

```

17         if(side[v] == side[u]) return false;
18     }
19 }
20 }
21 }
22 return true;
23 }

```

3.7 Topological Sort

```

1 vi topologicalSort(){
2     int visited = 0;
3     vi order, indegree(V);
4     for(auto & node : adjList){
5         for(edge & current : node){
6             int v = current.dest;
7             ++indegree[v];
8         }
9     }
10    queue<int> Q;
11    for(int i = 0; i < V; ++i){
12        if(indegree[i] == 0) Q.push(i);
13    }
14    while(!Q.empty()){
15        int source = Q.front();
16        Q.pop();
17        order.push_back(source);
18        ++visited;
19        for(edge & current : adjList[source]){
20            int v = current.dest;
21            --indegree[v];
22            if(indegree[v] == 0) Q.push(v);
23        }
24    }
25    if(visited == V) return order;
26    else return {};
27 }

```

3.8 Has Cycle?

```

1 bool hasCycle(){
2     vi color(V);
3     function<bool(int, int)> dfs = [&](int u, int parent){
4         color[u] = 1;

```

```

5         bool ans = false;
6         int ret = 0;
7         for(edge & current : adjList[u]){
8             int v = current.dest;
9             if(color[v] == 0)
10                 ans |= dfs(v, u);
11             else if(color[v] == 1 && (dir || v != parent || ret++))
12                 ans = true;
13         }
14         color[u] = 2;
15         return ans;
16     };
17     for(int u = 0; u < V; ++u)
18         if(color[u] == 0 && dfs(u, -1))
19             return true;
20     return false;
21 }

```

3.9 Articulation Bridges

```

1 pair<vb, vector<edge>> articulationBridges(){
2     vi low(V), label(V);
3     vb points(V);
4     vector<edge> bridges;
5     int time = 0;
6     function<int(int, int)> dfs = [&](int u, int p){
7         label[u] = low[u] = ++time;
8         int hijos = 0, ret = 0;
9         for(edge & current : adjList[u]){
10             int v = current.dest;
11             if(v == p && !ret++) continue;
12             if(!label[v]){
13                 ++hijos;
14                 dfs(v, u);
15                 if(label[u] <= low[v])
16                     points[u] = true;
17                 if(label[u] < low[v])
18                     bridges.push_back(current);
19                 low[u] = min(low[u], low[v]);
20             }
21             low[u] = min(low[u], label[v]);
22         }
23         return hijos;

```

```

24 };
25 for(int u = 0; u < V; ++u)
26     if(!label[u])
27         points[u] = dfs(u, -1) > 1;
28 return make_pair(points, bridges);
29 }

```

3.10 SCC Kosaraju's

```

1 vector<vi> scc(){
2     vi low(V), label(V);
3     int time = 0;
4     vector<vi> ans;
5     stack<int> S;
6     function<void(int)> dfs = [&](int u){
7         label[u] = low[u] = ++time;
8         S.push(u);
9         for(edge & current : adjList[u]){
10             int v = current.dest;
11             if(!label[v]) dfs(v);
12             low[u] = min(low[u], low[v]);
13         }
14         if(label[u] == low[u]){
15             vi comp;
16             while(S.top() != u){
17                 comp.push_back(S.top());
18                 low[S.top()] = V + 1;
19                 S.pop();
20             }
21             comp.push_back(S.top());
22             S.pop();
23             ans.push_back(comp);
24             low[u] = V + 1;
25         }
26     };
27     for(int u = 0; u < V; ++u)
28         if(!label[u]) dfs(u);
29     return ans;
30 }

```

3.11 Kruskal

```

1 vector<edge> kruskal(){
2     sort(edges.begin(), edges.end());

```

```

3     vector<edge> MST;
4     disjointSet DS(V);
5     for(int u = 0; u < V; ++u)
6         DS.makeSet(u);
7     int i = 0;
8     while(i < edges.size() && MST.size() < V - 1){
9         edge current = edges[i++];
10        int u = current.source, v = current.dest;
11        if(DS.findSet(u) != DS.findSet(v)){
12            MST.push_back(current);
13            DS.unionSet(u, v);
14        }
15    }
16    return MST;
17 }

```

3.12 Kuhn's Algorithm

```

1 bool tryKuhn(int u, vb & used, vi & left, vi & right){
2     if(used[u]) return false;
3     used[u] = true;
4     for(edge & current : adjList[u]){
5         int v = current.dest;
6         if(right[v] == -1 || tryKuhn(right[v], used, left, right)){
7             right[v] = u;
8             left[u] = v;
9             return true;
10        }
11    }
12    return false;
13 }
14 bool augmentingPath(int u, vb & used, vi & left, vi & right){
15     used[u] = true;
16     for(edge & current : adjList[u]){
17         int v = current.dest;
18         if(right[v] == -1){
19             right[v] = u;
20             left[u] = v;
21             return true;
22         }
23    }
24    for(edge & current : adjList[u]){
25        int v = current.dest;

```

```

26     if(!used[right[v]] && augmentingPath(right[v], used, left, right)){
27         right[v] = u;
28         left[u] = v;
29         return true;
30     }
31 }
32 return false;
33 }

```

3.13 Max Matching

```

1 //vertices from the left side numbered from 0 to l-1
2 //vertices from the right side numbered from 0 to r-1
3 //graph[u] represents the left side
4 //graph[u][v] represents the right side
5 //we can use tryKuhn() or augmentingPath()
6 vector<pair<int, int>> maxMatching(int l, int r){
7     vi left(l, -1), right(r, -1);
8     vb used(l);
9     for(int u = 0; u < l; ++u){
10         tryKuhn(u, used, left, right);
11         fill(used.begin(), used.end(), false);
12     }
13     vector<pair<int, int>> ans;
14     for(int u = 0; u < r; ++u){
15         if(right[u] != -1){
16             ans.emplace_back(right[u], u);
17         }
18     }
19     return ans;
20 }
21
22 void dfs(int u, vi & status, vi & parent){
23     status[u] = 1;
24     for(edge & current : adjList[u]){
25         int v = current.dest;
26         if(status[v] == 0){ //not visited
27             parent[v] = u;
28             dfs(v, status, parent);
29         }else if(status[v] == 1){ //explored
30             if(v == parent[u]){
31                 //bidirectional node u<-->v
32             }else{

```

```

33                 //back edge u-v
34             }
35         }else if(status[v] == 2){ //visited
36             //forward edge u-v
37         }
38     }
39     status[u] = 2;
40 }

```

3.14 LCA

```

1 struct tree{
2     vi parent, level, weight;
3     vector<vi> dists, DP;
4     int n, root;
5
6     void dfs(int u, graph & G){
7         for(edge & curr : G.adjList[u]){
8             int v = curr.dest;
9             int w = curr.cost;
10            if(v != parent[u]){
11                parent[v] = u;
12                weight[v] = w;
13                level[v] = level[u] + 1;
14                dfs(v, G);
15            }
16        }
17    }
18
19     tree(int n, int root): n(n), root(root), parent(n), level(n), weight(n),
20         dists(n, vi(20)), DP(n, vi(20)){
21         parent[root] = root;
22     }
23
24     tree(graph & G, int root): n(G.V), root(root), parent(G.V), level(G.V),
25         weight(G.V), dists(G.V, vi(20)), DP(G.V, vi(20)){
26         parent[root] = root;
27         dfs(root, G);
28     }
29
30     void pre(){
31         for(int u = 0; u < n; u++){
32             DP[u][0] = parent[u];

```



```

31     dists[u][0] = weight[u];
32 }
33 for(int i = 1; (1 << i) <= n; ++i){
34     for(int u = 0; u < n; ++u){
35         DP[u][i] = DP[DP[u][i - 1]][i - 1];
36         dists[u][i] = dists[u][i - 1] + dists[DP[u][i - 1]][i - 1];
37     }
38 }
39 }
40
41 int ancestor(int p, int k){
42     int h = level[p] - k;
43     if(h < 0) return -1;
44     int lg;
45     for(lg = 1; (1 << lg) <= level[p]; ++lg);
46     lg--;
47     for(int i = lg; i >= 0; --i){
48         if(level[p] - (1 << i) >= h){
49             p = DP[p][i];
50         }
51     }
52     return p;
53 }
54
55 int lca(int p, int q){
56     if(level[p] < level[q]) swap(p, q);
57     int lg;
58     for(lg = 1; (1 << lg) <= level[p]; ++lg);
59     lg--;
60     for(int i = lg; i >= 0; --i){
61         if(level[p] - (1 << i) >= level[q]){
62             p = DP[p][i];
63         }
64     }
65     if(p == q) return p;
66
67     for(int i = lg; i >= 0; --i){
68         if(DP[p][i] != -1 && DP[p][i] != DP[q][i]){
69             p = DP[p][i];
70             q = DP[q][i];
71         }
72     }
73     return parent[p];

```

```

74 }
75
76 int dist(int p, int q){
77     if(level[p] < level[q]) swap(p, q);
78     int lg;
79     for(lg = 1; (1 << lg) <= level[p]; ++lg);
80     lg--;
81     int sum = 0;
82     for(int i = lg; i >= 0; --i){
83         if(level[p] - (1 << i) >= level[q]){
84             sum += dists[p][i];
85             p = DP[p][i];
86         }
87     }
88     if(p == q) return sum;
89
90     for(int i = lg; i >= 0; --i){
91         if(DP[p][i] != -1 && DP[p][i] != DP[q][i]){
92             sum += dists[p][i] + dists[q][i];
93             p = DP[p][i];
94             q = DP[q][i];
95         }
96     }
97     sum += dists[p][0] + dists[q][0];
98     return sum;
99 }
100 };

```

3.15 Centroid

```

1 vector<int> g[MAXN]; int n;
2 bool tk[MAXN];
3 int fat[MAXN]; // father in centroid decomposition
4 int szt[MAXN]; // size of subtree
5 int calcsz(int x, int f){
6     szt[x] = 1;
7     for(auto y: g[x]) if(y != f && !tk[y]) szt[x] += calcsz(y, x);
8     return szt[x];
9 }
10 void cdfs(int x = 0, int f = -1, int sz = -1) { // O(n log n)
11     if(sz < 0) sz = calcsz(x, -1);
12     for(auto y: g[x]) if(!tk[y] && szt[y] * 2 >= sz) {
13         szt[x] = 0; cdfs(y, x, sz); return;

```

```

14 }
15 tk[x]=true;fat[x]=f;
16 for(auto y:g[x])if(!tk[y])cdfs(y,x);
17 }
18 void centroid(){memset(tk,false,sizeof(tk));cdfs();}

```

4 Flow

4.1 Dinics

```

1 struct Dinic {
2     int nodes, src, dst;
3     vector<int> dist, q, work;
4     struct edge {
5         int to, rev;
6         ll f, cap;
7     };
8     vector<vector<edge>> g;
9     Dinic(int x) : nodes(x), g(x), dist(x), q(x), work(x) {}
10    void add_edge(int s, int t, ll cap) {
11        g[s].pb((edge){t, sz(g[t]), 0, cap});
12        g[t].pb((edge){s, sz(g[s]) - 1, 0, 0});
13    }
14    bool dinic_bfs() {
15        fill(all(dist), -1);
16        dist[src] = 0;
17        int qt = 0;
18        q[qt++] = src;
19        for (int qh = 0; qh < qt; qh++) {
20            int u = q[qh];
21            rep(i, 0, sz(g[u])) {
22                edge &e = g[u][i];
23                int v = g[u][i].to;
24                if (dist[v] < 0 && e.f < e.cap)
25                    dist[v] = dist[u] + 1, q[qt++] = v;
26            }
27        }
28        return dist[dst] >= 0;
29    }
30    ll dinic_dfs(int u, ll f) {
31        if (u == dst) return f;
32        for (int &i = work[u]; i < sz(g[u]); i++) {
33            edge &e = g[u][i];

```

```

34        if (e.cap <= e.f) continue;
35        int v = e.to;
36        if (dist[v] == dist[u] + 1) {
37            ll df = dinic_dfs(v, min(f, e.cap - e.f));
38            if (df > 0) {
39                e.f += df;
40                g[v][e.rev].f -= df;
41                return df;
42            }
43        }
44    }
45    return 0;
46 }
47 ll max_flow(int _src, int _dst) {
48     src = _src, dst = _dst;
49     ll result = 0;
50     while (dinic_bfs()) {
51         fill(all(work), 0);
52         while (ll delta = dinic_dfs(src, 1e18)) result += delta;
53     }
54     return result;
55 }
56 };

```

4.2 Flow's Utilities

```

1 // Get path of max flow
2 void dfs_max_flow(int u, int v) {
3     each(i, g[u]) {
4         if (i.f > 0 && i.f < 1e9 && i.f < i.cap && i.to != v) {
5             res[u][i.to % n] = i.f;
6             i.f = 0;
7             dfs_max_flow(i.to, u);
8         }
9     }
10 }
11 // Convert a 2D matrix as a bipartite graph with 2 nodes (in/out)
12 void matrix_to_bipartite_graph(int n, int m) {
13     int s, t, dx[] = {1, -1, 0, 0}, dy[] = {0, 0, 1, -1};
14     Dinic nf(2 * n * m + 2);
15     rep(i, 0, n) {
16         rep(j, 0, m) {
17             char c = matrix[i][j];

```

```

18     int u = 2 * (n * j + i), cap = 1e9;
19     if(c == '#') continue;
20     else if(c == '.') cap = 1;
21     else if(c == 'A') s = u;
22     else if(c == 'B') t = u;
23     nf.add_edge(u, u+1, cap);
24     rep(k,0,4) {
25         int x = i+dx[k], y = j+dy[k], v = 2*(n*y+x);
26         if(x<0 || x>=n || y<0 || y>=m) continue;
27         nf.add_edge(u+1, v, cap);
28     }
29 }
30 }
31 ll mx=nf.max_flow(s,t+1);
32 }
33 // Get min cut
34 void dfs_min_cut(int u){ // Mark saturated nodes from source
35     vis[u] = 1;
36     each(i, g[u])
37         if(!vis[i.to] && i.f < i.cap)
38             dfs_min_cut(i.to);
39 }
40 void print_min_cut(int s) {
41     dfs_min_cut(s);
42     rep(i,0,n) { // Check for not saturated nodes from
43         rep(j,0,m) { // saturated nodes and mark them as part
44             int u = 2 * (n * j + i); // of the answer.
45             if(nf.vis[u]) {
46                 each(v, nf.g[u]){
47                     if(!nf.vis[v.to] && v.cap > 0)
48                         res[i][j] = v.to;
49                 }
50             }
51         }
52     }
53 }

```

4.3 Min cost-Max Flow

```

1 typedef ll tf;
2 typedef ll tc;
3 const tf INFFLOW=1e9;
4 const tc INFCOST=1e9;

```

```

5 struct MCF{
6     int n;
7     vector<tc> prio, pot; vector<tf> curflow; vector<int> prevedge,
8         prevnode;
9     priority_queue<pair<tc, int>, vector<pair<tc, int>>, greater<pair<tc,
10         int>>> q;
11     struct edge{int to, rev; tf f, cap; tc cost;};
12     vector<vector<edge>> g;
13     MCF(int n):n(n),prio(n),curflow(n),prevedge(n),prevnode(n),pot(n),g(n)
14         {}
15     void add_edge(int s, int t, tf cap, tc cost) {
16         g[s].pb((edge){t,sz(g[t]),0,cap,cost});
17         g[t].pb((edge){s,sz(g[s])-1,0,0,-cost});
18     }
19     pair<tf,tc> get_flow(int s, int t) {
20         tf flow=0; tc flowcost=0;
21         while(1){
22             q.push({0, s});
23             fill(ALL(prio),INFCOST);
24             prio[s]=0; curflow[s]=INFFLOW;
25             while(!q.empty()) {
26                 auto cur=q.top();
27                 tc d=cur.fst;
28                 int u=cur.snd;
29                 q.pop();
30                 if(d!=prio[u]) continue;
31                 for(int i=0; i<sz(g[u]); ++i) {
32                     edge &e=g[u][i];
33                     int v=e.to;
34                     if(e.cap<=e.f) continue;
35                     tc nprio=prio[u]+e.cost+pot[u]-pot[v];
36                     if(prio[v]>nprio) {
37                         prio[v]=nprio;
38                         q.push({nprio, v});
39                         prevnode[v]=u; prevedge[v]=i;
40                         curflow[v]=min(curflow[u], e.cap-e.f);
41                     }
42                 }
43             }
44             if(prio[t]==INFCOST) break;
45             fore(i,0,n) pot[i]+=prio[i];
46             tf df=min(curflow[t], INFFLOW-flow);
47             flow+=df;

```

```

45     for(int v=t; v!=s; v=prevnode[v]) {
46         edge &e=g[prevnode[v]][prevedge[v]];
47         e.f+=df; g[v][e.rev].f-=df;
48         flowcost+=df*e.cost;
49     }
50 }
51 return {flow,flowcost};
52 }
53 };

```

4.4 Hungarian

```

1  typedef long double td; typedef vector<int> vi; typedef vector<td> vd;
2  const td INF=1e100;//for maximum set INF to 0, and negate costs
3  bool zero(td x){return fabs(x)<1e-9;}//change to x==0, for ints/ll
4  struct Hungarian{
5      int n; vector<vd> cs; vi L, R;
6      Hungarian(int N, int M):n(max(N,M)),cs(n,vd(n)),L(n),R(n){
7          fore(x,0,N)fore(y,0,M)cs[x][y]=INF;
8      }
9      void set(int x,int y,td c){cs[x][y]=c;}
10     td assign() {
11         int mat = 0; vd ds(n), u(n), v(n); vi dad(n), sn(n);
12         fore(i,0,n)u[i]=*min_element(ALL(cs[i]));
13         fore(j,0,n){v[j]=cs[0][j]-u[0];fore(i,1,n)v[j]=min(v[j],cs[i][j]-u[i]);}
14         L=R=vi(n, -1);
15         fore(i,0,n)fore(j,0,n)
16             if(R[j]==-1&&zero(cs[i][j]-u[i]-v[j])){L[i]=j;R[j]=i;mat++;break;}
17         for(;mat<n;mat++){
18             int s=0, j=0, i;
19             while(L[s] != -1)s++;
20             fill(ALL(dad),-1);fill(ALL(sn),0);
21             fore(k,0,n)ds[k]=cs[s][k]-u[s]-v[k];
22             for(;;){
23                 j = -1;
24                 fore(k,0,n)if(!sn[k]&&(j==-1||ds[k]<ds[j]))j=k;
25                 sn[j] = 1; i = R[j];
26                 if(i == -1) break;
27                 fore(k,0,n)if(!sn[k]){
28                     auto new_ds=ds[j]+cs[i][k]-u[i]-v[k];
29                     if(ds[k] > new_ds){ds[k]=new_ds;dad[k]=j;}
30                 }

```

```

31     }
32     fore(k,0,n)if(k!=j&&sn[k]){auto w=ds[k]-ds[j];v[k]+=w,u[R[k]]-=w;
33         ;}
34     u[s] += ds[j];
35     while(dad[j]>=0){int d = dad[j];R[j]=R[d];L[R[j]]=j;j=d;}
36     R[j]=s;L[s]=j;
37 }
38 td value=0;fore(i,0,n)value+=cs[i][L[i]];
39 return value;
40 };

```

4.5 Edmonds-Karps

```

1  struct Edmons{
2      #define ll long long
3      int n;
4      vector<int>d;
5      vector<tuple<int,ll,ll>>edges;
6      vector<vector<int>> adj;
7      vector<pair<int,int>>cam;
8      Edmons(int _n):adj(_n+1,n(_n)){
9          ll sentFlow(int s,int t,ll f){
10             if(s==t)return f;
11             auto &[u,idx]=cam[t];
12             auto cap=get<1>(edges[idx]),&flow=get<2>(edges[idx]);
13             ll push=sentFlow(s,u,min(cap-flow,f));
14             flow+=push;
15             auto &flowr=get<2>(edges[idx^1]);
16             flowr-=push;
17             return push;
18         }
19         bool bfs(int s,int t){
20             d.assign(n+1,-1); d[s]=0;
21             cam.assign(n+1,{-1,-1});
22             queue<int> q({s});
23             while(!q.empty()){
24                 int u=q.front();
25                 q.pop();
26                 for(auto idx:adj[u]){
27                     auto &v=get<0>(edges[idx]);auto &cap=get<1>(edges[idx]),
28                         &flow=get<2>(edges[idx]);
29                     if(cap-flow>0 && d[v]==-1) d[v]=d[u]+1,cam[v]={u,idx},q.

```

```

17 point operator-(const point & p) const{return point(x - p.x, y - p.y);
18     };
19 point operator*(const ld & k) const{return point(x * k, y * k);}
20 point operator/(const ld & k) const{return point(x / k, y / k);}
21
22 point operator+=(const point & p){*this = *this + p; return *this;}
23 point operator-=(const point & p){*this = *this - p; return *this;}
24 point operator*=(const ld & p){*this = *this * p; return *this;}
25 point operator/=(const ld & p){*this = *this / p; return *this;}
26
27 point rotate(const ld & a) const{return point(x*cos(a) - y*sin(a), x*
28     sin(a) + y*cos(a));}
29 point perp() const{return point(-y, x);}
30 ld ang() const{
31     ld a = atan2l(y, x); a += le(a, 0) ? 2*pi : 0; return a;
32 }
33 ld dot(const point & p) const{return x * p.x + y * p.y;}
34 ld cross(const point & p) const{return x * p.y - y * p.x;}
35 ld norm() const{return x * x + y * y;}
36 ld length() const{return sqrtl(x * x + y * y);}
37 point unit() const{return (*this) / length();}

```

5.1 Puntos y líneas

```

37     bool operator==(const point & p) const{return eq(x, p.x) && eq(y, p.y);
    };
38     bool operator!=(const point & p) const{return !(*this == p);}
39     bool operator<(const point & p) const{return le(x, p.x) || (eq(x, p.x)
        && le(y, p.y));}
40     bool operator>(const point & p) const{return ge(x, p.x) || (eq(x, p.x)
        && ge(y, p.y));}
41     bool half(const point & p) const{return le(p.cross(*this), 0) || (eq(p
        .cross(*this), 0) && le(p.dot(*this), 0));}
42 };
43
44 istream &operator>>(istream &is, point & p){return is >> p.x >> p.y;}
45 ostream &operator<<(ostream &os, const point & p){return os << "(" << p.
    x << ", " << p.y << ")";}
46
47 int sgn(ld x){
48     if(ge(x, 0)) return 1;
49     if(le(x, 0)) return -1;
50     return 0;
51 }

```

```

52
53 void polarSort(vector<point> & P, const point & o, const point & v){
54     //sort points in P around o, taking the direction of v as first angle
55     sort(P.begin(), P.end(), [&](const point & a, const point & b){
56         return point((a - o).half(v), 0) < point((b - o).half(v), (a - o).
57             cross(b - o));
58     });
59 }
60 bool pointInLine(const point & a, const point & v, const point & p){
61     //line a+tv, point p
62     return eq((p - a).cross(v), 0);
63 }
64
65 bool pointInSegment(const point & a, const point & b, const point & p){
66     //segment ab, point p
67     return pointInLine(a, b - a, p) && leq((a - p).dot(b - p), 0);
68 }
69
70 int intersectLinesInfo(const point & a1, const point & v1, const point &
71     a2, const point & v2){
72     //lines a1+tv1 and a2+tv2
73     ld det = v1.cross(v2);
74     if(eq(det, 0)){
75         if(eq((a2 - a1).cross(v1), 0)){
76             return -1; //infinity points
77         }else{
78             return 0; //no points
79         }
80     }else{
81         return 1; //single point
82     }
83 }
84 point intersectLines(const point & a1, const point & v1, const point &
85     a2, const point & v2){
86     //lines a1+tv1, a2+tv2
87     //assuming that they intersect
88     ld det = v1.cross(v2);
89     return a1 + v1 * ((a2 - a1).cross(v2) / det);
90 }
91 int intersectLineSegmentInfo(const point & a, const point & v, const

```

```

92     point & c, const point & d){
93     //line a+tv, segment cd
94     point v2 = d - c;
95     ld det = v.cross(v2);
96     if(eq(det, 0)){
97         if(eq((c - a).cross(v), 0)){
98             return -1; //infinity points
99         }else{
100             return 0; //no point
101         }
102     }else{
103         return sgn(v.cross(c - a)) != sgn(v.cross(d - a)); //1: single point
104         , 0: no point
105     }
106 }
107
108 int intersectSegmentsInfo(const point & a, const point & b, const point
109     & c, const point & d){
110     //segment ab, segment cd
111     point v1 = b - a, v2 = d - c;
112     int t = sgn(v1.cross(c - a)), u = sgn(v1.cross(d - a));
113     if(t == u){
114         if(t == 0){
115             if(pointInSegment(a, b, c) || pointInSegment(a, b, d) ||
116                 pointInSegment(c, d, a) || pointInSegment(c, d, b)){
117                 return -1; //infinity points
118             }else{
119                 return 0; //no point
120             }
121         }else{
122             return 0; //no point
123         }
124     }else{
125         return sgn(v2.cross(a - c)) != sgn(v2.cross(b - c)); //1: single
126         point, 0: no point
127     }
128 }
129
130 ld distancePointLine(const point & a, const point & v, const point & p){
131     //line: a + tv, point p
132     return abs(v.cross(p - a)) / v.length();
133 }

```

5.2 Circulos

```

1 ld distancePointCircle(const point & c, ld r, const point & p){
2     //point p, circle with center c and radius r
3     return max((ld)0, (p - c).length() - r);
4 }
5
6 point projectionPointCircle(const point & c, ld r, const point & p){
7     //point p (outside the circle), circle with center c and radius r
8     return c + (p - c).unit() * r;
9 }
10
11 pair<point, point> pointsOfTangency(const point & c, ld r, const point &
12     p){
13     //point p (outside the circle), circle with center c and radius r
14     point v = (p - c).unit() * r;
15     ld d2 = (p - c).norm(), d = sqrt(d2);
16     point v1 = v * (r / d), v2 = v.perp() * (sqrt(d2 - r*r) / d);
17     return {c + v1 - v2, c + v1 + v2};
18 }
19
20 vector<point> intersectLineCircle(const point & a, const point & v,
21     const point & c, ld r){
22     //line a+tv, circle with center c and radius r
23     ld h2 = r*r - v.cross(c - a) * v.cross(c - a) / v.norm();
24     point p = a + v * v.dot(c - a) / v.norm();
25     if(eq(h2, 0)) return {p}; //line tangent to circle
26     else if(1e(h2, 0)) return {}; //no intersection
27     else{
28         point u = v.unit() * sqrt(h2);
29         return {p - u, p + u}; //two points of intersection (chord)
30     }
31 }
32
33 vector<point> intersectSegmentCircle(const point & a, const point & b,
34     const point & c, ld r){
35     //segment ab, circle with center c and radius r
36     vector<point> P = intersectLineCircle(a, b - a, c, r), ans;
37     for(const point & p : P){
38         if(pointInSegment(a, b, p)) ans.push_back(p);
39     }
40     return ans;
41 }

```

```

39
40 pair<point, ld> getCircle(const point & m, const point & n, const point
41     & p){
42     //find circle that passes through points p, q, r
43     point c = intersectLines((n + m) / 2, (n - m).perp(), (p + n) / 2, (p
44         - n).perp());
45     ld r = (c - m).length();
46     return {c, r};
47 }
48
49 vector<point> intersectionCircles(const point & c1, ld r1, const point &
50     c2, ld r2){
51     //circle 1 with center c1 and radius r1
52     //circle 2 with center c2 and radius r2
53     point d = c2 - c1;
54     ld d2 = d.norm();
55     if(eq(d2, 0)) return {}; //concentric circles
56     ld pd = (d2 + r1*r1 - r2*r2) / 2;
57     ld h2 = r1*r1 - pd*pd/d2;
58     point p = c1 + d*pd/d2;
59     if(eq(h2, 0)) return {p}; //circles touch at one point
60     else if(1e(h2, 0)) return {}; //circles don't intersect
61     else{
62         point u = d.perp() * sqrt(h2/d2);
63         return {p - u, p + u};
64     }
65 }
66
67 int circleInsideCircle(const point & c1, ld r1, const point & c2, ld r2)
68 {
69     //test if circle 2 is inside circle 1
70     //returns "-1" if 2 touches internally 1, "1" if 2 is inside 1, "0" if
71     they overlap
72     ld l = r1 - r2 - (c1 - c2).length();
73     return (ge(l, 0) ? 1 : (eq(l, 0) ? -1 : 0));
74 }
75
76 int circleOutsideCircle(const point & c1, ld r1, const point & c2, ld r2)
77 {
78     //test if circle 2 is outside circle 1
79     //returns "-1" if they touch externally, "1" if 2 is outside 1, "0" if
80     they overlap
81     ld l = (c1 - c2).length() - (r1 + r2);

```

```

75     return (ge(l, 0) ? 1 : (eq(l, 0) ? -1 : 0));
76 }
77
78 int pointInCircle(const point & c, ld r, const point & p){
79     //test if point p is inside the circle with center c and radius r
80     //returns "0" if it's outside, "-1" if it's in the perimeter, "1" if
        it's inside
81     ld l = (p - c).length() - r;
82     return (le(l, 0) ? 1 : (eq(l, 0) ? -1 : 0));
83 }
84
85 vector<vector<point>> tangents(const point & c1, ld r1, const point & c2
        , ld r2, bool inner){
86     //returns a vector of segments or a single point
87     if(inner) r2 = -r2;
88     point d = c2 - c1;
89     ld dr = r1 - r2, d2 = d.norm(), h2 = d2 - dr*dr;
90     if(eq(d2, 0) || le(h2, 0)) return {};
91     point v = d*dr/d2;
92     if(eq(h2, 0)) return {{c1 + v*r1}};
93     else{
94         point u = d.perp()*sqrt(h2)/d2;
95         return {{c1 + (v - u)*r1, c2 + (v - u)*r2}, {c1 + (v + u)*r1, c2 + (
            v + u)*r2}};
96     }
97 }
98
99 ld signed_angle(const point & a, const point & b){
100     return sgn(a.cross(b)) * acosl(a.dot(b) / (a.length() * b.length()));
101 }
102
103 ld intersectPolygonCircle(const vector<point> & P, const point & c, ld r
    ){
104     //Gets the area of the intersection of the polygon with the circle
105     int n = P.size();
106     ld ans = 0;
107     for(int i = 0; i < n; ++i){
108         point p = P[i], q = P[(i+1)%n];
109         bool p_inside = (pointInCircle(c, r, p) != 0);
110         bool q_inside = (pointInCircle(c, r, q) != 0);
111         if(p_inside && q_inside){
112             ans += (p - c).cross(q - c);
113         }else if(p_inside && !q_inside){

```

```

114         point s1 = intersectSegmentCircle(p, q, c, r)[0];
115         point s2 = intersectSegmentCircle(c, q, c, r)[0];
116         ans += (p - c).cross(s1 - c) + r*r * signed_angle(s1 - c, s2 - c);
117     }else if(!p_inside && q_inside){
118         point s1 = intersectSegmentCircle(c, p, c, r)[0];
119         point s2 = intersectSegmentCircle(p, q, c, r)[0];
120         ans += (s2 - c).cross(q - c) + r*r * signed_angle(s1 - c, s2 - c);
121     }else{
122         auto info = intersectSegmentCircle(p, q, c, r);
123         if(info.size() <= 1){
124             ans += r*r * signed_angle(p - c, q - c);
125         }else{
126             point s2 = info[0], s3 = info[1];
127             point s1 = intersectSegmentCircle(c, p, c, r)[0];
128             point s4 = intersectSegmentCircle(c, q, c, r)[0];
129             ans += (s2 - c).cross(s3 - c) + r*r * (signed_angle(s1 - c, s2 -
                c) + signed_angle(s3 - c, s4 - c));
130         }
131     }
132 }
133 return abs(ans)/2;
134 }

```

5.3 Poligonos

```

1 ld perimeter(vector<point> & P){
2     int n = P.size();
3     ld ans = 0;
4     for(int i = 0; i < n; i++){
5         ans += (P[i] - P[(i + 1) % n]).length();
6     }
7     return ans;
8 }
9
10 ld area(vector<point> & P){
11     int n = P.size();
12     ld ans = 0;
13     for(int i = 0; i < n; i++){
14         ans += P[i].cross(P[(i + 1) % n]);
15     }
16     return abs(ans / 2);
17 }
18

```



```

19 vector<point> convexHull(vector<point> P){
20     sort(P.begin(), P.end());
21     vector<point> L, U;
22     for(int i = 0; i < P.size(); i++){
23         while(L.size() >= 2 && leq((L[L.size() - 2] - P[i]).cross(L[L.size()
24             - 1] - P[i]), 0)){
25             L.pop_back();
26         }
27         L.push_back(P[i]);
28     }
29     for(int i = P.size() - 1; i >= 0; i--){
30         while(U.size() >= 2 && leq((U[U.size() - 2] - P[i]).cross(U[U.size()
31             - 1] - P[i]), 0)){
32             U.pop_back();
33         }
34         U.push_back(P[i]);
35     }
36     L.pop_back();
37     U.pop_back();
38     L.insert(L.end(), U.begin(), U.end());
39     return L;
40 }
41
42 bool pointInPerimeter(const vector<point> & P, const point & p){
43     int n = P.size();
44     for(int i = 0; i < n; i++){
45         if(pointInSegment(P[i], P[(i + 1) % n], p)){
46             return true;
47         }
48     }
49     return false;
50 }
51
52 bool crossesRay(const point & a, const point & b, const point & p){
53     return (geq(b.y, p.y) - geq(a.y, p.y)) * sgn((a - p).cross(b - p)) >
54         0;
55 }
56
57 int pointInPolygon(const vector<point> & P, const point & p){
58     if(pointInPerimeter(P, p)){
59         return -1; //point in the perimeter
60     }
61     int n = P.size();

```

```

59     int rays = 0;
60     for(int i = 0; i < n; i++){
61         rays += crossesRay(P[i], P[(i + 1) % n], p);
62     }
63     return rays & 1; //0: point outside, 1: point inside
64 }
65
66 //point in convex polygon in O(log n)
67 //make sure that P is convex and in ccw
68 //before the queries, do the preprocess on P:
69 // rotate(P.begin(), min_element(P.begin(), P.end()), P.end());
70 // int right = max_element(P.begin(), P.end()) - P.begin();
71 //returns 0 if p is outside, 1 if p is inside, -1 if p is in the
    perimeter
72 int pointInConvexPolygon(const vector<point> & P, const point & p, int
    right){
73     if(p < P[0] || P[right] < p) return 0;
74     int orientation = sgn((P[right] - P[0]).cross(p - P[0]));
75     if(orientation == 0){
76         if(p == P[0] || p == P[right]) return -1;
77         return (right == 1 || right + 1 == P.size()) ? -1 : 1;
78     }else if(orientation < 0){
79         auto r = lower_bound(P.begin() + 1, P.begin() + right, p);
80         int det = sgn((p - r[-1]).cross(r[0] - r[-1])) - 1;
81         if(det == -2) det = 1;
82         return det;
83     }else{
84         auto l = upper_bound(P.rbegin(), P.rend() - right - 1, p);
85         int det = sgn((p - l[0]).cross((l == P.rbegin() ? P[0] : l[-1]) - l
86             [0])) - 1;
87         if(det == -2) det = 1;
88         return det;
89     }
90 }
91
92 vector<point> cutPolygon(const vector<point> & P, const point & a, const
    point & v){
93     //returns the part of the convex polygon P on the left side of line a+
94     tv
95     int n = P.size();
96     vector<point> lhs;
97     for(int i = 0; i < n; ++i){
98         if(geq(v.cross(P[i] - a), 0)){

```

```

97     lhs.push_back(P[i]);
98 }
99 if(intersectLineSegmentInfo(a, v, P[i], P[(i+1)%n]) == 1){
100     point p = intersectLines(a, v, P[i], P[(i+1)%n] - P[i]);
101     if(p != P[i] && p != P[(i+1)%n]){
102         lhs.push_back(p);
103     }
104 }
105 }
106 return lhs;
107 }

```

6 Matematicas

6.1 Exponenciacion Binaria

```

1 ll binpow(ll a, ll b, ll mod) {
2     a %= mod;
3     ll res = 1;
4     while (b > 0) {
5         if (b & 1)
6             res = res * a % mod;
7         a = a * a % mod;
8         b >>= 1;
9     }
10    return res;
11 }
12
13 ll binpow(ll a, ll b) {
14     if (b == 0)
15         return 1;
16     ll res = binpow(a, b / 2);
17     if (b % 2)
18         return res * res * a;
19     else
20         return res * res;
21 }

```

6.2 GCD y LCD

```

1 ll gcd(ll a, ll b){
2     ll r;
3     while(b != 0) r = a % b, a = b, b = r;

```

```

4     return a;
5 }
6
7 ll lcm(ll a, ll b){
8     return b * (a / gcd(a, b));
9 }
10
11 ll gcd(const vector<ll>& nums){
12     ll ans = 0;
13     for(ll num : nums) ans = gcd(ans, num);
14     return ans;
15 }
16
17 ll lcm(const vector<ll>& nums){
18     ll ans = 1;
19     for(ll num : nums) ans = lcm(ans, num);
20     return ans;
21 }

```

6.3 Euclides extendido e inverso modular

```

1 tuple<lli, lli, lli> extendedGcd(lli a, lli b){
2     if(b == 0){
3         if(a > 0) return {a, 1, 0};
4         else return {-a, -1, 0};
5     }else{
6         auto[d, x, y] = extendedGcd(b, a%b);
7         return {d, y, x - y*(a/b)};
8     }
9 }
10
11 lli modularInverse(lli a, lli m){
12     auto[d, x, y] = extendedGcd(a, m);
13     if(d != 1) return -1; // inverse doesn't exist
14     if(x < 0) x += m;
15     return x;
16 }

```

6.4 Fibonacci

```

1 //very fast fibonacci
2 inline void modula(lli & n, lli mod){
3     while(n >= mod) n -= mod;
4 }

```

```

5
6 lli fibo(lli n, lli mod){
7     array<lli, 2> F = {1, 0};
8     lli p = 1;
9     for(lli v = n; v >= 1; p <= 1);
10    array<lli, 4> C;
11    do{
12        int d = (n & p) != 0;
13        C[0] = C[3] = 0;
14        C[d] = F[0] * F[0] % mod;
15        C[d+1] = (F[0] * F[1] << 1) % mod;
16        C[d+2] = F[1] * F[1] % mod;
17        F[0] = C[0] + C[2] + C[3];
18        F[1] = C[1] + C[2] + (C[3] << 1);
19        modula(F[0], mod), modula(F[1], mod);
20    }while(p >= 1);
21    return F[1];
22 }
23
24 const long M = 1000000007; // modulo
25 map<long, long> F;
26
27 long f(long n) {
28     if (F.count(n)) return F[n];
29     long k=n/2;
30     if (n%2==0) { // n=2*k
31         return F[n] = (f(k)*f(k) + f(k-1)*f(k-1)) % M;
32     } else { // n=2*k+1
33         return F[n] = (f(k)*f(k+1) + f(k-1)*f(k)) % M;
34     }
35 }
36
37 main(){
38     long n;
39     F[0]=F[1]=1;
40     while (cin >> n)
41         cout << (n==0 ? 0 : f(n-1)) << endl;
42 }

```

6.5 Criba de Primos

```

1 vector<int> linearPrimeSieve(int n){
2     vector<int> primes;

```

```

3     vector<bool> isPrime(n+1, true);
4     for(int i = 2; i <= n; ++i){
5         if(isPrime[i])
6             primes.push_back(i);
7         for(int p : primes){
8             int d = i * p;
9             if(d > n) break;
10            isPrime[d] = false;
11            if(i % p == 0) break;
12        }
13    }
14    return primes;
15 }

```

6.6 Triangulo de Pascal

```

1 vector<vector<lli>> ncrSieve(int n){
2     vector<vector<lli>> Ncr(n+1);
3     Ncr[0] = {1};
4     for(int i = 1; i <= n; ++i){
5         Ncr[i].resize(i + 1);
6         Ncr[i][0] = Ncr[i][i] = 1;
7         for(int j = 1; j <= i / 2; j++){
8             Ncr[i][i - j] = Ncr[i][j] = Ncr[i - 1][j - 1] + Ncr[i - 1][j];
9         }
10        return Ncr;
11    }

```

6.7 Cambio de bases

```

1 string decimalToBaseB(lli n, lli b){
2     string ans = "";
3     lli d;
4     do{
5         d = n % b;
6         if(0 <= d && d <= 9) ans = (char)(48 + d) + ans;
7         else if(10 <= d && d <= 35) ans = (char)(55 + d) + ans;
8         n /= b;
9     }while(n != 0);
10    return ans;
11 }
12
13 lli baseBtoDecimal(const string & n, lli b){
14     lli ans = 0;

```

```

15 for(const char & d : n){
16     if(48 <= d && d <= 57) ans = ans * b + (d - 48);
17     else if(65 <= d && d <= 90) ans = ans * b + (d - 55);
18     else if(97 <= d && d <= 122) ans = ans * b + (d - 87);
19 }
20 return ans;
21 }

```

6.8 Factorizacion

```

1 vector<pair<lli, int>> factorize(lli n){
2     vector<pair<lli, int>> f;
3     for(lli p : primes){
4         if(p * p > n) break;
5         int pot = 0;
6         while(n % p == 0){
7             pot++;
8             n /= p;
9         }
10        if(pot) f.emplace_back(p, pot);
11    }
12    if(n > 1) f.emplace_back(n, 1);
13    return f;
14 }

```

7 Varios

7.1 String a vector int

```

1 //Convertir una cadena de numeros separados por " " en vector de enteros
2 //Leer varias de esas queries
3 cin.ignore();
4 while(q--){
5     string s;
6     getline(cin, s);
7     vector<int> qr;
8     stringstream ss(s);
9     int num;
10    while (ss >> num)    qr.push_back(num);
11 }

```

7.2 Generar permutaciones

```

1 //Generar todas las permutaciones de un arreglo

```

```

2 sort(all(a));
3 do{
4     //hacer lo que quieras con la perm generada
5 }while(next_permutation(all(a)));

```

7.3 2-Sat

```

1 struct twoSat{
2     int s;
3     vector<vector<int>> g,gr;
4     vector<int> visited,ids,topologic_sort,val;
5     twoSat(int n){
6         s=n;
7         g.assign(n*2+1,vector<int>());
8         gr.assign(n*2+1,vector<int>());
9         visited.assign(n*2+1,0);
10        ids.assign(n*2+1,0);
11        val.assign(n+1,0);
12    }
13    void addEdge(int a,int b){
14        g[a].push_back(b);
15        gr[b].push_back(a);
16    }
17    void addOr(int a,bool ba,int b,bool bb){
18        addEdge(a+(ba?s:0),b+(bb?0:s));
19        addEdge(b+(bb?s:0),a+(ba?0:s));
20    }
21    void addXor(int a,bool ba,int b,bool bb){
22        addOr(a,ba,b,bb);
23        addOr(a,!ba,b,!bb);
24    }
25    void addAnd(int a,bool ba,int b,bool bb){
26        addXor(a,!ba,b,bb);
27    }
28    void dfs(int u){
29        if(visited[u]!=0) return;
30        visited[u]=1;
31        for(int node:g[u])dfs(node);
32        topologic_sort.push_back(u);
33    }
34    void dfsr(int u,int id){
35        if(visited[u]!=0) return;
36        visited[u]=1;

```

```

37     ids[u]=id;
38     for(int node:gr[u])dfs(node,id);
39 }
40 bool algo(){
41     for(int i=0;i<s*2;i++) if(visited[i]==0) dfs(i);
42     fill(visited.begin(),visited.end(),0);
43     reverse(topologic_sort.begin(),topologic_sort.end());
44     int id=0;
45     for(int i=0;i<topologic_sort.size();i++){
46         if(visited[topologic_sort[i]]==0)dfs(topologic_sort[i],id
47             ++);
48     }
49     for(int i=0;i<s;i++){
50         if(ids[i]==ids[i+s]) return false;
51         val[i]=(ids[i]>ids[i+s]?0:1);
52     }
53     return true;
54 };

```

7.4 Bits

```

1 // Return the numbers the numbers of 1-bit in x
2 int __builtin_popcount (unsigned int x)
3 // Returns the number of trailing 0-bits in x. x=0 is undefined.
4 int __builtin_ctz (unsigned int x)
5 // Returns the number of leading 0-bits in x. x=0 is undefined.
6 int __builtin_clz (unsigned int x)
7 // x of type long long just add 'll' at the end of the function.
8 int __builtin_popcountll (unsigned long long x)
9 // Get the value of the least significant bit that is one.
10 v=(x&(-x))

```

7.5 Matrix

```

1 const int N=100, MOD=1e9+7;
2 struct Matrix {
3     ll a[N][N];
4     Matrix() {memset(a,0,sizeof(a));}
5     Matrix operator *(Matrix other) { // Product of a matrix
6         Matrix product=Matrix();
7         rep(i,0,N) rep(j,0,N) rep(k,0,N) {
8             product.a[i][k] += a[i][j]*other.a[j][k];
9             product.a[i][k] %= MOD;

```

```

10     }
11     return product;
12 }
13 };
14 Matrix expo_power(Matrix a, ll n) { // Matrix exponentiation
15     Matrix res=Matrix();
16     rep(i,0,N) res.a[i][i]=1; // Matriz identidad
17     while(n){
18         if(n&1) res=res*a;
19         n>>=1;
20         a=a*a;
21     }
22     return res;
23 } // Ej. Matrix M=Matrix(); M.a[0][0]=1; M=M*M; Matrix res=
    expo_power(M,k);

```

7.6 Mo's Algorithm

```

1 void remove(idx); // TODO: remove value at idx from data structure
2 void add(idx); // TODO: add value at idx from data structure
3 int get_answer(); // TODO: extract the current answer of the data
4 structure
5 int block_size;//Recomended sqrt(n)
6
7 struct Query {
8     int l, r, idx;
9     bool operator<(Query other) const
10     {
11         return make_pair(l / block_size, r) <
12             make_pair(other.l / block_size, other.r);
13     }
14 };
15
16 vector<int> mo_s_algorithm(vector<Query> queries) {
17     vector<int> answers(queries.size());
18     sort(queries.begin(), queries.end());
19
20     // TODO: initialize data structure
21
22     int cur_l = 0;
23     int cur_r = -1;
24     // invariant: data structure will always reflect the range [cur_l,

```

```

    cur_r]
25 for (Query q : queries) {
26     while (cur_l > q.l) {
27         cur_l--;
28         add(cur_l);
29     }
30     while (cur_r < q.r) {
31         cur_r++;
32         add(cur_r);
33     }
34     while (cur_l < q.l) {
35         remove(cur_l);
36         cur_l++;
37     }
38     while (cur_r > q.r) {
39         remove(cur_r);
40         cur_r--;
41     }
42     answers[q.idx] = get_answer();
43 }
44 return answers;
45 }

```

7.7 PBS

```

1
2 1.Crear un arreglo con para procesar
3 2.Para cada elemento inicializar 1 l y en q+1 r;
4 for(int i=1;i<=n;i++){
5     m[i].x=1,m[i].y=q+1;
6 }
7 bool flag=true;
8 while(flag){
9     flag=false;
10    // limpiar la estructura de datos
11    for(int i=0;i<=4*n+5;i++)st[i]=0,lazy[i]=0;
12    for(int i=1;i<=n;i++){
13        //Si es diefente l!=r se procesa;
14        if(m[i].x!=m[i].y){ flag=true;tocheck[(m[i].x+m[i].y)/2].
15            push_back(i);}
16    for(int i=1;i<=q;i++){
17        if(!flag)break;
18        // Se aplican las queries

```

```

18    update(0,n-1,qs[i].x,qs[i].y,qs[i].z,0);
19    update(0,n-1,qs[i].x,qs[i].x,qs[i].k,0);
20    while(tocheck[i].size()){
21        int id=tocheck[i].back();
22        tocheck[i].pop_back();
23        // Se obserba si se cumblío la caondicion para el
24        elemeto
25        if(ai[id]<=query(0,n-1,S[id],S[id],0)) m[id].y=i;
26        else m[id].x=i+1;
27    }
28 }
29 // Solo se imprime
30 for(int i=1;i<=n;i++){
31     if(m[i].x<=q) cout<<m[i].x<<endl;
32     else cout<<-1<<endl;
33 }

```

7.8 Dates

```

1 int dateToInt(int y, int m, int d){
2     return 1461*(y+4800+(m-14)/12)/4+367*(m-2-(m-14)/12*12)/12-
3         3*((y+4900+(m-14)/12)/100)/4+d-32075;
4 }
5 void intToDate(int jd, int& y, int& m, int& d){
6     int x,n,i,j;x=jd+68569;
7     n=4*x/146097;x-=(146097*n+3)/4;
8     i=(4000*(x+1))/1461001;x-=1461*i/4-31;
9     j=80*x/2447;d=x-2447*j/80;
10    x=j/11;m=j+2-12*x;y=100*(n-49)+i+x;
11 }
12 int DayOfWeek(int d, int m, int y){ //starting on Sunday
13     static int ttt[]={0, 3, 2, 5, 0, 3, 5, 1, 4, 6, 2, 4};
14     y-=m<3;
15     return (y+y/4-y/100+y/400+ttt[m-1]+d)%7;
16 }

```

8 Template

```

1 #include<bits/stdc++.h>
2 using namespace std;
3
4 #define forn(i,n) for(int i=0; i<n; i++)

```

```
5 #define forr(i,a,n)    for(int i=a; i<n; i++)
6 #define fore(i,a,n)   for(int i=a; i<=n; i++)
7 #define each(a,b)     for(auto a: b)
8 #define all(v)        v.begin(),v.end()
9 #define sz(a)         (int)a.size()
10 #define debln(a)      cout << a << "\n"
11 #define deb(a)        cout << a << " "
12 #define pb            push_back
13
14 typedef long long ll;
15 typedef vector<int> vi;
16 typedef pair<int,int> ii;
17
18 void sol(){
19
20 }
21
22 int main(){
23     ios::sync_with_stdio(false);cin.tie(0);
24
25     int t=1;
26     cin>>t;
27     while(t--){
28         sol();
29     }
30
31     return 0;
32 }
```