

Stat 760 Homework 7 Question 4

Will Bliss and Jakob Lovato

3/18/2022

```
#Generate data

#Radius of circles containing 10%, 20%, and 30% of area of unit square
R1 <- sqrt(0.1 / pi)
R2 <- sqrt(0.2 / pi)
R3 <- sqrt(0.3 / pi)

#Centers to use for each circle
c1 <- c(1 - R1, R1)
c2 <- c(R2, R2)
c3 <- c(1 - R3, 1 - R3)

#Generate points inside circles
insidex <- c()
insidey <- c()
while(TRUE){
  randx <- runif(1, min = 0, max = 1)
  randy <- runif(1, min = 0, max = 1)
  if((randx - c1[1]) ^ 2 + (randy - c1[2]) ^ 2 < (R1 ^ 2)){
    insidex <- c(insidex, randx)
    insidey <- c(insidey, randy)
  }
  if((randx - c2[1]) ^ 2 + (randy - c2[2]) ^ 2 < (R2 ^ 2)){
    insidex <- c(insidex, randx)
    insidey <- c(insidey, randy)
  }
  if((randx - c3[1]) ^ 2 + (randy - c3[2]) ^ 2 < (R3 ^ 2)){
    insidex <- c(insidex, randx)
    insidey <- c(insidey, randy)
  }
  if(length(insidex) >= 300){break}
}
inside <- data.frame(x = insidex, y = insidey)
plot(inside, asp = 1, col = "red")


#Generate points outside of circles
outsidex <- c()
outsidey <- c()
while(TRUE){
  randx <- runif(1, min = 0, max = 1)
  randy <- runif(1, min = 0, max = 1)
  if(((randx - c1[1]) ^ 2 + (randy - c1[2]) ^ 2 > (R1 ^ 2))
```

```

    & (randx - c2[1]) ^ 2 + (randy - c2[2]) ^ 2 > (R2 ^ 2)
    & (randx - c3[1]) ^ 2 + (randy - c3[2]) ^ 2 > (R3 ^ 2)){
      outsidex <- c(outside, randx)
      outsidex <- c(outside, randy)
      if(length(outside) >= 300){break}
    }
  }
outside <- data.frame(x = outside, y = outsidex)
points(outside, asp = 1, col = "blue")

#Overlay circles
draw.circle(c3[1], c3[2], R3)
draw.circle(c1[1], c1[2], R1)
draw.circle(c2[1], c2[2], R2)
lines(c(0,0), c(0,1))
lines(c(0,0), c(1,0))
lines(c(1,1), c(1,0))
lines(c(0,1), c(1,1))
lines(c(0,1), c(0,0))

```



```

#combine data
#class A = 0, class B = 1
outside <- cbind(outside, "class" = 0)
inside <- cbind(inside, "class" = 1)
data <- rbind(outside, inside)

#Generatre sigmoid function (activation function)
sigmoid <- function(x){
  1 / (1 + (exp(-x)))
}

derivative <- function(x){
  sigmoid(x) * (1 - sigmoid(x))
}

```

```

}

#Generate random initial weights
randWeights <- matrix(c(runif(2 * 10)), nrow = 2,
                      ncol = 10, byrow = TRUE)

#Store current step of neural network in training
nn <- list(
  input = cbind(data[, -3], "ones" = rep(1, 600)),
  w1 = rbind(randWeights, rep(0, ncol(randWeights))),
  w2 = rbind(matrix(runif(10), ncol = 1, byrow = TRUE), 0),
  target = data[, 3],
  preds = matrix(rep(0, nrow(data)), ncol = 1, byrow = TRUE),
  hidden = rep(0, 6001)
)

gamma <- 0.75

#train the model
for(count in 1:10000){
  #keep track of error
  errors <- c()
  #keep track of predictions
  predictions <- c()
  #update for every data point
  for(i in 1:600){
    #feed forward
    nn$hidden <- c(sigmoid(as.matrix(nn$input[i,]) %*% as.matrix(nn$w1)), 1)
    nn$preds <- c(sigmoid(nn$hidden %*% nn$w2), 1)
    predictions <- c(predictions, nn$preds[1])
    #backprop
    e <- nn$preds[-length(nn$preds)] - nn$target[i]
    errors <- c(errors, e)
    D1 <- diag(as.vector(nn$hidden[-length(nn$hidden)]
                      * (1 - as.vector(nn$hidden[-length(nn$hidden)]))))
    D2 <- as.vector(nn$preds[-length(nn$preds)]
                  * (1 - as.vector(nn$preds[-length(nn$preds)])))
    delta2 <- D2 * e
    delta1 <- (D1 %*% t(t(nn$w2[-11]))) * delta2
    nn$w2 <- nn$w2 + (-gamma * delta2 * as.matrix(nn$hidden))
    nn$w1 <- nn$w1 + (-gamma * t(delta1 %*% as.matrix(nn$input[i,])))
  }
}


#test neural network on 100x100 grid
pixels <- expand.grid(seq(0, 1, by = .01), seq(0, 1, by = .01))
pixels <- cbind(pixels, rep(1, nrow(pixels)))
classifiedPixels <- cbind(pixels[, -3], class = 0)
pixelPredictions <- c()
for(i in 1:nrow(pixels)){
  o1 <- cbind(sigmoid(as.matrix(pixels[i,]) %*% as.matrix(nn$w1)), 1)
  o2 <- sigmoid(o1 %*% as.matrix(nn$w2))
  pixelPredictions <- c(pixelPredictions, o2)
  #Define boundary as 0.95

```

```

if(o2 < 0.95){
  classifiedPixels[i,3] <- 0
}
else{
  classifiedPixels[i,3] <- 1
}
}
plot(classifiedPixels[which(classifiedPixels[,3] == 1), -3], col = "red", asp = 1)
points(classifiedPixels[which(classifiedPixels[,3] == 0), -3], col = "blue")

```



We also created a heatmap to see areas where classification is more difficult for the Neural Network. As expected, the expected values are further from 0 and 1 around the edges of the circles.

```

#Create Heatmap
heatmap <- cbind(pixels[, -3], pixelPredictions)
ggplot(heatmap, aes(heatmap[,1], heatmap[,2], fill = heatmap[,3])) +
  geom_tile() +
  scale_fill_distiller(palette = "Spectral")

```

