

Операционные системы

Анализ файловой структуры UNIX. Команды для работы с файлами и каталогами

Фахми Джакси Гамал Адли

11 марта 2025

Российский университет дружбы народов, Москва, Россия

Цели и задачи работы

Ознакомление с файловой системой Linux, её структурой, именами и содержанием каталогов. Приобретение практических навыков по применению команд для работы с файлами и каталогами, по управлению процессами, по проверке использования диска и обслуживанию файловой системы.

- 1 Выполнить приимеры
- 2 Выполнить дествия по работе с каталогами и файлами
- 3 Выполнить действия с правами доступа
- 4 Получить дополнительные сведения при помощи справки по командам.

Процесс выполнения лабораторной работы

```
jaksigamal@jaksigamal:~$ touch abc1
jaksigamal@jaksigamal:~$ cp abc1 april
jaksigamal@jaksigamal:~$ cp abc1 may
jaksigamal@jaksigamal:~$ mkdir monthly
jaksigamal@jaksigamal:~$ cp april may monthly
jaksigamal@jaksigamal:~$ cp monthly/may monthly/june
jaksigamal@jaksigamal:~$ ls monthly
april  june  may
jaksigamal@jaksigamal:~$ mkdir monthly.00
jaksigamal@jaksigamal:~$ cp -r monthly monthly.00
jaksigamal@jaksigamal:~$ cp -r monthly.00 /tmp
jaksigamal@jaksigamal:~$
```

Рис. 1: Выполнение примеров

```
jaksigamal@jaksigamal:~$ mv april july
jaksigamal@jaksigamal:~$ mv july monthly.00
jaksigamal@jaksigamal:~$ ls monthly.00
july  monthly
jaksigamal@jaksigamal:~$ mv monthly.00 monthly.01
jaksigamal@jaksigamal:~$ mkdir reports
jaksigamal@jaksigamal:~$ mv monthly.01 reports
jaksigamal@jaksigamal:~$ mv reports/monthly.01 reports/monthly
jaksigamal@jaksigamal:~$ █
```

Рис. 2: Выполнение примеров

Выполнение примеров

```
jaksigamal@jaksigamal:~$ touch may
jaksigamal@jaksigamal:~$ ls -l may
-rw-r--r--. 1 jaksigamal jaksigamal 0 map 11 12:33 may
jaksigamal@jaksigamal:~$ chmod u+x may
jaksigamal@jaksigamal:~$ ls -l may
-rwxr--r--. 1 jaksigamal jaksigamal 0 map 11 12:33 may
jaksigamal@jaksigamal:~$ chmod u-x may
jaksigamal@jaksigamal:~$ chmod u-x may
jaksigamal@jaksigamal:~$ ls -l may
-rw-r--r--. 1 jaksigamal jaksigamal 0 map 11 12:33 may
jaksigamal@jaksigamal:~$ mkdir monthly
mkdir: невозможно создать каталог «monthly»: Файл существует
jaksigamal@jaksigamal:~$ chmod g-r,o-r monthly
jaksigamal@jaksigamal:~$ touch abc1
jaksigamal@jaksigamal:~$ chmod g+w abc1
jaksigamal@jaksigamal:~$
```

Рис. 3: Выполнение примеров

Создание директорий и копирование файлов

```
jaksigamal@jaksigamal:~$ cp /usr/include/linux/sysinfo.h ~
jaksigamal@jaksigamal:~$ mv sysinfo.h equipment
jaksigamal@jaksigamal:~$ mkdir ski.places
jaksigamal@jaksigamal:~$ mv equipment ski.places/
jaksigamal@jaksigamal:~$ mv ski.places/equipment ski.places/equiplist
jaksigamal@jaksigamal:~$ touch abc1
jaksigamal@jaksigamal:~$ cp abc1 ski.places/equiplist2
jaksigamal@jaksigamal:~$ cd ski.places/
jaksigamal@jaksigamal:~/ski.places$ mkdir equipment
jaksigamal@jaksigamal:~/ski.places$ mv equiplist equipment/
jaksigamal@jaksigamal:~/ski.places$ mv equiplist2 equipment/
jaksigamal@jaksigamal:~/ski.places$ cd
jaksigamal@jaksigamal:~$ mkdir newdir
jaksigamal@jaksigamal:~$ mv newdir ski.places/
jaksigamal@jaksigamal:~$ mv ski.places/newdir/ ski.places/plans
jaksigamal@jaksigamal:~$ |||
```

Рис. 4: Работа с каталогами

Работа с командой chmod

```
jaksigamal@jaksigamal:~$ mkdir australia play
jaksigamal@jaksigamal:~$ touch my_os feathers
jaksigamal@jaksigamal:~$ chmod 744 australia/
jaksigamal@jaksigamal:~$ chmod 711 play/
jaksigamal@jaksigamal:~$ chmod 544 my_os
jaksigamal@jaksigamal:~$ chmod 664 feathers
jaksigamal@jaksigamal:~$ ls -l
итого 0
-rw-rw-r--. 1 jaksigamal jaksigamal 0 map 11 12:34 abc1
drwxr--r--. 1 jaksigamal jaksigamal 0 map 11 12:35 australia
-rw-rw-r--. 1 jaksigamal jaksigamal 0 map 11 12:35 feathers
drwxr-xr-x. 1 jaksigamal jaksigamal 74 фев 11 21:00 git-extended
-rw-r--r--. 1 jaksigamal jaksigamal 0 map 11 12:33 may
drwx--x--x. 1 jaksigamal jaksigamal 24 map 11 12:32 monthly
-r-xr--r--. 1 jaksigamal jaksigamal 0 map 11 12:35 my_os
drwx--x--x. 1 jaksigamal jaksigamal 0 map 11 12:35 play
drwxr-xr-x. 1 jaksigamal jaksigamal 14 map 11 12:33 reports
drwxr-xr-x. 1 jaksigamal jaksigamal 50 map 6 12:08 site
drwxr-xr-x. 1 jaksigamal jaksigamal 28 map 11 12:34 ski.places
drwx-----. 1 jaksigamal jaksigamal 8 фев 11 20:35 snap
drwxr-xr-x. 1 jaksigamal jaksigamal 10 фев 11 20:28 work
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 Видео
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 Документы
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 Загрузки
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 Изображения
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 Музыка
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 Общедоступные
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 'Рабочий стол'
drwxr-xr-x. 1 jaksigamal jaksigamal 0 фев 11 20:14 Шаблоны
jaksigamal@jaksigamal:~$
```

```
qemu:x:107:107;qemu user:/:/sbin/nologin
polkitd:x:114:114:User for polkitd:/:/sbin/nologin
rtkit:x:172:172:RealtimeKit:/:/sbin/nologin
chrony:x:997:994:chrony system user:/var/lib/chrony:/sbin/nologin
dnsmasq:x:996:993:Dnsmasq DHCP and DNS server:/var/lib/dnsmasq:/usr/sbin/nologin
gluster:x:995:992:GlusterFS daemons:/run/gluster:/sbin/nologin
rpc:x:32:32:Rpcbind Daemon:/var/lib/rpcbind:/sbin/nologin
pipewire:x:994:991:PipeWire System Daemon:/run/pipewire:/usr/sbin/nologin
unbound:x:993:990:Unbound DNS resolver:/var/lib/unbound:/sbin/nologin
nm-openconnect:x:992:989:NetworkManager user for OpenConnect:/:/sbin/nologin
rpcuser:x:29:29:RPC Service User:/var/lib/nfs:/sbin/nologin
wsdd:x:991:988:Web Services Dynamic Discovery host daemon:/:/sbin/nologin
sssd:x:990:986:User for sssd:/run/sss:/sbin/nologin
openvpn:x:989:985:OpenVPN:/etc/openvpn:/sbin/nologin
nm-openvpn:x:988:984:Default user for running openvpn spawned by NetworkManager:/:/sbin/nologin
flatpak:x:987:983:Flatpak system helper:/usr/sbin/nologin
/etc/passwd
```

Рис. 6: Файл /etc/passwd

Работа с файлами и правами доступа

```
jaksigamal@jaksigamal:~$ cp feathers file.old
jaksigamal@jaksigamal:~$ mv file.old play/
jaksigamal@jaksigamal:~$ mkdir fun
jaksigamal@jaksigamal:~$ cp -R play/ fun/
jaksigamal@jaksigamal:~$ mv fun/ play/games
jaksigamal@jaksigamal:~$ chmod u-r feathers
jaksigamal@jaksigamal:~$ cat feathers
cat: feathers: Отказано в доступе
jaksigamal@jaksigamal:~$ cp feathers feathers2
cp: невозможно открыть 'feathers' для чтения: Отказано в доступе
jaksigamal@jaksigamal:~$ chmod u+r feathers
jaksigamal@jaksigamal:~$ chmod u-x play/
jaksigamal@jaksigamal:~$ cd play/
bash: cd: play/: Отказано в доступе
jaksigamal@jaksigamal:~$ chmod +x play/
jaksigamal@jaksigamal:~$
```

Рис. 7: Работа с файлами и правами доступа

```
MOUNT(8)                                     System Administration                                     MOUNT(8)

NAME
    mount - mount a filesystem

SYNOPSIS
    mount [-h|-V]

    mount [-l] [-t fstype]

    mount -a [-fFnrsvw] [-t fstype] [-O optlist]

    mount [-fnrsvw] [-o options] device|mountpoint

    mount [-fnrsvw] [-t fstype] [-o options] device mountpoint

    mount --bind|--rbind|--move olddir newdir

    mount --make-[shared|slave|private|unbindable|rshared|rslave|rprivate|runbindable] mountpoint

DESCRIPTION
    All files accessible in a Unix system are arranged in one big tree, the file hierarchy, rooted at /. These files can be spread out over several devices. The mount command serves to attach the filesystem found on some device to the big file tree. Conversely, the umount(8) command will detach it again. The filesystem is used to control how data is stored on the device or provided in a virtual way by network or other services.

    The standard form of the mount command is:

        mount -t type device dir

    This tells the kernel to attach the filesystem found on device (which is of type type) at the directory dir. The option -t type is optional. The mount command is usually able to detect a filesystem. The root permissions are necessary to mount a filesystem by default. See section "Non-superuser mounts" below for more details. The previous contents (if any) and owner and mode of dir become invisible, and as long as this filesystem remains mounted, the pathname dir refers to the root of the filesystem on device.

Manual page mount(8) line 1 (press h for help or q to quit)
```

```
FCK(8)                                     System Administration                                     FCK(8)

NAME
    fsck - check and repair a Linux filesystem

SYNOPSIS
    fsck [-lsAVRTMNP] [-r [fd]] [-C [fd]] [-t fstype] [filesystem...] [--] [fs-specific-options]

DESCRIPTION
    fsck is used to check and optionally repair one or more Linux filesystems. filesystem can be a device name
    (e.g., /dev/hdc1, /dev/sdb2), a mount point (e.g., /, /usr, /home), or a filesystem label or UUID specifier
    (e.g., UUID=8868abf6-88c5-4a83-98b8-bfc24057f7bd or LABEL=root). Normally, the fsck program will try to
    handle filesystems on different physical disk drives in parallel to reduce the total amount of time needed
    to check all of them.

    If no filesystems are specified on the command line, and the -A option is not specified, fsck will default
    to checking filesystems in /etc/fstab serially. This is equivalent to the -As options.

    The exit status returned by fsck is the sum of the following conditions:

    0
        No errors

    1
        Filesystem errors corrected

    2
        System should be rebooted

    4
        Filesystem errors left uncorrected

    8
        Operational error

    16

Manual page fsck(8) line 1 (press h for help or q to quit)
```

Рис 9: Команда fsck

```
MKFS(8)                                     System Administration                                     MKFS(8)

NAME
    mkfs - build a Linux filesystem

SYNOPSIS
    mkfs [options] [-t type] [fs-options] device [size]

DESCRIPTION
    This mkfs frontend is deprecated in favour of filesystem specific mkfs.<type> utils.

    mkfs is used to build a Linux filesystem on a device, usually a hard disk partition. The device argument is either the device name (e.g., /dev/hda1, /dev/sdb2), or a regular file that shall contain the filesystem. The size argument is the number of blocks to be used for the filesystem.

    The exit status returned by mkfs is 0 on success and 1 on failure.

    In actuality, mkfs is simply a front-end for the various filesystem builders (mkfs.fstype) available under Linux. The filesystem-specific builder is searched for via your PATH environment setting only. Please see the filesystem-specific builder manual pages for further details.

OPTIONS
    -t, --type type
        Specify the type of filesystem to be built. If not specified, the default filesystem type (currently ext2) is used.

    fs-options
        Filesystem-specific options to be passed to the real filesystem builder.

    -V, --verbose
        Produce verbose output, including all filesystem-specific commands that are executed. Specifying this option more than once inhibits execution of any filesystem-specific commands. This is really only useful for testing.

    -h, --help
        Display help text and exit.

Manual page mkfs(8) line 1 (press h for help or q to quit)
```

Рис. 10: Команда mkfs

```
KILL(1)                                User Commands                                KILL(1)
```

NAME

kill - terminate a process

SYNOPSIS

```
kill [-signal|-s signal|-p] [-q value] [-a] [--timeout milliseconds signal] [--] pid|name...
```

```
kill -l [number] | -L
```

DESCRIPTION

The command **kill** sends the specified signal to the specified processes or process groups.

If no signal is specified, the **TERM** signal is sent. The default action for this signal is to terminate the process. This signal should be used in preference to the **KILL** signal (number 9), since a process may install a handler for the TERM signal in order to perform clean-up steps before terminating in an orderly fashion. If a process does not terminate after a **TERM** signal has been sent, then the **KILL** signal may be used; be aware that the latter signal cannot be caught, and so does not give the target process the opportunity to perform any clean-up before terminating.

Most modern shells have a builtin **kill** command, with a usage rather similar to that of the command described here. The **--all**, **--pid**, and **--queue** options, and the possibility to specify processes by command name, are local extensions.

If signal is 0, then no actual signal is sent, but error checking is still performed.

ARGUMENTS

The list of processes to be signaled can be a mixture of names and PIDs.

pid

Each pid can be expressed in one of the following ways:

n

where n is larger than 0. The process with PID n is signaled.

0

Manual page kill(1) line 1 (press h for help or q to quit)

Выводы по проделанной работе

В ходе данной работы мы ознакомились с файловой системой Linux, её структурой, именами и содержанием каталогов. Научились совершать базовые операции с файлами, управлять правами их доступа для пользователя и групп. Ознакомились с Анализом файловой системы. А также получили базовые навыки по проверке использования диска и обслуживанию файловой системы.