



CATALYSIS CENTER FOR  
**ENERGY INNOVATION**

AN ENERGY FRONTIER RESEARCH CENTER

# NEXTorch: A Design and Bayesian Optimization Toolkit for Chemical Sciences and Engineering

Yifan Wang

Dec 2023 Vlab Workshop



# About Me

- Graduated from Vlachos Group Dec 2021
- ML Research Scientist at Meta
- Based in San Francisco
- Research interests: AI data annotation, active learning, generative AI, reinforcement learning from human feedback (RLHF)
- LinkedIn: <https://www.linkedin.com/in/wangyifan411/>


## Blackbox functions<sup>[1]</sup>

- Expensive computer model or laboratory experiments
- Unknown explicit model form
- Multi-dimensional

## Active learning<sup>[2]</sup>


- An algorithm “learning” from data, proposing next experiments, and improving prediction accuracy with fewer training data or lower cost

Use **active learning** to **reduce experimental (computational) cost** and **improve accuracy** of the surrogate model



[1] D.R. Jones, M. Schonlau, and W. J. Welch, J. Glob. Optim. **13**, 455 (1998).

[2] Settles, B. *Active Learning Literature Survey*. *Active Learning Literature Survey* (2009).



## Bayesian Statistics

$$\text{Posterior} \quad \text{Data} \quad \text{Prior} \\ P(f|D) \propto P(D|f)P(f)$$



Thomas Bayes


- Initial sampling can be generated through design of experiments (DoE)
- The surrogate model is typically a Gaussian Process (GP)
- Next experiment points are generated by acquisition functions (exploration vs. exploitation)



## Toolkit for Design of Experiments + Bayesian Optimization

### Workflow

(1) Automated (2) Human-in-the-loop optimization



- Install via pip `pip install nextorch`
- Key dependencies

python™ **pyDOE** PyTorch BoTorch

<https://botorch.org/>

[1] **Y. Wang**, T. Chen, and D.G. Vlachos, J. Chem. Inf. Model. 61, 5312–5319 (2021).

GitHub: <https://github.com/VlachosGroup/nextorch>

Documentation: <https://nextorch.readthedocs.io/en/latest/index.html>



nextorch  
NEX Torch  
latest

Search docs

GETTING STARTED

NEXTorch

USER DOCUMENTATION

Introduction

Installation

Overview

Input and Output

Parameter

Design of Experiment

Data Type and Preprocessing

BoTorch Models and Functions

Experiment

Visualization

Examples

INTRO TO BO

Key Concepts in BO

Applications of BO

API REFERENCE

nextorch.io

nextorch.doe

nextorch.parameter

Read the Docs v: latest

» Welcome to nextorch's documentation!

Edit on GitHub

## Welcome to nextorch's documentation!

### Getting Started

- NEX Torch

### User Documentation

- Introduction
- Installation
- Overview
- Input and Output
- Parameter
- Design of Experiment
- Data Type and Preprocessing
- BoTorch Models and Functions
- Experiment
- Visualization
- Examples

### Intro to BO


- Key Concepts in BO
- Applications of BO

### API Reference


- nextorch.io
- nextorch.doe
- nextorch.parameter
- nextorch.utils
- nextorch.bo
- nextorch.plotting

### Appendix


- NEX Torch modules and functions
- Tutorials with code examples
- Introduction to BO theory
- BO applications in literature




Example 3 - Langmuir  
Hinshelwood  
mechanism



Example 4 - Nitrogen-  
doped carbon catalysts



Example 5 - Plug flow  
reactor yield



Example 8 - Stub tuner  
of the microwave cavity

[1] E.O. Ebikade, et al, React. Chem. Eng. (2020).


[2] T. Chen, et al, Ind. Eng. Chem. Res. 59, 10418 (2020).

<https://nextorch.readthedocs.io/en/latest/index.html>





- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Starting from  $x = 0, 0.25, 0.5, 0.75$




Demo instructions: [https://github.com/VlachosGroup/vlab\\_workshop\\_2023/tree/main/NEXTorch](https://github.com/VlachosGroup/vlab_workshop_2023/tree/main/NEXTorch)

Notebook location: [https://github.com/VlachosGroup/nextorch/blob/main/examples/notebooks/01\\_simple\\_1d.ipynb](https://github.com/VlachosGroup/nextorch/blob/main/examples/notebooks/01_simple_1d.ipynb)

# BO Examples in 1D


- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 1, acquisition function – expected improvement (EI)






# BO Examples in 1D

- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 2




# BO Examples in 1D

- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 3




# BO Examples in 1D

- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 4




# BO Examples in 1D

- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 5




# BO Examples in 1D

- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 6



# BO Examples in 1D


- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 7






# BO Examples in 1D

- Find the minima of  $f(x) = (6x - 2)^2 \sin(12x - 4); x \in [0,1]$
- Iteration 8



# Case Study – HMF Yield Optimization

Fructose




$$u \frac{dC_i}{dx} = R_i$$

HMF

LA,  
FA,  
Fructose,  
Humins

...



- Goal: maximize the HMF yield ( $Y$ ) to improve productivity and reduce downstream costs.
- Three key input parameters ( $X$ ) and bounds:
  - $X_1$ , **Temperature** – (140 – 200 °C)
  - $X_2$ , **pH** – (0 – 1)
  - $X_3$ , **Residence time** – (0.01 – 100 min), sampled in log space (-2,2)

[1] T.D. Swift et al., *ACS Catal.* 4, **2014**, 259.

[2] Desir, P.; Saha, B.; Vlachos, D. G. *Energy Environ. Sci.* 2019.

Model available in Python and MATLAB: <https://github.com/VlachosGroup/Fructose-HMF-Model>




# Optimized Latin Hypercube design (LHS)

Initial Sampling plan:

- Monte Carlo sampling
- Maximize the distance between points
- Maximize the information gain in the sampling space

**2D example (level = 4, 16 samples)**




# Sampling Plans

## Design 1


Full factorial (level = 4)

64 samples



## Design 2

64 random samples




## Design 3

10 samples from Latin hypercube (LHS)


54 samples from 54 BO loops,

Acquisition function – EI



- LHS is an efficient space-filling, Monte Carlo sampling method
- We compare response surfaces of HMF yield at **pH=0.7** with varying temperature and residence time

# Surrogate Model Performance




- LHS+BO produces more accurate surrogate models



# Single-, Multi-Objective Optimization

## Maximize HMF Yield



- Optimal condition: Temperature – 200 ° C  
pH – 0.705  
Residence time – 0.076 min (4.56 s)



- LHS+BO locates a higher optimal value compared to others
- The runtime of core BO functions completes in seconds per iteration on a laptop CPU
- NEXTorch requires little code and reduces the time or materials for **computations** or **lab experiments**

## Co-maximize HMF Yield and Selectivity


- HMF Yield = Fructose Conversion  $\times$  HMF Selectivity
- Fructose Conversion  $\leq 100\%$






# More Examples

## Basic API Usage




Example 1 - Simple 1d  
nonlinear function




Example 2 - Sin(x) 1d  
function

## Mixed Type Parameters




Example 10 - Plug flow  
reactor yield with mixed  
type inputs


## Applications in Reaction Engineering




Example 3 - Langmuir  
Hinshelwood  
mechanism



Example 4 - Nitrogen-  
doped carbon catalysts




Example 5 - Plug flow  
reactor yield




Example 8 - Stub tuner  
of the microwave cavity


## Multi-Objective Optimization(MOO)




Example 6 - Multi-  
objective optimization  
for an ellipse function



Example 7 - Multi-  
objective optimization  
for plug flow reactor



Example 9 - Multi-  
objective optimization  
for Microwave  
operating conditions



Example 11 - Multi-  
objective optimization  
for plug flow reactor