

Aurox language specification

Jakub Grobelny

16 maja 2019

1 Syntax

Character classification:

- $\langle whitespace \rangle$ — HT, LF, CR, SPACE
- $\langle digit \rangle$ — 0-9
- $\langle lowercase \rangle$ — underscore or any other lowercase Unicode characters¹
- $\langle uppercase \rangle$ — any uppercase Unicode characters²
- $\langle special \rangle$ — '-', '+', '*', '/', '=', '>', '<', '.', '!', '@', '%', '^, ' ', '&', '\$, '|'

Any character sequence beginning with character # ending with LF are *comments*.

$\langle operator \rangle ::= \langle special \rangle$
| $\langle special \rangle \langle operator \rangle$

$\langle keyword \rangle ::= \text{let} \mid \text{in} \mid \text{if} \mid \text{and} \mid \text{or} \mid \text{then}$
| **match** | **else** | **with** | **type** | **import**
| **define** | **_** | **defop** | **end** | **case**

¹All characters X which satisfy `char_type(X, lower)` predicate in SWI Prolog

²All characters X which satisfy `char_type(X, upper)` predicate in SWI Prolog

$\langle identifier \rangle ::= \langle lowercase \rangle \langle alphanum \rangle$
 $\langle type\ identifier \rangle ::= \langle uppercase \rangle \langle alphanum \rangle$
 $\langle alphanum \rangle ::= \langle alphanum\ char \rangle \langle alphanum \rangle \mid \epsilon$
 $\langle alphanum\ char \rangle ::= \langle lowercase \rangle \mid ? \mid \langle digit \rangle$
 $\langle integer \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle integer \rangle$
 $\langle float \rangle ::= \langle integer \rangle . \langle digit\ sequence \rangle \langle exponent \rangle \mathbf{e}$
 $\quad \mid \langle integer \rangle \langle exponent \rangle$
 $\langle digit\ sequence \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle digit\ sequence \rangle$
 $\langle e \rangle ::= \mathbf{e} \mid \mathbf{E}$
 $\langle exponent \rangle ::= \langle e \rangle - \langle integer \rangle$
 $\quad \mid \langle e \rangle \langle integer \rangle$
 $\langle string \rangle ::= \text{``} \langle char\ sequence \rangle \text{''} \mid \text{'''}$
 $\langle char \rangle ::= \text{' } \langle character \rangle \text{'}$
 $\langle char\ sequence \rangle ::= \langle character \rangle \mid \langle character \rangle \langle char\ sequence \rangle$
 $\langle character \rangle ::= \text{Unicode} \mid \backslash \backslash \mid \backslash \mathbf{b} \mid \backslash \mathbf{n} \mid \backslash \mathbf{f} \mid \backslash \mathbf{a} \mid \backslash \mathbf{r} \mid \backslash \mathbf{t} \mid \backslash \mathbf{0} \mid \backslash \text{''} \mid \backslash \text{'}$
 $\langle operator\ declaration \rangle ::= \mathbf{defop} \langle operator \rangle \langle integer \rangle \langle associativity \rangle$
 $\langle associativity \rangle ::= \mathbf{left} \mid \mathbf{right} \mid \mathbf{none} \mid \mathbf{prefix} \mid \mathbf{postfix}$
 $\langle import \rangle ::= \mathbf{import} \langle import\ list \rangle \mathbf{end}$
 $\langle import\ list \rangle ::= \epsilon \mid \langle string \rangle \langle import\ list \rangle$
 $\quad \mid \langle type\ name \rangle \langle import\ list \rangle$
 $\langle definition \rangle ::= \mathbf{define} \langle function\ name \rangle \langle formal\ parameters \rangle : \langle type \rangle = \mathbf{end}$
 $\langle function\ name \rangle ::= \langle identifier \rangle \mid (\langle operator \rangle)$

$$\begin{aligned}
\langle \textit{formal parameters} \rangle &::= \langle \textit{variable name} \rangle \langle \textit{formal parameters} \rangle \mid \epsilon \\
\langle \textit{variable name} \rangle &::= \langle \textit{identifier} \rangle \mid _ \\
\langle \textit{type} \rangle &::= \langle \textit{function type} \rangle \\
&\quad \mid \langle \textit{function type} \rangle , \langle \textit{tupe} \rangle \\
\langle \textit{function type} \rangle &::= \langle \textit{algebraic data type} \rangle \\
&\quad \mid \langle \textit{function type} \rangle (->) \langle \textit{algebraic data type} \rangle \\
\langle \textit{algebraic data type} \rangle &::= \langle \textit{type name} \rangle \langle \textit{atomic type sequence} \rangle \\
&\quad \mid \langle \textit{atomic type} \rangle \\
\langle \textit{atomic type sequence} \rangle &::= \langle \textit{atomic type} \rangle \langle \textit{atomic type sequence} \rangle \mid \epsilon \\
\langle \textit{atomic type} \rangle &::= \langle \textit{identifier} \rangle \mid \langle \textit{type name} \rangle \\
&\quad \mid [\langle \textit{type} \rangle] \mid (\langle \textit{type} \rangle) \\
\langle \textit{type definition} \rangle &::= \mathbf{type} \langle \textit{type name} \rangle \langle \textit{formal parameters} \rangle \mathbf{with} \\
&\quad \langle \textit{type constructors} \rangle \mathbf{end}
\end{aligned}$$

2 Semantics

3 Type system