

MARGE: Tutorial using presence-absence data and the `marge` R-package

Jakub Stoklosa & David I. Warton

23 November, 2020

This tutorial documents fitting multivariate adaptive regression splines using generalized estimating equations (MARGE) via the `marge` R-package. We also fit some additional models and compare them with MARGE using a predictive squared error (PSE) on test data. Computational times for each model fit are also reported. For specific details on the MARGE algorithm see:

Stoklosa, J. and Warton, D.I. (2018). A generalized estimating equation approach to multivariate adaptive regression splines. *Journal of Computational and Graphical Statistics*, **27**, pp. 245–253.

Also, see `?marge` for further details on the fitting function, input arguments and output.

Load the `marge`, `mgcv` and `BayesTree` R-packages.

```
suppressMessages(library("marge"))
suppressMessages(library("mgcv"))
suppressMessages(library("BayesTree"))
```

We use the `leptsrine` data set which is provided within the `marge` R-package and analyzed in Stoklosa and Warton (2018). These data are binary (presence-absence) data collected on plant species for 8,678 sites located in the Blue Mountains region. These data contain nine environmental predictor variables collected at each site. Our objective is to predict the presence of the species *Leptospermum trinervium* using the environmental predictor variables. There are 1,751 absences and 6,927 presences. The `leptsrine` data consists of training and test sets, such that $N_{train} = 4,339$. The nine environmental predictor variables have been standardized. See `?leptsrine` for further details.

Load the data, label the training and test data as objects and set data dimensions.

```
data("leptsrine")

dat1 <- leptsrine[[1]] # Training data.
dat1_t <- leptsrine[[2]] # Test data.

Y <- dat1$Y # Response variable.
N <- length(Y) # Sample size (number of clusters).
n <- 1 # Cluster size.
id <- rep(1:N, each = n) # The ID of each cluster.
```

```
X_pred <- dat1[, -10]      # A matrix of the nine environmental predictor variables (note
                           # that we remove the response variable).
X_predt <- dat1_t[, -11]  # The provided test data already contains a column of ones (for
                           # the intercept term).
```

Below we fit a MARS model, a generalized additive model (GAM), a Bayesian additive regression tree (BART) model and MARGE (with two different penalties, $\lambda = 2$ and $\lambda = \log(N)$). We record the computational times (in seconds) and calculate the predictive squared errors (PSE) on test data.

Set the required arguments and tuning parameters to fit models.

```
family <- "binomial"      # The selected "exponential" family for the GLM/GEE.
corstr <- "independence"  # The selected "working correlation" structure (used for GEEs).

is.gee <- FALSE           # Is the model a GEE?
nb <- FALSE               # Is this a negative binomial model?

tols <- 0.0001             # A set tolerance (stopping condition) in the forward pass for MARS.
tols_score <- 0.0001      # A set tolerance (stopping condition) in forward pass for MARGE.
M <- 21                   # A set threshold for the maximum no. of basis functions to be used.
pen <- 2                   # Penalty to be used in GCV (required for MARS).
minspan <- NULL           # A set minimum span value.

print.disp <- FALSE       # Print ALL the output?
```

Fit models and record the computational times.

Model fitting can take ~12 minutes to complete (this depends on your computer speed/memory).

```
# BART.

X_pred_bart <- as.matrix(cbind(rep(1, nrow(X_pred)), X_pred))
colnames(X_pred_bart)[1] <- "Intercept"
start <- Sys.time()
model_bart <- bart(x.train = X_pred_bart, y.train = Y, x.test = as.matrix(X_predt),
                  verbose = FALSE)
end <- Sys.time()
t1 <- difftime(end, start, units = "secs")
```

```
# GAM.



start <- Sys.time()
model_gam <- gam(Y ~ s(FC, k = 8) + s(RAIN_WET_QTR) + s(TMP_MIN) + s(TMP_SEAS) +
                  s(TMP_MN) + s(TMP_MAX) + s(RAIN_DRY_QTR) + s(TMP_MN_COLD_QTR) +
                  s(TMP_MN_WARM_QTR), data = dat1, family = "binomial")
end <- Sys.time()
t2 <- difftime(end, start, units = "secs")
```

```
# MARS.
```

```
start <- Sys.time()
model_own <- mars_ls(X_pred, Y, pen, tols, M, minspan,
                    print.disp, family, nb)
end <- Sys.time()
t3 <- difftime(end, start, units = "secs")
```

```
# MARGE.
```

```
start <- Sys.time()
model_marge <- marge(X_pred, Y, N, n, id, family, corstr, pen, tols_score, M, minspan,
                    print.disp, nb, is.gee)
```



```
end <- Sys.time()
t4 <- difftime(end, start, units = "secs")
```

Calculate the predictive squared error (PSE) on test data using each fitted model.

```
H <- function(a) {1 / (1 + exp(-a))} # An inverse logit function (required for PSE below).

pred_own_y <- predict(model_own, X_predt, X_pred)
pred_marge_2_y <- predict(model_marge, X_predt, X_pred, TRUE, "2")
pred_marge_log_y <- predict(model_marge, X_predt, X_pred, TRUE, "logN")

mu_bart <- apply(pnorm(model_bart$yhat.test), 2, mean)
var_bart <- mu_bart*(1 - mu_bart)
PSE_pred_bart <- mean((dat1_t$Y - mu_bart)^2/var_bart, na.rm = TRUE)

mu_gam <- H(predict(model_gam, newdata = dat1_t))
var_gam <- mu_gam*(1 - mu_gam)
PSE_pred_gam <- mean((dat1_t$Y - mu_gam)^2/var_gam, na.rm = TRUE)

mu_own <- H(pred_own_y$eta.p)
var_own <- mu_own*(1 - mu_own)
PSE_pred_own <- mean((dat1_t$Y - mu_own)^2/var_own, na.rm = TRUE)

mu_marge_2 <- H(pred_marge_2_y$eta.p)
mu_marge_log <- H(pred_marge_log_y$eta.p)
var_marge_2 <- mu_marge_2*(1 - mu_marge_2)
var_marge_log <- mu_marge_log*(1 - mu_marge_log)
PSE_pred_marge_2 <- mean((dat1_t$Y - mu_marge_2)^2/var_marge_2, na.rm = TRUE)
PSE_pred_marge_log <- mean((dat1_t$Y - mu_marge_log)^2/var_marge_log, na.rm = TRUE)

PSE_pred_list <- c(PSE_pred_bart, PSE_pred_gam, PSE_pred_own,
                  PSE_pred_marge_2, PSE_pred_marge_log)
```

Display results - these PSE values should match the results given in Table 3 of Stoklosa and Warton (2018), except for BART (which should be similar).

```
res1 <- PSE_pred_list
res2 <- cbind(t1, t2, t3, t4)

res <- cbind(c(round(res2, digits = 2), round(res2, digits = 2)[4]), round(res1, digits = 3))

rownames(res) <- c("BART", "GAM", "MARS", "MARGE_2_ind", "MARGE_logN_ind")
colnames(res) <- c("time (sec.)", "PSE")

print(res)
```

```
##           time (sec.)  PSE
## BART           145.06 0.852
## GAM             12.54 0.913
## MARS           183.88 0.941
## MARGE_2_ind    212.86 0.846
## MARGE_logN_ind 212.86 0.839
```