

eQRAP Logistika – Setup

Two-file version: `Code.gs` + `Index.html` (+ `appsscript.json`). About 20 minutes.

1. Create the Sheet and the script

1. Open **sheets.new** with your company Google account. Name it e.g. *eQRAP Logistika – DB*.
2. Menu **Extensions** → **Apps Script**. Rename the project to *eQRAP Logistika*.

2. Paste the two files

1. Open `Code.gs` in the editor, delete everything, paste the whole `Code.gs`. Save (Ctrl+S).
2. Click + → **HTML**, type `Index` (without `.html`), delete the example, paste `Index.html`. Save.
3. **Project Settings** (gear) → tick *Show "appsscript.json" manifest file* → back in the editor open `appsscript.json`, replace its content, save.

The HTML file must be named exactly `Index` – the code opens it by this name.

3. Run setup()

1. In the toolbar choose the function **setup** → **Run**.
2. Allow the permissions (*Advanced* → *Go to eQRAP Logistika* → *Allow* – it is your own script).
3. The Sheet now has all tabs (`SET_...`, `QRAP`, `AUDIT_LOG ...`) with example settings.

4. Photo folder

Create a Drive folder (e.g. *eQRAP fotky*). Copy the ID from its URL (the part after `/folders/`) into tab **SET_CONFIG** → **PHOTO_FOLDER_ID**.

5. Settings for testing

- **SET_ROUTING**: put your own e-mail in every row (Find & replace `.*@example\.com` with regex on).
- **SET_PEOPLE**: add yourself: roles `SUPERVISOR, PILOT, MANAGER, ADMIN, TL`, areas `*`, active `TRUE`.
- To try the kiosk, change your roles to `KIOSK` and area to `WH1` (the kiosk can never sign).

6. Deploy

1. **Deploy** → **New deployment** → type **Web app**.
2. Execute as: **Me**. Who has access: **Anyone within your domain** (with a @gmail account: *Only myself*).
3. Deploy, copy the URL ending in `/exec` into **SET_CONFIG** → **APP_URL**.

7. Triggers, check, demo

1. Run **installTriggers** (hourly reminders, daily digest, weekly archive).
2. Run **selfTest** – the log shows ✓ / ✗ for every check.
3. Optional: run **seedDemoData** for 9 example QRAPs.

8. Use it

- Kiosk tablet: signed in with the kiosk account, open `.../exec?page=board&area=WH1` full screen.
- Supervisors: same URL on the phone, or scan the QR code on a QRAP detail page.

9. After every code change

Deploy → **Manage deployments** → **Edit (pencil)** → **Version: New version** → **Deploy**. Otherwise the `/exec` URL keeps the old code. While developing, use *Deploy* → *Test deployments* (`/dev` URL).