

TTP- Time-Triggered Protocol for Fault-Tolerant Real-Time Systems

Milestone 3: Critical Evaluation and Transfer

Jaleel Ur Rehman
Electronics Engineering
Hochschule Hamm-Lippstadt
jaleel.ur-rehman@stud.hshl.de

Strengths of the Approach

- **Temporal Encapsulation and Testability:**
 - Node interactions strictly confined to predefined time slots.
 - Nodes can be developed and tested independently in both value and time domains.
 - Eliminates the need for system-wide regression testing when a local task is modified (unlike ET architectures where local timing changes cause global effects).
- **Replica Determinism:**
 - Replicated nodes execute state changes simultaneously in the time domain.
 - Guarantees identical results across replicas, enabling transparent active redundancy without complex runtime consensus algorithms.
- **Integrated Services with Zero Overhead:**
 - Clock synchronization, membership tracking, and group acknowledgments are achieved implicitly via TDMA timing and C-state CRC checks.
 - No extra protocol frames are required, maximizing payload efficiency.
- **High Data Efficiency:**
 - Achieves 53.3% data efficiency (vs. 24–27% for competing protocols) by eliminating sender addresses, message names, and explicit ACKs through *a priori* knowledge.

Limitations, Risks, and Unrealistic Assumptions

Inflexibility and Static Topology

- The fixed TDMA schedule makes the system rigid.
- Adding/removing nodes or changing message formats requires complete schedule redeployment.
- Unsuitable for open systems, plug-and-play networks, or Industrial IoT where nodes frequently join/leave.

Bandwidth Inefficiency at Low Loads

- Static allocation means bandwidth is wasted if a node has no data to send in its assigned slot.
- ET protocols can dynamically reuse this idle bandwidth, making them more efficient for highly variable workloads.

The Fail-Silent Assumption

- TTP assumes nodes either produce correct output or no output at all.

- Enforcing this requires expensive hardware-level space/time redundancy and error-detection logic.
- **Fails completely against Byzantine faults** (inconsistent outputs to different receivers), which the C-state CRC cannot detect.

Scalability and Cold-Start Issues

- **Clock Sync Scalability:** The fault-tolerant averaging algorithm degrades in accuracy for large numbers of nodes distributed across great physical distances.
- **Cold-Start Collisions:** During global power-ups, probabilistic waiting intervals (I1, I3) may still result in temporary bus collisions.

Application Transfer: Suitable vs. Unsuitable Scenarios

Table 1: Application Suitability Analysis for TTP

Scenario Type	Suitability	Technical Justification
Safety-Critical Control (Brake/Steer-by-wire, Flight control)	Suitable	Requires hard deadlines, determinism, and fault tolerance that TT provides.
Periodic Data Transfer (Engine control, sensor sampling)	Suitable	Perfect fit for static TDMA scheduling; highly predictable workload.
Static Mixed-Criticality (Known tasks/periods at design time)	Suitable	Allows strict separation of critical and non-critical traffic via time slots.
High-Bandwidth Aperiodic (LiDAR, Cameras, OTA updates)	Unsuitable	Inconsistent, high-volume bandwidth breaks static TDMA scheduling.
Dynamic/Plug-and-Play (Industrial IoT sensor networks)	Unsuitable	Adding/removing nodes requires full, costly schedule redeployment.
Low-Cost Body Electronics (Window lifts, seat controls)	Unsuitable	Hardware cost of TTP's fail-silent enforcement is unjustified; CAN is sufficient.

Runtime, Memory, and Scalability Implications

- **Runtime Complexity:** Very low. No arbitration or dynamic scheduling decisions; minimal CPU overhead for the communication controller.
- **Memory Requirements:** Higher ROM/RAM needed for schedule tables, C-state storage, and membership bit vectors. (Tradeoff: memory vs. runtime complexity).
- **Implementation Implications:** Requires specialized communication controller hardware and redundant checking logic to enforce fail-silence, increasing initial development costs but lowering maintenance costs.