Synaptic State or KV-Cache?

A Unified Account of Softmax Attention, Hebbian Synaptic State, and Recurrent Latent Reasoning,
with a Dual-Timescale Architecture Proposal and a Matched-Compute Evaluation Protocol

Jalendar Reddy Maligireddy
Ph.D. Candidate, Information Technology, University of the Cumberlands
Edison, New Jersey, USA
jalendarreddy97@gmail.com

Preprint draft — October 27, 2026

Abstract

Softmax attention stores context as an explicit key–value cache whose size grows with sequence length; Hebbian "synaptic" models such as the Dragon Hatchling (BDH) store it in a fixed-size, positive, high-dimensional state that is rewritten at every token; and recurrent latent reasoners such as BDH-CQ learn tasks from demonstrations by writing them into such a state and then iterating in latent space. We ask a single question: *when, and at what cost, should inference-time memory be synaptic rather than a cache?* We (i) formalise all three families as instances of one associative-memory operator with explicit write, read, forgetting, and workspace maps; (ii) show that any single-timescale decaying state couples retention and interference, so it cannot both adapt quickly and retain earlier episodes; (iii) specify *Compact Dual-Timescale Latent Reasoning* (CDLR), which pairs a fast episodic Hebbian state with a slow, gated, consolidated memory bank, a halting latent workspace, a local readout adapter, and a built-in audit trail; (iv) critically audit the empirical claims of BDH and BDH-CQ, separating paper-stated limits from inferred gaps; and (v) specify a preregistrable, matched-parameter/token/compute evaluation protocol that reports accuracy, memory, and latency jointly and treats negative results as first-class. We report no large-scale results; the contribution is the framework, the analysis, the falsifiable hypotheses, and the protocol needed to test them.

Keywords: attention, linear attention, fast weights, Hebbian plasticity, state-space models, continual learning, complementary learning systems, latent reasoning, evaluation methodology.

1 Introduction

The Transformer [52] replaced recurrence with attention "dispensing with recurrence and convolutions entirely" (52, Abstract) and accepted an $O(T^2d)$ per-layer cost in sequence length T in exchange for constant path length and full parallelism (52, §4, Table 1). At inference time this design keeps every past key and value: the context is *stored*, not *learned*. Two recent papers from the Pathway group challenge this choice from the opposite end. *The Dragon Hatchling* (BDH; 34) argues that inference-time working memory can rely "entirely on synaptic plasticity with Hebbian learning" (Abstract), in a state of size $n \times d$ per layer that does not grow with context (§3, Eq. 5), and reports parity with GPT-2-style baselines from 10M to 1B parameters on Europarl translation (§4.2, Fig. 7). *BDH-CQ* [16] builds a reasoning system in which demonstrations update a recurrent memory and a query is solved by iterating in latent space without verbal chain of thought (§3.2–3.3, Eqs. 1–4),

reporting 29.5% pass@2 on the public ARC-AGI-1 evaluation at a computed $0.00070 per task (§5, Table 1).

These are strong and interesting claims. They also leave open the question that matters for the next architecture class: **is a fixed-size synaptic state a better inference-time memory than a KV-cache, and under what accounting?** Four observations motivate this paper.

1. The three families are usually described in incompatible vocabularies (operators, synapses, recurrent memory), which hides what is actually different: what is written, how it is forgotten, and how it is read.
2. "Bounded" is not "small". A state of $n \times d$ with $n = 32{,}768$ and $d = 256$ per layer (34, §4.1) is larger than a 768-wide Transformer's KV-cache until several thousand tokens (Section 3). Memory claims therefore need explicit byte accounting.
3. A single decaying state cannot both adapt to a new task and keep an old one: retention and interference are the same quantity (Proposition 1). BDH's own merged-model language mixing (34, §7.1) and the near-total forgetting of our own preliminary probes (Section A) are consistent with this. Complementary learning systems theory [35, 37] and synaptic consolidation models [6, 18] suggest the remedy: a second, slower timescale.
4. The evidence base is narrow: one corpus family and a GPT-2-style baseline for BDH (34, §4.2, App. B.2), one benchmark family and proprietary internals for BDH-CQ (16, §3.3, §4.1). Neither compares against modern linear-recurrent models such as Mamba [22], RetNet [51], xLSTM [4], Gated/Delta linear attention [58–60] or test-time-memory models such as Titans [5] at matched compute.

Contributions. The contributions below do not depend on any experiment we ran.

C1. Unified formalisation (Section 3). We define an *associative-memory operator* $(\mathcal{M}, \omega, \rho, \lambda, \kappa, \mathcal{F})$ and place softmax attention, linear attention and SSMs, BDH-GPU, graph-form BDH, BDH-CQ, and CDLR in it, with matching byte and FLOP accounting.

C2. A plasticity–stability result for single-timescale states (Proposition 1). For any state with data-independent exponential forgetting, the retention of an old episode and its interference with a new one are the same function of lag, so no choice of decay can get both. We discuss when input-dependent gating weakens this.

C3. The CDLR architecture class (Section 4). A fast episodic Hebbian state $\mathbf{S}$, a slow gated consolidated bank $\mathbf{C}$, a halting latent workspace, a local (no-BPTT) readout adapter, and an audit interface that can certify "no parameter updates at inference". We state four falsifiable hypotheses (H1–H4).

C4. A critical audit of BDH and BDH-CQ (Section 6). Every claim is tied to a section or table, and we separate paper-stated limitations$^{(\mathrm{P})}$ from gaps we infer$^{(\mathrm{I})}$. Among the inferred gaps are an unreconciled cost basis in BDH-CQ and a 1B–600B scaling statement that no reported data supports.

C5. A matched-compute evaluation protocol (Section 5). Five experiment tracks (language modelling bakeoff beyond Europarl; associative-recall capacity and length generalisation testing BDH Claim 7; an ablation ladder isolating Hebbian and dual-timescale effects from plain linear attention; continual streams; black-box or labelled-reimplementation latent reasoning). Results are reported as accuracy × memory × latency Pareto fronts, with a preregistration and negative-results policy.

Scope and honesty statement. This is a framework, analysis, and protocol paper. We do *not* claim ARC-AGI parity with BDH-CQ, scaling to hundreds of billions of parameters, or a solution to the no-backpropagation-through-time gap of Kosowski et al. [34, §7.2]. The only numbers we report from our own code are small CPU probes, kept to Section A and labelled as such.

2 Background and Related Work

Softmax attention. Scaled dot-product attention computes $\mathrm{softmax}(QK^\top/\sqrt{d_k})V$ (52, Eq. 1), with $h = 8$ heads of $d_k = d_v = 64$ in the base model (§3.2.2). The authors note the $O(T^2 d)$ cost, propose restricted attention for long inputs, and list less sequential generation as future work (§4, §7). Later work made exact attention IO-efficient [12] and added relative positions [45, 49] and segment recurrence [10]. The inference-time KV-cache, which Kosowski et al. [34, Table 3] describes as "not localized at neurons", grows linearly in T.

Linear attention, fast weights, and SSMs. Replacing the softmax kernel with a feature map ϕ turns attention into a recurrence on the matrix $\sum_\tau \phi(k_\tau) v_\tau^\top$ [9, 31]. Schlag et al. [48] showed that this is a fast-weight programmer [3] and introduced a delta-rule update. Gated, decayed, and selective variants include RetNet [51], GLA [58], Mamba [22], Mamba-2 with its state-space duality [11], xLSTM [4], DeltaNet [59], and Gated DeltaNet [60]. Test-time-training layers [50], Titans [5], and the test-time-regression view [55] read all of these as online optimisation of an associative memory. Our formalisation (Section 3) follows this line. What we add is to place BDH's positive high-dimensional neuron state and BDH-CQ's latent workspace in the same frame, and to make a *consolidation* map κ explicit. Prior unifications leave κ implicit or absent. Fixed-state models are known to trail attention on associative recall and copying [2, 28]. Any claim for synaptic memory must therefore be tested on exactly those tasks (Section 5, E2). Ahn et al. [1] use a shallow linear Transformer to reproduce Transformer *optimisation* phenomena (Adam–SGD gap, heavy-tailed gradient noise); it is an analysis proxy, not an efficient-attention architecture, and its protocol has not been applied to BDH-GPU.

BDH. BDH models a language model as local graph dynamics among n neuron particles with Hebbian synapse reweighting (34, §2, Table 1). Its tensor form BDH-GPU(n, d) has $(3 + o(1))nd$ parameters, with $E \in \mathbb{R}^{d\times n}$ and $D_x, D_y \in \mathbb{R}^{n\times d}$, positive ReLU activations, and linear attention in neuron dimension n (§3, Def. 4, Eq. 4). It scales in n with $d = 256$ fixed (App. B.2, Table 5), and the authors report about 5% non-zero activations (§4.1), emergent modular scale-free structure (§5), and monosemantic synapses (§6.3). Claim 7 (§6.1, App. C.2) states that linear attention in $\mathbb{R}^n$ can separate $\tilde{O}(n)$ facts under non-adversarial keys and $\tilde{\Omega}(\sqrt{n})$ without assumptions.

BDH-CQ and latent reasoning. BDH-CQ writes demonstrations into $\mathbf{S}_t = U_\theta(\mathbf{S}_{t-1}, D_t)$ with fixed θ, initialises a workspace $\mathbf{H}_0 = E_\theta(x^*, \mathbf{S}_K)$, iterates $\mathbf{H}_{r+1} = F_\theta(\mathbf{H}_r, \mathbf{S}_K)$, and decodes $\hat{y} = G_\theta(\mathbf{H}_R)$ (16, §3.2–3.3, Eqs. 1–4). Related latent and recurrent depth approaches include Universal Transformers [13], adaptive computation time [21], Coconut [23], and recurrent-depth scaling [19], in contrast to verbal chain of thought [56]. On ARC [8], HRM [54] and TRM [29] are recurrent solvers; BDH-CQ distinguishes itself by not using task identities or evaluation demonstrations in training (16, §1–2).

Continual learning and complementary learning systems. Sequential training causes catastrophic interference [17, 38]. Remedies include regularisation [32, 61], episodic memory and

Table 1: Inference-time memory as an associative-memory operator (Definition 1). Entries for prior work cite the source; "n.d." = not disclosed. ϕ is a feature map, $\odot$ the Hadamard product, U a decay/rotation operator, G_s a sparse synapse mask.

Model	State $\mathcal{M}$ and write ω	Read ρ	Forget λ	κ	$\mathcal{F}$
Softmax attn. [52]	append (k_t, v_t); size $2Td$	$\mathrm{softmax}(q^\top K/\sqrt{d_k})V$	none (window)	–	–
Linear attn. [31]	$\mathbf{S} \leftarrow \mathbf{S} + \phi(k)v^\top$; $d_\phi \times d$	$\phi(q)^\top \mathbf{S}/\phi(q)^\top z$	none	–	–
RetNet/GLA/Mamba-2 [11, 51, 58]	$\mathbf{S} \leftarrow \Lambda_t \mathbf{S} + kv^\top$	$q^\top \mathbf{S}$	fixed or input-gated	–	–
DeltaNet [59, 60]	$\mathbf{S} \leftarrow \mathbf{S} + \beta k(v - \mathbf{S}^\top k)^\top$	$q^\top \mathbf{S}$	overwrite (+gate)	–	–
Titans [5]	MLP weights by surprise gradient	MLP(q)	weight decay	–	–
BDH-GPU [34, Eq. 4–5]	$\rho \leftarrow (\rho + v^* x^\top)U$; $n \times d$/layer, $x \geq 0$ sparse	$\rho\, x_t$ (positive $x_t \in \mathbb{R}^n$)	RoPE/ALiBi-like U (§2.4, §6.1)	–	–
BDH graph [34, Eq. 6]	$\sigma \leftarrow \sigma + (yx^\top \odot G_s)U$ on edges	local E/I dynamics	U	–	–
BDH-CQ [16, Eqs. 1–4]	$\mathbf{S}_t = U_\theta(\mathbf{S}_{t-1}, D_t)$, n.d.	via E_θ, F_θ, n.d.	n.d.	–	R loops
CDLR (ours)	fast $\mathbf{S}$ (Hebbian/delta) + slow bank $\mathbf{C}$	normalised read of $\mathbf{S}$ and gated $\mathbf{C}$	decay on $\mathbf{S}$; gated on $\mathbf{C}$	✓	halting R

replay [36, 47], and episodic control [46]. Deep networks also lose plasticity under long streams [15]. Complementary learning systems (CLS) theory holds that a fast hippocampal system stores episodes and a slow neocortical system consolidates them through interleaved replay [35, 37]. Cascade and multi-timescale synapse models show that coupling fast and slow variables extends memory lifetime far beyond a single exponential [6, 18]. Hebbian and three-factor rules [20, 24, 42] and differentiable plasticity [40] supply the local update rules we use. CDLR differs in where it puts the slow timescale: at *inference time, across episodes*, with explicit gating, a fixed byte budget, and an audit trail.

3 A Unified Formalisation of Inference-Time Memory

Notation. T is the sequence length (tokens) and n the BDH neuron count. These two axes are often both written "n" in the literature (52, Table 1, vs. 34, §3), and conflating them produces misleading complexity comparisons. We write d for the low-rank/model width, L for layers, and b for bytes per stored scalar.

Definition 1 (Associative-memory operator)**.** *An inference-time memory layer is a tuple* $(\mathcal{M}, \omega, \rho, \lambda, \kappa, \mathcal{F})$*: a state space* $\mathcal{M}$*; a* write $\omega : \mathcal{M} \times \mathcal{X} \to \mathcal{M}$ *applied per input; a* read $\rho : \mathcal{M} \times \mathcal{Q} \to \mathbb{R}^{d_v}$*; a* forgetting *map* λ *(decay, gating, or eviction); an optional* consolidation *map* $\kappa : \mathcal{M} \times \mathcal{B} \to \mathcal{B}$ *into a slower store* $\mathcal{B}$*; and an optional* workspace $\mathcal{F}$ *that iterates reads before emitting output. Slow parameters* θ *are fixed at inference unless stated.*

Table 1 instantiates the definition. The rows differ in three places: (a) whether $\mathcal{M}$ grows with T; (b) whether keys live in a low signed space ($d_k = 64$) or a high positive sparse space ($n \sim 10^4$–10^6); (c) whether κ and $\mathcal{F}$ exist.

Attention as operator vs. synaptic state vs. recurrent latent memory. Softmax attention is a *nonparametric* memory: the read is a kernel smoother over stored pairs, and nothing is learned at inference. Linear attention, SSMs and BDH-GPU are *parametric* memories: the read is a linear

map whose matrix is *learned online* by a Hebbian (outer-product) or delta (error-correcting) rule. The fast-weight view of Schlag et al. [48] makes this exact. BDH-GPU adds two biases: keys/queries are positive and sparse in a high dimension $n \gg d$, and the per-model weights are shared across layers (34, §4.1). BDH-CQ adds a third element, a *workspace* that re-reads a fixed $\mathbf{S}_K$ for R steps (16, Eq. 3). Iterative computation is thereby separated from token emission. In Definition 1 this is $\mathcal{F}$.

Byte accounting. Per layer and per sequence, a softmax KV-cache stores $2Td_{\text{model}}b$ bytes, growing in T. BDH-GPU stores ndb bytes regardless of T (34, Eq. 5). The two are equal at

$$T^\star = \frac{n\,d}{2\,d_{\text{model}}}. \tag{1}$$

For the 25M BDH-GPU configuration ($n = 32{,}768$, $d = 256$; 34, §4.1) against a $d_{\text{model}} = 768$ Transformer, $T^\star \approx 5{,}461$ tokens per layer[(I)]. Below $T^\star$ the bounded state is the *larger* memory. This is consistent with, and independent of, the paper's FLOP crossover of about 4096 tokens at $d = 256$ (§4.2). Constant memory pays off only for long contexts or many concurrent episodes, and fair comparisons must report bytes at several T rather than asymptotic class alone (Section 5).

Capacity. For a linear associative state with n-dimensional keys, interference between stored items grows with key overlap. BDH Claim 7 (§6.1; App. C.2) gives $\tilde{O}(n)$ separable facts for non-adversarial keys and $\tilde{\Omega}(\sqrt{n})$ in the worst case. To our knowledge it has not been measured against recall benchmarks [2]. We turn this into hypothesis H1 (Section 4) and experiment E2.

3.1 Single-timescale states couple retention and interference

Consider a linear state with data-independent forgetting, $\mathbf{S}_t = \lambda \mathbf{S}_{t-1} + u_t$, $0 < \lambda < 1$, where u_t is the write at step t (Hebbian $\phi(k_t)v_t^\top$ or similar). Let a stream switch at time t_0 from task A (writes u_t^A) to task B (writes u_t^B), with both stationary in mean, $\mathbb{E}u^A = \bar{u}^A$, $\mathbb{E}u^B = \bar{u}^B$.

Proposition 1 (Retention–interference coupling)**.** *At lag $\Delta \geq 0$ after the switch, in expectation and in the stationary limit before t_0,*

$$\mathbb{E}\,\mathbf{S}_{t_0+\Delta} = \tfrac{1}{1-\lambda}\big(\lambda^\Delta\,\bar{u}^A + (1-\lambda^\Delta)\,\bar{u}^B\big).$$

The normalised weight of task A, $\alpha(\Delta) = \lambda^\Delta$, is simultaneously (i) the retention *of A (the signal available for a later A-query) and (ii) the* interference *of A with B-queries. Define retention horizon $H_{\text{ret}}(\varepsilon) = \min\{\Delta : \alpha(\Delta) \leq \varepsilon\}$ and adaptation horizon $H_{\text{ad}}(\delta) = \min\{\Delta : \alpha(\Delta) \leq \delta\}$. For any λ, $H_{\text{ret}}(\varepsilon)/H_{\text{ad}}(\delta) \to \log\varepsilon/\log\delta$, independent of λ. In particular, if A must stay retrievable ($\alpha \geq \varepsilon$) and B must be uncontaminated ($\alpha \leq \delta$) at the same lag, with $\varepsilon > \delta$, no λ satisfies both.*

Proof sketch. Unroll the recursion: $\mathbf{S}_{t_0+\Delta} = \lambda^\Delta \mathbf{S}_{t_0} + \sum_{j=1}^{\Delta} \lambda^{\Delta-j} u^B_{t_0+j}$. In the stationary limit, $\mathbb{E}\mathbf{S}_{t_0} = \bar{u}^A/(1-\lambda)$, and $\sum_j \lambda^{\Delta-j} = (1-\lambda^\Delta)/(1-\lambda)$. Both horizons solve $\lambda^\Delta = c$, so $\Delta = \log c/\log\lambda$; their ratio does not depend on λ. Requiring $\lambda^\Delta \geq \varepsilon > \delta \geq \lambda^\Delta$ is a contradiction. □

Remark 1 (What the proposition does and does not say). It is a statement about one shared, linearly superposed state. It does not rule out good continual behaviour for (a) input-dependent gates (λ_t in Mamba/GLA/Gated DeltaNet), which can freeze the state but then also stop adapting, unless a gate learns *when* a new task starts (task-boundary inference); (b) delta rules, which remove interference along overwritten keys but also erase the overwritten association; (c) high-dimensional




Figure 1: CDLR data flow. Orange: fast timescale (within episode, decays). Blue: slow timescale (across episodes, gated, never overwritten by an unmatched task). Green: latent workspace. Slow parameters θ are frozen at inference; only $\mathbf{S}$, $\mathbf{C}$ and the optional readout adapter change, and the audit log records every change.

sparse keys, which reduce overlap between $\bar{u}^A$ and $\bar{u}^B$ so that A and B coexist. Case (c) is BDH's implicit bet. It holds only while tasks occupy near-disjoint neurons, which the language mixing of Kosowski et al. [34, §7.1] suggests is not guaranteed. The cascade models of Fusi et al. [18] and Benna and Fusi [6] escape the coupling by adding variables with different time constants. This is the design principle behind CDLR.

4 Compact Dual-Timescale Latent Reasoning (CDLR)

Specification pending empirical confirmation. Until E3 (including the byte-transfer control) and E4 land, CDLR should be read as a design class and evaluation target, not a demonstrated method.

CDLR is an architecture *class*, specified by the operator of Definition 1 with both κ and $\mathcal{F}$ present and a hard byte budget. Figure 1 gives the data flow.

Backbone. $\phi_\theta : \mathcal{X} \to \mathbb{R}^n_{\ge 0}$ maps inputs to positive, sparse, high-dimensional codes. The reference instantiation is a BDH-GPU stack (34, Def. 4) with k-winners-take-all sparsification and ℓ_2 normalisation. A Transformer or SSM backbone with a positive projection head is a valid control, which lets the protocol separate "BDH backbone" effects from "memory architecture" effects.

Fast episodic state S. $\mathbf{S} \in \mathbb{R}^{n \times d_v}$ with normaliser $z \in \mathbb{R}^n$:

$$\mathbf{S} \leftarrow \lambda \mathbf{S} + \eta\, \phi(k)\, w_\theta(k,v)^\top, \qquad z \leftarrow \lambda z + \eta\, \phi(k), \qquad \rho_{\mathbf{S}}(q) = \frac{\phi(q)^\top \mathbf{S}}{\phi(q)^\top z + \epsilon}. \tag{2}$$

$\eta = \mathrm{softplus}(\cdot)$ and $\lambda = \mathrm{sigmoid}(\cdot)$ are slow parameters. A delta-rule variant $\mathbf{S} \leftarrow \lambda \mathbf{S} + \eta\, \phi(k)(w - \mathbf{S}^\top \phi(k))^\top$ [48, 59] is a first-class ablation, because it changes the capacity regime of H1.

Slow consolidated bank C and consolidation κ. $\mathbf{C} = \{(\mathbf{C}_j, \mathbf{k}_j)\}_{j=1}^M$ holds at most M slots, each a matrix of the shape of $\mathbf{S}$ (or a rank-r factorisation), with a summary key $\mathbf{k}_j$. A small reservoir buffer $\mathcal{R}$ of past codes supports replay, as in CLS [37]. At a consolidation event (an episode

boundary, or a novelty trigger when the read error of $\mathbf{S}$ exceeds a threshold), we form a candidate $\hat{\mathbf{C}} = \mathrm{unit}(\frac{1}{2}\mathbf{S} + \frac{1}{2}\,\Pi(\mathcal{R}))$, where Π computes class- or key-conditioned means of replayed codes. Let $j^\star = \arg\max_j \cos(\hat{\mathbf{C}}, \mathbf{C}_j)$. Then

$$\kappa : \begin{cases} \mathbf{C}_{j^\star} \leftarrow (1-\beta)\mathbf{C}_{j^\star} + \beta\hat{\mathbf{C}} & \text{if } \cos(\hat{\mathbf{C}}, \mathbf{C}_{j^\star}) \geq \tau, \\ \text{allocate a new slot (evict least-used if } |\mathbf{C}| = M) & \text{otherwise.} \end{cases} \tag{3}$$

Reads from $\mathbf{C}$ are gated: $g_j = \mathrm{softmax}_j(\gamma \cdot s_j)$, where s_j is either key similarity $\cos(\mathbf{k}_j, \bar{\phi}_{\mathrm{ctx}})$ (unsupervised) or the fit of $\mathbf{C}_j$ to a small labelled support set (supervised; this leaks task information and must be reported as such). The term is omitted when $\max_j s_j < \tau_{\mathrm{gate}}$. Because $\mathbf{C}_j$ is only written when matched, task A's slot is not diluted by task B's writes, which breaks the coupling of Proposition 1 at the cost of M extra states and a task-boundary or novelty signal.

Latent workspace. Following BDH-CQ's public equations (16, Eqs. 2–4), but with our own open choices for every function:

$$\mathbf{H}_0 = E_\theta(x^*, \rho_{\mathbf{S}}(\phi(x^*)), \textstyle\sum_j g_j \rho_{\mathbf{C}_j}(\phi(x^*))), \tag{4}$$

$$\mathbf{H}_{r+1} = \mathbf{H}_r + F_\theta([\mathbf{H}_r; \rho_{\mathbf{S}}(\kappa_k(W_q \mathbf{H}_r))]), \quad r < R, \tag{5}$$

$$\hat{y} = G_\theta(\mathbf{H}_{r^\star}), \quad r^\star = \min\{r : \max \mathrm{softmax}(G_\theta(\mathbf{H}_r)) \geq c\} \wedge R, \tag{6}$$

where κ_k is k-WTA and c a confidence threshold for halting, as in ACT [21]. Every re-read uses the same $\mathbf{S}$, so the workspace adds compute but no memory that grows with R.

Local adapter. An optional readout $W\phi + b$ adapts online by a three-factor rule [20]: $e_t = \gamma e_{t-1} + \phi_t$, $W \mathrel{+}= \eta_W(y_t - p_t)e_t^\top$. Nothing flows into the backbone or back through time. For a linear head with $\gamma = 0$ this coincides with the cross-entropy gradient of that head. Its locality lies in what it does *not* touch, and we do not claim it closes the no-BPTT gap of Kosowski et al. [34, §7.2].

Audit interface. Every `predict` call emits a record: activation sparsity and entropy, top units, $\|\mathbf{S}\|_F$, $\|\Delta\mathbf{H}\|$ per step, halting step, selected slots and gate values, consolidation actions, latency, and a cryptographic hash of θ before and after. The hash turns the claim "no parameter updates at inference" (16, §1) into a checkable property. Slot-level storage also makes targeted deletion of a consolidated episode possible, which weight-level unlearning cannot easily offer (Section 7).

Training. Slow parameters are meta-trained on episodes. Gradients flow through the K within-episode writes, which is BPTT over demonstrations, so CDLR is not BPTT-free during meta-training. At inference only $\mathbf{S}$, $\mathbf{C}$ and W change. β, τ, M are hyperparameters, swept under the same budget as baselines.

Complexity. Per token and layer, a write costs $O(nd_v)$ and a read $O(nd_v)$. The workspace adds $O(R\,nd_v)$ per query, and the bank adds $O(|\{j : g_j > 0\}|\,nd_v)$. Memory is $(1+M)nd_vb + |\mathcal{R}|nb$, constant in T and in the number of past episodes. Equation (1) applies with nd replaced by $(1+M)nd_v$.

Falsifiable hypotheses.

Hypothesis 1 (Capacity)**.** *At matched state bytes, recall accuracy of a positive, sparse, high-n Hebbian state decays with the number of stored pairs N at a rate consistent with $\tilde{O}(n)$ capacity for random keys and degrades toward the $\tilde{\Omega}(\sqrt{n})$ regime for correlated keys (BDH Claim 7). The delta variant beats the Hebbian variant on correlated keys.*

Hypothesis 2 (Dual timescale)**.** *On interleaved task streams, CDLR lowers forgetting relative to every single-state model with the same total bytes, including input-gated SSMs, at no more than a fixed relative loss in plasticity. The gain disappears when the bank is removed, or when its byte budget is instead given to a larger* $\mathbf{S}$*.*

Hypothesis 3 (Workspace)**.** *Latent iterations improve accuracy on compositional demonstration-conditioned tasks over $R = 1$ at matched FLOPs, and halting reduces mean compute without loss in accuracy.*

Hypothesis 4 (Where synaptic memory should lose)**.** *On exact copying and high-cardinality multi-query recall at $T < T^{\star}$, softmax attention dominates every bounded-state model on accuracy and on bytes. Reporting this region is part of the result.*

5 A Matched-Compute Evaluation Protocol

Claims about new architecture classes fail most often on accounting rather than ideas. Cost indicators disagree [14], and baselines that are tuned less carefully look worse. We therefore fix the protocol before running it.

5.1 Principles

P1. Matched budgets on three axes. Non-embedding parameters, training tokens, and training FLOPs are matched within $\pm 5\%$. Every comparison is run twice, once matched on parameters and once on FLOPs, because BDH-GPU's $O(ndL)$ per-token cost (34, §4.2) and parameter count $3nd$ diverge from a Transformer's. The BDH Arena probe in Section A, where BDH had $1.9\times$ the parameters and $12\times$ the wall time, shows what happens otherwise.

P2. Equal tuning effort. Each architecture gets the same number of learning-rate/weight-decay sweep points (e.g. 6) on a held-out split. We report the best-of-sweep and the median-of-sweep.

P3. Modern baselines. At minimum: Transformer++ (RoPE, SwiGLU, pre-norm), one selective SSM (Mamba or Mamba-2), one gated/delta linear attention (GLA or Gated DeltaNet), plain linear attention (elu+1) at BDH's width, BDH-GPU from the public code, and CDLR. xLSTM and Titans where code permits.

P4. Joint reporting. Accuracy (or loss), *memory* = parameter bytes + peak inference-state bytes at stated T and batch, and *latency* (p50/p95 at batch 1, plus throughput at saturation) on named hardware. Results are Pareto fronts. Single ratios such as accuracy/(KB$\times$ms) may appear only next to the raw numbers.

P5. Statistics. ≥ 3 seeds (5 where affordable). Proportions get Wilson intervals [57], paired comparisons get exact McNemar tests [39] or paired bootstrap, and multiple comparisons are Holm-corrected.

P6. Preregistration and negative results. Hypotheses H1–H4, metrics, and stopping rules are frozen in the repository before runs start. Refuted hypotheses are reported in the main text with the same prominence as confirmed ones.

P7. Reproducibility. Code, configs, seeds, logs, and audit JSON are released, following the NeurIPS reproducibility checklist [44]. Closed systems are evaluated only as black boxes, and the paper says so.

5.2 Experiment tracks

E1. Language-modelling bakeoff beyond Europarl. Scales of about 30M, 125M, and 350M non-embedding parameters at roughly 20 tokens per parameter [26] on a public web corpus (FineWeb-Edu; 43). A Europarl byte-level replication [33] anchors the results to Kosowski et al. [34, App. B.2]. Outcomes: validation loss vs. FLOPs scaling curves [30], downstream zero-shot accuracy on a fixed small suite, and bytes/latency at $T \in \{512, 2\text{k}, 8\text{k}, 32\text{k}\}$.

E2. Associative recall, capacity, and length generalisation (tests BDH Claim 7, H1, H4). Multi-query associative recall [2] with N pairs swept until failure, at $n \in \{2^{12}, \ldots, 2^{16}\}$ and matched state bytes for every model. Keys are drawn i.i.d. (non-adversarial) and with controlled correlation ρ_{key} (adversarial-leaning). We fit capacity $N_{50}(n)$, the N at 50% recall, and test whether its exponent is near 1 (random keys) or near $\frac{1}{2}$ (correlated keys). Length generalisation: train at T, test at $2T$–$16T$ on recall, copying [28], and RULER-style needle tasks [27], with BDH's damping (RoPE/ALiBi-like U; 34, §6.1) ablated.

E3. Ablation ladder isolating Hebbian and dual-timescale effects. Each rung adds one component at fixed bytes and FLOPs: (a) linear attention, elu+1, $d_\phi = d$; (b) + positivity and ReLU low-rank keys; (c) + high dimension $n \gg d$ (BDH-GPU-like); (d) + k-WTA sparsity; (e) + decay λ / BDH damping; (f) Hebbian $\rightarrow$ delta rule; (g) + slow bank $\mathbf{C}$ and κ; (h) + latent workspace $R > 1$ with halting; (i) + local adapter. A *byte-transfer control* at rung (g) gives the bank's bytes to a larger $\mathbf{S}$, so that "more memory" and "a second timescale" are not confounded. A second control replaces the BDH backbone with a Transformer backbone plus positive head.

E4. Continual streams (H2). Streams $A \rightarrow B \rightarrow A \rightarrow \ldots$ with controlled interference: permuted mappings, class-incremental symbol tasks, and a language-domain stream (Europarl language pairs; code$\rightarrow$prose). Metrics: average accuracy, forgetting, backward and forward transfer [36], relearning speed over the first k steps, plasticity loss over long streams [15], and total bytes. Baselines: frozen, full fine-tuning, replay [47], EWC [32], a fast-state-only model, and input-gated SSMs. Each method is reported with and without access to task-boundary signals.

E5. Demonstration-conditioned latent reasoning (H3). ARC-AGI-1 public evaluation, ConceptARC [41], and RE-ARC-generated controls [25], with no evaluation tasks or task identifiers in training (the BDH-CQ condition; 16, §1). BDH-CQ appears in only two forms: (i) its *reported* numbers, cited as such, or a black-box API run if access is granted; (ii) a *clearly labelled reimplementation* of its published Eqs. 1–4 ("BDH-CQ-R"), never presented as BDH-CQ. Contamination controls: disjoint hashes between training mixtures and evaluation grids, and a freshly authored held-out set. Cost is reported per task under an explicit, published accounting (GPU type, seconds, price, and pipeline stages included).

5.3 Compute envelope

At $6ND$ training FLOPs, the E1 grid (30M/0.6B, 125M/2.5B, 350M/7B tokens) costs about 1.7×10^{19} FLOPs per architecture-seed, or about 2.5×10^{20} for five architectures and three seeds. At a sustained 1.25×10^{14} FLOP/s (an A100 at $\sim$40% utilisation), this is about 550 GPU-hours,

or about 1.1k with sweeps. E2–E4 are an order of magnitude cheaper. The plan fits an academic budget. Main-track claims at ICLR/NeurIPS/ICML should wait until it has been executed.

6 Critical Analysis of BDH and BDH-CQ

Both papers make real contributions. BDH gives an unusually explicit bridge from attention to local synaptic dynamics, with a clear parameter count, public code, and testable theoretical claims. BDH-CQ reports an *independent black-box audit* that reproduced its headline 29.5% pass@2 without weight access (16, §5), byte-identical repeat runs (§6.6), Wilson intervals, and candid failure analyses (§6.2–6.4, App. A). Our critique is about what the evidence licenses. It is not about intent. Table 2 summarises it. $^{(P)}$ marks a limitation the authors state, and $^{(I)}$ marks a gap we infer from what is and is not reported.

Open problems that follow.

1. **Measured capacity.** Does BDH-GPU's high-n positive state reach Claim 7's regime on standard recall, and does it beat gated/delta models at equal *bytes*, not equal parameters? (E2)
2. **Which ingredient matters?** Is BDH's advantage, where one exists, due to positivity, sparsity, high n, weight sharing, or damping? None of the published experiments isolates these. (E3)
3. **Interference.** Merging by concatenation (34, §7.1) and continual adaptation both need a mechanism that keeps tasks apart. Proposition 1 says decay alone cannot provide it. (E4)
4. **Latent reasoning without a proprietary pipeline.** How much of BDH-CQ's ARC performance survives in an open reimplementation of Eqs. 1–4 without its candidate construction and ranking? (E5)
5. **Cost accounting.** Cost-per-task frontiers need one published accounting: hardware, pipeline stages, and effort tier.

7 Discussion

Why dual timescale is the right next class. Softmax attention avoids the plasticity–stability dilemma by never forgetting within the window and never learning across windows. Fixed-state models (linear attention, SSMs, BDH-GPU) learn online but share one state, so by Proposition 1 they trade retention against interference. Weight-level continual learning [32, 61] works on the slowest timescale and requires gradients. CDLR adds the timescale that is missing at inference: episodes are consolidated into gated slots, by analogy with hippocampal-to-neocortical transfer [37] and multi-timescale synapses [6], while memory stays bounded and slow weights stay frozen. The prediction is falsifiable (H2), and E3's byte-transfer control is designed to refute it if it is wrong.

Where CDLR should lose. H4 is a claim for softmax attention, and we hold it as likely. Below $T^\star$ (Equation (1)), and on exact copying or high-cardinality recall [2, 28], a KV-cache is both smaller and more accurate. A hybrid with local softmax attention plus CDLR memory is the natural compromise and should be included in E1–E2. Bank selection needs either a task-boundary/novelty signal or a labelled support set. The unsupervised gate may fail where tasks share inputs, as in our permutation probes (Section A).

Table 2: Claims, evidence, and gaps. [P]: paper-stated; [I]: our inference.

Claim (source)	Evidence reported	Gap
BDH rivals GPT-2 at 10M–1B params (34, Abstract; §4.2, Fig. 7)	Europarl En–Pl/En–Cs byte-level, 1.2B tokens; GPTXL baseline (nanoGPT + Transformer-XL buffer + ALiBi), App. B.2, Table 4	[I] One corpus family; values graphical only; no modern linear/SSM baselines in experiments though cited (§4.3); no FLOP-matched curve.
Monosemantic synapses (§6.3)	Mann–Whitney $U = 2368$, $p < 10^{-14}$, 50+50 LLM-generated sentences, one concept pair, one layer	[I] Single concept pair; no comparison with SAE features in Transformers [7].
Capacity $\tilde{O}(n)$ / $\tilde{\Omega}(\sqrt{n})$ (Claim 7, §6.1, App. C.2)	Proof sketch (JL + Azuma)	[I] Not measured on recall benchmarks; motivates E2.
Reasoning generalises over length/time (§1 motivation)	–	[P] Thermodynamic-limit/PAC-like bounds are a goal (Abstract, §1). [I] Not directly tested.
Long context, no hard bound (§6.1)	–	[P] Damping (RoPE+ALiBi-like) still required.
Model merging by concatenation in n (§7.1, Table 2)	Merged 38M model, X→En loss 0.39–0.43	[P] Merged model mixes languages when translating from English.
Training without BPTT (§7.2)	English loss $\approx 0.65 \rightarrow 0.75$–$1.05$	[P] Degradation; cross-language concept matching lost.
Sparse/neuromorphic execution (§2.4)	Cost estimate	[P] CPU sparse kernels 10^2–$10^5\times$ less cost-effective than GPU BDH-GPU. [I] Energy not measured.
BDH-CQ 29.5% pass@2 ARC-AGI-1, \$0.00070/task (16, Abstract; §5, Table 1)	118/400, Wilson [25.24, 34.15]; ≈0.85 H200 GPU-s at \$3/h; independent black-box audit	[I] §6.6 prices STANDARD effort (also 118/400) at \$0.00265246/task and MIN at \$0.00088399. The relation to the \$0.00070 headline is not stated.
Architecture	"Dimensions, exact update rules, and implementation details remain proprietary" (§3.3); recipe proprietary (§4.1)	[P] Not reproducible from text. [I] No ablation separating BDH backbone from candidate construction/ranking pipeline.
Generalisation to ConceptARC (§6.1, Table 1)	95/160 semantic, 96/160 opaque pass@2	[P] ConceptARC is in the training mixture (§4.2); exposure via training or checkpoint selection not ruled out (§6.5).
pass@2 semantics (§6.6)	75 single-candidate records	[P] pass@2 is not two independent attempts for every input.
Compositional boundaries (§6.2–6.3, App. A.3)	Ordering 1/24 at length 8; colour swap 0/72 composed; conditional rule selection 100%→56.7%	[P] Stated weaknesses. Ladders are single-family, 40 tasks (App. A.4); mechanic rates confounded by LLM authoring (App. A.2).
Scaling "1B to 600B" (§9.2)	No figure, table, or numbers	[I] Unsupported by reported data.

Interpretability. Positive sparse codes and slot-structured memory make some quantities directly inspectable: which neurons wrote, which slot was read, and how many workspace steps ran. These are audit signals, not explanations. Claims of monosemanticity need standard metrics and baselines (Table 2).

Limitations. (i) No large-scale results are reported here; the protocol's cost is given in Section 5. (ii) Proposition 1 is a linear, expected-value statement; nonlinear readouts and input-dependent gates need a richer analysis. (iii) CDLR adds hyperparameters $(M, \tau, \beta, \gamma, R, c)$ that could absorb tuning budget, which is why P2 fixes the sweep size. (iv) Meta-training uses BPTT across demonstrations. (v) Our audit of BDH-CQ relies on its text alone, because the system is closed.

Ethics and broader impact. Models that learn at inference change behaviour after deployment. That raises the risk of memory poisoning through crafted demonstrations, by analogy with training-time poisoning [53], and the risk that consolidated slots retain personal data. The CDLR audit log, the parameter hash, and slot-level deletion are partial mitigations: they make writes visible and reversible. Deployments should cap consolidation rates, require provenance for consolidated episodes, and support rollback. Bounded-memory inference can lower serving energy for long contexts, but only above $T^\star$, and this should be measured, not assumed.

8 Conclusion

Softmax attention, Hebbian synaptic state, and recurrent latent memory are three settings of one associative-memory operator. They differ in growth, key geometry, forgetting, consolidation, and workspace. This view exposes a structural limit of any single-timescale state, retention–interference coupling, and points to a remedy grounded in complementary learning systems: CDLR, a fast episodic state plus a slow gated consolidated bank with a latent workspace and an audit trail. We audited the evidence behind BDH and BDH-CQ, separating what the authors state from what we infer. We also specified a matched-compute protocol under which both they and CDLR can be confirmed or refuted. The next step is to run that protocol and report the results, including the cases where the KV-cache wins.

Code and data availability. Protocol code, configurations, and preliminary probe logs will be released at `https://github.com/Jalendar10/synaptic-state-vs-kv-cache` (commit pinned in the repository; protocol frozen in `prereg/e1_e5_protocol_v0.json`).

References

[1] Kwangjun Ahn, Xiang Cheng, Minhak Song, Chulhee Yun, Ali Jadbabaie, and Suvrit Sra. Linear attention is (maybe) all you need (to understand transformer optimization). In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2310.01082.

[2] Simran Arora, Sabri Eyuboglu, Aman Timalsina, Isys Johnson, Michael Poli, James Zou, Atri Rudra, and Christopher Ré. Zoology: Measuring and improving recall in efficient language models. *arXiv preprint arXiv:2312.04927*, 2023.

[3] Jimmy Ba, Geoffrey E. Hinton, Volodymyr Mnih, Joel Z. Leibo, and Catalin Ionescu. Using fast weights to attend to the recent past. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2016.

[4] Maximilian Beck, Korbinian Pöppel, Markus Spanring, Andreas Auer, Oleksandra Prudnikova, Michael Kopp, Günter Klambauer, Johannes Brandstetter, and Sepp Hochreiter. xLSTM: Extended long short-term memory. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2405.04517.

[5] Ali Behrouz, Peilin Zhong, and Vahab Mirrokni. Titans: Learning to memorize at test time. *arXiv preprint arXiv:2501.00663*, 2025.

[6] Marcus K. Benna and Stefano Fusi. Computational principles of synaptic memory consolidation. *Nature Neuroscience*, 19(12):1697–1706, 2016.

[7] Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, et al. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023.

[8] François Chollet. On the measure of intelligence. *arXiv preprint arXiv:1911.01547*, 2019.

[9] Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, David Belanger, Lucy Colwell, and Adrian Weller. Rethinking attention with performers. In *International Conference on Learning Representations (ICLR)*, 2021.

[10] Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc Le, and Ruslan Salakhutdinov. Transformer-XL: Attentive language models beyond a fixed-length context. In *Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 2978–2988, 2019.

[11] Tri Dao and Albert Gu. Transformers are SSMs: Generalized models and efficient algorithms through structured state space duality. In *International Conference on Machine Learning (ICML)*, 2024. arXiv:2405.21060.

[12] Tri Dao, Daniel Y. Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[13] Mostafa Dehghani, Stephan Gouws, Oriol Vinyals, Jakob Uszkoreit, and Łukasz Kaiser. Universal transformers. In *International Conference on Learning Representations (ICLR)*, 2019.

[14] Mostafa Dehghani, Anurag Arnab, Lucas Beyer, Ashish Vaswani, and Yi Tay. The efficiency misnomer. In *International Conference on Learning Representations (ICLR)*, 2022.

[15] Shibhansh Dohare, J. Fernando Hernandez-Garcia, Qingfeng Lan, Parash Rahman, A. Rupam Mahmood, and Richard S. Sutton. Loss of plasticity in deep continual learning. *Nature*, 632: 768–774, 2024.

[16] Björn Engdahl, Adrian Kosowski, Jan Chorowski, Zuzanna Stamirowska, Przemysław Uznański, Junlin Jiang, Rohan Phadke, Remigiusz Kinas, and Richard Zhong. BDH-CQ: In-context learning with recurrent latent reasoning. *arXiv preprint arXiv:2608.09888*, 2026.

[17] Robert M. French. Catastrophic forgetting in connectionist networks. *Trends in Cognitive Sciences*, 3(4):128–135, 1999.

[18] Stefano Fusi, Patrick J. Drew, and Larry F. Abbott. Cascade models of synaptically stored memories. *Neuron*, 45(4):599–611, 2005.

[19] Jonas Geiping, Sean McLeish, Neel Jain, John Kirchenbauer, Siddharth Singh, Brian R. Bartoldson, Bhavya Kailkhura, Abhinav Bhatele, and Tom Goldstein. Scaling up test-time compute with latent reasoning: A recurrent depth approach. *arXiv preprint arXiv:2502.05171*, 2025.

[20] Wulfram Gerstner, Marco Lehmann, Vasiliki Liakoni, Dane Corneil, and Johanni Brea. Eligibility traces and plasticity on behavioral time scales: Experimental support of NeoHebbian three-factor learning rules. *Frontiers in Neural Circuits*, 12:53, 2018.

[21] Alex Graves. Adaptive computation time for recurrent neural networks. *arXiv preprint arXiv:1603.08983*, 2016.

[22] Albert Gu and Tri Dao. Mamba: Linear-time sequence modeling with selective state spaces. *arXiv preprint arXiv:2312.00752*, 2023.

[23] Shibo Hao, Sainbayar Sukhbaatar, DiJia Su, Xian Li, Zhiting Hu, Jason Weston, and Yuandong Tian. Training large language models to reason in a continuous latent space. *arXiv preprint arXiv:2412.06769*, 2024.

[24] Donald O. Hebb. *The Organization of Behavior: A Neuropsychological Theory*. Wiley, New York, 1949.

[25] Michael Hodel. Addressing the abstraction and reasoning corpus via procedural example generation. *arXiv preprint arXiv:2404.07353*, 2024.

[26] Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. Training compute-optimal large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[27] Cheng-Ping Hsieh, Simeng Sun, Samuel Kriman, Shantanu Acharya, Dima Rekesh, Fei Jia, Yang Zhang, and Boris Ginsburg. RULER: What's the real context size of your long-context language models? *arXiv preprint arXiv:2404.06654*, 2024.

[28] Samy Jelassi, David Brandfonbrener, Sham M. Kakade, and Eran Malach. Repeat after me: Transformers are better than state space models at copying. In *International Conference on Machine Learning (ICML)*, 2024.

[29] Alexia Jolicoeur-Martineau. Less is more: Recursive reasoning with tiny networks. *arXiv preprint arXiv:2510.04871*, 2025.

[30] Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

[31] Angelos Katharopoulos, Apoorv Vyas, Nikolaos Pappas, and François Fleuret. Transformers are RNNs: Fast autoregressive transformers with linear attention. In *International Conference on Machine Learning (ICML)*, pages 5156–5165, 2020.

[32] James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska,

Demis Hassabis, Claudia Clopath, Dharshan Kumaran, and Raia Hadsell. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114 (13):3521–3526, 2017.

[33] Philipp Koehn. Europarl: A parallel corpus for statistical machine translation. In *Proceedings of Machine Translation Summit X*, pages 79–86, 2005.

[34] Adrian Kosowski, Przemysław Uznański, Jan Chorowski, Zuzanna Stamirowska, and Michał Bartoszkiewicz. The dragon hatchling: The missing link between the transformer and models of the brain. *arXiv preprint arXiv:2509.26507*, 2025.

[35] Dharshan Kumaran, Demis Hassabis, and James L. McClelland. What learning systems do intelligent agents need? Complementary learning systems theory updated. *Trends in Cognitive Sciences*, 20(7):512–534, 2016.

[36] David Lopez-Paz and Marc'Aurelio Ranzato. Gradient episodic memory for continual learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2017.

[37] James L. McClelland, Bruce L. McNaughton, and Randall C. O'Reilly. Why there are complementary learning systems in the hippocampus and neocortex: Insights from the successes and failures of connectionist models of learning and memory. *Psychological Review*, 102(3): 419–457, 1995.

[38] Michael McCloskey and Neal J. Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. In *Psychology of Learning and Motivation*, volume 24, pages 109–165. Academic Press, 1989.

[39] Quinn McNemar. Note on the sampling error of the difference between correlated proportions or percentages. *Psychometrika*, 12(2):153–157, 1947.

[40] Thomas Miconi, Kenneth O. Stanley, and Jeff Clune. Differentiable plasticity: Training plastic neural networks with backpropagation. In *International Conference on Machine Learning (ICML)*, pages 3559–3568, 2018.

[41] Arseny Moskvichev, Victor Vikram Odouard, and Melanie Mitchell. The ConceptARC benchmark: Evaluating understanding and generalization in the ARC domain. *Transactions on Machine Learning Research*, 2023. arXiv:2305.07141.

[42] Erkki Oja. Simplified neuron model as a principal component analyzer. *Journal of Mathematical Biology*, 15(3):267–273, 1982.

[43] Guilherme Penedo, Hynek Kydlíček, Loubna Ben Allal, Anton Lozhkov, Margaret Mitchell, Colin Raffel, Leandro Von Werra, and Thomas Wolf. The FineWeb datasets: Decanting the web for the finest text data at scale. In *Advances in Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track*, 2024.

[44] Joelle Pineau, Philippe Vincent-Lamarre, Koustuv Sinha, Vincent Larivière, Alina Beygelzimer, Florence d'Alché Buc, Emily Fox, and Hugo Larochelle. Improving reproducibility in machine learning research (a report from the NeurIPS 2019 reproducibility program). *Journal of Machine Learning Research*, 22(164):1–20, 2021.

[45] Ofir Press, Noah A. Smith, and Mike Lewis. Train short, test long: Attention with linear biases enables input length extrapolation. In *International Conference on Learning Representations (ICLR)*, 2022.

[46] Alexander Pritzel, Benigno Uria, Sriram Srinivasan, Adrià Puigdomènech Badia, Oriol Vinyals, Demis Hassabis, Daan Wierstra, and Charles Blundell. Neural episodic control. In *International Conference on Machine Learning (ICML)*, pages 2827–2836, 2017.

[47] David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P. Lillicrap, and Greg Wayne. Experience replay for continual learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[48] Imanol Schlag, Kazuki Irie, and Jürgen Schmidhuber. Linear transformers are secretly fast weight programmers. In *International Conference on Machine Learning (ICML)*, pages 9355–9366, 2021.

[49] Jianlin Su, Murtadha Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. RoFormer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

[50] Yu Sun, Xinhao Li, Karan Dalal, Jiarui Xu, Arjun Vikram, Genghan Zhang, Yann Dubois, Xinlei Chen, Xiaolong Wang, Sanmi Koyejo, Tatsunori Hashimoto, and Carlos Guestrin. Learning to (learn at test time): RNNs with expressive hidden states. *arXiv preprint arXiv:2407.04620*, 2024.

[51] Yutao Sun, Li Dong, Shaohan Huang, Shuming Ma, Yuqing Xia, Jilong Xue, Jianyong Wang, and Furu Wei. Retentive network: A successor to transformer for large language models. *arXiv preprint arXiv:2307.08621*, 2023.

[52] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 30, 2017. arXiv:1706.03762.

[53] Eric Wallace, Tony Z. Zhao, Shi Feng, and Sameer Singh. Concealed data poisoning attacks on NLP models. In *Proceedings of NAACL-HLT*, pages 139–150, 2021.

[54] Guan Wang, Jin Li, Yuhao Sun, Xing Chen, Changling Liu, Yue Wu, Meng Lu, Sen Song, and Yasin Abbasi Yadkori. Hierarchical reasoning model. *arXiv preprint arXiv:2506.21734*, 2025.

[55] Ke Alexander Wang, Jiaxin Shi, and Emily B. Fox. Test-time regression: A unifying framework for designing sequence models with associative memory. *arXiv preprint arXiv:2501.12352*, 2025.

[56] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc Le, and Denny Zhou. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[57] Edwin B. Wilson. Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association*, 22(158):209–212, 1927.

[58] Songlin Yang, Bailin Wang, Yikang Shen, Rameswar Panda, and Yoon Kim. Gated linear attention transformers with hardware-efficient training. In *International Conference on Machine Learning (ICML)*, 2024. arXiv:2312.06635.

[59] Songlin Yang, Bailin Wang, Yu Zhang, Yikang Shen, and Yoon Kim. Parallelizing linear transformers with the delta rule over sequence length. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2406.06484.

[60] Songlin Yang, Jan Kautz, and Ali Hatamizadeh. Gated delta networks: Improving Mamba2 with delta rule. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2412.06464.

[61] Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. In *International Conference on Machine Learning (ICML)*, pages 3987–3995, 2017.

A Preliminary Probes (Not Main Results)

Status. These are single-machine CPU runs on synthetic toy tasks with models of 5×10^4 to 1.6×10^6 parameters. They test whether the protocol and the audit pipeline run end to end and show what mismatched budgets do. They provide *no* evidence about the hypotheses at scale, about ARC, or about the BDH §7.2 gap. All numbers come from run files in the project repository (seed and date in the logs).

P1: Episodic write without weight change (Tiny-CDLR, 52,531 params). BDH backbone (Pathway `bdh.py`, unchanged, n_{embd}=32, 2 layers, 256 sparse units), K=4 demonstrations per episode on a random key→value map with 16 classes (chance 0.0625). Accuracy with demonstrations written into $\mathbf{S}$ was 1.00, vs. 0.086 for the same queries with an empty $\mathbf{S}$. The parameter hash was identical before and after inference. Mean halting step was 1.23 of R=3.

P2: A→B→A with full interference. A and B are different permutations of the same 16 inputs. A fast-state-only arm forgot A completely after B (A accuracy 1.00 → 0.00; first-5 relearning accuracy 0.04). The dual-timescale arm kept A at 1.00 (first-5 relearning 0.80). *Caveat:* slot selection used a labelled 32-token support set at evaluation, which is a task-identity signal, so this probe does not test the unsupervised gate.

P3: Local adapter vs. BPTT (negative result). On a lag-1 permutation stream over a small pretrained BDH (3 seeds, 150 steps/phase), a local delta-rule readout with fast Oja memory reached 0.81 average online accuracy vs. 0.91 for full BPTT, at about 2.3× lower per-step cost. *Both forgot task A almost completely* (accuracy forgetting gap 0.97 in both), as Proposition 1 predicts for a single shared state.

P4: Why matched budgets matter. A 300-step Shakespeare character run had BDH reach validation loss 1.875 vs. 2.43–2.44 for a Transformer and a linear-attention model. BDH had 1.9× the parameters (1.64M vs. 0.87M) and took 12× the wall time, and the baselines were still on an early plateau. The comparison is not matched and supports no ranking. In a toy Tiny-CDLR vs. Transformer recall comparison, the undertrained Transformer was far less accurate (0.25 vs. 1.00) but 28× faster and used less memory at this context length.

B Reporting Checklist for Architecture Bakeoffs

1. Non-embedding params, training tokens, training FLOPs (method stated), wall time, hardware.
2. Sweep grid and size per architecture; best and median of sweep.
3. Inference bytes: parameters + state at each reported T and batch; latency p50/p95; throughput.
4. Seeds, intervals, paired tests, multiple-comparison correction.
5. Data provenance and contamination checks (hash overlap) for every evaluation set.
6. For closed systems: black-box status, access date, and exactly which numbers are quoted.
7. Preregistered hypotheses with outcome (confirmed / refuted / inconclusive).

C Notation

T	sequence length (tokens)
n	neuron dimension (BDH) / key-feature dimension
d, d_v, d_{model}	low-rank width, value width, Transformer width
$\mathbf{S}, z$	fast episodic state and normaliser
$\mathbf{C}_j, \mathbf{k}_j, M$	slow bank slot, slot key, slot budget
λ, η	fast decay, fast write rate
κ, β, τ	consolidation map, merge rate, merge threshold
$\mathbf{H}_r, R, c$	workspace state, max steps, halting confidence
$T^\star$	byte crossover between KV-cache and bounded state (Equation (1))