

# Advanced JavaScript

## Lab 2

### **A. JavaScript as Object Oriented Programing**

A.1. Using the constructor method for creating Objects, write a script that allows you to create a rectangle object that

- Should have width and height properties.
- Implement a method for calculating its area
- Implement a method for calculating its perimeter.
- Implement displayInfo() function to display a message declaring the width, height, area, and perimeter of the created object.

A.2. Create your own object that contains a list of numerical sequence, with the following details

- Your constructor takes 3 parameters to define start, end of list and step
- The list should be private and filled with private method
- You can create getter and setter for the list if needed
- Allow the user to apply the following functionality to his created sequence
  - Append or prepend a new value within the same numerical sequence
  - Dequeue or pop a value,
  - you have to ensure that you are pushing value within the same **sequence** otherwise through exception
  - you have to ensure that there is no duplicated value otherwise through exception
- **all of the properties should be defined using accessor and/or data descriptor, prevent them from being deleted, iterated or being modified.**
- **Override .toString() function to display a message with all of the list content.**
- you can add any property you need.

**A.3. Create your box object that contains books objects, ensure that you can**

- a. Create a book object and add it to the box object content property
- b. Count # of books inside the box
- c. Delete any of these books in the box according to a book title.  
Note: You should delete a single copy of the books with the same title.
- d. Create Class Property that counts numbers of created books objects and Class method to retrieve it.
- e. Use `.toString()` to display the box instance's dimensions and how books are stored in it.
- f. Implement `.valueOf()` so that if there is more than one box object we can get the total number of books in these boxes by adding them  
i.e. if box1 has 5 books and box2 has 2 books,  
then box1 + box2 should return 7

**Note:**

- Use Constructor Pattern for creating the Book Objects
- There is no inheritance
- Using global variables is not allowed
- No Class methods and properties are allowed except for those required in part d.
- Box object has the following properties:  
height, width, length, material, and content.
  - The content property contains an array of book objects
- Book object has the following properties:  
title, numofChapters, author, numofPages, publisher, numofCopies
- You should use accessor and/or data descriptor for defining properties, and if needed, prevent them from being deleted, iterated, or being modified.
- You can define any function needed for both box and book objects