

Barangay Incident Reporting System - API Design

This document describes the REST API endpoints, authentication, and core data models for the Barangay Incident Reporting System.

Overview

- Base URL: /api
- Auth: Bearer token (JWT) in Authorization header
- Content-Type: application/json
- Roles: resident, personnel, admin

Authentication

Method	Endpoint	Description
POST	/auth/register	Create a new user (fullName, email, password, role).
POST	/auth/login	Login and receive token.
GET	/auth/me	Get current user profile (protected).

Incidents

Method	Endpoint	Description
POST	/incidents	Create incident (resident).
GET	/incidents/my-reports	List resident incidents (resident).
PATCH	/incidents/resident/:id	Resident update (notes/details).
GET	/incidents/admin/all	List all incidents (admin).
PATCH	/incidents/admin/:id	Admin update (status, adminNotes, assignedTo).
GET	/incidents/personnel/assigned	List assigned incidents (personnel).
PATCH	/incidents/personnel/:id	Personnel update (status, personnelNotes).

Users (Admin)

Method	Endpoint	Description
GET	/users	List all users (admin).

Data Models (Summary)

- User: fullName, email, password (hashed), role, createdAt.

- Incident: title, description, location, incidentDate, status, reportedBy, assignedTo, residentNotes, adminNotes, personnelNotes, createdAt.

Error Responses

- 400 Bad Request: Validation errors (express-validator).
- 401 Unauthorized: Missing/invalid token.
- 403 Forbidden: Insufficient role.
- 404 Not Found: Invalid route.
- 500 Server Error: Unhandled exceptions.