

# NEWS for VAST 3.8.0

## Purpose of document:

This document lists substantial changes in R package VAST for each numbered release starting at 3.5.0. VAST depends upon utility functions within package FishStatsUtils, and this document therefore lists new features, bug fixes, deprecated features, and other changes occurring via edits to both VAST and FishStatsUtils.

## CHANGES IN VAST 3.8.0

### CHANGING DEPENDENCIES

- Requires FishStatsUtils version  $\geq 2.10.0$

### NEW FEATURES

- Allows users to implement a necessary identifiability constraint when estimating a loadings matrix for spatio-temporal variation across both years and species.

## CHANGES IN VAST 3.7.1

### CHANGING DEPENDENCIES

- Requires FishStatsUtils version  $\geq 2.9.1$

### NEW FEATURES

- Change `fit\_model` to include `getJointPrecision=TRUE` by default, so that range-edge metrics are computed by default.

### BUG FIXES

- Change the default `projargs` used when plotting to Lon-Lat, to avoid errors arising from applying custom projections to global coastline maps without also specifying a reduced subset of countries.

26

## 27 **CHANGES IN VAST 3.7.0**

### 28 **CHANGING DEPENDENCIES**

- 29 • Requires FishStatsUtils version  $\geq 2.9.0$

### 30 **NEW FEATURES**

- 31 • Integrate package `effects` to plot covariate-response curves based on user-specified  
32 formulae for density and catchability covariates (including basis-spline, polynomial,  
33 interaction or other basis-expansion methods) along with confidence intervals.
- 34 • Improve `predict` feature added in release 3.6.0 including: (1) adding an integrated-  
35 test to confirm that it behaves identically to `predict.glm` in some simple cases; (2)  
36 improving documentation; and (3) confirming that it can be integrated with package  
37 `pdp` to make partial dependence plots.
- 38 • Re-adding continuous integration: (1) eliminating usage of TravisCI and instead (2)  
39 adding files to trigger the GitHub “CI” Action (based on substantial contributions  
40 from Cole Monnahan).
- 41 • Adding a simplified user-interface for seasonal spatio-temporal models (based on  
42 substantial contributions from Andrew Allyn).

### 43 **BUG FIXES**

- 44 • Update `plot\_quantile\_residuals` to ensure that a residual  $>0.5$  corresponds to data  
45 above the median from the predictive distribution, and a residual  $<0.5$  corresponds to  
46 data below the median from the predictive distribution (the previous version had that  
47 swapped due to the sign-change caused by using a uniform-to-chi-squared function  
48 for aggregating quantile residuals).

49

## 50 **CHANGES IN VAST 3.6.1**

## BUG FIXES

- Update `map` object which was generated incorrectly for several topics related to backwards compatibility, as well as for some types of spatially varying coefficient model.

## CHANGES IN VAST 3.6.0

### CHANGING DEPENDENCIES

- Requires FishStatsUtils version  $\geq 2.8.0$

### NEW FEATURES

- Expanding use of formula interface to specify covariates. A separate formula is now specified for each linear predictor for density (X1\_formula/X2\_formula) or catchability (Q1\_formula/Q2\_formula). Catchability formulas are parsed by user-supplied data frame `catchability\_data`. However, the user can still use previous interface, either by passing X\_itp / X\_gtp directly, or by passing a single formula.
- Allowing user to specify spatially varying coefficients for each density linear predictor separately (X1config\_cp / X2config\_cp), and adding new feature to allow users to specify a spatially varying catchability covariate (Q1config\_k / Q2config\_k). This allows users to, for example, estimate a differences in gear performance between two surveys where gear performance varies spatially as a random field.
- Adding generic predict function for S3 class `fit\_model`; the function is very slow but could be expanded in the future to be similar to predict functions for other common regression packages.

### ISSUES RESOLVED

- Identify issue whereby VAST was giving different results when run using R version  $\geq 4.0.0$ , compared with earlier R versions. This occurred due to changes in base-R

with how integers are sampled, as documented in [issue #244](#). A new option ``calculate_kmeans( ..., backwards_compatible_kmeans=FALSE)`` has been added for users wanting to generate an identical k-means object to previous R versions; this is used e.g., in integrated-tests to ensure that results from prior versions can be replicated exactly.

## **BUG FIXES**

- Update ``projargs`` strings passed to package `sp / RGDAL`, to keep up with changes to using PROJ6. The previous use of `projargs` strings was throwing annoying warning messages, but the change did not appear to impact functionality.

## **CODE AND STABILITY IMPROVEMENTS**

- Omega (spatial random effects), Epsilon (spatio-temporal random effects), and Delta (overdispersion random effects) are now built to have zero-length when these features are not needed (by making one dimension have length-0). This is intended to (1) decrease memory required in the former approach of mapping these off, and (2) eliminating the chance that users might inadvertently set starting values to non-zero values, which would previously have resulted in incorrect results.
- ``make_covariates(.)`` has been re-structured to change the order of operations, resulting in a more stable implementation for use with factors and interactions

## **CHANGES IN VAST 3.5.1**

### **BUG FIXES**

- Fix error in compiling CPP version 9.3.0 and 9.4.0, which occurred using `rtools40` as required by R version  $\geq 4.0.0$ . This involved change function ``abs(.)`` to ``fabs(.)`` in these CPP files.

## 101 **CHANGES in VAST 3.5.0**

### 102 **CHANGING DEPENDENCIES**

- 103 • Requires FishStatsUtils version  $\geq 2.7.0$
- 104 • Requires R package DHARMa

### 105 **NEW FEATURES**

- 106 • Added a feature for barrier-SPDE, where vertices of the SPDE mesh that occur over  
107 land have a correlation of zero with nearby vertices.
- 108 • Changed density covariates to index by `X_gctp` (rather than `X_gtp`), so that manual  
109 editing can be used to implement cohort effects.
- 110 • Allows probability-integral-transform (PIT) residuals for delta-models, using  
111 DHARMa for plotting tools.

### 112 **DEPRECATED AND DEFUNCT**

- 113 • Eliminated deprecated and generally unused feature for seasonal modelling, whereby  
114 input `t_iz` is now replaced by `t_i`. This change simplifies code in CPP files in multiple  
115 places. Seasonal modelling is still feasible using the spatially-varying-coefficient  
116 features involving covariates.

117