

Telemetry Sources: OS Events, Sysmon, Endpoint Data

Windows event basics

Security events (important IDs):

Event ID	What
4624/4625	Logon / failed logon
4672	Admin logon (privileged)
4688	Process creation (needs audit)
4769/4771	Kerberos service-ticket / fail
4720-4765	Account management (new user, reset pw)
7045	Service installed
1102/1104	Log cleared / Windows log filled

Sysmon (system-level, via config):

Sysmon ID	What
1	ProcessCreation (full cmdline!)
3	NetworkConnection (full)
6	DriverLoad
7/8/9	ImageLoaded/CreateRemoteThread (injection flags)
11/13	FileCreate/RegistryValueSet
23	FileDelete
25/26	ProcessTampering/FileDeleteLogged

```
install: sysmon.exe -accepteula -i config.xml
```

Linux telemetry

auditd: rules on execve, file access, network (audit)

systemd journal: service changes

bash history / auth.log: login, sudo

ETW on Windows implements many of the above via providers

Correlation-ish thinking

Single events are noise; chains are signal:

4624(user, ip) then 4688 then 7045 then 4769 → 'possible lateral'

No telemetry = no detection. Baseline everything, then alert on anomalies.

The engineering reality

Ship the fields you'll analyze: cmdline, parent PID, integrity, source IP, hash

Time synchronization (NTP) everywhere – correlation depends on clock

Centralize (SIEM) for the search; endpoint there for speed

Telemetry isn't a feature – it's the foundation of the pyramid of detection. If you can't describe the Tool layers (OS+sysmon+network), your detections are built on sand.

[← EDR vs Antivirus: The Modern...](#)

[Behavioral Detection & Alert R...](#)