

Service Enumeration Deep

Service-by-service enumeration

SMB (445/139)

```
nmap -p 445 --script smb-enum-shares,smb-enum-users 10.0.0.20
smbclient -L //10.0.0.20 -N          # null session
enum4linux -a 10.0.0.20             # one-stop shop
```

Shares named "backup" or "finance" are gold – check permissions.

LDAP (389/636)

```
ldapsearch -x -h 10.0.0.20 -b "dc=domain,dc=local" "objectclass=*"
# Kali has: ldapsearch, ldapenum, ad-enum modules
```

Users, groups, service accounts, group policies – AD in a few queries.

SNMP (161/162)

```
snmpwalk -v2c -c public 10.0.0.20 1.3.6.1.2.1
snmp-check 10.0.0.20 -c public
```

Default community "public" is an attacker's cheat sheet.

RPC (111 TCP/UDP, 135 TCP)

```
nmap -sV -p 111,135 --script rpcinfo 10.0.0.20
rpcclient -U '' 10.0.0.20 -N          # null session (Windows legacy)
```

Interpret what you find

Every service response has:

Config evidence (sysdescr, firmware versions)

Weak auth (anonymous access, default creds)

Enabled methods (WRITE shares, bind permissions, LDAP modify)

Documentation discipline

```
echo "ENUM: SMB shares for 10.0.0.20" > enum-smb.txt  
smbclient -L //10.0.0.20 -N >> enum-smb.txt
```

Save everything. Your future self needs this during exploitation and writing the report.

← Port Scanning: SYN, Connect,...

OS Fingerprinting: Passive, Ac...