

Egress Abuse, DoS & Lateral Patterns

Egress abuse (data leaving)

HTTP(S) POST exfil to unlisted domains

DNS tunneling (already covered)

Cloud storage abuse (Drive/Dropbox URLs)

Email exfil (SMTP), IM

Steganography in images; appended blobs after valid content

DoS patterns (a checklist)

Volumetric (L2-L4 amplification): DNS/NTP/SSDP reflection, SYN flood

Protocol/stateful: slowloris (hang connections), resource exhaustion (open many TCP), TCP state table overflow

Application: HTTP flood, login storms, expensive-query floods, PDF-render bombs, zip-bombs on unpack

Physical: switch MAC floods, STP thrashing (covered earlier)

Lateral movement taxonomy

Remote code exec (ps/x/x), WMI, scheduled tasks, winRM, SSH

Shared credentials/key material (pwdump → spray)

Token/PnT (PtH, pass-the-cache)

RDP with stolen creds

Detection backbone: network logs of new SMB/TCP-135 sessions, unusual cmd/pss child processes, Kerberos Service Ticket requests for exotic services

The synthesis

Think in `sessions` and `artifacts`:

Who talks to whom on what port, at what cadence, to what dst IP?

Are there NEW internal connections (the #1 lateral signal)?

Is data egressing (post-login bulk bytes)?

A single 'flat' week of logs yields 100 candidate signals; a configured analytics engine turns the top 5 into alerts.

Every phase in an attack has a signature in the *session* not the file. Sessions are the bloodstream; learn to read them and both offense and defense become physics rather than luck.

[← Wireless Attacks & Security](#)

Module complete ✓