

The University of New South Wales

COMP9315 DBMS Implementation

21T1 Final Exam

[\[Instructions\]](#) [\[PostgreSQL\]](#) [\[C\]](#)
[\[Q1\]](#) [\[Q2\]](#) [\[Q3\]](#) [\[Q4\]](#) [\[Q5\]](#) **[\[Q6\]](#)** [\[Q7\]](#) [\[Q8\]](#)

Question 6 (7 marks)

Consider the following scenario:

- R is a relation with $bR = 40$ data pages and no overflow pages
- S is a relation with $bS = 20$ data pages and no overflow pages
- a buffer pool with $N = 25$ buffers

Ignoring the cost of writing the final result tuples, calculate *minimum cost* estimates for the $(R \bowtie S)$ operation for each of following join strategies:

- a. block nested loop join, where you can choose either table as the outer relation
- b. sort-merge join, where neither table is sorted initially
- c. sort-merge join, where R is initially sorted, but S is not
- d. sort-merge join, where S is initially sorted, but R is not
- e. sort-merge join, where both tables are initially sorted

For each cost, show the *minimum number* of buffers required to achieve this cost.

Show all working.

Instructions:

- Type your answer to this question into the file called `q6.txt`
- Submit via: **give cs9315 exam_q6 q6.txt**
or via: Webcms3 > exams > Final Exam > Q6 submission > Make Submission

End of Question